

Safe Operation of Vacuum Trucks Handling Flammable and Combustible Liquids in Petroleum Service

API RECOMMENDED PRACTICE 2219
FOURTH EDITION, JUNE 2016



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this Recommended Practice should consult with the appropriate authorities having jurisdiction.

Users of this Recommended Practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the Recommended Practice. At all times users should employ sound business, scientific, engineering, and judgment safety when using this Recommended Practice.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

Page

1	Scope	1
1.1	General	1
1.2	Applicability	1
1.3	Basic Vacuum Operations	1
1.4	Concept of Hazard vs Risk	2
1.5	Job Hazard Analysis	2
2	Normative References	2
3	Definitions	3
4	Safe Handling of Hazardous Materials	6
4.1	Hazardous Materials Awareness	6
4.2	Product Information	7
4.3	Personal Protective Equipment	7
4.4	Hazardous Materials Regulations	8
4.5	Emergency Response	8
5	Safe Vacuum Truck Operations	8
5.1	General	8
5.2	Atmospheric Testing	9
5.3	Conductive and Non-conductive Hose	10
5.4	Bonding and Grounding	11
5.5	Testing of Bonding and Grounding Static Lines	12
5.6	Vacuum Pumps and Blowers	13
5.7	Vacuum Exhaust Venting and Vapor Recovery	14
5.8	Transfer Operations	15
5.9	Over-pressure and Under-pressure	17
5.10	Gauging and Sampling	18
5.11	Non-petroleum Products	18
5.12	Operation of Vehicles	18
5.13	Personnel Safety	19
	Annex A (informative) Vacuum Truck Design and Equipment	20
	Annex B (informative) Vacuum Truck Preventative Maintenance	28
	Annex C (informative) Safe Vacuum Truck Operations	29
	Annex D (informative) Safe Operation of Vacuum Trucks to Remove Flammable and Combustible Liquids from Underground Tanks at Service Station and Commercial Facilities	38
	Annex E (informative) Pneumatic Conveyor Trucks	42
	Annex F (informative) Vacuum Truck Operating Experience and Incidents	46
	Bibliography	49
	Figures	
A.1	Typical Vacuum Truck with Rotary Vane Pump	20
A.2	Typical Vacuum Truck with Liquid Ring Pump or Rotary Lobe Blower	21
A.3	Typical Sliding (Rotary) Vane Pump	22
A.4	Liquid Ring Pump	23
A.5	Rotary Lobe Blower (Two-lobe Impeller)	24

Contents

	Page
A.6 Rotary Lobe Blower (Three-lobe Impeller)	24
Tables	
C.1 Example Vacuum/Flow Rate Table	31
C.2 Hose Flow Rate Adjustment Chart	32
C.3 Suggested Vacuum Pump Airflow Rate/Hose Diameter Adjustment Required When the Suction Hose is Partially Submerged (Skimming) to Minimize the Amount of Air Entering the Vacuum System	32

Introduction

Vacuum truck personnel working in petroleum facilities shall be trained in the safe operation of the vacuum equipment; familiar with the hazards of the products being handled; and aware of relevant facility permit requirements, safety procedures, and emergency response requirements. It is the responsibility of the vacuum truck owner and operator to comply with (1) applicable federal, state, and local regulations; (2) this RP; and (3) facility requirements regarding the safe operation of vacuum trucks, including, but not limited to, the following items:

- construction, inspection, maintenance, and certification of the vacuum tank;
- selection and safe operation of the vacuum truck, vacuum pump, hoses, and accessories;
- regulatory requirements for safe highway operation of the truck;
- proper transportation, handling, and disposal of hazardous materials;
- safe vacuum truck loading, unloading, and transport operations within the facility;
- training and qualification of operators and other assigned vacuum truck personnel.

Although the material contained in this document is intended to be consistent with regulatory requirements, API 2219 is not a compliance document. Each user or operator must ensure compliance with all applicable laws and regulations. The United States Department of Transportation (DOT) *Code of Federal Regulations*, 49 *CFR*, specifies the minimum requirements for the design, construction, maintenance, testing, and operation of vehicles used for handling and transporting hazardous materials within the United States. Criteria for minimum training and qualifications of drivers and operators are also found in 49 *CFR*. The Department of Labor, Occupational Safety, and Health Administration's (OSHA) requirements for safety, health, and hazard awareness applicable to operators and other personnel working with vacuum truck operations are found in the *Code of Federal Regulations*, 29 *CFR* 1910. U.S. Coast Guard regulations in 33 *CFR* 154 for bulk transfer of hazardous materials to and from vessels at marine facilities could include certain vacuum truck transfer operations.

The procedures contained herein are intended to apply to vacuum trucks, skids, and trailers used in flammable and combustible liquid service. These requirements include, but are not limited to, 49 *CFR* parts 178.345–178.348 as well as DOT 407 and DOT 412 (formerly designated MC307 and MC312) cargo tank trailers used in vacuum and transfer operations for handling and transporting flammable and combustible liquids and corrosive materials.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Safe Operation of Vacuum Trucks in Petroleum Service

1 Scope

1.1 General

This fourth edition of Safe Operation of Vacuum Trucks in Petroleum Service provides information concerning the safe operation of vacuum trucks engaged in all aspects of handling flammable and combustible liquids, associated waste water, produced water, sour water, basic sediment and water (BS&W), caustics, spent acids, or other fluids stemming from petroleum operations, products, powders, and the hazard of dust explosions. This publication discusses the types of vacuum pumps and cargo tanks associated with vacuum truck operations, the common hazards associated with those vacuum truck operations, and representative safe work practices and precautions to help prevent accidents and injuries. Annex F provides brief descriptions of a variety of incidents involving vacuum trucks, including offloading into open areas. These may be useful in reviewing specific operating procedures or developing materials for safety meetings or pre-job briefings.

The scope of this Recommended Practice (RP) includes the use of vacuum/pressure trucks, skids, portable tanks, and trailers (herein referred to as vacuum trucks) to remove flammable and combustible liquids from tanks and equipment and to clean up liquid hydrocarbon spills. The scope includes movement of liquid mixtures (such as “produced water”, BS&W, or tank bottoms) that may contain sufficient hydrocarbon material to present comparable hazards.

These safe practices also apply to the operation of portable vacuum tanks, skids, and trailers typically used in emergency flammable and combustible liquid spill cleanup activities. While not included in the specific scope of this standard, Annex E presents information related to pneumatic (air moving) trucks and hoppers, typically used in the petroleum industry for removal of dry materials such as catalysts, dusts, powders, or residue.

1.2 Applicability

Vacuum trucks are used in all segments of the petroleum industry with varied applications. Appropriate safe operating practices may vary because of different hazards associated with the materials to be moved and the facilities serviced. This RP seeks to assist in the development and implementation of practical and safe operating practices that will help identify hazards and reduce risks.

1.3 Basic Vacuum Operations

The two basic types of vacuum truck operations are as follows.

- a) Vacuum loading and off-loading operations that eliminate or minimize the introduction of air into the system by:
 - 1) completely submerging the suction nozzle into the liquid during the transfer process, or
 - 2) directly connecting the transfer hose to the source or receiving tank, vessel, or container below the surface level of the liquid contained therein.
- b) Vacuum truck operations that introduce air into the system during the transfer process, including:
 - 1) air conveying operations (Annex E) involving the incidental removal of solid materials when the suction hose is either partially submerged or not submerged (or, if submerged, when air is entrained or entrapped in the material) or the intentional removal of solids when used in a vacuum excavation system; or
 - 2) liquid transfer operations where the end of the hose is not directly connected to the source or receiving tank, container, or vessel or the nozzle is not submerged into the liquid within the tank, container, or vessel; or