

Cementing Float Equipment Testing

API SPECIFICATION 10F
FOURTH EDITION, JULY 2018

ERRATA 1, MAY 2020
ERRATA 2, JUNE 2020



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this specification should consult with the appropriate authorities having jurisdiction.

Users of this specification should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2018 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this recommended practice are as follows:

- the term “shall” denotes a minimum requirement in order to conform to the specification;
- the term “should” denotes a recommendation or that which is advised but not required in order to conform to the specification;
- the term “may” is used to express permission or a provision that is optional; and
- the term “can” is used to express possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

	Page
1 Scope	1
2 Normative References	1
2.1 Use of SI and U.S. Customary Units	1
3 Terms and Definitions	1
4 Symbols and Abbreviations	2
5 General Information	2
5.1 Function of Cementing Float Equipment	2
5.2 Performance of Cementing Float Equipment	3
6 Calibration	3
6.1 General	3
6.2 Timers	3
6.3 Flow Meter Systems	4
6.4 Pressure Measuring Systems	4
6.5 Temperature Measuring Systems	4
6.6 Data Acquisition System	4
6.7 Volumetric Glassware and Liquid Receivers	4
6.8 Balances	4
7 Flow Durability Time Categories	4
7.1 Categories	4
7.2 Auto-fill Equipment-Reverse Flow Test	5
8 Flow Durability Rate Categories	5
9 Apparatus and Materials	5
9.1 Flow Loop	5
10 Durability Test	10
10.1 Test Setup	10
11 Static High-temperature/High-pressure Category Rating	12
12 High-temperature/High-pressure Test Cell	12
12.1 Apparatus	12
12.2 Test Cell Procedure	13
13 Extrapolation and Interpolation of Test Results	14
13.1 Extrapolation	14
13.2 Interpolation	14
14 Reporting of Results	15
15 Marking	15
Annex A (informative) Results of Performance Tests on Cementing Float Equipment	16
Annex B (informative) Evaluation of Elastomers in Nonaqueous Fluids	18
Bibliography	19
Figures	
1 Forward Flow	6

Contents

	Page
2 Reverse Flow	7
3 Backflow Pressure Testing	8
4 Typical Controlled Pressure-Temperature Test Cell	13

Tables

1 Categories of Flow Durability Tests for Float Equipment	4
2 Reverse Flow Duration for Casing Fill-up Equipment	5
3 Forward Flow Rates for Flow Durability Testing	5
4 Temperature Categories of Static High-temperature Tests	12
5 Pressure Categories of High-pressure Tests	12

Cementing Float Equipment Testing

1 Scope

This specification provides testing and marking requirements for cementing float equipment to be used in oil and natural gas well construction.

2 Normative References

The following referenced documents are indispensable for the application of this document. For undated references, the latest edition of the referenced document applies (including any addenda/errata). For dated references, only the edition cited applies. However, not all documents listed may apply to your specific needs. The body of the standard should be referred to for how these documents are specifically applied.

API Recommended Practice 13B-1, *Field Testing Water-Based Drilling Fluids*

API Specification 13A, *Drilling Fluid Materials*

API Specification Q1, *Quality Management System Requirements for Manufacturing Organizations for the Petroleum and Natural Gas Industry*

For a list of other documents associated with this standard, see the Bibliography.

2.1 Use of SI and U.S. Customary Units

This document contains derived metric units (SI) and U.S. customary oilfield units. For the purposes of this document, the conversion between the systems is not exact and has been intentionally rounded to allow for ease of use in calibration and measurement.

3 Terms and Definitions

For the purposes of this specification, the following terms and definitions apply.

3.1

annulus

Area between the casing and open hole or previously set casing.

3.2

autofill (auto-fill)

A feature incorporated in the design of some float equipment that allows the flow check system(s) to be initially disengaged so fluid may pass in either direction when running a string of casing. This feature facilitates casing fill-up and may also be used for surge reduction.

NOTE This action may reduce surge pressures in the well that may otherwise be present if float valves remained closed during running of the casing.

3.3

float equipment

float equipment assembly

Casing accessories that contain one or more check valves and become part of the lower section of a casing string for the purpose of preventing the reverse flow of cement once placed in a wellbore annulus.