



IPC-4413
2023 - December
Specification for Finished Fabric
Woven from Low Dk Glass
for Printed Boards

An international standard developed by IPC



BUILD ELECTRONICS BETTER

IPC Mission

IPC is a global trade association dedicated to furthering the competitive excellence and financial success of its members, who are participants in the electronics industry.

In pursuit of these objectives, IPC will devote resources to management improvement and technology enhancement programs, the creation of relevant standards, protection of the environment, and pertinent government relations.

IPC encourages the active participation of all its members in these activities and commits to full cooperation with all related organizations.

About IPC Standards

IPC standards and publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for their particular need. Existence of such IPC standards and publications **shall not** in any respect preclude any entity from manufacturing or selling products not conforming to such IPC standards and publication, nor **shall** the existence of such IPC standards and publications preclude their voluntary use.

IPC standards and publications are approved by IPC committees without regard to whether the IPC standards or publications may involve patents on articles, materials or processes. By such action, IPC does not assume any liability to any patent owner, nor does IPC assume any obligation whatsoever to parties adopting an IPC standard or publication. Users are wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

The use and implementation of IPC standards and publications are voluntary and part of a relationship entered into by customer and supplier. When an IPC standard or publication is revised or amended, the use of the latest revision or amendment as part of an existing relationship is not automatic unless required by the contract. IPC recommends the use of the latest revision or amendment.

IPC Position Statement on Specification Revision Change

IPC welcomes comments for improvements to any standard in its library. All comments will be provided to the appropriate committee.

If a change to technical content is requested, data to support the request is recommended. Technical comments to include new technologies or make changes to published requirements should be accompanied by technical data to support the request. This information will be used by the committee to resolve the comment.

Standards Improvement Recommendations

To submit your comments, visit the IPC Status of Standardization page at www.ipc.org/status.



IPC-4413

Specification for Finished Fabric Woven from Low Dk Glass for Printed Boards

Developed by the Woven Glass Reinforcement Task Group (3-12D)
of the Base Materials General Committee 3-10 of IPC

Users of this publication are encouraged to participate in the
development of future revisions.

Contact:

IPC
3000 Lakeside Drive, Suite 105N
Bannockburn, Illinois
60015-1249
Tel 847 615.7100
Fax 847 615.7105

This Page Intentionally Left Blank

Acknowledgment

Any document involving a complex technology draws material from a vast number of sources across many continents. While the principal members of the 3-12D of the Woven Glass Reinforcement Task Group are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of the IPC extend their gratitude.

3-10 Base Materials General Committee

Chair
Steven Bowles
Lockheed Martin

3-12 D Woven Glass Reinforcement Task Group

Chair
Thomas Keily
JPS Composite Materials Corp.
Vice Chair
Bo Wang
BoTech Enterprises

Technical Liaisons of the IPC Board of Directors

Bob Neves
Microtek (Changzhou)
Laboratories

3-12D Woven Glass Reinforcement Task Group

Masahiro Awano
Nitto Boseki Co., Ltd.
Erik Bergum
Founder PCB USA
Albert B. Block
National Instruments
Gerald Leslie Bogert
Bechtel Plant Machinery Inc.
Jack Bramel
Jack Bramel & Associates
Ralph Buoniconti
Sabic
JianWei Cai
Shengyi Technology Co., Ltd.
Shrinvas Chada
General Dynamics Advanced
Information Systems.
Zhiman Chen
ZhuZhou CRRC Times Electric Co.
Ltd.
Brandon Davis
Northrup Grumman Space Systems
Don Dupriest
Lockheed Martin Missiles & Fire
Control
Steven R. Ethridge
Dell Inc.
Terry M. Fischer
Resonac America Inc.
Mahendra Gandhi
Northrup Grumman Space Systems
Stuart Hartfield
Daikin America, Inc.
Kohji Hattori
Unitika Fiber Co. Ltd.
Daniel Heitner
Glenair Inc.

Scott Hinaga
Cisco Systems Inc.
Darren Hitchcock
Panasonic Industrial Devices Sales
Company of America
Thomas Keily
JPS Composite Materials Corp.
Dana Korf
Nano Dimension
Raj Kumar
Northrup Grumman Space Systems
Kevin Kusiak
Lockheed Martin Corporation
Pierre Kuyll
Daikin America
Jeremy Lakoskey
Sierra Space
Christina Landon
Naval Surface Warfare Ctr
Emi Lee
Isola Group SARM
Minsu Lee
Korea Packaging Integration
Association
Doug Leys
AGC-MMA
Shenxing Liu
Shengyi Technology Co., Ltd.
John B. Marke
UL LLC
Jonathan McCarney
Albemarle Corporation
Graham Naisbitt
GEN3
Robert Neves
Microtek Laboratories China

Glenn Oliver
Lockheed Martin Missile & Fire
Control
Mark Reese
Arlon Electronic Materials
Enrique P. Sanchez
Cirexx International Inc.
Karl A. Sauter
Oracle America, Inc.
Tony R. Senese
Panasonic Industrial Device Sales
Company of America
Russell S. Shepherd
NTS Anaheim
Bhanu Sood
NASA Goddard Space Flight
Center
Ingrid Swenson
TTM Technologies, Inc.
Tsukasa Tawa
Asahi Kasei Corporation
Stephen L. Tisdale
Tisdale Environmental Consulting
LLC
Makoto Ueda
Nitto Boseki Co., Ltd.
Yuhei Urabayashi
Nitto Boseki Co., Ltd.
Crystal E. Vanderpan
UL LLC
Bo Wang
Botech Enterprises
John Wright
Arlon Electronic Materials
Jack Zhu
Veoneer China Co., Ltd.

This Page Intentionally Left Blank

Table of Contents

1	SCOPE	1		
1.2	Purpose.....	1	1.11.14.1 Broken Pick.....	3
1.3	Designation	1	1.11.14.2 Mis-picks.....	3
1.4	Classification.....	1	1.11.15 Plain Weave.....	3
1.5	Measurement Units.....	1	1.11.16 Splits	3
1.6	Definition of Requirements.....	1	1.11.17 Spread Glass Fabric	3
1.7	Process Control Requirements.....	1	1.11.18 Tears.....	3
1.8	Order of Precedence.....	1	1.11.19 TEX System.....	3
1.8.1	Conflict	2	1.11.20 Waste	3
1.8.2	Clause References	2	1.11.21 Waviness	3
1.8.3	Appendices.....	2	1.12 Yarn Nomenclature	3
1.8.3.1	Appendix A	2	1.12.1 US System.....	3
1.8.3.2	Appendix B	2	1.12.2 SI/Metric	4
1.8.3.3	Appendix C	2	1.12.3 Conversion from US System to SI.....	4
1.9	Use of “Lead”	2	2	APPLICABLE DOCUMENTS
1.10	Abbreviations and Acronyms.....	2	2.2	American Society for Testing and Materials
1.11	Terms and Definitions.....	2		(ASTM)
1.11.2	Bias Filling Yarns	2	2.3	International Standards
1.11.3	Bow Filling Yarns.....	2	2.4	National Conference of Standards Laboratories
1.11.4	Creases	2		(NCSL).....
1.11.5	Defects	2	3	REQUIREMENTS.....
1.11.5.1	Major Defect.....	2	3.2	Filament Diameter
1.11.5.2	Minor Defect.....	2	3.3	Bare Glass Nominal Measurement
1.11.5.3	Defect per Hundred Units	2	3.4	Chemical Requirements
1.11.6	Low Dk Glass (Electrical Grade Glass Fiber) ...	2	3.4.	1 Finish Level (Organic Content)
1.11.6.1	Permittivity (Dielectric Constant) for Base Low Dk Glass.....	2	3.5	Workmanship
1.11.6.2	Density	2	3.6	Alternate Fabric Styles and Weaves.....
1.11.7	End Missing	3	4	QUALITY ASSURANCE.....
1.11.8	Feather Length	3	4.2	Responsibility for Inspection
1.11.9	Fabric Finish	3	4.2.1	Test Equipment and Inspection Facilities
1.11.10	Fish Eye	3	4.2.2	Preparation of Samples
1.11.11	Leno End Out.....	3	4.2.3	Standard Laboratory Conditions.....
1.11.12	Lot or Batch Size	3	4.3	Inspection Requirements and Acceptability.....
1.11.13	Mark	3	4.3.1	Sample Size.....
1.11.13.1	Heavy Mark.....	3	4.3.2	Sampling Plans.....
1.11.13.2	Light Mark	3	4.3.3	Acceptable Quality Level (AQL).....
1.11.14	Pick	3	4.4	Test Methods
			4.4.1	Fabric Appearance.....

4.4.2	Fabric Count.....	8		
4.4.3	Weave Type.....	8		
4.4.4	Fabric Thickness.....	8		
4.4.5	Weight per Unit Area.....	9		
4.4.6	Fabric Length.....	9		
4.4.7	Fabric Width.....	9		
4.4.8	Finish Level (Organic Content).....	9		
4.4.9	Bias or Bowed Filling.....	9		
5	PREPARATION FOR DELIVERY.....	10		
5.2	Packing.....	10		
5.3	Marking.....	10		
6	NOTES.....	10		
6.2	New Styles.....	10		
	APPENDIX A.....	11		
	APPENDIX B.....	13		
	APPENDIX C.....	15		
			Tables	
	Table 3-1	Classification of Defects.....		5
	Table 3-2	Filament Diameter Designations.....		5
	Table 3-3	Nominal Length per Weight.....		6
	Table 4-1	Sample Size per Number of Rolls Shipped.....		7
	Table 4-2	Sample Size per Yardage of Individual Roll Shipped and the Acceptable Quality Level.....		7
	Table A1-1	Cross Reference to ISO Standards.....		11
	Table AI-2	Cross Reference Between IPC-4413, ASTM and ISO Documents.....		11
	Table BI-1	Finished Glass Styles for SI System.....		13
	Table BI-2	Finished Glass Styles for US System.....		14

This Page Intentionally Left Blank

This Page Intentionally Left Blank

Specification for Finished Fabric Woven from Low Dk Glass for Printed Boards

1 SCOPE

This specification covers finished fabrics woven from low Dk electrical grade glass fiber yarns that are intended as a reinforcing material in laminated plastics for electrical and electronic use. All fabrics covered by this specification are plain weave.

1.2 Purpose This specification determines the nomenclature, definitions, general and chemical requirements for the glass, and physical requirements for finished woven glass fiber fabrics.

1.3 Designation Appendix II of this standard provides a style designator for each finished fabric glass style, with specifications on yarn, fabric count, thickness and weight in both SI and US system. Fabrics listed in Appendix II also categorize fabrics by their current availability status.

1.4 Classification

CLASS 1 General Electronic Products Includes products suitable for applications where the major requirement is function of the completed assembly.

CLASS 2 Dedicated Service Electronic Products Includes products where continued performance and extended life is required, and for which uninterrupted service is desired but not critical. Typically, the end-use environment would not cause failures.

CLASS 3 High Performance/Harsh Environment Electronic Products Includes products where continued high performance or performance-on-demand is critical, equipment downtime cannot be tolerated, end-use environment may be uncommonly harsh, and the equipment must function when required, such as life support or other critical systems.

1.5 Measurement Units All dimensions and tolerances in this specification are expressed in hard SI (metric) units and bracketed soft imperial [inch] units. Users of this specification are expected to use metric dimensions. All dimensions ≥ 1 mm [0.0394 in] will be expressed in millimeters and inches. All dimensions < 1 mm [0.0394 in] will be expressed in micrometers and microinches.

1.6 Definition of Requirements The words **shall** or **shall not** are used in the text of this document wherever there is a requirement for materials, preparation, process control or acceptance.

The word “should” reflects recommendations and is used to reflect general industry practices and procedures for guidance only.

Line drawings and illustrations are depicted herein to assist in the interpretation of the written requirements of this Standard. The text takes precedence over the figures.

1.7 Process Control Requirements The primary goal of process control is to continually reduce variation in the processes, products, or services to provide products or processes meeting or exceeding User requirements. Process control tools such as IPC-9191, JESD557 or other User-approved system may be used as guidelines for implementing process control.

Manufacturers of Class 3 products **shall** develop and implement a documented process control system.

A documented process control system, if established, **shall** define process control and corrective action limits.

This may or may not be a statistical process control system. The use of “statistical process control” (SPC) is optional and should be based on factors such as design stability, lot size, production quantities, and the needs of the Manufacturer, see 4.1.

Process control methodologies **shall** be used in the planning, implementation and evaluation of the manufacturing processes used to produce soldered electrical and electronic assemblies. The philosophy, implementation strategies, tools and techniques may be applied in different sequences depending on the specific company, operation, or variable under consideration to relate process control and capability to end product requirements.

When a decision or requirement is to use a documented process control system, failure to implement process corrective action and/or the use of continually ineffective corrective actions would be grounds for disapproval of the process and associated documentation.

1.8 Order of Precedence The contract takes precedence over this Standard, referenced standards and drawings. In the event of conflict, the following order of precedence applies: