

# Lock Mandrels and Landing Nipples

API SPECIFICATION 14L  
THIRD EDITION, JUNE 2020



American  
Petroleum  
Institute

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

This specification is under the jurisdiction of the API SC19, Subcommittee on Completion Equipment.

Standards referenced herein may be replaced by other international or national standards that can be shown to meet or exceed the requirements of the referenced standard. Manufacturers electing to use another standard in lieu of a referenced standard are responsible for documenting equivalency.

The verbal forms used to express the provisions in this specification are as follows:

- the term “shall” denotes a minimum requirement in order to conform to the standard;
- the term “should” denotes a recommendation or that which is advised but not required in order to conform to the standard;
- the term “may” is used to express permission or a provision that is optional;
- the term “can” is used to express possibility or capability.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every 5 years. A one-time extension of up to 2 years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards and Publications Department, API, 1220 L Street, NW, Washington, DC 20005, [standards@api.org](mailto:standards@api.org).

## Contents

	Page
1	Scope..... 1
2	Normative References ..... 1
3	Terms and Definitions ..... 3
4	Abbreviated Terms ..... 6
5	Functional Specification ..... 6
5.1	General ..... 6
5.2	Functional Characteristics of Lock Mandrels and Landing Nipples ..... 7
5.3	Well Parameters ..... 7
5.4	Operational Parameters ..... 8
5.5	Environmental Compatibility ..... 8
5.6	Compatibility with the Related Well Equipment ..... 9
5.7	Design Validation Grades ..... 9
6	Technical Specification ..... 10
6.1	General ..... 10
6.2	Technical Characteristics of Lock Mandrels and Landing Nipples ..... 10
6.3	Design Criteria ..... 10
6.4	Design Verification ..... 13
6.5	Design Validation ..... 14
6.6	Design Changes ..... 21
6.7	Scaling Limits..... 21
6.8	Design Documentation ..... 22
7	Supplier/Manufacturer Requirements ..... 22
7.1	Documentation and Data Control ..... 22
7.2	User/Purchaser Documentation..... 22
7.3	Product Identification ..... 24
7.4	Quality Control ..... 24
7.5	Assembly Verification..... 32
8	Repair ..... 32
	Annex A (informative) API Monogram Program Use of the API Monogram by Licensees ..... 33
	Annex B (informative) Example of Landing Nipple Validation Test Dimensional Check Sheet ..... 37
	Annex C (informative) Requirements for Equipment in HPHT Environments ..... 38
	Bibliography..... 49

## Figures

1	Landing Nipple and Lock Mandrel Schematic ..... 7
B.1	Example of Landing Nipple Validation Test Dimensional Check Sheet ..... 37

## Contents

	Page
<b>C.1</b> HPHT Design Flowchart .....	43

### Tables

<b>1</b>	Validation Grades for Lock Mandrels .....	10
<b>2</b>	Validation Grades for Landing Nipples.....	10
<b>3</b>	Design Validation Grade Hierarchy.....	14
<b>4</b>	Landing Nipple V2 Validation Test .....	15
<b>5</b>	Lock Mandrel V2 Validation Test.....	16
<b>6</b>	Lock Mandrel V1 Validation Test.....	17
<b>7</b>	Lock Mandrel V0 Validation Test.....	19
<b>8</b>	Elastomer Material Specification Requirements .....	25
<b>9</b>	Thermoplastic Material Specification Requirements.....	25
<b>10</b>	Maximum Severity Level for Defects in Castings .....	30
<b>C.1</b>	Lock Mandrel Design Validation Hierarchy .....	38
<b>C.2</b>	Landing Nipple Design Validation Hierarchy.....	38
<b>C.3</b>	Lock Mandrel V1-H Validation Test .....	45

## Introduction

This specification has been developed by users/purchasers and suppliers/manufacturers of lock mandrels and landing nipples intended for use in the petroleum and natural gas industry worldwide. This specification is intended to give requirements and information to both parties in the selection, manufacture, testing, and use of lock mandrels and landing nipples. Furthermore, this specification addresses the minimum requirements with which the supplier/manufacturer is to comply to claim conformity to this specification.

This specification has been structured to allow for grades of increased requirements in design validation. These variations allow the user/purchaser to select the grade required for a specific application.

This edition has been revised to include one set of quality requirements. There are six design validation grades for lock mandrels (V3, V2, V1, V0, V1-H, and V0-H) and three design validation grades for landing nipples (V3, V2, and V2-H) that provide the user/purchaser the choice of requirements to meet specific preference or application. Design verification requirements were expanded. The complexity and severity of the validation testing increases as the grade number decreases.

Users of this specification should be aware that requirements above those outlined in this specification may be needed for individual applications. This specification is not intended to inhibit a supplier/manufacturer from offering, or the user/purchaser from accepting, alternative equipment or engineering solutions. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the supplier/manufacturer should identify any variations from this specification and provide details.

# Lock Mandrels and Landing Nipples

## 1 Scope

This specification provides the requirements for lock mandrels and landing nipples within the production/injection conduit for the installation of flow control or other equipment used in the petroleum and natural gas industries. It includes the interface connections to the flow control device or other equipment, but does not cover flow control devices, the connections to the well conduit, alternate technologies, or other requirements covered by other existing API or ISO specifications.

## 2 Normative References

The following referenced documents are indispensable for the application of this document. The way in which these referenced documents are cited determines the extent (in whole or part) to which they apply. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Specification 5B, *Specification for Threading, Gauging, and Thread Inspection of Casing, Tubing, and Line Pipe Threads*

API Technical Report 5C3, *Calculating Performance Properties of Pipe Used as Casing or Tubing, Seventh Edition*

API Specification 6A, *Specification for Wellhead and Tree Equipment*

API Specification 14A, *Specification for Subsurface Safety Valves*

API Specification 20A, *Carbon Steel, Alloy Steel, Stainless Steel, and Nickel Base Alloy Castings for Use in the Petroleum and Natural Gas Industry*

API 579-1/ASME FFS-1, *Fitness-For-Service*

API Specification Q1, *Specification for Quality Management System Requirements for Manufacturing Organizations for the Petroleum and Natural Gas Industry*

ANSI/NACE MR0175<sup>1</sup> /ISO 15156 (all parts), *Petroleum and natural gas industries—Materials for use in H<sub>2</sub>S-containing environments in oil and gas production*

ASME<sup>2</sup> Boiler and Pressure Vessel Code, Section V, *Non-destructive examination*

ASME Boiler and Pressure Vessel Code, Section VIII, Division 1, *Rules for construction of pressure vessels*

ASME Boiler and Pressure Vessel Code, Section VIII, Division 2, *Alternative Rules*

ASME Boiler and Pressure Vessel Code, Section IX, *Welding and Brazing Qualifications*

ASNT SNT-TC-1A,<sup>3</sup> *Personnel Qualification and Certification in Nondestructive Testing*

---

<sup>1</sup> NACE International (formerly the National Association of Corrosion Engineers), 1440 South Creek Drive, Houston, Texas 77084-4906, [www.nace.org](http://www.nace.org).

<sup>2</sup> American Society of Mechanical Engineers, Two Park Avenue, New York, New York 10016-5990, [www.asme.org](http://www.asme.org).

<sup>3</sup> American Society for Nondestructive Testing, PO Box 28518, 1711 Arlingate Lane, Columbus, Ohio 43228-0518, USA.