

Inspection and Classification of Used Drill Stem Elements

API RECOMMENDED PRACTICE 7G-2
SECOND EDITION, OCTOBER 2020



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC, 20001.

Copyright © 2020 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this standard are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This standard was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

1	Scope.....	1
2	Normative References	1
3	Terms, Definitions, Symbols, and Abbreviations	1
3.1	Terms and Definitions	1
3.2	Symbols	7
3.3	Abbreviations	8
4	General Figures	9
5	Conformance	10
5.1	Basis for Inspection.....	10
5.2	Repeatability of Results	11
6	Quality Assurance.....	12
6.1	General	12
6.2	Standardization and Operating Procedures.....	12
6.3	Equipment Description.....	12
6.4	Personnel Qualification.....	12
6.5	Dynamic Test Data Demonstrating the System Capabilities for Detecting the Reference Indicators.....	12
6.6	Reports.....	12
7	Qualification of Inspection Personnel	12
7.1	General	13
7.2	Written Procedure	13
7.3	Qualification Responsibility and Requirements	13
7.4	Training Programs	13
7.5	Examinations	13
7.6	Experience	14
7.7	Requalification	14
7.8	Documentation	14
7.9	NDT Personnel Certification	14
8	General Inspection Procedures	14
8.1	General	15
8.2	Owner/Operator Work Site Requirements for Quality Inspection.....	15
8.3	Documents at Job Site	15
8.4	Pre-inspection Procedures	15
8.5	Drill Pipe and Tool Joint Classification Markings	16
8.6	Post-inspection Procedures	16
9	General Nondestructive Inspection Method Requirements	20
9.1	General	20
9.2	Equipment.....	20
9.3	Illumination	21
9.4	Magnetic Particle Inspection Equipment.....	22
9.5	Ultrasonic Inspection Equipment.....	25
9.6	Electromagnetic Inspection Units	25
10	Drill Stem Element Inspection and Classification	25
10.1	Pipe Body—Full-length Visual Inspection.....	25
10.2	Drill Body—OD Gauging.....	26
10.3	Pipe Body—Ultrasonic Wall-thickness Gauging	28
10.4	Pipe body—Full-length EMI	31
10.5	Pipe Body—Full-length Ultrasonic Transverse and Wall Thickness	32

10.6	Pipe Body—Full-length Ultrasonic Transverse, Wall Thickness, and Longitudinal Inspection	35
10.7	Drill Pipe Body—External Magnetic Particle Inspection of the Critical Area.....	39
10.8	Drill Pipe Body—Bidirectional External Magnetic Particle Inspection of the Critical Area	42
10.9	Pipe Body—Full-length Wall-loss Inspection	45
10.10	Pipe Body—Ultrasonic Inspection of the Critical Area	47
10.11	Pipe Body—Calculation of Cross-sectional Area.....	51
10.12	Pipe Body—Document Review (Traceability)	52
10.13	Pipe Body—Evaluation and Classification.....	53
10.14	Tool Joints	57
10.15	Tool Joints—Check for Box Swell and Pin Stretch	62
10.16	Repair of Rejected Tool Joints	64
10.17	Tool Joints—Check Tool Joint Pin, Box OD, and Eccentric Wear.....	64
10.18	Tool Joints—Measure Tool Joint Pin and Box OD and Check for Eccentric Wear.....	66
10.19	Tool Joints—Check Tool Joint Pin and Box Tong Space.....	67
10.20	Tool Joints—Measure Tool Joint Pin and Box Tong Space	68
10.21	Tool Joint—Magnetic Particle Inspection of the Pin Threads	69
10.22	Tool Joint—Magnetic Particle Inspection of Box Threads	71
10.23	Tool Joints—Measure Tool Joint Pin ID	73
10.24	Magnetic Particle Inspection of the Connection OD for Heat-check Cracking.....	74
10.25	Bidirectional Wet Magnetic Particle Inspection of the Connection OD for Heat-check Cracking	75
10.26	Tool Joints—Measure the Tool Joint Counterbore Depth, Pin-base Length, Seal Width, Check Shoulder Flatness, Taper Contact Angle, and Seal Shoulder Flatness	79
10.27	BHA Connection—Visual Inspection of Bevels, Seals, Threads, and Stress-relief Features	80
10.28	BHA—Measure Box OD, Pin ID, Counterbore Diameter, and Benchmark Location if a Benchmark Is Present	83
10.29	BHA—Check Bevel Diameter	85
10.30	BHA—Measure Bevel Diameter	86
10.31	BHA—Magnetic Particle Inspection of the Pin and Box Threads	87
10.32	BHA Connection—Liquid Penetrant Inspection of the Pin and Box Threads	89
10.33	BHA—Dimensional Measurement of Stress-relief Features.....	91
10.34	Length Measurements of the Counterbore, Pin, and Pin Neck.....	93
10.35	Drill Collar—Visual Full-length OD and ID, Markings, Fish-neck Length, and Tong Space.....	95
10.36	Drill Collar Elevator Groove and Slip Recess Magnetic Particle Inspection	96
10.37	Drill Collar Elevator-groove and Slip-recess Measurement	98
10.38	Subs (Full-length Visual OD and ID), Fish-neck Length, Section-change Radius, and Markings	100
10.39	Float-bore Recess Measurements.....	101
10.40	Magnetic Particle Inspection of Subs—Full-length, Internal, and External	102
10.41	HWDP—Visual Full-length OD and ID, Markings, and Tong Space	104
10.42	Visual Inspection and Wear Pattern Report for Kelly	105
10.43	Magnetic Particle Evaluation of Critical Areas on Kellys	107
10.44	Magnetic Particle Evaluation, Full-length, of the Drive Section on Kellys.....	108
10.45	Stabilizer (Full-length Visual OD and ID), Fish-neck Length, Blade Condition, Ring Gauge, and Markings.....	108
10.46	Magnetic Particle Inspection of the Base of Stabilizer Blades for Cracking	110
10.47	Function Test.....	111
10.48	Bidirectional, Wet Magnetic Particle Inspection of the Base of Stabilizer Blade for Cracking	112
10.49	Visual Inspection of Jars (Drilling and Fishing), Accelerators, and Shock Subs	115
10.50	Maintenance Review	116
10.51	Dimensional Measurement of Wear Areas as Specified by OEM Requirements	117

10.52	OEM-designated Testing for Used Equipment	117
10.53	MWD/LWD—Visual, Full-length OD and ID, and Markings (Including Visual Inspection of Hard-banding and Coatings)	118
10.54	Motors and Turbines—Visual, Full-length OD and ID, and Markings (Including Visual Inspection of Hard-banding and Coatings)	119
10.55	Reamers, Scrapers, and Hole Openers—Visual, Full-length OD and ID, and Markings (Including Visual Inspection of Hard-banding and Coatings)	120
10.56	Rotary Steerable—Visual, Full-length OD and ID, and Markings (Including Visual Inspection of Hard-banding)	121
10.57	Full-length Drift	122
10.58	Proprietary Equipment Inspection	124
10.59	Hard-banding Inspection.....	125
10.60	Transverse Magnetic Particle Inspection of Tool Joint OD and ID under the Pin Threads	128
10.61	Drill Pipe Body—Internal Magnetic Particle Inspection of the Critical Area.....	130
10.62	Drill Pipe Body—Bidirectional, Internal Magnetic Particle Inspection of the Critical Area	132
10.63	API External Upset-thread Connection Inspection.....	133
Annex A	(normative) Original Equipment Manufacturer Requirements.....	136
Annex B	(normative) Required and Additional Inspections by Product and Class of Service	138
Annex C	(normative) SI Units	149
Annex D	(normative) USC Units.....	178
Annex E	(informative) Inspection Level Guidelines	206
Annex F	(informative) Proprietary Drill Stem Connection Inspection.....	210
Annex G	(informative) Used Work String Tubing Proprietary Connection Thread Inspection	215
Bibliography	217

Figures

1	Drill Pipe Nomenclature	9
2	Last Engaged Threads	10
3	Drill Pipe and Tool Joint Color Code Identification	19
4	Ultrasonic End-area Inspection—Effective Length.....	49
5	Pin-base Identification Markings	58
6	Tool Joint Slot and Groove Marking System.....	58
7	Lead Gauge Check on Pin Threads	64
8	Tool Joint Classification Measurements.....	66
9	Pin Measurement Areas	80
10	Box Measurement Areas.....	84
11	Low-torque Connection	85
12	Stress-relief Groove	92
13	Boreback Box.....	92
14	Location of Last Full-depth Thread	94
15	Pin-base Length.....	94
16	Elevator and Slip Groove	99
17	Float-bore recess.....	102
18	Measurement of Kelly Wear-pattern Angle	107

Tables

B.1	Pipe-body Field Inspection Available for Used Drill Pipe.....	138
B.2	Used Tool Joint Field Inspections Available	139
B.3	BHA Connection Field Inspections Available.....	140
B.4	Drill Collar Inspections Available (Other Than Connections).....	140

B.5	Sub Inspections Available (Other Than Connections)	141
B.6	HWDP Inspections Available (Other Than Connections)	141
B.7	Kelly/Top Drive Inspections Available (Other Than Connections)	141
B.8	Stabilizer Inspections Available (Other Than Connections)	142
B.9	Jar (Drilling and Fishing), Accelerator, and Shock Sub Inspections Available (Other Than Connections)	142
B.10	MWD/LWD Inspections Available (Other Than Connections)	143
B.11	Motor and Turbine Inspections Available (Other Than Connections)	143
B.12	Reamer, Scraper, and Hole-opener Inspections Available (Other Than Connections)	144
B.13	Rotary Steerable Equipment Inspections Available (Other Than Connections)	144
B.14	Proprietary Equipment Inspections Available (Other Than Connections)	145
B.15	Used Work String Tubing	145
B.16	Pin-base Marking System	146
B.17	Pipe Manufacturer and Processor Symbols	146
B.18	Classification of Used Drill Pipe	147
B.19	Classification of Used Work String Tubing	148
C.1	Longitudinal Magnetizing Force for ID Inspections	149
C.2	Current Requirements of Internal-conductor Magnetization	149
C.3	Compensated Thread Lengths and Contact-point Size for Lead Measurements Parallel to Taper Cone	150
C.4	Dimensional Values for Classification of Drill Pipe Tubes	151
C.5	Dimensional Values for Classification of Used Work String Tubing	152
C.6	Used Tool Joint Criteria	153
C.7	Tool Joint Connection Dimensional Requirements	157
C.8	Used Tool Joint Bevel Diameters	158
C.9	Drill Collar Connection Dimensions (Without Stress-relief Features)	159
C.10	Dimensional Limits on Used BHA Connections with Stress-relief Features	161
C.11	Used Drill Collar Bevel Diameters	162
C.12	Bending-strength Ratios for BHAs	167
C.13	Drill Collar Elevator Groove and Slip Recess	172
C.14	Float-valve Recess in Bit Subs	172
C.15	Used Bit-box and Bit-bevel Diameters	173
C.16	API Work String Tubing EUE Connection Criteria	173
C.17	Tool Joint Mass per Meter for Various OD/ID Combinations	174
C.18	Drill Collar Mass per Meter for Various OD/ID Combinations	176
D.1	Longitudinal Magnetizing Force for ID Inspections	178
D.2	Current Requirements of Internal-conductor Magnetization	178
D.3	Compensated Thread Lengths and Contact-point Size for Lead Measurements Parallel to Taper Cone	179
D.4	Dimensional Values for Classification of Drill Pipe Tubes	180
D.5	Dimensional Values for Classification of Used Work String Tubing	181
D.6	Used Tool Joint Criteria	182
D.7	Tool Joint Connection Dimensional Requirements	186
D.8	Used Tool Joint Bevel Diameter	187
D.9	Drill Collar Connection Dimensions (Without Stress-relief Features)	188
D.10	Dimensional Limits on Used BHA Connections with Stress-relief Features	190
D.11	Used Drill Collar Bevel Diameters	191
D.12	Bending-strength Ratios for BHAs	195
D.13	Drill Collar Elevator Groove and Slip Recess	200
D.14	Float-valve Recess in Bit Subs	200
D.15	Used Bit-box and Bit-bevel Diameters	201
D.16	API Work String Tubing EUE Connection Criteria	201
D.17	Tool Joint Mass per Foot for Various OD/ID Combinations	202
D.18	Drill Collar Mass per Meter for Various OD/ID Combinations	204
E.1	Inspection Levels	206

Inspection and Classification of Used Drill Stem Elements

1 Scope

This standard specifies the required inspection for each level of inspection, procedures for the inspection, and testing of used drill stem elements. For the purposes of this standard, drill stem elements include drill pipe body, tool joints, rotary shouldered connections, drill collar, heavy-weight drill pipe (HWDP), and the ends of drill stem elements that make up with them.

This standard also specifies the qualification of inspection personnel, a description of inspection methods and apparatus calibration, and standardization procedures for various inspection methods. The evaluation of imperfections and the marking of inspected drill stem elements is included.

This standard provides information for the evaluation of imperfections, the marking of inspected drill stem elements, and the requirements regarding the minimum information needed for the inspection of original equipment manufacturers' (OEM's) specialized tools.

2 Normative References

The following referenced standards are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced standard (including any addenda/errata) applies.

API Specification 5DP, *Drill Pipe*

API Specification 7-1, *Rotary Drill Stem Elements*

API Specification 7-2, *Threading and Gauging of Rotary Shouldered Thread Connections*

API Recommended Practice 5A3, *Thread Compounds for Casing, Tubing, Line Pipe, and Drill Stem Elements*

3 Terms, Definitions, Symbols, and Abbreviations

3.1 Terms and Definitions

For the purposes of this standard, the following terms and definitions apply.

3.1.1

agency

Entity contracted to inspect used drill stem elements using the methods and criteria specified.

3.1.2

A-scan

Ultrasonic instrument display where distance is represented on the horizontal axis and signal strength on the vertical axis.

3.1.3

bending-strength ratio

Ratio of the section modulus of the box thread at its last engaged thread to the pin thread at its last engaged thread.