

Sizing, Selection, and Installation of Pressure-relieving Devices

Part I—Sizing and Selection

API STANDARD 520
TENTH EDITION, AUGUST 2020

ERRATA 1, MAY 2023



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this standard should consult with the appropriate authorities having jurisdiction.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the standard. At all times users should employ sound business, scientific, engineering, and judgment safety when using this standard.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, Suite 1100, Washington, DC.

Foreword

API Standard 520, *Sizing, Selection, and Installation of Pressure-relieving Devices*, is the result of several years' work by engineers in the petroleum industry. The information in this standard is intended to supplement the information contained in Section VIII—*Pressure Vessels*, of the ASME *Boiler and Pressure Vessel Code*. The recommendations presented in this publication are not intended to supersede applicable laws and regulations.

Users of this standard are reminded that no publication of this type can be complete, nor can any written document be substituted for qualified engineering analysis.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, "may" denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, "can" denotes a statement of possibility or capability.

The current edition of this standard, published in two parts, has been updated with respect to the practices generally used in the installation of all devices covered in the previous editions; the current edition also contains additional information based on revisions suggested by many individuals and several organizations.

The First Edition of this standard was initially released as a recommended practice in 1955. The Second Edition was published in two parts: Part I, *Design*, in 1960 and Part II, *Installation*, in 1963. The Third Edition of Part I was issued in November 1967 and reaffirmed in 1973. The Fourth Edition was issued in December 1976, the Fifth Edition was issued in July 1990, the Sixth Edition was issued in March 1993, the Seventh Edition was issued in January 2000, the Eighth Edition was issued in December 2008, and the Ninth Edition was issued in July 2014.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

1	Scope	1
2	Normative References	1
3	Terms, Definitions, Acronyms, and Abbreviations	2
3.1	Terms and Definitions	2
3.2	Acronyms and Abbreviations	8
4	Pressure-relief Devices	8
4.1	General	8
4.2	Pressure-relief Valves	8
4.3	Rupture Disk Devices	34
4.4	Pin-actuated Devices	52
4.5	Open Flow Paths or Vents	54
4.6	Other Types of Devices	54
5	Procedures for Sizing	54
5.1	Determination of Relief Requirements	54
5.2	API Effective Area and Effective Coefficient of Discharge	55
5.3	Backpressure	56
5.4	Relieving Pressure	61
5.5	Development of Sizing Equations	66
5.6	Sizing for Gas or Vapor Relief	67
5.7	Sizing for Steam Relief	84
5.8	Sizing for Liquid Relief: Pressure-relief Valves Requiring Capacity Certification	91
5.9	Sizing for Liquid Relief: Pressure-relief Valves Not Requiring Capacity Certification	95
5.10	Special Considerations for Non-Newtonian Fluids	96
5.11	Sizing for Two-phase Liquid/Vapor Relief	97
5.12	Sizing for Rupture Disk Devices	97
5.13	Sizing for Open Flow Paths or Vents	98
Annex A	(informative) Rupture Disk Device Specification Sheet	99
Annex B	(informative) Review of Flow Equations Used in Sizing Pressure-relief Devices	104
Annex C	(informative) Sizing for Two-phase Liquid/Vapor Relief	125
Annex D	(informative) Pressure-relief Valve Specification Sheets	147
Annex E	(informative) Capacity Evaluation of Rupture Disk and Piping System 100 % Vapor Flow and Constant Pipe Diameter	157
Annex F	(informative) Valve Selection Example: Restricted Lift	163
	Bibliography	164

Figures

1	Conventional Pressure-relief Valve with a Single Adjusting Ring for Blowdown Control	10
2	Balanced-bellows Pressure-relief Valve	11
3	Balanced-bellows Pressure-relief Valve with an Auxiliary Balanced Piston	12
4	Conventional Pressure-relief Valve with Threaded Connections	13
5	Pressure-relief Valve Operation—Vapor/Gas Service	14
6	Typical Relationship Between Lift of Disk in a Pressure-relief Valve and Vessel Pressure	15
7	Pressure-relief Valve Operation—Liquid Service	16
8	Typical Effects of Superimposed Backpressure on the Opening Pressure of Conventional Pressure-relief Valves	18
9	Typical Effects of Backpressure on the Set Pressure of Balanced Pressure-relief Valves	19

10	Pop-action Pilot-operated Valve (Flowing Type)	23
11	Pop-action Pilot-operated Valve (Nonflowing Type)	24
12	Modulating Pilot-operated Valve (Flowing Type).....	25
13	Pilot-operated Relief Valve with a Nonflowing Modulating Pilot Valve	26
14	Low-pressure Pilot-operated Valve (Diaphragm Type)	27
15	Pressure Level Relationships for Pressure-relief Valves	28
16	Typical Relationship Between Lift of Disk or Piston and Vessel Pressure in a Pop-action Pilot-operated Pressure-relief Valve	29
17	Typical Relationship Between Lift of Disk or Piston and Vessel Pressure in a Modulating-action Pilot-operated Pressure-relief Valve	30
18	Different Options for Restricting Lift in Spring-loaded Pressure-relief Valves	33
19	Pressure Level Relationships for Rupture Disk Devices.....	35
20	Rupture Disk Device in Combination with a Pressure-relief Valve.....	36
21	Forward-acting Solid Metal Rupture Disk.....	39
22	Forward-acting Scored Rupture Disk	40
23	Forward-acting Composite Rupture Disk.....	41
24	Reverse-acting Rupture Disk with Knife Blades.....	42
25	Reverse-acting Scored Rupture Disk.....	44
26	Graphite Rupture Disk.....	45
27	Rupture Disk Application Parameters Assuming No Superimposed Backpressure	48
28	Common Types of Manufacturing Ranges and Corresponding Burst Pressure Marking	49
29	Rupture Disk Application Parameters with Superimposed Backpressure	51
30	Buckling Pin Valve	53
31	Backpressure Correction Factor, K_b , for Balanced Spring-loaded Pressure-relief Valves (Vapors and Gases).....	59
32	Capacity Correction Factor, K_w , Due to Backpressure on Balanced Spring-loaded Pressure-relief Valves in Liquid Service.....	60
33	Curve for Evaluating Coefficient C in the Flow Equation from the Specific Heat Ratio, Assuming Ideal Gas Behavior (USC Units)	74
34	Curve for Evaluating Coefficient C in the Flow Equation from the Specific Heat Ratio, Assuming Ideal Gas Behavior (SI Units)	75
35	Sample of Completed Pressure-relief Valve Specification Sheet	77
36	Values for F_2 for Subcritical Flow	80
37	Constant Backpressure Correction Factor, K_b , for Conventional Pressure-relief Valves	93
38	Capacity Correction Factor, K_v , Due to Viscosity.....	93
39	Capacity Correction Factors Due to Overpressure for Noncertified Pressure-relief Valves in Liquid Service	95
A.1	Rupture Disk Device Specification Sheet.....	103
C.1	Correlation for Nozzle Critical Flow of Flashing and Nonflashing Systems.....	134
C.2	Correlation for Nozzle Critical Flow of Inlet Subcooled Liquid	140
C.3	Backpressure Correction Factor, K_b , for Balanced-bellows Pressure-relief Valves (Liquids)	143
D.1	Spring-loaded Pressure-relief Valve Specification Sheet.....	151
D.2	Pilot-operated Pressure-relief Valve Specification Sheet.....	156
E.1	Pressure-relief System for Example Problem	161
E.2	Curve Fit for $C_p/C_v = 1.4$ (Crane 410, Chart A-22).....	162
Tables		
1	Spring-loaded Pressure-relief Valve Performance Characteristics as a Function of Valve Trim	21
2	Design Guidance for Pressure-relief Valve Trim Options.....	22
3	Example of Allowable Backpressures for a Multiple Conventional Pressure-relief Valve Installation.....	58
4	Set Pressure and Accumulation Limits for Pressure-relief Devices	62

5	Example Determination of Relieving Pressure for Operating Contingencies for a Single Relief Device Installation	63
6	Example Determination of Relieving Pressure for Operating Contingencies for a Multiple Relief Device Installation	64
7	Example Determination of Relieving Pressure for Fire Contingencies for a Single Relief Device Installation.....	65
8	Example Determination of Relieving Pressure for Fire Contingencies for a Multiple Relief Device Installation.....	66
9	Example Determination of Relieving Pressure for Fire Contingencies for a Supplemental Valve Installation	67
10	Properties of Gases	70
11	Values of Coefficient C	73
12	Superheat Correction Factors, K_{SH} (USC Units).....	86
13	Superheat Correction Factors, K_{SH} (SI Units)	88
A.1	Rupture Disk Device Specification Sheet Instructions	99
B.1	Results for Supercritical Fluid Example Problem B.1.3.....	108
B.2	Results for Subcooled Liquid Example Problem B.2.2	111
B.3	Results for Gas Example Problem B.3.3.....	120
C.1	Two-phase Liquid/Vapor Relief Scenarios for Pressure-relief Valves	125
C.2	Results for Direct Integration Example C.2.1.2	132
D.1	Instructions for Spring-loaded Pressure-relief Valve Specification Sheet	147
D.2	Instructions for Pilot-operated Pressure-relief Valve Specification Sheet	152
E.1	Determination of Overall Piping Resistance Factor, K	158

Sizing, Selection, and Installation of Pressure-relieving Devices

Part I—Sizing and Selection

1 Scope

This standard applies to the sizing and selection of pressure-relief devices (PRDs) used in refineries, chemical facilities, and related industries for equipment that has a maximum allowable working pressure (MAWP) of 15 psig (103 kPag) or greater. The pressure-relief devices covered in this standard are intended to protect unfired pressure vessels and related equipment against overpressure from operating and fire contingencies.

This standard includes basic definitions and information about the operational characteristics and applications of various pressure-relief devices. It also includes sizing procedures and methods based on steady-state flow of Newtonian fluids.

Pressure-relief devices protect a vessel against overpressure only; they do not protect against structural failure when the vessel is exposed to extremely high temperatures such as during a fire. See API 521 for information about appropriate ways of reducing pressure and restricting heat input.

Atmospheric and low-pressure storage tanks covered in API 2000 and pressure vessels used for the transportation of products in bulk or shipping containers are not within the scope of this standard.

The rules for overpressure protection of fired vessels are provided in ASME *BPVC*, Section I and are not within the scope of this standard.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Standard 520, *Sizing, Selection, and Installation of Pressure-relieving Devices, Part II—Installation*

API Standard 521, *Pressure-relieving and Depressuring Systems*

API Standard 526, *Flanged Steel Pressure-relief Valves*

API Standard 527, *Seat Tightness of Pressure-relief Valves*

API Standard 2000, *Venting Atmospheric and Low-pressure Storage Tanks*

ASME *Boiler and Pressure Vessel Code (BPVC)* ¹, *Section I: Power Boilers*

ASME *Boiler and Pressure Vessel Code (BPVC)*, *Section VIII: Pressure Vessels, Division 1: Rules for Construction of Pressure Vessels*

ASME *Boiler and Pressure Vessel Code (BPVC)* Code Case 2203 ², *Omission of Lifting Device Requirements for Pressure Relief Valves on Air, Water Over 140 °F, or Steam Service*

ASME B31.1, *Power Piping*

ASME B31.3, *Process Piping*

ASME PTC 25, *Pressure Relief Devices*

¹ American Society of Mechanical Engineers, Two Park Avenue, New York, New York 10016, www.asme.org.

² Code Cases are temporary in nature and may not be acceptable in all jurisdictions. The user should verify the current applicability of the referenced Code Cases.