

# Subsurface Completion Isolation (Barrier) Valves and Related Equipment

API SPECIFICATION 19V  
SECOND EDITION, MAY 2019

ERRATA 1, SEPTEMBER 2019



AMERICAN PETROLEUM INSTITUTE

**Date of Issue:** September 2019

**Affected Publication:** API Specification 19V, *Subsurface Completion Isolation (Barrier) Valves and Related Equipment*, Second Edition, May 2019

## **Errata 1**

*Section 1.2.2: The third paragraph shall be replaced with the following:*

When FEA has identified plastic strain in excess of 0.2 %, a ratcheting analysis shall be performed per ASME BPVC, Section VIII, Division 3, Article KD-234, or ASME BPVC, Section VIII, Division 2, Section 5.5.7. The material performance data shall be obtained via testing performed as defined in section 1.2.4.

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

# Contents

	Page
1 Scope .....	1
2 Normative References .....	1
3 Terms and Definitions .....	3
4 Acronyms.....	9
5 Functional Requirements .....	9
5.1 General.....	9
5.2 Functional Characteristics .....	11
5.3 Well Parameters .....	12
5.4 Operational Parameters .....	12
5.5 Environmental Compatibility .....	12
5.6 Compatibility with Related Well Equipment .....	13
5.7 Optional User/Purchaser Selected Requirements.....	13
6 Technical Specification .....	14
6.1 General.....	14
6.2 Technical Characteristics.....	14
6.3 Design Criteria .....	14
6.4 Materials.....	15
6.5 Performance Envelope .....	18
6.6 Design Documentation .....	18
6.7 Design Verification.....	19
6.8 Design Validation.....	20
6.9 Design Changes .....	20
6.10 Functional Test .....	22
6.11 Final Design Review and Approval.....	22
7 Supplier/Manufacturer Requirements.....	22
7.1 General.....	22
7.2 Documentation .....	22
7.3 Product Identification .....	24
7.4 Quality Requirements .....	25
7.5 Material Documentation .....	26
7.6 Additional Processes .....	26
7.7 Traceability .....	27
7.8 Quality Controls .....	27
7.9 Shear-device Validation.....	32
7.10 Assembly and Functional Test.....	32
7.11 Manufacturing Nonconformities.....	32
8 Handling, Storage, and Preparation for Transport.....	32
9 Repair/Redress .....	33
Annex A (informative) SCIV Type Descriptions and Applications Overview .....	34
Annex B (normative) Validation Requirements for SCIVs .....	37

## Contents

	Page
Annex C (normative) Functional Testing.....	47
Annex D (normative) Validation Requirements for SCIV Tools.....	50
Annex E (normative) Performance Envelopes .....	52
Annex F (informative) Alternate (Barrier) Leakage Test Acceptance Criteria .....	54
Annex G (informative) Debris-settling Design Validation.....	56
Annex H (informative) Closure While Flowing Slurry Test.....	59
Annex I (normative) High-pressure High-temperature Requirements .....	60
Annex J (informative) API Monogram Program Use of the API Monogram by Licensees.....	66
Bibliography.....	70

## Figures

E.1 Example Performance Envelope .....	53
--	----

## Tables

1 Annex Applicability Summary .....	9
2 SCIV Types.....	10
3 SCIV Validation Grade Summary .....	11
4 SCIV Quality Levels .....	11
5 Thermoplastic Material Properties.....	18
6 Quality Level Requirements for QL1 and QL2 .....	25
7 Inspection Sample Size .....	29
B.1 Slurry Flow Rates .....	46

## Introduction

This specification has been developed by user/purchasers and supplier/manufacturers of SCIVs and related equipment as defined herein and is intended for use in the petroleum and natural gas industry worldwide to give requirements and information to both parties in the selection, manufacture, testing, and use. Further, this specification addresses the minimum requirements with which the supplier/manufacturer is to comply so as to claim conformity with this specification.

This specification has been structured with six different types of SCIVs. This differentiation is due to the range of product functionality, such as the direction in which pressure is held and its use in pre- or post-production/injection operations.

This specification has been structured with grades of increased requirements in quality control and design validation. These grades allow the user/purchaser to select the level of requirements for a specific application.

There are two quality levels: QL2 is the minimum grade of quality offered by this specification and QL1 is the highest grade provided. Additional quality requirements can be specified by the user/purchaser as supplemental requirements.

There are four design validation grades, which provide the user/purchaser with a choice of requirements to meet their preference or application. V3 is the minimum grade and V1 is the most stringent grade provided. V1H is for HPHT applications.

Annexes B, C, D, E, and I are normative, and Annexes A, F, G, H, and J are informative. Table 1 provides a summary of the applicability of the annexes included within this specification.

The International System of Units (SI) is used in this specification; however, US Customary (USC) or other units are also shown for reference.

It is required that users of this specification be aware that requirements beyond those outlined in this specification can be needed for individual applications. This specification is not intended to inhibit a supplier/manufacturer from offering, or the user/purchaser from accepting, alternative equipment or engineering solutions. This can be particularly applicable where there is innovative or developing technology. Where an alternative is offered, it is the responsibility of the supplier/manufacturer to identify any variations from this specification and provide details.

# Subsurface Completion Isolation (Barrier) Valves and Related Equipment

## 1 Scope

This specification provides the requirements for subsurface completion isolation (barrier) valves (SCIV) and related equipment as they are defined herein for use in the petroleum and natural gas industries. Included are the requirements for design, design validation grades, quality levels, manufacturing, functional evaluation, repair, redress, handling, and storage. SCIVs provide a means of isolating the formation or creating a blockage in the tubular to facilitate the performance of pre- and/or post-production/injection operational activities in the well.

Additional requirements for HPHT products are included in Annex I.

When closed, the SCIV provides an obstacle or impediment to flow and/or pressure from above and/or below and a means of isolating the formation within a conduit. The SCIV is not designed as an emergency or fail-safe flow-controlling safety device.

This specification does not cover installation and maintenance, control systems such as computer systems, and control conduits not integral to the SCIV. Also not included are products covered under ISO 17078, ISO 16070, ISO 14310, ISO 10432, ISO 10423, and the following products: downhole chokes, wellhead plugs, sliding sleeves, casing-mounted flow-control valves, injection valves, well-condition-activated valves, or drill-stem test tools. This specification does not cover the end connections to the well conduit.

## 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API<sup>1</sup> Technical Report 5C3, *Calculating Performance Properties of Pipe Used as Casing or Tubing, Annex A*

API Specification 20A, *Carbon Steel, Alloy Steel, Stainless Steel, and Nickel Base Alloy Castings for Use in the Petroleum and Natural Gas Industry*

API. *Manual of Petroleum Measurement Standards Chapter 10.4, Determination of Sediment and Water in Crude Oil by the Centrifuge Method (Field Procedure)*

API Specification Q1, *Specification for Quality Management System Requirements for Manufacturing Organizations for the Petroleum and Natural Gas Industry*

ANSI/NACE MR0175-2015/ISO 15156, *Petroleum and natural gas industries – Materials for use in H<sub>2</sub>S-containing environments in oil and gas production*

ASME<sup>2</sup> Boiler and Pressure Vessel Code (BPVC), Section II, *Materials Specification—Part D: Properties*

ASME. Boiler and Pressure Vessel Code (BPVC), Section VIII, *Rules for Construction of Pressure Vessels—Division 1, UW-40: Procedures for Post-weld Heat Treatment*

ASME. Boiler and Pressure Vessel Code (BPVC), Section VIII, *Rules for Construction of Pressure Vessels—Division 2, Part 5: Design by Analysis*

ASME. Boiler and Pressure Vessel Code (BPVC), Section VIII, *Rules for Construction of Pressure Vessels—Division 3: Alternative Rules for Construction of High Pressure Vessels*

---

<sup>1</sup> American Petroleum Institute, 200 Massachusetts Avenue, Washington, DC 20001, [www.api.org](http://www.api.org).

<sup>2</sup> American Society for Mechanical Engineers, 2 Park Avenue, New York, New York 10016, [www.asme.org](http://www.asme.org).