

Inspection, Assessment, and Repair of Coke Drums and Peripheral Components in Delayed Coking Units

API TECHNICAL REPORT 934-J
(COMPLEMENTS API TECHNICAL REPORT 934-G)
FIRST EDITION, SEPTEMBER 2021



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001.

Copyright © 2021 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

Page

1	Scope	1
2	Background	1
2.1	References	1
2.2	Terms and Definitions	4
2.3	Acronyms and Abbreviations	6
3	Inspection and Monitoring of Coke Drums	7
3.1	General	7
3.2	Inspection for Cracks	7
3.3	Inspecting for Bulges	23
3.4	Inspecting for Metal Loss and Cladding Damage	28
3.5	Monitoring for Drum Bowing, Tilting, and Lift at the Base	29
3.6	Use of Strain Gauges and Shell Temperature Measurements to Monitor Drum Damage	32
3.7	Frequency of Inspection	32
4	Damage Assessment	36
4.1	Thermal-mechanical Loading of Coke Drums	36
4.2	Shell Cracking	36
4.3	Shell Bulging	37
4.4	Corrosion and Erosion	38
4.5	Skirt Cracking and Distortion	39
4.6	Overheating Damage (Fire Damage)	39
4.7	Fatigue Life	39
5	Welding Associated with Repairs	39
5.1	General	39
5.2	Filler Metal Selection	40
5.3	Electrode Baking	42
5.4	Preheating	43
5.5	Controlled Deposition Welding/Temper Bead Welding	43
5.6	Postweld Heat Treatment	46
6	Types of Repairs Associated with Coke Drums	48
6.1	General	48
6.2	Weld Repairs Made from Inside Surface	48
6.3	Weld Repairs Made from Outside Surface	50
6.4	Weld Repairs Made from Both Sides	51
6.5	Replacing Large Sections of Cylindrical Shell Plates	52
6.6	Skirt Repairs, Retrofits, and Replacement	53
6.7	Repairs and Modifications to Unheading Devices	59
6.8	Repairs to Feed Nozzles	60
6.9	Inspection Insulation Windows	62
6.10	Foundation Repairs	63
7	Life Extension Techniques	73
7.1	General	73
7.2	Temporary Repairs of Cracks	73
7.3	Repairs Designed to Last an Extended Period of Time	74
7.4	Use of Structural Weld Overlay to Extend Life	75

Contents

	Page
Annex A (informative) Controlled Deposition Welding/Temper Bead Welding	
Using a SMAW Process and a GMAW Process	81
Annex B (informative) Relevant References on Coke Drums But Not Imbedded in Document.	85
Bibliography	90

Figures

1	VT Examination of a Coke Drum Surface That Displays “Elephant Skin” Cracking.	8
2	PT from the Outside Surface Highlighted Cracks in the Vicinity of the Skirt Attachment Weld	9
3	PT from the Outside Surface Displays an Area with “Elephant Skin” Cracking	9
4	Cracking On the External Surface at an Insulation Clip Displayed by Wet Fluorescent MT	10
5	SWUT Can Be Used from the Outside Surface to Find and Size Cracks Typically in the Vicinity of the Skirt Attachment (Shown as Types “A,” “B,” and “C” Cracks).	10
6	Typical Transducer Arrangement for TOFD Inspection of Welds	11
7	B-scan Image Obtained by the Application of the TOFD UT Technique Showing the Presence of an Embedded Flaw	12
8	Typical Output for TOFD Inspection of Crack Initiating in the Cladding on the Inside Surface and Propagating Through-wall	12
9	TOFD Output for Through-wall Crack in Coke Drum Shell.	13
10	TOFD Image from Crack Propagating from the ID Surface	13
11	Beam Forming, Time Delay, and Focusing and Steering Principle Involved with a PAUT Probe	14
12	PAUT Crystal Arrangement Provides an Improved Ability to Detect Crack-like Flaws Compared with Single Crystal UT	15
13	PAUT for a Type B Crack at a Shell-to-Skirt Attachment. PAUT Transducers Are Placed Both on the Inside and Outside Surface of the Coke Drum	15
14	PAUT of Cracking (Type A) from the Outside Surface on the Coke Drum at the Skirt Attachment.	16
15	ACFM Currents Flowing Around a Surface Crack.	17
16	ACFM Tool Determined the Depth and Length of a Crack That Initiated on the Coke Drum Internal Surface. A Crack Was Found During the Internal Visual Examination of the Coke Drum Using a Remotely Controlled Video Camera	18
17	Illustration Showing Optimal Times to Record AE Data in a Typical Operating Cycle Involving a Two-coke Drum Unit	20
18	Example of Energy vs Time and Temperature Graphs for Quench Half Cycle	21
19	Example of AET Data Displaying Characteristics of Active Flaws (Red Data).	21
20	Example of AET Results Depicting AE Sensor and Skin Thermocouple (TC) Locations Along with Follow-up Areas Provided to the Equipment Owner.	22
21	Bulges on the Inside Surface of a Coke Drum Found by Internal VT Examination Are Highlighted Using Oblique Lighting.	24
22	Use of a Straight Edge from the ID and OD to Measure Bulging.	25
23	Laser Profiling Measurements Show the Growth of Bulging over a 5-year Period.	26
24	Laser Profile Data Are Shown for Five Sets of Measurements in a Vertical Section Comparison and a Polar Plot Comparison.	26
25	Laser Profiling Detected a Sharp Deep Distortion at Middle Course of Two Different Drums.	27
26	Photos from a Video Camera Show Internal Damage in Coke Drum	28
27	Monitoring of Tilting Progression in Two Coke Drums and Comparison with Site-defined Acceptable Limits	29
28	Comparison of Tilting and Shortening in a Coke Drum	30
29	Measurements Taken on Two Coke Drums Show Ovalization and the Resulting Lift at the Base Ring	31

Contents

Page

30	The Dimensions for the Soak Band, Heated Bands, and Thermal Gradient Bands for PWHT of a Drum As Provided in the Guidelines in WRC 452.	47
31	Removal of the Cladding as Required for Weld Repairs Made from Inside Surface.	48
32	After Welding, the Weld Reinforcement Is Ground Flush with the Inside Side Surface of the Base Metal.	49
33	The Cladding Restoration Weld Involves Depositing a Butter Layer on the Cladding Bevel, Followed by Depositing Two Layers of Weld Metal over the Entire Area Where the Cladding Has Been Removed	49
34	The Cladding Restoration Weld Is Ground Flush with the Cladding Surface	50
35	Typical Geometry for a Weld Repair Made from Both Sides of Coke Drum Wall.	51
36	Typical Skirt Attachment Details and Dimensions	54
37	Most Common Locations for Cracking of a Welded Vessel-to-Skirt Attachment	55
38	Skirt Attachment Repair Sequence	56
39	Typical Coke Drum Skirt Keyhole System	57
40	Cracking Initiated at the Slot Keyhole and Propagating Through the Skirt Attachment Weld.	57
41	A Tongue-and-Groove Skirt Design.	58
42	A Welded Skirt Retrofitted to a Bracketed Sliding Skirt	59
43	Typical Insulated Feed Entry into a Drum Bottom Cover	61
44	Typical Insulated Feed Entry into the Side of the Drum Bottom Cover	61
45	Nozzle with Retractable Feed Device in the Retracted Position	62
46	Typical Inspection Insulation Windows Used on Coke Drums	63
47	Internal View and External View of the Drum Cylindrical Section Generated with Laser Mappings.	64
48	Base Ring Modifications and Concrete Excavation	64
49	Setting the Jacks and Lifting the Drum	65
50	Grouting Process After Lifting.	65
51	Modifications of Base Ring, Including New Gusset Plates and Positioning and Installation of Multiple Flat Jacks	66
52	Grouted to Match Tabletop Surface	66
53	Final Grout Stage.	67
54	Completed Installation	67
55	Drawing of Non-bolted Anchor Blocks	70
56	Inspection and Crack Excavation Performed Prior to Weld Overlay Repairs	76
57	Through-wall Crack Repaired	77
58	Finished Structural Overlay Deposit.	77
A.1	The Excavation for a CDW/TBW Repair Should Have an Opening That Is 2.5 Times the Depth	81
A.2	Application of First Layer Using CDW/TBW.	82
A.3	Application of Second and Third Layer Using CDW/TBW	82
A.4	The Remaining Fill Passes Are Made Using Normal Bead Sequencing	82
A.5	Completed Weld with Crown Ground Off	83

Tables

1	Primary Source of Information or Control Document for General Categories of Information on Coke Drums and Peripheral Components.	1
2	Typical Onstream (Non-turnaround) Inspection Techniques and Suggested Frequencies for Coke Drums	33
3	Typical Off-stream (e.g. Turnaround) Inspection Techniques and Suggested Frequencies for Coke Drums	35
4	Typical Filler Metal Choices for Coke Drum Repairs.	40

Contents

	Page
5 Typical Minimum Preheat Temperatures for Coke Drum Repairs	43
6 Requirements for CDW as Stated in API 510, TBW as Stated in NB-23, and TBW as Stated in ASME Code Section IX	44
7 Typical Welding Parameters Using a Nickel-based Consumable	51
A.1 Typical Welding Parameters for the First Three Passes of a CDW/TBW Procedure Using a SMAW Process	81
A.2 Typical Welding Parameters for the First Three Passes of a CDW/TBW Procedure Using a GMAW Process	84

Inspection, Assessment, and Repair of Coke Drums and Peripheral Components in Delayed Coking Units

1 Scope

This document includes information and guidance on the practices used by industry practitioners on the inspection, assessment, and repair of coke drums and peripheral components in delayed coking units. The guidance is general and does not reflect specific details associated with a design offered by licensors of delayed coking technology or inspection tools, repair techniques, and/or engineering assessments offered by contractors. For details associated with the design offered by a licensor or services provided by contractors, the licensor or contractor should be consulted for guidance and recommendations for their specific design details, inspection techniques, assessment procedures, and repair practices. **This document is a technical report and as such provides generally used practices in industry and is not an API Recommended Practice.**

This document complements information contained in API 934-G, which also contains information and guidance on the practices used by industry practitioners on coke drums and peripheral components. There is some overlap in the information and guidance provided in this document and in API 934-G; however, one of these documents will be considered the primary source of information or control document for this information. Table 1 shows which technical report will serve as the primary source of information or the control document for each of the general categories of information.

Table 1—Primary Source of Information or Control Document for General Categories of Information on Coke Drums and Peripheral Components

Information Category	Control Document
General Information on Delayed Coking	API 934-G
Results on Past Industry Surveys of Coke Drums	API 934-G
Description of Damage Mechanisms for Coke Drums	API 934-G
Design	API 934-G
Materials Selection	API 934-G
Fabrication	API 934-G
Operating Practices	API 934-G
Inspection Associated with Finding and Characterizing Damage	API 934-G
Inspection Associated with Repairs	API 934-J
Damage Assessment	API 934-J
Repairs	API 934-J
Welding Considerations	API 934-J
Life Extension	API 934-J

2 Background

2.1 References

The following referenced documents are employed as guidance in the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the reference document (including any amendments) applies.

API 510, *Pressure Vessel Inspection Code: In-service Inspection, Rating, Repair, and Alteration*