

Positive Displacement Pumps—Rotary

API STANDARD 676
FOURTH EDITION, FEBRUARY 2022



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

	Page
1	Scope..... 1
2	Normative References 1
3	Terms and Definitions 4
4	General 10
4.1	Unit Responsibility 10
4.3	Pump Designations..... 10
5.1	[●] Units of Measure..... 16
5.2	Statutory Requirements 16
5.3	Documentation Requirements 16
6	Basic Design 16
6.1	General 16
6.2	Selection and Rating of Pump Type..... 19
6.3	Pressure-containing and Pressure-retaining Parts 19
6.4	Casing Connections..... 20
6.5	Auxiliary Connections 21
6.6	Flanges 22
6.7	External Forces and Moments..... 23
6.8	Rotating Elements 25
6.9	Mechanical Shaft Seals 26
6.10	Bearings and Bearing Housings 27
6.11	Vibration Limits 28
6.12	Lubrication 29
6.13	Materials 30
6.14	Nameplates and Rotation Arrows 36
7	Accessories 36
7.1	Drivers 36
7.2	Couplings and Guards 38
7.3	Belt Drives 40
7.4	Baseplates 41
7.5	Pressure-limiting Valves (PLVs)..... 43
7.6	Controls and Instrumentation..... 44
7.7	Auxiliary Piping 44
7.8	Pulsation and Vibration Control Requirements for Multiphase Skids..... 44
7.9	Special Tools..... 44
8	Inspection, Testing, and Preparation for Shipment 45
8.1	General 45
8.2	Inspection 45
8.3	Testing 47
8.4	Preparation for Shipment..... 51
9	Vendor's Data 52
9.1	General 52
	Annex A (informative) Rotary Pump Datasheets 53

Contents

	Page
Annex B (informative) Factors Affecting Twin Screw Pump Wear Rate and Volumetric Efficiency	64
Annex C (informative) Inspector's Checklist.....	69
Annex D (informative) Contract Documents and Engineering Design Data.....	71
Annex E (informative) Rotary Pump Vendor Drawing and Data Requirements (VDDRs).....	76
Annex F (informative) Net Positive Suction Head (NPSH) vs Net Positive Inlet Pressure (NPIP)	88
Annex G (informative) Typical P&D for MPP Pumps.....	90
Bibliography.....	91

Figures

1	Sliding Vane Pump (Vane in Rotor)	11
2	Single Lobe Pump	11
3	Three Lobe Pump	12
4	External Gear Pump	12
5	Internal Gear Pump	12
6	Progressing/Progressive Cavity Pump (PCP)	13
7	Twin Screw Pump (with Timed Gears).....	13
8	Three-screw Pump (with Untimed Gears)	13
9	Rotary Pump Consolidated Range Chart (Typical Range in SI Units).....	14
10	Rotary Pump Consolidated Range Chart (Typical Range in USC Units).....	15

Tables

1	Pump Classification Type Identification	10
2	Nozzle Loadings	23
3	Welding Requirements.....	34
4	Material Inspection Standards	46
5	Test Tolerances.....	50
C.1	Inspector's Checklist.....	69

Introduction

This standard is based on the accumulated knowledge and experience of manufacturers and users of rotary positive displacement pumps. The objective of this standard is to provide a purchase specification to facilitate the procurement and manufacturer of rotary positive displacement pumps for use in petroleum, chemical, and gas industry services.

The primary purpose of this standard is to establish minimum requirements. This limitation in scope is one of charter as opposed to interest and concern.

Energy conservation is of concern and has become increasingly important in all aspects of equipment design, application, and operation. Thus innovative, energy-conserving approaches should be aggressively pursued by the manufacturer and the user during these steps. Alternative approaches that may result in improving energy utilization should be thoroughly investigated and brought forth. This is especially true of new equipment proposals, since the evaluation of purchase options will be based increasingly on total life costs as opposed to acquisition cost alone. Equipment manufacturers, in particular, are encouraged to suggest alternatives to those specified when such approaches achieve improved energy effectiveness and reduced total life costs without sacrifice of safety or reliability.

This standard requires the purchaser to specify certain details and features. Although it is recognized that the purchaser may desire to modify, delete, or amplify sections of this standard, it is strongly recommended that such modifications, deletions, and amplifications be made by supplementing this standard, rather than by rewriting or incorporating sections thereof into another standard.

API standards are published as an aid to procurement of standardized equipment and materials. These standards are not intended to inhibit purchasers or producers from purchasing or producing products made to other standards.

Positive Displacement Pumps—Rotary

1 Scope

This standard covers the minimum requirements for rotary positive displacement process pumps and pump units for use in the petroleum, petrochemical, and gas industry services. Controlled-volume pumps, hydraulically driven pumps and positive displacement reciprocating pumps are not included (see API 674 for positive displacement reciprocating pumps and API 675 for controlled-volume pumps).

For rotary positive displacement pumps in auxiliary services (e.g. lube oil systems), manufacturer's standard with demonstrated experience is acceptable.

- Annex A contains datasheets which purchasers are encouraged to use (informative).
- Annex B provides guidance for factors affecting twin screw efficiencies (informative).
- Annex C contains an inspector's checklist (informative).
- Annex D contains information on Contract Documents and Engineering Design Data (informative)
- Annex E contains forms which may be used to indicate vendor drawing and data requirements (VDDRs) (informative).
- Annex F gives guidance regarding net positive suction head (NPSH) vs net positive inlet pressure (NPIP) (informative).
- Annex G provides a typical P&ID for multiphase pump skids (informative).

This standard requires the purchaser to specify certain details and features. A bullet [•] at the beginning of a paragraph indicates that either a decision by, or further information from, the purchaser is required. Further information should be shown on the datasheets (see example in Annex A) or stated in the quotation request and purchase order.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Recommended Practice 500, *Recommended Practice for Classification of Locations for Electrical Installations at Petroleum Facilities Classified as Class I, Division 1, and Division 2*

API 500, *Classification of Locations for Electrical Installations in Petroleum Refineries*

API Recommended Practice 520, *Sizing, Selection, and Installation of Pressure-Relieving Devices in Refineries; Part I—Sizing and Selection*

API Recommended Practice 520, *Sizing, Selection, and Installation of Pressure-relieving Devices in Refineries; Part II—Installation*

API Standard 526, *Flanged Steel Pressure Relief Valves*

API Standard 541, *Form-wound Squirrel-cage Induction Motors—500 Horsepower and Larger*

API Standard 546, *Brushless Synchronous Machines—500 kVA and Larger*