

Refractory Installation Quality Control— Inspection and Testing of Refractory Brick Systems and Materials

API STANDARD 975
FIRST EDITION, NOVEMBER 2021



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this Standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Important Information Concerning Use of Asbestos or Alternative Materials

Asbestos is specified or referenced for certain components of the equipment described in some API standards. It has been of extreme usefulness in minimizing fire hazards associated with petroleum processing. It has also been a universal sealing material, compatible with most refining fluid services.

Certain serious adverse health effects are associated with asbestos, among them the serious and often fatal diseases of lung cancer, asbestosis, and mesothelioma (a cancer of the chest and abdominal linings). The degree of exposure to asbestos varies with the product and the work practices involved.

Consult the most recent edition of the Occupational Safety and Health Administration (OSHA), U.S. Department of Labor, Occupational Safety and Health Standard for Asbestos, Tremolite, Anthophyllite, and Actinolite, 29 *Code of Federal Regulations* Section 1910.1001; the U.S. Environmental Protection Agency, National Emission Standard for Asbestos, 40 *Code of Federal Regulations* Sections 61.140 through 61.156; and the U.S. Environmental Protection Agency (EPA) rule on labeling requirements and phased banning of asbestos products (Sections 763.160–179).

There are currently in use and under development several substitute materials to replace asbestos in certain applications. Manufacturers and users are encouraged to develop and use effective substitute materials that can meet the specifications for and the operating requirements of the equipment to which they would apply.

SAFETY AND HEALTH INFORMATION WITH RESPECT TO PARTICULAR PRODUCTS OR MATERIALS CAN BE OBTAINED FROM THE EMPLOYER, THE MANUFACTURER, OR SUPPLIER OF THAT PRODUCT OR MATERIAL, OR THE MATERIAL SAFETY DATASHEET.

Contents

	Page
1	Scope..... 1
2	Normative References 1
3	Terms and Definitions 2
4	Responsibilities 4
4.1	Owner/Equipment Manufacturer (EM) 4
4.2	Installer 5
4.3	Refractory Manufacturer 6
4.4	Inspector 6
5	Materials 7
5.1	General 7
5.2	Physical-chemical and Visual Property..... 7
5.3	Packaging and Marking 7
5.4	Shipping..... 7
5.5	Storage and Weather Protection..... 8
5.6	Shelf Life—Mortars 8
5.7	Discarding Criteria 8
5.8	Regulations and Safety Data Sheets (SDS) 8
5.9	Anchors..... 8
5.10	Expansion Materials 9
6	Refractory QA/QC, Examination, and Testing..... 9
6.1	General 9
6.2	Physical Property 9
6.3	Physical Attributes 9
6.4	Pre-shipment Requirements 11
7	Installation/Execution..... 11
8	Repair 14
9	Preparation for Shipment..... 14
	Annex A (informative) Glossary 16
	Annex B (informative) Development of Refractory Compliance Data Sheet—Material Requirements 21
	Annex C (informative) Defects in Dense Fireclay and Insulating Firebrick..... 27
	Bibliography..... 30

Figures

B.1	Manufacturer’s Product Compliance Data Sheet—Brick Materials (Sample)..... 25
B.2	Manufacturer’s Product Compliance Data Sheet—Mortar Materials 26

Contents

	Page
C.1 Warpage	27
C.2 Laminations	27
C.3 Fins	28
C.4 External Cracks	28
C.5 Edge and Corner Damage	28
C.6 Voids and Air Pockets	29
C.7 Edge and Internal	29

Tables

1 Maximum Temperature for Anchor Tips	8
2 Lot Size, Sample Size, and Rejection Levels for Physical Attributes.....	11
B.1 Test Methods for Compliance Data Sheets Property Listings.....	22
B.2 Dense Refractory Requirements (Fireclay Brick)	22
B.3 Dense Refractory Brick (High-alumina Brick)	23
B.4 Insulating Firebrick Requirements	23
B.5 Refractory Mortars Requirements.....	24

Refractory Installation Quality Control—Inspection and Testing of Refractory Brick Systems and Materials

1 Scope

This standard provides installation quality control (QC) procedures for aluminum silicate dense and insulating fire brick refractory systems and may be used to supplement owner specifications. Materials, equipment, and personnel are qualified by the methods described, and applied refractory quality is closely monitored, based on defined procedures and acceptance criteria. The responsibilities of inspection personnel who monitor and direct the QC process are also defined (see 4.4).

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API 936, *Refractory Installation Quality Control—Inspection and Testing Monolithic Refractory Lining and Materials*

API 976, *Refractory Installation Quality Control—Inspection and Testing AES/RCF Fiber Linings and Materials*

ASTM C16, ¹ *Standard Test Method for Load Testing Refractory Shapes at High Temperatures*

ASTM C27, *Standard Classification of Fireclay and High-Alumina Refractory Brick*

ASTM C113, *Standard Test Method for Reheat Change of Refractory Brick*

ASTM C133, *Standard Test Method for Cold Crushing Strength and Modulus of Rupture of Refractories*

ASTM C134, *Standard Test Methods for Size, Dimensional Measurements, and Bulk Density of Refractory Brick and Insulating Firebrick*

ASTM C155, *Standard Classification of Insulating Firebrick*

ASTM C210, *Standard Test Method for Reheat Change of Insulating Firebrick*

ASTM C832, *Standard Test Method of Measuring Thermal Expansion and Creep of Refractories Under Load*

Harbison-Walker Refractories Company,² *Modern Refractory Practice*, Fifth Edition, Indresco, Pittsburgh, Pennsylvania

ISO 3187,³ *Refractory Products—Determination of Creep in Compression*

ISO 5017, *Dense Shaped Refractory Products—Determination of Bulk Density, Apparent Porosity and True Porosity*

ISO 10059-2, *Dense, Shaped Refractory Products—Determination of Cold Compressive Strength—Part 2: Test with Packing*

¹ ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, Pennsylvania 19428-2959, www.astm.org.

² Harbison-Walker International, 1305 Cherrington Parkway, Suite 100, Pittsburgh, PA 15108, thinkhwi.com.

³ International Organization for Standardization, ISO Central Secretariat, Chemin de Blandonnet 8, CP 401 - 1214 Vernier, Geneva, Switzerland, www.iso.org.