



**CGA P-96—2023  
RECIPROCATING CRYOGENIC  
PUMPS AND PUMP  
INSTALLATIONS FOR  
HYDROGEN AND  
LIQUEFIED NATURAL GAS**

**FIRST EDITION**

## PREFACE

As part of a program of harmonization of industry standards, the Compressed Gas Association (CGA) has published CGA P-96, *Reciprocating Cryogenic Pumps and Pump Installations for Hydrogen and Liquefied Natural Gas*, jointly produced by members of the International Harmonization Council.

This publication is intended as an international harmonized standard for the worldwide use and application of all members of the Asia Industrial Gases Association (AIGA), Compressed Gas Association (CGA), European Industrial Gases Association (EIGA), and Japan Industrial and Medical Gases Association (JIMGA). Each association's technical content is identical, except for regional regulatory requirements and minor changes in formatting and spelling.

### PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, [www.cganet.com](http://www.cganet.com).

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at [www.cganet.com](http://www.cganet.com). For more information contact CGA at Phone: 703-788-2700, ext. 799. E-mail: [customerservice@cganet.com](mailto:customerservice@cganet.com).

Work Item 20-81  
Atmospheric Gases and Equipment Committee

FIRST EDITION: 2023

© 2023 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, McLean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

<b>Contents</b>	<b>Page</b>
1 Introduction.....	1
2 Scope and purpose .....	1
3 Definitions.....	1
4 Description of a reciprocating cryogenic pump and pump installation and components.....	2
5 Description of individual components.....	3
5.1 Tanks.....	3
5.2 Pump.....	5
5.3 Vaporizers .....	9
5.4 Piping and piping components .....	10
5.5 Valves.....	10
6 Material selection .....	11
7 Instrumentation.....	12
8 Insulation.....	15
9 Installation .....	16
9.1 General.....	16
9.2 Layout.....	16
9.3 Net positive suction head available .....	16
9.4 Piping.....	17
9.5 Area classification.....	17
9.6 Risk assessment .....	18
10 Operation.....	18
11 Maintenance and repair.....	20
11.1 Maintenance.....	20
11.2 Repair procedures .....	20
11.3 Parts.....	20
12 References .....	20

## Figures

Figure 1—Example of a general arrangement of a typical cryogenic pump installation .....	3
Figure 2—Example of a simplified thermosiphon tank piping arrangement.....	4
Figure 3—Example of a simplified conventional tank piping arrangement .....	5
Figure 4—Example of cryogenic reciprocating pump components.....	6
Figure 5—Example of a cold- and warm-end assembly components of a cryogenic reciprocating pump (cross section) .....	7
Figure 6a—Example of a cold end without a precompression chamber.....	8
Figure 6b—Example of a cold end with a precompression chamber.....	8
Figure 7—Example of pump instrumentation.....	15

## Tables

Table 1—Design criteria and guidance for material selection.....	11
Table 2—Typical materials of construction for reciprocating pumps.....	12
Table 3—Instrument list .....	15

## 1 Introduction

Reciprocating cryogenic pumps are key components in hydrogen and liquefied natural gas (LNG) service. To ensure that pumps operate both safely and reliably in liquefied flammable gas service, it is important that reciprocating pumps are correctly designed, installed, operated, and maintained as required for the duty.

Pumping these fluids is accompanied by some degree of hazard. The hazards include liquid under pressure, cryogenic temperatures, volume and pressure increases due to vaporization, and flammability of the vapor.

This publication contains a summary of industrial practices and is based on the combined knowledge, experiences, and practices of industrial gas and equipment suppliers to manage these hazards.

## 2 Scope and purpose

This publication covers cryogenic reciprocating pumps and pump installations for hydrogen and LNG service.

The information contained in this publication only applies to new installations designed after the publication of this document and not to existing installations. However, the information contained in this publication may benefit existing installations or those in the project phase.

This publication does not cover:

- Cryogenic reciprocating pumps and installations for liquid oxygen, argon, and nitrogen, which are covered in CGA P-48, *Reciprocating Cryogenic Pumps and Pump Installations for Oxygen, Argon, and Nitrogen* [1];<sup>1</sup>
- Centrifugal liquid oxygen pumps, which are covered in CGA G-4.7, *Stationary, Electric-Motor-Driven, Centrifugal Liquid Oxygen Pumps* [2]; and
- Carbon dioxide pumps, which are covered in CGA G-6.3, *Carbon Dioxide Cylinder Filling and Handling Procedures* and EIGA Doc 83, *Recommendations for Filling of Cylinders and Bundles with Carbon Dioxide* [3, 4].

## 3 Definitions

### 3.1 Publication terminology

#### 3.1.1 Shall

Indicates that the procedure is mandatory. It is used wherever the criterion for conformance to specific recommendations allows no deviation.

#### 3.1.2 Should

Indicates that the procedure is recommended.

#### 3.1.3 May

Indicates that the procedure is optional.

#### 3.1.4 Will

Is used only to indicate the future, not a degree of requirement.

#### 3.1.5 Can

Indicates a possibility or ability.

---

<sup>1</sup> References are shown by bracketed numbers and are listed in order of appearance in the reference section.