



# **Spectral Effects of Lighting on Visual Performance at Mesopic Lighting Levels**

**Spectral Effects of Lighting  
on Visual Performance at  
Mesopic Lighting Levels**

Publication of this Technical Memorandum has been approved by the IES. Suggestions for revisions should be directed to the IES.

*Copyright 2012 by the Illuminating Engineering Society of North America.*

*Approved by the IES Board of Directors, March 2, 2012 as a Transaction of the Illuminating Engineering Society of North America.*

*All rights reserved. No part of this publication may be reproduced in any form, in any electronic retrieval system or otherwise, without prior written permission of the IES.*

Published by the Illuminating Engineering Society of North America, 120 Wall Street, New York, New York 10005.

IES Standards and Guides are developed through committee consensus and produced by the IES Office in New York. Careful attention is given to style and accuracy. If any errors are noted in this document, please forward them to Rita Harrold, Director of Technology, at the above address for verification and correction. The IES welcomes and urges feedback and comments.

*Printed in the United States of America.*

*ISBN # 978-0-87995-269-3*

#### **DISCLAIMER**

IES publications are developed through the consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on lighting recommendations. While the IES administers the process and establishes policies and procedures to promote fairness in the development of consensus, it makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

The IES disclaims liability for any injury to persons or property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and making this document available, the IES is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the IES undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The IES has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does the IES list, certify, test or inspect products, designs, or installations for compliance with this document. Any certification or statement of compliance with the requirements of this document shall not be attributable to the IES and is solely the responsibility of the certifier or maker of the statement.

**1 Prepared by the IES Mesopic Committee:**

**N. Clanton, Chair**

C. Andersen \*  
J. Bullough  
D. Crawford  
R. Gibbons \*  
R. Herrett  
L. Leetzow  
I. Lewin  
A. Lewis  
M. Bryan  
J. Melnyk  
N. Miller  
S. Wentworth

\*Advisory



# Contents

<b>1.0</b>	<b>Introduction</b> . . . . .	<b>1</b>
<b>2.0</b>	<b>Known Factors in Determining Spectral Effects</b> . . . . .	<b>1</b>
<b>2.1</b>	<b>Limitations of the <math>V(\lambda)</math> Curve</b> . . . . .	<b>1</b>
<b>2.2</b>	<b>Light Source Spectrum and Visual Response</b> . . . . .	<b>2</b>
2.2.1	Adaptation Luminance . . . . .	3
<b>3.0</b>	<b>Determining Effective Luminance</b> . . . . .	<b>3</b>
<b>3.1</b>	<b>Calculation Procedure</b> . . . . .	<b>4</b>
<b>3.2</b>	<b>Effective Luminance Factors</b> . . . . .	<b>5</b>
<b>3.3</b>	<b>Average Levels and Uniformities</b> . . . . .	<b>5</b>
<b>4.0</b>	<b>Calculating Effective Luminance from CIE 191</b> . . . . .	<b>5</b>
<b>5.0</b>	<b>Effects Needing Further Research</b> . . . . .	<b>6</b>
<b>5.1</b>	<b>Glare</b> . . . . .	<b>6</b>
<b>5.2</b>	<b>Chromatic Effects</b> . . . . .	<b>6</b>
<b>5.3</b>	<b>Roadway Visual Tasks</b> . . . . .	<b>7</b>
<b>5.4</b>	<b>Safety and Visual performance</b> . . . . .	<b>8</b>
<b>5.5</b>	<b>Environmental Issues</b> . . . . .	<b>8</b>
<b>5.6</b>	<b>Other Factors</b> . . . . .	<b>9</b>
5.6.1	Observer Age . . . . .	9
5.6.2	Pavement Reflectance . . . . .	9
5.6.3	Headlamp Effects . . . . .	9
<b>Annex A</b>	<b>– ELF Tables</b> . . . . .	<b>10</b>
<b>Annex B</b>	<b>– BASIC Code for Mesopic or Effective Luminance</b> . . . . .	<b>13</b>
<b>Annex C</b>	<b>– S/P Ratios of Common Light Sources</b> . . . . .	<b>14</b>
<b>References</b>	. . . . .	<b>15</b>



---

## 1.0 INTRODUCTION

---

This technical memorandum examines the spectral effects of lighting at low luminances typically found in nighttime conditions, focusing on visual performance, with brief discussions of roadway visual tasks, glare, chromatic effects, environmental effects, and others. Spectral effects that are known to occur primarily at higher levels (e.g.,  $>5 \text{ cd/m}^2$ ) are not addressed, and in most night-time environments there is enough ambient light to prevent true scotopic vision.

In recent years a number of studies have been done on lighting under mesopic conditions. However, much of this work has simply highlighted the need for more research, as the complexity of the problems of reconciling vision and photometry becomes evident. As knowledge and technology evolve, this document will be revised.

Lighting design normally uses rated lamp lumens, based on the photopic ( $2^\circ$ ) spectral sensitivity curve  $V(\lambda)$ , as the basis for the design. Recommended light levels almost always refer to photopic light levels. However, there are limitations to the applicability of the  $V(\lambda)$  function. This technical memorandum formally acknowledges the existence of problems with an assumption that photometric quantities based on  $V(\lambda)$ , or any other function, exhibit linear proportionality to visual performance as conditions change into the mesopic range, and provides information for challenging and overcoming this assumption.

A method of modifying photometric values for mesopic conditions has been developed for application and design procedures, based on the recent system of mesopic photometry developed by the Commission Internationale de l'Eclairage (CIE) in Report 191.<sup>1</sup> Details of this method are used and outlined in **Section 2** later in this document. Use of this methodology is recommended, as it allows photometric quantities to take into account the extent to which spectral effects at mesopic light levels influence visual performance.

Evidence has accumulated showing a relationship that in some cases may be significant between lamp spectral power distribution (SPD) and visual performance. Under reduced adaptation luminances, two lamps with identical lumen output, but with different SPDs, may produce different levels of visual performance. The significant question is what *visual performance* will be produced using the different sources? A key related question is, "what level of lighting from the different sources is needed in order to provide equivalent visual performance or equivalent appearance of brightness?" Note that

equivalent brightness does not necessarily produce equal visual performance. This technical memorandum discusses these issues and provides guidance for lighting practice based more closely on visual performance at mesopic light levels

---

## 2.0 KNOWN FACTORS IN DETERMINING SPECTRAL EFFECTS

---

Despite there being little direct empirical evidence, it is often accepted that adequate visibility at night is a significant factor in accident reduction, the facilitation of traffic flow, and providing security. It is therefore highly relevant to determine what aspects of outdoor lighting design affect visual performance, and how visual performance may be improved, within budgetary and technical constraints. Current practices rely on several simplifying assumptions, which do not always hold true.

### 2.1 Limitations of the $V(\lambda)$ Curve

Visual performance, especially under mesopic conditions, is not a simple matter. Illuminating engineers and vision scientists have known for over a hundred years that the way in which the visual system responds to different light source spectral distributions depends on the lighting and viewing conditions.<sup>2,3,4</sup> Equivalent lumen output of different lamps may be perceived differently. Lamps, however, are given a rated lumen output as if the human sensitivity to the light output of any particular lamp is always identical.

The definitions of photometric quantities have been standardized by the CIE.<sup>2,3</sup> CIE states that "Light is radiant power weighted according to the spectral sensitivity of the human visual system". To obtain a lumen value, the spectral power distribution (SPD) of the light source is integrated with the relative spectral luminous sensitivity of the human visual system, specifically the photopic ( $2^\circ$ ) luminous efficacy function. The spectral sensitivity curve that is used to define  $V(\lambda)$  applies only to on-axis viewing under high light levels.  $V(\lambda)$ , shown in **Figure 1**, is the sensitivity curve of the visual system that is used most often to relate visual response to the wavelength of the light source.

To the extent that  $V(\lambda)$  approximates the spectral sensitivity of the human visual system to light for a given visual response, the lumens determined in the photometric laboratory, and ultimately used by the designer, will have predictive value in characterizing expected visual responses. Similarly derived quantities such as illuminance (lux and footcandles), inten-