



ATIS-0500032

ATIS Standard on -

**ATIS STANDARD FOR IMPLEMENTATION OF AN IMS-BASED NG9-1-1
SERVICE ARCHITECTURE**



As a leading technology and solutions development organization, the Alliance for Telecommunications Industry Solutions (ATIS) brings together the top global ICT companies to advance the industry's most pressing business priorities. ATIS' nearly 200 member companies are currently working to address the All-IP transition, 5G, network functions virtualization, big data analytics, cloud services, device solutions, emergency services, M2M, cyber security, network evolution, quality of service, billing support, operations, and much more. These priorities follow a fast-track development lifecycle — from design and innovation through standards, specifications, requirements, business use cases, software toolkits, open source solutions, and interoperability testing.

ATIS is accredited by the American National Standards Institute (ANSI). The organization is the North American Organizational Partner for the 3rd Generation Partnership Project (3GPP), a founding Partner of the oneM2M global initiative, a member of and major U.S. contributor to the International Telecommunication Union (ITU), as well as a member of the Inter-American Telecommunication Commission (CITEL). For more information, visit www.atis.org.

Notice of Disclaimer & Limitation of Liability

The information provided in this document is directed solely to professionals who have the appropriate degree of experience to understand and interpret its contents in accordance with generally accepted engineering or other professional standards and applicable regulations. No recommendation as to products or vendors is made or should be implied.

NO REPRESENTATION OR WARRANTY IS MADE THAT THE INFORMATION IS TECHNICALLY ACCURATE OR SUFFICIENT OR CONFORMS TO ANY STATUTE, GOVERNMENTAL RULE OR REGULATION, AND FURTHER, NO REPRESENTATION OR WARRANTY IS MADE OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. ATIS SHALL NOT BE LIABLE, BEYOND THE AMOUNT OF ANY SUM RECEIVED IN PAYMENT BY ATIS FOR THIS DOCUMENT, AND IN NO EVENT SHALL ATIS BE LIABLE FOR LOST PROFITS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. ATIS EXPRESSLY ADVISES THAT ANY AND ALL USE OF OR RELIANCE UPON THE INFORMATION PROVIDED IN THIS DOCUMENT IS AT THE RISK OF THE USER.

NOTE - The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to whether use of an invention covered by patent rights will be required, and if any such use is required no position is taken regarding the validity of this claim or any patent rights in connection therewith. Please refer to [<http://www.atis.org/legal/patentinfo.asp>] to determine if any statement has been filed by a patent holder indicating a willingness to grant a license either without compensation or on reasonable and non-discriminatory terms and conditions to applicants desiring to obtain a license.

Published by

**Alliance for Telecommunications Industry Solutions
1200 G Street, NW, Suite 500
Washington, DC 20005**

Copyright © 2016 by Alliance for Telecommunications Industry Solutions
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. For information contact ATIS at 202.628.6380. ATIS is online at < <http://www.atis.org> >.

ATIS-0500032

ATIS Standard on

ATIS Standard for Implementation of an IMS-based NG9-1-1 Service Architecture

Alliance for Telecommunications Industry Solutions

Approved November 21, 2016

Abstract

This Standard defines the Stage 2 (architecture) and Stage 3 (protocol) specifications for an IMS-based NG9-1-1 Service Architecture. This Standard includes the architecture, functional elements, call flows, protocols, and interfaces which were derived from the Stage 1 requirements in ATIS-0500023, "Applying Common IMS to NG9-1-1 Networks".

Foreword

The Alliance for Telecommunication Industry Solutions (ATIS) serves the public through improved understanding between carriers, customers, and manufacturers.

The ESIF IP Multimedia Subsystem for 9-1-1 (IMS911) subgroup led this joint work effort that addresses the application of common IMS (Stage 1, 2, and 3) for the processing, transport, and/or delivery of Emergency Service calls within the NG9-1-1 network to the appropriate PSAP. This is a joint effort with the Emergency Services Interconnection Forum Next Generation Emergency Service (ESIF NGES) Subcommittee, Packet Technologies and Systems Committee (PTSC) and the Wireless Technologies and Systems Committee Systems and Network Subcommittee (WTSC SN).

The Emergency Services Interconnection Forum (ESIF) provides a forum to facilitate the identification and resolution of technical and/or operational issues related to the interconnection of wireline, wireless, cable, satellites, Internet and emergency services networks.

The ESIF Next Generation Emergency Services (NGES) Subcommittee coordinates emergency services needs and issues with and among SDOs and industry forums/committees, within and outside ATIS, and develops emergency services (such as E9-1-1) standards, and other documentation related to advanced (i.e., Next Generation) emergency services architectures, functions, and interfaces for communications networks.

The Packet Technologies and Systems Committees (PTSC) develops and recommends standards and technical reports related to services, architectures, and signaling, in addition to related subjects under consideration in other North American and international standards bodies. PTSC coordinates and develops standards and technical reports relevant to telecommunications networks in the U.S., reviews and prepares contributions on such matters for submission to U.S. ITU-T and U.S. ITU-R Study Groups or other standards organizations, and reviews for acceptability or per contra the positions of other countries in related standards developments and takes or recommends appropriate actions.

The Wireless Technologies and Systems Committee (WTSC) develops and recommends standards and technical reports related to wireless and/or mobile services and systems, including service descriptions and wireless technologies. WTSC develops and recommends positions on related subjects under consideration in other North American, regional, and international standards bodies.

The WTSC Systems and Networks Subcommittee (WTSC SN) develops, maintains, amends and enhances American National Standards and ATIS deliverables related to system aspects, networks, and terminals within the GSM family (GSM/EGPRS/UMTS) such as circuit-switched, packet-switched and IP Multimedia services including future developments.

Suggestions for improvement of this document are welcome. They should be sent to the Alliance for Telecommunications Industry Solutions, ESIF, 1200 G Street NW, Suite 500, Washington, DC 20005.

At the time of consensus on this document, the committees responsible for its development, had the following leadership:

T. Reese, ESIF Chair, ESIF IMS911 Co-Chair, ESIF NGES Co-Chair (Ericsson)

J. English, ESIF First Vice-Chair (APCO International)

S. Sherwood, ESIF Second Vice-Chair (Verizon Wireless)

C. Militeau, ESIF IMS911 Chair, ESIF NGES Chair (West Safety Services)

M. Dolly, PTSC Chair (AT&T)

V. Shaikh, PTSC Vice-Chair (Applied Communication Sciences)

D. Zelmer, WTSC Chair (AT&T)

M. Younge, WTSC Vice-Chair (T-Mobile)

P. Musgrove, WTSC SN Chair (AT&T)

G. Schumacher, WTSC SN Vice-Chair (Sprint)

D. Sennett, Technical Editor (AT&T)

T. Breen, Technical Editor (Comtech)

Table of Contents

ATIS Standard on	i
Table of Contents	iii
Table of Figures.....	v
Table of Tables.....	vi
Preface	1
1 Scope, Purpose, & Application	1
1.1 Scope	1
1.2 Purpose	2
1.3 Application	2
2 Normative References	2
3 Informative References.....	4
4 Definitions, Acronyms, & Abbreviations.....	4
4.1 Definitions.....	4
4.2 Acronyms & Abbreviations	6
5 Introduction.....	7
6 Assumptions & Requirements	8
6.1 Basic Assumptions.....	8
6.2 Requirements	9
7 Architecture	9
7.1 Overview.....	9
7.2 IMS-Based NG9-1-1 Service Architecture Functional Elements	10
7.2.1 <i>Emergency Call Session Control Function (E-CSCF)</i>	10
7.2.2 <i>Interrogating Call Session Control Function (I-CSCF)</i>	10
7.2.3 <i>Location Retrieval Function (LRF)</i>	11
7.2.4 <i>Routing Determination Function (RDF)</i>	11
7.2.5 <i>Location Server (LS)</i>	11
7.2.6 <i>Interconnecting Border Control Function (IBCF)</i>	11
7.2.7 <i>Legacy Network Gateway (LNG)</i>	11
7.2.8 <i>Emergency Call Routing Function (ECRF)</i>	12
7.2.9 <i>Legacy PSAP Gateway (LPG)</i>	12
7.2.10 <i>Application Server (AS)</i>	12
7.2.11 <i>Multimedia Resource Function Controller (MRFC)</i>	12
7.2.12 <i>Multimedia Resource Function Processor (MRFP)</i>	12
7.2.13 <i>Transit Function (TRF)</i>	13
7.3 Reference Protocols	13
8 Stage 2 Call Flows.....	15
8.1 Legacy Wireline Origination to i3 and Legacy PSAPs	15
8.1.1 <i>Delivery of Legacy Wireline Emergency Call Origination to i3 PSAP</i>	15
8.1.2 <i>Delivery of Legacy Wireline Emergency Call Origination to Legacy PSAP</i>	17
8.2 Legacy CMRS Origination to i3 and Legacy PSAPs.....	20
8.2.1 <i>Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP Using WCM</i>	20
8.2.2 <i>Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP Using WCM</i>	23
8.2.3 <i>Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP using NCAS</i>	28

ATIS-0500032

- 8.2.4 Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP using NCAS 31
- 8.3 IMS Originating Network to i3 and Legacy PSAPs – LbyV 36
 - 8.3.1 Delivery of Emergency Call Origination from IMS Origination Network to i3 PSAP with LbyV 36
 - 8.3.2 Delivery of Emergency Call Origination from IMS Origination Network to Legacy PSAP with LbyV 38
- 8.4 IMS Originating Network to i3 and Legacy PSAPs – LbyR 42
 - 8.4.1 Delivery of Emergency Call Origination from IMS Origination Network to i3 PSAP with LbyR 42
 - 8.4.2 Delivery of Emergency Call Origination from IMS Origination Network to Legacy PSAP with LbyR 45
- 8.5 Non-IMS Originating Network to i3 and Legacy PSAPs – LbyV..... 49
 - 8.5.1 Delivery of Emergency Call Origination from Non-IMS Origination Network to i3 PSAP with LbyV . 49
 - 8.5.2 Delivery of Emergency Call Origination from Non-IMS Origination Network to Legacy PSAP with LbyV 53
- 8.6 Non-IMS VoIP Originating Network to i3 and Legacy PSAPs – LbyR..... 57
 - 8.6.1 Delivery of Emergency Call Origination from Non-IMS Origination Network to i3 PSAP with LbyR . 57
 - 8.6.2 Delivery of Emergency Call Origination from Non-IMS Origination Network to Legacy PSAP with LbyR 60
- 8.7 TTY Calls to Legacy/i3 PSAPs..... 65
 - 8.7.1 TTY Calls from IMS Originating Network to Legacy PSAP via NG9-1-1 65
 - 8.7.2 TTY Calls from Legacy Originating Network to an i3 PSAP via NG9-1-1 67
 - 8.7.3 TTY Calls from Legacy Originating Network to a Legacy PSAP via NG9-1-1..... 69
- 8.8 Call Transfer/Bridging 71
 - 8.8.1 Support for Emergency Call Transfer Requests from i3 PSAPs to Secondary PSAPs/Destinations 72
 - 8.8.2 Support for Emergency Call Transfer Requests from Legacy PSAPs to Secondary PSAPs/Destinations 104
- 8.9 Policy Routing Scenarios 116
- 8.10 Failure Scenarios..... 119
 - 8.10.1 Error Conditions 119
- 8.11 PSAP Callback Flows 120
- 9 Stage 3 120
 - 9.1 Procedures & Header Usage for the Emergency CSCF (E-CSCF)..... 120
 - 9.1.1 Header Usage 122
 - 9.2 Procedures & Header Usage for the Location Retrieval Function (LRF)..... 122
 - 9.2.1 Processing of Origination from i3-Compliant Originating Network or LNG..... 122
 - 9.2.2 Using Incoming Signaling Information to Facilitate Error Handling 123
 - 9.2.3 Header Usage 123
 - 9.2.4 Procedures at Policy Routing Function (PRF)..... 123
 - 9.3 Procedures at the RDF 123
 - 9.4 Procedures at the LNG 124
 - 9.4.1 SS7 Wireline to SIP Header Mapping Example 124
 - 9.4.2 CAMA Wireline to SIP Header Mapping Example 125
 - 9.4.3 FG D Wireline to SIP Header Mapping Example..... 125
 - 9.4.4 SS7 Wireline Compatibility Mode to SIP Header Mapping Example..... 125
 - 9.4.5 CAMA MF WCM to SIP Header Mapping Example..... 126
 - 9.4.6 FG D MF WCM to SIP Header Mapping Example 126
 - 9.4.7 SS7 NCAS to SIP Header Mapping Example..... 127
 - 9.4.8 CAMA MF NCAS to SIP Header Mapping Example..... 127
 - 9.4.9 FG D MF NCAS to SIP Header Mapping Example 128
 - 9.5 Procedures at the LPG..... 128
 - 9.6 Procedures at the IBCF..... 129
 - 9.6.1 Entry Point IBCF 130
 - 9.6.2 Exit Point IBCF..... 130
 - 9.7 Procedures at the I-CSCF 130
 - 9.8 Procedures at the Conferencing Application Server (AS) 130
 - 9.9 Procedures at the Multimedia Resource Function Controller (MRFC) 131
 - 9.10 Procedures at the Multimedia Resource Function Processor (MRFP)..... 131
 - 9.11 Procedures at the Transit Function 131

Annex A (normative) – SIP INVITE Profile for Emergency Calls 132

Annex B (informative) – Message Examples 135

 B.1 Legacy Fixed Line UE to Traditional Legacy PSAP (Wireline) Example 135

 B.2 Legacy Mobile UE to Traditional Legacy PSAP (Wireless) Example 136

 B.3 Fixed Line IP OSP UE to Traditional Legacy PSAP Example..... 136

 B.4 Mobile IP OSP UE to Traditional Legacy PSAP Example..... 136

Table of Figures

Figure 7-1: IMS origination network emergency call architecture from 3GPP TS 23.167 9

Figure 7-2: IMS-Based NG9-1-1 Service Architecture 10

Figure 8-1: Delivery of Legacy Wireline Emergency Call Origination to i3 PSAP 15

Figure 8-2: Delivery of Legacy Wireline Emergency Call Origination to Legacy PSAP 18

Figure 8-3: Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP Using WCM 21

Figure 8-4: Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP Using WCM..... 24

Figure 8-5: Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP Using NCAS 28

Figure 8-6: Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP Using NCAS..... 32

Figure 8-7: Delivery of IMS Emergency Call Origination to i3 PSAP with LbyV 36

Figure 8-8: Delivery of IMS Emergency Call Origination to Legacy PSAP with LbyV 39

Figure 8-9: Delivery of IMS Emergency Call Origination to i3 PSAP with LbyR..... 43

Figure 8-10: Delivery of IMS Emergency Call Origination to Legacy PSAP with LbyR 46

Figure 8-11: Delivery of Non-IMS Emergency Call Origination to i3 PSAP with LbyV 51

Figure 8-12: Delivery of Non-IMS Emergency Call Origination to Legacy PSAP with LbyV 54

Figure 8-13: Delivery of Non-IMS Emergency Call Origination to i3 PSAP with LbyR 58

Figure 8-14: Delivery of Non-IMS Emergency Call Origination to Legacy PSAP with LbyR 61

Figure 8-15: TTY Calls from IMS Originating Network to Legacy PSAP via NG9-1-1 66

Figure 8-16: TTY Calls from Legacy Originating Network to an i3 PSAP via NG9-1-1 68

Figure 8-17: TTY Calls from Legacy Originating Network to a Legacy PSAP via NG9-1-1 70

Figure 8-18: Conferencing Functional Architecture 73

Figure 8-19: i3 PSAP Establishes Conference with Conferencing AS/MRFC..... 74

Figure 8-20: i3 PSAP Requests that IBCF/B2BUA be Invited to the Conference 76

Figure 8-21: i3 PSAP Requests that a Secondary i3 PSAP be Invited to the Conference..... 78

Figure 8-22: i3 PSAP Requests that a Secondary Legacy PSAP be Invited to the Conference 80

Figure 8-23: Primary i3 PSAP Disconnects from the Conference – Secondary PSAP is an I3 PSAP 82

Figure 8-24: Primary i3 PSAP Disconnects from the Conference – Secondary PSAP is a Legacy PSAP 83

Figure 8-25: Secondary i3 PSAP Completes the Transfer and Terminates the Call..... 85

Figure 8-26: Secondary Legacy PSAP/LPG Completes the Transfer and Terminates the Call87

Figure 8-27: Primary i3 PSAP Invokes the Conference 89

Figure 8-28: Application Server (AS) Bridges Call #1 and Call #2 via IBCF#2 91

Figure 8-29: Application Server (AS) Invites Secondary i3 PSAP to Conference 93

Figure 8-30: Application Server (AS) Invites Secondary Legacy PSAP to Conference 96

Figure 8-31: Primary i3 PSAP Drops out of Conference with Secondary i3 PSAP 99

Figure 8-32: Primary i3 PSAP Drops out of Conference with Secondary Legacy PSAP	100
Figure 8-33: Conference AS/MRFC Released by Secondary i3 PSAP	102
Figure 8-34: Conference AS/MRFC Released by Secondary Legacy PSAP.....	103
Figure 8-35: Legacy PSAP Requests Transfer; LPG Establishes Conference with Conferencing AS/MRFC	105
Figure 8-36: Primary Legacy PSAP Disconnects from the Conference – Secondary PSAP is an I3 PSAP	108
Figure 8-37: Primary Legacy PSAP Disconnects from the Conference – Secondary PSAP is a Legacy PSAP	109
Figure 8-38: Legacy PSAP Establishes Conference with Conferencing AS/MRFC.....	111
Figure 8-39: Primary Legacy PSAP Drops out of Conference with Secondary i3 PSAP	114
Figure 8-40: Primary Legacy PSAP Drops out of Conference with Secondary Legacy PSAP.....	115
Figure 8-41: IMS Based Call to i3 PSAP – PRF Example	118

Table of Tables

Table 9-1: Mapping at LNG	124
Table 9-2: SS7 Wireline to SIP Header Mapping Example.....	124
Table 9-3: CAMA MF Wireline to SIP Header Mapping Example	125
Table 9-4: FG D MF Wireline to SIP Header Mapping Example.....	125
Table 9-5: SS7 WCM to SIP Header Mapping Example.....	126
Table 9-6: CAMA MF WCM to SIP Header Mapping Example	126
Table 9-7: FG D MF WCM to SIP Header Mapping Example.....	127
Table 9-8: SS7 NCAS to SIP Header Mapping Example.....	127
Table 9-9: CAMA MF NCAS to SIP Header Mapping Example	128
Table 9-10: FG D MF NCAS to SIP Header Mapping Example.....	128
Table A-1: SIP INVITE Header Profile Legend	132
Table A-2: SIP INVITE Header Profile	133

Preface

ATIS has developed a Next Generation 9-1-1 network and emergency call processing architecture based on contributions received since 2011 and based on requirements by a number of wireless carriers to have an IP Multimedia Subsystem (IMS)-compatible NG9-1-1 design¹. Additionally, the NENA i3 Architecture Working Group² deferred the IMS-based ESInet development to ATIS. ATIS' goal in developing this standard has been transparent interoperability between the two network designs.

ATIS' intent in this development work was to produce a standard method for IMS-based carriers to offer NG9-1-1 services wholly within their IMS platforms, while maintaining consistency and interoperability with the NENA i3 ESInet/NGCS (Next Generation Core Services) design goals. This kind of standards approach allows IMS-based carriers to take advantage of complete IMS interoperability and features found in their existing IMS ecosystems, while still remaining interoperable with downstream i3 PSAPs that implement NENA i3 standards and interfaces.

It is also ATIS' goal to assure that terminating NG9-1-1 entities, such as i3 PSAPs, find the upstream networks that are built on the ATIS IMS-based NG9-1-1 Service Architecture to be as completely interoperable with their systems and networks as that of a NENA i3 NG9-1-1 standard SIP-based architecture. This goal of transparency, both upstream and downstream between architectures, ensures that an i3 PSAP should find no difference whether the i3 PSAP interconnects to a NENA i3 ESInet with NGCS, or interconnects to an ATIS IMS-based NG9-1-1 Service Architecture. This consistent interoperability principle has guided all of ATIS' development work since the beginning, as documented within the original Issue Statement underlying this work.

The ATIS IMS-based NG9-1-1 Service Architecture provides compatibility for IMS-based carriers acting as an NG9-1-1 System Service Provider (911SSP) to seamlessly interoperate with NENA i3 ESInet architectures.

For entities early in the process of selecting ESInet solutions, the expectation within this ATIS development work was that the ATIS IMS-based NG9-1-1 Service Architecture would offer a choice for carriers that already had an IMS ecosystem, but not be considered a viable architecture choice for 9-1-1 service entities that had no plans for an IMS infrastructure.

Public Safety entities should naturally understand the applicability of an IMS-based NG9-1-1 Service Architecture network approach to processing emergency calls, yet in this case, they can remain confidently focused on NENA i3-based NG9-1-1 architectures, (this is because IMS may be of interest to carriers, not to jurisdictions), which means that Public Safety's progress and momentum to adopt NG9-1-1 will not be impeded by the introduction of this ATIS NG9-1-1 Service Architecture standard.

1 Scope, Purpose, & Application

1.1 Scope

This ATIS Standard applies IP Multimedia Subsystem (IMS) architecture concepts to Next Generation 9-1-1 (NG9-1-1) networks to encompass:

- Definition of an IMS-based NG9-1-1 Emergency Services Network architecture and set of additional gateway functional elements that are integrated into this IMS-based NG9-1-1 Service Architecture, adopted from the existing NENA i3 architecture, to support the delivery of emergency calls to legacy and NG9-1-1/i3 PSAPs.
- NG9-1-1 network deployment scenarios showing an IMS-based NG9-1-1 Service Architecture interconnecting with a variety of originating network and PSAP types, and associated Stage 2/3 call flows.

¹ IMS is a set of standards based on the IETF RFC 3261 [Ref 18] family of standards that also introduces additional requirements, specific for carrier operators not differentiated in the more general SIP RFCs.

² The NENA i3 Architecture Working Group developed NENA-STA-010.2 [Ref 27].