

Specification for the Fabrication of Structural Steel Pipe

API SPECIFICATION 2B
SIXTH EDITION, JULY 2001

EFFECTIVE DATE: JANUARY 1, 2002

REAFFIRMED, SEPTEMBER 2020

ADDENDUM 1, MARCH 2021



SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

FOREWORD

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows. Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

CONTENTS

	Page
1 SCOPE	1
2 REFERENCES	1
3 DEFINITIONS	1
4 MATERIAL	1
5 FABRICATION	2
5.1 General	2
5.2 Welding Procedure Qualification	2
5.3 Welder and Welding Operator Qualification	2
5.4 Longitudinal Welds	2
5.5 Girth Welds	2
5.6	3
6 DIMENSIONS AND TOLERANCES	3
6.1 Diameter, Length, and Wall Thickness	3
6.2 Roundness	3
6.3 Circumference	3
6.4 Straightness	3
6.5 Pipe Ends	3
7 INSPECTION AND REPAIR	3
7.1 Inspection	3
7.2 Weld Inspection	3
7.3 Nondestructive Examination	3
7.4 Repair of Base Metal Imperfections	3
8 MARKING	4
APPENDIX A—SUPPLEMENTARY REQUIREMENTS	6
APPENDIX B—METRIC CONVERSION TABLE	8
Figures	
A-1—Plate Rolling Direction Orientation	6
Tables	
B-1—Metric Conversion Table	8

Suggestions for Ordering API 2B Pipe

In placing orders for steel pipe to be fabricated in accordance with API Specification 2B, the purchaser should specify the following on the purchase order:

- Specification API 2B
- Quantity As required
- Size Nominal length, wall thickness, and outside diameter
- ASTM (or other industry standard) designation for steel plate Specification/Grade/
Supplementary requirements
- Delivery date and shipping instructions As required

The purchaser should state whether any of the following optional requirements are to apply:

- Mill test certificate for steel plate
- End finish (specify, if not standard 30 degree bevel)
- SR1, plate direction of rolling
Longitudinal—"S-IL"
Transverse—"S-IT"
- SR2, notch toughness (specify test temperatures and minimum energy requirements)
- SR3, 100% radiographic examination (joint can quality assurance)
- SR4, matching weld toughness for designated plate material

Nothing in this specification should be interpreted as indicating a preference by the committee for any optional requirement. In the selection of requirements, the purchaser must be guided by the purchaser's experience and by the service for which the pipe is intended.

Specification for the Fabrication of Structural Steel Pipe

1 Scope

This specification covers the fabrication of structural steel pipe formed from plate steel with longitudinal and circumferential butt-welded seams, typically in sizes 14 in. outside diameter (OD) and larger (40 in. and larger for LWDS) with wall thickness $\frac{3}{8}$ in. and greater (up to a nominal 40 ft in length) suitable for use in construction of welded offshore structures. The use of the ERW process or spiral welded pipe is not included in this specification. Pipe fabricated under this specification is intended to be used primarily in piling and main structural members, including tubular truss connections, where internal stiffeners are not usually required.

2 References

The following specifications and standards become a part of and shall be considered concurrently with this specification:

ASTM¹

- A 6–99 *General Requirements for Rolled Steel Plates, Shapes, Sheet Piling, and Bars for Structural Use*
- A 20-99 *General Requirements for Delivery of Steel Plates for Pressure Vessels*
- A 370-97 *Mechanical Testing of Steel Products*
- E 23-98 *Notched Bar Impact Testing of Metallic Materials*

AWS²

- D1.1-2000 *Structural Welding Code—Steel*

3 Definitions

For the purpose of this standard, the following definitions apply:

- 3.1 can:** A section of structural steel pipe with no girth seam.
- 3.2 fabricator:** The person, firm, company, or corporation executing the contract or agreement with the purchaser to fabricate the structural steel pipe under this specification.
- 3.3 girth weld:** A circumferential butt-welded seam lying in a plane perpendicular to the longitudinal axis of the pipe, used to join tubular sections into lengths of straight pipe.

3.4 longitudinal seam: A butt-welded seam which parallels the axis of the pipe.

3.5 longitudinally welded double seam (LWDS) pipe: A can with two longitudinal seams, one of which may be made in the flat plate condition.

3.6 manufacturer: The firm, company, or corporation-furnishing plate steel used in the fabrication of the structural steel pipe.

3.7 mill pipe: A structural steel pipe consisting of multiple cans joined by girth welds.

3.8 pile: A cylindrical tubular member fabricated from one or more lengths of structural steel pipe, usually driven through a leg or sleeve of an offshore platform, that carries vertical loads and resists lateral forces.

3.9 pipe weld: A longitudinal seam made after the plate has been formed into pipe.

3.10 plate weld: A longitudinal seam made between flat plates which are subsequently formed into pipe.

3.11 purchaser: The person, firm, company, or corporation entering into a contract or agreement for the purchase of structural steel pipe fabricated under this specification.

3.12 single seam welded pipe: A can with one longitudinal seam, produced by a continuous welding process.

3.13 structural steel pipe: A cylindrical tubular member formed from steel plate, having a uniform material and wall thickness, with longitudinal and/or circumferential butt welded seams, comprising of the following types: can, single seam welded pipe, longitudinally welded double seam (LWDS) and mill pipe.

4 Material

4.1 Pipe furnished to this specification shall be fabricated from plate steel as specified by the purchaser.

4.2 The purchaser shall specify the grade and quality of plate steel to be used. When the plate steel is furnished by the fabricator, a mill test certificate must be available and shall be furnished to the purchaser upon request. All plate shall bear

¹ASTM, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428.

²American Welding Society, 550 N.W. Le Jeune Road, Miami, Florida 33126.