

RTCA, Inc.
1150 18th Street NW, Suite 910
Washington, DC 20036
USA

**Minimum Operational Performance Standards
for
Rechargeable Lithium Batteries and
Battery Systems**

RTCA DO-311A
December 19, 2017

Prepared by: SC-225
© 2017 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was prepared by Special Committee 225 (SC-225) and approved by the RTCA Program Management Committee (PMC) on December 19, 2017. It supersedes RTCA DO-311 dated March 13, 2008. It also supersedes DO-347 Certification Test Guidance for Small and Medium Sized Rechargeable Lithium Batteries and Battery Systems, dated December 18, 2013.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal advisory committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include, but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The recommendations of RTCA are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders and several advisory circulars.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the United States Government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

DISCLAIMER

This publication is based on material submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document shall constitute an acceptance thereof "as is" and be subject to this disclaimer.

This Page Intentionally Left Blank

EXECUTIVE SUMMARY

This document was prepared by RTCA Special Committee SC-225. Members of this committee included representatives from battery and cell manufacturers, avionics manufacturers, aircraft manufacturers, aircraft operators, pilot and flight attendant associations, regulatory and other government agencies, and related industry associations.

The SC-225 committee reviewed and considered regulatory requirements, multiple standards, and resources associated with rechargeable lithium batteries in developing this standard. These include FAA Special Conditions related to rechargeable lithium batteries and battery systems, RTCA/DO-311, RTCA/DO-347, UL 1642, UL 2054, UN Section 38.3, and IEC 62133.

This standard provides design, testing, and installation guidance for rechargeable lithium battery systems that are permanently installed on aircraft including standalone and embedded batteries. It addresses all sizes of rechargeable lithium battery systems regardless of energy content (watt-hours). Batteries or battery systems that are less than two watt-hours are exempt from this standard if they have met the requirements of applicable UL or IEC standards. Otherwise, the requirements of this standard apply.

Section 1 (Introduction) identifies battery categories by energy content, venting provisions, and architecture.

Section 2 (Qualification Requirements and Test Procedures) contains the requirements and test procedures that are performed on rechargeable lithium battery systems. They include general, performance, safety, and environmental requirements and tests.

Section 3 (Installation Considerations) provides installation considerations that may impact the design of the battery system. It also provides installation considerations for the installer. Section 3 does not contain requirements.

Three appendices are included. Appendix A provides additional safety considerations pertinent to storage, shipping, handling and disposal of rechargeable lithium batteries and battery systems. Appendix B provides optional methods of testing shelf life and float life. Appendix C provides an alternate test method for the battery thermal runaway containment test. FAA has not acknowledged Appendix C as an acceptable means of compliance, or an alternate equivalent test for section 2.4.5.5.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1	INTRODUCTION.....	1
1.1	Purpose.....	1
1.2	Scope.....	1
1.3	System Overview.....	1
1.4	Battery Categories.....	2
1.4.1	Energy Categories.....	2
1.4.2	Venting Categories.....	2
1.4.3	Architecture Categories.....	2
1.5	Regulatory Responsibilities for Installed Equipment.....	3
1.6	Test Procedures.....	3
1.7	References.....	3
1.8	Definition of Terms.....	4
1.8.1	Acronyms and Abbreviations.....	7
2	REQUIREMENTS, GUIDELINES, AND TEST PROCEDURES.....	9
2.1	General Requirements.....	9
2.1.1	Fire Protection.....	9
2.1.2	Design Assurance.....	9
2.1.3	Marking.....	9
2.1.3.1	Standalone Battery Marking.....	9
2.1.3.2	Embedded Battery Marking.....	10
2.1.4	General Safety Requirements.....	10
2.1.4.1	Battery Protective Features.....	11
2.1.4.2	Battery Warning Features.....	11
2.1.5	Charging and Discharging Protection.....	11
2.1.6	Overdischarge Protection.....	11
2.1.7	Mitigation of Cell Failures.....	12
2.1.8	Venting Provisions.....	12
2.1.9	Shelf Life and Float Life.....	13
2.1.10	Design Guidelines.....	13
2.1.10.1	General Guidelines.....	13
2.1.10.2	Cell Balancing.....	14
2.1.10.3	State of Health Function.....	15
2.1.10.4	State of Charge Function.....	15
2.1.10.5	Built-In-Test.....	15
2.1.10.6	Parasitic Drain.....	15
2.1.10.7	Prevention from Bus Back Charging.....	15
2.1.10.8	Electrical Bonding.....	15
2.1.10.9	Dissimilar Metals.....	15
2.1.11	Quality.....	15
2.1.11.1	Configuration Control.....	16
2.1.11.2	Workmanship.....	16

2.1.12	Maintenance Documentation Guidance	16
2.2	Equipment Requirements – Standard Conditions	17
2.2.1	Performance Requirements	17
2.2.1.1	Physical Examination.....	17
2.2.1.2	Acceptance Test Procedure	17
2.2.1.3	Insulation Resistance.....	17
2.2.1.4	Handle Strength.....	18
2.2.1.5	Rated Capacity	18
2.2.1.6	Capacity at Low and High Temperatures.....	18
2.2.1.7	Constant Voltage Discharge for High Rate Batteries.....	18
2.2.1.8	Charge Acceptance.....	18
2.2.1.9	Charge Retention.....	18
2.2.1.10	Cycling of High Rate Batteries	18
2.2.1.11	Rapid Discharge at Short-Time Operating High Temperature	19
2.2.1.12	Short Circuit Protection	19
2.2.1.13	Overdischarge Protection.....	19
2.2.1.14	Overcharge Protection	19
2.2.2	Safety Requirements	19
2.2.2.1	Short Circuit without Protection	19
2.2.2.2	Overdischarge without Protection.....	20
2.2.2.3	Single Cell Thermal Runaway Containment.....	20
2.2.2.4	Battery Thermal Runaway Containment.....	20
2.2.2.5	Explosion Containment	20
2.2.2.6	Drop Impact Resistance	20
2.3	Equipment Requirements – Environmental Conditions	21
2.3.1	Environmental Performance Requirements.....	21
2.3.2	Environmental Test Procedures	22
2.4	Equipment Test Procedures.....	22
2.4.1	Definitions of Terms and Conditions of Test.....	22
2.4.2	Test Matrix	23
2.4.3	Test Setup.....	25
2.4.3.1	Special Electrical Grounding Provision	25
2.4.4	Performance Tests.....	25
2.4.4.1	Physical Examination (Paragraph 2.2.1.1)	25
2.4.4.2	Acceptance Test Procedure (Paragraph 2.2.1.2)	25
2.4.4.3	Insulation Resistance Test (Paragraph 2.2.1.3)	26
2.4.4.4	Handle Strength Test (Paragraph 2.2.1.4)	26
2.4.4.5	Capacity Test (Paragraph 2.2.1.5).....	26
2.4.4.6	Capacity Test at Low and High Temperatures (Paragraph 2.2.1.6)	27
2.4.4.7	Constant Voltage Discharge Test for High Rate Batteries (Paragraph 2.2.1.7)	27
2.4.4.8	Charge Acceptance Test (Paragraph 2.2.1.8).....	28
2.4.4.9	Charge Retention Test (Paragraph 2.2.1.9)	29
2.4.4.10	Cycle Test for High Rate Batteries (Paragraph 2.2.1.10)	29
2.4.4.11	Rapid Discharge Test at Short-Time Operating High Temperature (Paragraph 2.2.1.11)	30
2.4.4.12	Short Circuit Test with Protection Enabled (Paragraph 2.2.1.12).....	31
2.4.4.13	Overdischarge Test (Paragraph 2.2.1.13).....	31
2.4.4.13.1	Test Method for Standalone Batteries	32
2.4.4.13.2	Test Method for Embedded Batteries	32
2.4.4.14	Overcharge Test (Paragraph 2.2.1.14)	33
2.4.5	Safety Tests	34
2.4.5.1	Short Circuit Test of a Cell (Paragraph 2.2.2.1).....	34

2.4.5.2	Short Circuit Test of a Battery without Protection (Paragraph 2.2.2.1)	35
2.4.5.3	Overdischarge Test without Protection (Paragraph 2.2.2.2)	36
2.4.5.3.1	Test Method for Standalone Batteries	36
2.4.5.3.2	Test Method for Embedded Batteries	37
2.4.5.4	Single Cell Thermal Runaway Containment Test (Paragraph 2.2.2.3)	38
2.4.5.4.1	Test Method for Single Cell Thermal Runaway via Overcharging	38
2.4.5.4.2	Test Method for Single Cell Thermal Runaway via Overheating	39
2.4.5.5	Battery Thermal Runaway Containment Test (Paragraph 2.2.2.4)	40
2.4.5.5.1	Test Method for Battery Thermal Runaway via Overcharging	41
2.4.5.5.2	Test Method for Battery Thermal Runaway via Overheating	42
2.4.5.6	Explosion Containment Test (Paragraph 2.2.2.5)	42
2.4.5.7	Drop Impact Test (Paragraph 2.2.2.6)	43
3	INSTALLATION CONSIDERATIONS	45
3.1	Manufacturer Considerations	45
3.1.1	Aircraft Warning System	45
3.1.2	Aircraft Environment	45
3.1.3	Failure Protection	45
3.2	Installer Considerations	45
3.2.1	Hazardous Battery Emissions	45
3.2.2	Installation Design	46
3.2.3	Additional Considerations for Installed Equipment	46
3.3	Test Procedures for Installed Equipment	46
4	MEMBERSHIP	47
APPENDIX A: SAFETY GUIDELINES FOR USERS OF RECHARGEABLE LITHIUM BATTERIES		A-1
A.1	Electric Burn Hazard	A-1
A.2	Electric Shock Hazard	A-1
A.3	Thermal Runaway	A-1
A.4	Damage to Connectors	A-2
A.5	Storage	A-2
A.6	Shipping	A-2
A.7	Disposal	A-2
A.8	Mixing of Cells	A-2
A.9	Cell Polarity	A-2
APPENDIX B: OPTIONAL TEST METHODS		B-1
B.1	Shelf Life Test	B-1
B.2	Float Life Test	B-1

APPENDIX C: ALTERNATE TEST METHOD FOR BATTERY THERMAL RUNAWAY CONTAINMENT TEST.....		C-1
C.1	Prerequisites	C-2
C.2	Test Method	C-2
APPENDIX D: RTCA DO-311A DISSENTING OPINION LETTER.....		D-1
APPENDIX E: RESPONSE TO TRUE BLUE DISSENT.....		E-1

TABLE OF TABLES

Table 1–1: Energy Categories.....	2
Table 2–1: Environmental Tests	21
Table 2–2: Test Matrix.....	23

TABLE OF FIGURES

Figure 2–1: Internal Test Points for Overcharge Testing.....	34
Figure 2–2: Internal Test Points for Single Cell Safety Tests.....	39

1 INTRODUCTION

1.1 Purpose

This Minimum Operational Performance Standard (MOPS) is for rechargeable lithium batteries and battery systems permanently installed on aircraft. It provides design, analysis, testing, and installation guidance for rechargeable lithium batteries and battery systems. The tests defined in this document provide a standardized method for verification (i.e. pass/fail) and characterization (i.e. report results) of the safety and performance of batteries and battery systems.

This standard is intended for designers and manufacturers of rechargeable lithium batteries and battery systems, aircraft manufacturers, aircraft equipment installers, and users within the aviation community. Meeting the requirements of this standard provides a means of assuring that the batteries and battery systems will perform their intended function(s) safely under conditions encountered in aeronautical operations. To ensure safe operation on the aircraft, it is imperative that users of this standard thoroughly understand the aircraft performance requirements and the capabilities and limitations of the batteries and battery systems. It is the equipment installers' responsibility to ensure that the batteries and battery systems meet the certification and installation requirements of the aircraft. Any regulatory application of this standard is the responsibility of the applicable government agency.

1.2 Scope

This standard applies to rechargeable lithium batteries and battery systems that are permanently installed on aircraft. For the purpose of this standard, a battery or battery system is considered permanently installed equipment when it is included as part of the type design of the aircraft (or supplemental/amended type design). This standard also applies to rechargeable lithium batteries contained within Portable Electronic Devices (PEDs) that are part of the type design. This standard does not apply to primary (non-rechargeable) lithium batteries.

Note: *Rechargeable lithium batteries within PEDs that are not part of the type design are outside the scope of this standard; these PEDs fall under the purview of Federal Aviation Administration (FAA) Flight Standards Division and are regulated by operational rules under Title 14 of the Code of Federal Regulations (CFR). PEDs that are not part of the type design, especially those being recharged on the flight deck, present similar hazards as permanently installed equipment.*

This standard does not require individual cell level testing or characterization of cell/battery aging. Other standards such as UL, IEC, and UN may be used to perform cell level testing or to characterize aging effects of the cell/battery.

1.3 System Overview

Rechargeable lithium batteries and battery systems of various chemical compositions, sizes, and construction details are being widely promoted for aircraft applications. Among their desirable characteristics are high energy content per unit weight, relatively constant voltage during discharge, and long cycle life. Rechargeable lithium batteries and battery systems can provide power throughout the aircraft, including engine or Auxiliary Power Unit (APU) starting, avionics, emergency, and other systems. Because of their high specific energy/power and potential thermal instability, they can present hazards if improperly designed, assembled, tested, installed, used, handled, or stored.