

RTCA, Inc.  
1828 L Street, NW, Suite 805  
Washington, DC 20036-5133 USA

# **Minimum Operational Performance Standards for Global Positioning System / Aircraft-Based Augmentation System Airborne Equipment**

RTCA DO-316  
April 14, 2009

Prepared by: SC-159  
2009 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: [www.rtca.org](http://www.rtca.org)

Please visit the RTCA Online Store for document pricing and ordering information.

## Foreword

This document was prepared by RTCA Special Committee 159 (SC-159) and approved by the RTCA Program Management Committee (PMC) on April 14, 2009.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity, and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of Minimum Operation Performance Standards (MOPS) for electronic systems and equipment that support aviation; and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization (ICAO) and the International Telecommunication Union (ITU) and other appropriate international organizations can be based.

The recommendations of RTCA are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders (TSO).

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank

# TABLE OF CONTENTS

|            |  |           |
|------------|--|-----------|
| <b>1.0</b> | <b><i>PURPOSE AND SCOPE</i></b> .....                                  | <b>1</b>  |
| <b>1.1</b> | <b>Introduction</b> .....  | <b>1</b>  |
| <b>1.2</b> | <b>System Overview</b> .....   | <b>3</b>  |
| 1.2.1      | GNSS Satellite Signal Characteristics .....                            | 3         |
| <b>1.3</b> | <b>Operational Goals</b> .....   | <b>4</b>  |
| 1.3.1      | Operational Environment.....   | 4         |
| 1.3.2      | International Compatibility .....                                      | 4         |
| <b>1.4</b> | <b>Equipment Type</b> .....  | <b>5</b>  |
| <b>1.5</b> | <b>FDE with Barometric Aiding</b> .....                                | <b>5</b>  |
| <b>1.6</b> | <b>Test Considerations</b> .....                                       | <b>5</b>  |
| 1.6.1      | Environmental Tests .....  | 5         |
| 1.6.2      | Bench Tests.....   | 5         |
| <b>1.7</b> | <b>Definition of Key Terms</b> .....                                   | <b>6</b>  |
| 1.7.1      | General Terms .....  | 6         |
| 1.7.2      | Alert Limits and Protection Levels .....                               | 6         |
| 1.7.3      | Fault Detection and Exclusion (FDE) Terms.....                         | 7         |
| <b>1.8</b> | <b>Assumptions and Approach to Selected Issues</b> .....               | <b>12</b> |
| 1.8.1      | General.....   | 12        |
| <b>2.0</b> | <b><i>EQUIPMENT PERFORMANCE AND TEST PROCEDURES</i></b> .....          | <b>15</b> |
| <b>2.1</b> | <b>General Requirements</b> .....                                      | <b>15</b> |
| 2.1.1      | Requirements Applicable to GPS Equipment .....                         | 15        |
| 2.1.2      | Requirements for En Route and Terminal Mode .....                      | 22        |
| 2.1.3      | Requirements for LNAV .....  | 29        |
| <b>2.2</b> | <b>Airborne Equipment Performance - Environmental Conditions</b> ..... | <b>32</b> |
| 2.2.1      | Environmental Tests .....  | 32        |
| <b>2.3</b> | <b>Test Methods and Procedures</b> .....                               | <b>37</b> |
| 2.3.1      | Reserved .....   | 39        |
| 2.3.2      | Step Detector Test.....  | 39        |
| 2.3.3      | Initial Acquisition Test Procedures.....                               | 41        |
| 2.3.4      | Satellite Reacquisition Time Test .....                                | 44        |
| 2.3.5      | Interference Rejection Test.....                                       | 45        |
| 2.3.6      | Accuracy Tests.....  | 47        |
| 2.3.7      | Integrity Monitoring Test Procedures .....                             | 59        |
| <b>3.0</b> | <b><i>INSTALLED EQUIPMENT PERFORMANCE</i></b> .....                    | <b>69</b> |
| <b>4.0</b> | <b><i>OPERATIONAL CHARACTERISTICS</i></b> .....                        | <b>71</b> |
| <b>5.0</b> | <b><i>MEMBERSHIP</i></b> .....   | <b>73</b> |
|            | <b>APPENDIX A</b> .....  | <b>1</b>  |
|            | <b>APPENDIX B STANDARD GPS ASSUMPTIONS</b> .....                       | <b>1</b>  |
| <b>B.1</b> | <b>GPS Constellation</b> .....   | <b>1</b>  |
| <b>B.2</b> | <b>GPS Satellite Failure</b> .....                                     | <b>1</b>  |
| <b>B.3</b> | <b>GPS Constellation for Availability Analysis</b> .....               | <b>1</b>  |
| <b>B.4</b> | <b>Signal Quality Monitoring</b> .....                                 | <b>2</b>  |
| B.4.1      | Dead Zones .....   | 2         |

|   |  |          |
|---|--|----------|
| B.4.2   | False Peaks.....   | 2        |
| B.4.3   | Distortions.....   | 3        |
| B.4.4   | Threat Models.....   | 3        |
| <b>APPENDIX C STANDARD RECEIVED SIGNAL AND INTERFERENCE ENVIRONMENT.....</b>                        |  | <b>1</b> |
| <b>C.1</b>  | <b>Introduction.....</b>   | <b>1</b> |
| <b>C.2</b>  | <b>Operating Interference Environment .....</b>                                | <b>1</b> |
| C.2.1   | Out-of-Band Interference.....  | 1        |
| C.2.2   | In-Band and Near-Band Interference.....  | 2        |
| C.2.3   | GNSS Noise.....  | 4        |
| <b>C.3</b>  | <b>Minimum Standard Antenna Frequency Selectivity .....</b>                    | <b>4</b> |
| <b>APPENDIX D RESERVED .....</b>  |  | <b>1</b> |
| <b>APPENDIX E BASELINE WEIGHTED NAVIGATION SOLUTION AND NAVIGATION SYSTEM ERROR ALGORITHMS.....</b> |  | <b>1</b> |
| <b>E.1</b>  | <b>Introduction.....</b>   | <b>1</b> |
| <b>E.2</b>  | <b>Baseline Navigation Solution.....</b>                                       | <b>1</b> |
| <b>E.3</b>  | <b>References.....</b>   | <b>2</b> |
| <b>APPENDIX F EXAMPLE VELOCITY AND VELOCITY FIGURE OF MERIT COMPUTATION .....</b>                   |  | <b>1</b> |
| <b>F.1</b>  | <b>Introduction.....</b>   | <b>1</b> |
| <b>F.2</b>  | <b>Velocity Solution with Figure of Merit.....</b>                             | <b>1</b> |
| <b>F.3</b>  | <b>References.....</b>   | <b>3</b> |
| <b>APPENDIX G REQUIREMENTS FOR BAROMETRIC ALTIMETER AIDING .....</b>                                |  | <b>1</b> |
| <b>G.1</b>  | <b>General.....</b>  | <b>1</b> |
| <b>G.2</b>  | <b>Altimeter Aiding with GNSS Calibration.....</b>                             | <b>1</b> |
| G.2.1   | Requirements for Calibration .....   | 1        |
| G.2.2   | Calculation of $\sigma_{\text{baro}}$ .....                                    | 2        |
| G.2.3   | Actual Use of the Altitude Measurement to Augment GNSS .....                   | 3        |
| <b>G.3</b>  | <b>Barometric Altimeter Aiding Using Baro-corrected Pressure Altitude.....</b> | <b>4</b> |
| G.3.1   | Requirements for calibration .....   | 4        |
| G.3.2   | Calculation of $\sigma_{\text{baro}}$ .....                                    | 4        |
| G.3.3   | Actual Use of the Barometric Altitude Measurement to Augment GNSS .....        | 5        |
| G.3.4   | Requirements for Pilot Interaction .....                                       | 5        |
| <b>G.4</b>  | <b>Test Procedures.....</b>  | <b>5</b> |
| <b>G.5</b>  | <b>References.....</b>   | <b>5</b> |
| <b>APPENDIX H STANDARD OUTPUT FORMAT.....</b>   |  | <b>1</b> |
| <b>H.1</b>  | <b>Introduction.....</b>   | <b>1</b> |
| <b>H.2</b>  | <b>GPS Minimum Output and Output Timing .....</b>                              | <b>1</b> |
| H.2.1   | Minimum GPS Output.....  | 1        |
| H.2.2   | Timing .....   | 3        |
| <b>H.3</b>  | <b>Other Desirable GPS Outputs .....</b>                                       | <b>4</b> |
| <b>H.4</b>  | <b>Summary.....</b>  | <b>4</b> |
| <b>H.5</b>  | <b>References.....</b>   | <b>4</b> |

|  |          |
|--|----------|
| <b>APPENDIX I RESERVED</b> .....   | <b>1</b> |
| <b>APPENDIX J WEIGHTS FOR USE IN GENERAL LEAST SQUARES SOLUTIONS AND TROPOSPHERIC CORRECTION ALGORITHM</b> ..... | <b>1</b> |
| <b>J.1 Weights</b> .....   | <b>1</b> |
| J.2 Variance of Ionospheric Delay .....  | 1        |
| J.3 Variance of Airborne Receiver Errors .....   | 2        |
| J.4 Tropospheric Correction Model.....   | 3        |
| J.5 Model Standard Deviation for Tropospheric Error.....   | 5        |
| <b>APPENDIX K FAULT DETECTION AND EXCLUSION REFERENCES</b> .....   | <b>1</b> |
| <b>APPENDIX L THE DIRECT AND INDIRECT GEODETIC PROBLEMS FOR GREAT CIRCLE NAVIGATION</b> .....                    | <b>1</b> |
| <b>L.1 General</b> .....   | <b>1</b> |
| <b>L.2 Definitions of Terms</b> .....  | <b>1</b> |
| <b>L.3 Nomenclature</b> .....  | <b>2</b> |
| <b>L.4 WGS-84 Parameters (from [5])</b> .....  | <b>2</b> |
| <b>L.5 The Indirect Problem</b> .....  | <b>2</b> |
| <b>L.6 The Direct Problem</b> .....  | <b>4</b> |
| <b>L.7 Validation</b> .....  | <b>6</b> |
| <b>L.8 References</b> .....  | <b>7</b> |
| <b>APPENDIX M</b> .....  | <b>1</b> |
| <b>M.1 Introduction</b> .....  | <b>1</b> |
| <b>M.2 (Initial) Acquisition and Reacquisition Testing Statistical Justification</b> .....                       | <b>1</b> |
| <b>M.3 Accuracy Statistical Justification</b> .....  | <b>2</b> |
| <b>M.4 General Simulator Scenario Conditions</b> .....   | <b>4</b> |
| Guidelines .....   | 4        |
| <b>M.5 Example Test Set-up and Compensation of Signals, Noise and Interference</b> .....                         | <b>5</b> |
| M.5.1 Description of the Test Set-up .....   | 5        |
| M.5.2 Use of the Test Set-up for the Accuracy Test (See 2.3.6) .....   | 6        |
| <b>APPENDIX N REFERENCE MATERIAL FOR DETERMINING THE MEAN SEA LEVEL HEIGHT FROM WGS-84 COORDINATES</b> .....     | <b>1</b> |
| <b>N.1 Introduction</b> .....  | <b>1</b> |
| N.1.1 General Altimetry.....   | 1        |
| N.1.2 Mean Sea Level (MSL) Altitude .....  | 1        |
| N.1.3 Barometric Altitude.....   | 2        |
| N.1.4 Radar Altitude .....   | 2        |
| N.1.5 GPS Altitude .....   | 2        |
| <b>APPENDIX O GLOSSARY AND ACRONYMS</b> .....  | <b>1</b> |
| <b>APPENDIX P RESERVED</b> .....   | <b>1</b> |
| <b>APPENDIX Q RESERVED</b> .....   | <b>1</b> |
| <b>APPENDIX R REQUIREMENTS AND TEST PROCEDURES FOR TIGHTLY INTEGRATED GPS/INERTIAL SYSTEMS</b> .....             | <b>1</b> |
| <b>R.1 Introduction</b> .....  | <b>1</b> |

|  |   |                 |
|--|---|-----------------|
| <b>R.2</b>   | <b>Requirements.....</b>  | <b>1</b>        |
| R.2.1  | General FDE Requirements .....  | 1               |
| R.2.2  | Unique Additional Requirements .....                                      | 3               |
| <b>R.3</b>   | <b>Tightly Integrated GPS/Inertial Design Concepts .....</b>              | <b>9</b>        |
| R.3.1  | Integration Methods .....   | 9               |
| R.3.2  | Detection and Exclusion Mechanisms .....                                  | 11              |
| <b>R.4</b>   | <b>Assumptions.....</b>   | <b>12</b>       |
| R.4.1  | Signal Error Model .....  | 12              |
| R.4.2  | Satellite Clock Drift Characteristics .....                               | 13              |
| <b>R.5</b>   | <b>Validation.....</b>  | <b>13</b>       |
| R.5.1  | Categorization of Detection and Exclusion Mechanisms .....                | 13              |
| R.5.2  | Covariance Simulation.....  | 14              |
| R.5.3  | False Alert Probability .....   | 15              |
| R.5.4  | Fault Free Accuracy Performance .....                                     | 15              |
| R.5.5  | Off-Line Rare Normal Verification .....                                   | 16              |
| R.5.6  | Off-Line Detection/Exclusion Verification .....                           | 16              |
| R.5.7  | On-Line Validation .....  | 19              |
| R.5.8  | Gravity Compensation Validation .....                                     | 19              |
| R.5.9  | Ionospheric Error Models .....  | 20              |
| <b>R.6</b>   | <b>References.....</b>  | <b>21</b>       |
| <b><i>APPENDIX S RESERVED.....</i></b>                                     |   | <b><i>1</i></b> |
| <b><i>APPENDIX T RESERVED.....</i></b>                                     |   | <b><i>1</i></b> |
| <b><i>APPENDIX U GUIDANCE MATERIAL FOR INTERFACING WITH ADS-B.....</i></b> |   | <b><i>1</i></b> |
| <b>U.1</b>   | <b>Purpose and Scope .....</b>  | <b>1</b>        |
| <b>U.2</b>   | <b>Position Output and Validity .....</b>                                 | <b>1</b>        |
| <b>U.3</b>   | <b>Horizontal Figure of Merit (HFOM<sub>P</sub>) .....</b>                | <b>1</b>        |
| <b>U.4</b>   | <b>Horizontal Protection Limit (HPL).....</b>                             | <b>1</b>        |
| <b>U.5</b>   | <b>Velocity.....</b>  | <b>2</b>        |
| <b>U.6</b>   | <b>Vertical Figure of Merit and Vertical Protection Limit (VPL) .....</b> | <b>2</b>        |

## FIGURES

|            |   |    |
|------------|---|----|
| FIGURE 1-1 | DIAGRAM OF FDE CONDITIONS.....                        | 8  |
| FIGURE 1-2 | MARKOV CHAIN FOR FDE .....                            | 9  |
| FIGURE 1-3 | EXAMPLE FDE EVENTS .....                              | 10 |
| FIGURE 2-1 | SENSITIVITY AND DYNAMIC RANGE CONFIGURATION .....     | 20 |
| FIGURE C-1 | INTERFERENCE LEVELS AT THE ANTENNA PORT .....         | 1  |
| FIGURE C-2 | IN-BAND AND NEAR-BAND INTERFERENCE ENVIRONMENTS ..... | 2  |
| FIGURE C-3 | FREQUENCY SELECTIVITY.....                            | 5  |
| FIGURE H-1 | GPS TIMING RELATIONSHIPS .....                        | 3  |
| FIGURE M-1 | (RE)ACQUISITION TEST PROBABILITY STATISTICS.....      | 2  |
| FIGURE M-2 | PSEUDORANGE ACCURACY TEST PASS CRITERIA .....         | 3  |
| FIGURE M-3 | PSEUDORANGE ACCURACY TEST PASS PROBABILITY .....      | 4  |
| FIGURE M-4 | EXAMPLE TEST SET-UP .....                             | 5  |
| FIGURE R-1 | FLIGHT PROFILE ASSUMED FOR THE COASTING TIMES .....   | 8  |

## TABLES

|  |    |
|--|----|
| TABLE 2-1 URA VALUES .....   | 24 |
| TABLE 2-2 GPS ENVIRONMENTAL TEST REQUIREMENTS .....                      | 36 |
| TABLE 2-3 GRADUATED SAMPLING PASS/FAIL CRITERIA .....                    | 43 |
| TABLE 2-4 STEADY STATE ACCURACY TEST CWI VALUES* .....                   | 48 |
| TABLE 2-5 SATELLITE EQUIVALENT POWER SPECTRAL DENSITY .....              | 49 |
| TABLE 2-6 PASS THRESHOLD TABLE .....                                     | 51 |
| TABLE 2-7 PLATFORM DYNAMICS FOR HORIZONTAL VELOCITY ACCURACY TEST .....  | 54 |
| TABLE 2-8 PLATFORM DYNAMICS FOR VERTICAL VELOCITY ACCURACY TEST .....    | 57 |
| TABLE 2-9 MAXIMUM NUMBER OF OUTCOMES TO OFF-LINE FDE TEST .....          | 65 |
| TABLE B-1 OPTIMIZED 24 GPS CONSTELLATION .....                           | 1  |
| TABLE B-2 GPS CONSTELLATION ON DECEMBER 1, 1995 AT 00:00 UTC .....       | 2  |
| TABLE C-1 OUT-OF-BAND PULSE INTERFERENCE .....                           | 2  |
| TABLE C-2 IN-BAND AND NEAR-BAND INTERFERENCE BANDWIDTH DEFINITIONS ..... | 3  |
| TABLE C-3 IN-BAND AND NEAR-BAND PULSE INTERFERENCE .....                 | 4  |
| TABLE C-4 EFFECTIVE NOISE DENSITY FOR ALL GNSS SOURCES .....             | 4  |
| TABLE C-5 FREQUENCY SELECTIVITY .....                                    | 5  |
| TABLE G-1 PRESSURE GRADIENT ERRORS (KNOWN GL) .....                      | 3  |
| TABLE G-2 PRESSURE GRADIENT ERRORS (UNKNOWN GL) .....                    | 3  |
| TABLE H-1 MINIMUM GPS OUTPUT .....                                       | 2  |
| TABLE J-1 METEOROLOGICAL PARAMETERS FOR TROPOSPHERIC DELAY .....         | 4  |
| TABLE L-1 TEST CASE INPUT .....  | 6  |
| TABLE L-2 TEST CASE OUTPUT .....   | 7  |
| TABLE L-3 NUMBER OF ITERATIONS .....                                     | 7  |
| TABLE M-1 GRADUATED SAMPLING PASS/FAIL CRITERIA .....                    | 2  |
| TABLE R-1 SUMMARY OF FDE REQUIREMENTS .....                              | 1  |
| TABLE R-2 SUMMARY OF FAILURE TYPE PROBABILITIES .....                    | 4  |
| TABLE R-3 ACCURACY COASTING PERFORMANCE EXAMPLE .....                    | 7  |
| TABLE R-4 INTEGRITY COASTING PERFORMANCE EXAMPLE .....                   | 8  |
| TABLE R-5 EQUIVALENT ALTITUDE ACCURACY .....                             | 11 |
| TABLE R-6 REQUIRED NUMBER OF TRIALS FOR EACH FAILURE MODE .....          | 17 |

This Page Intentionally Left Blank

## 1.0 PURPOSE AND SCOPE

### 1.1 Introduction

This document contains minimum operational performance standards (MOPS) for airborne navigation equipment using the Global Positioning System (GPS). DO-316 only provides standards for single-frequency airborne supplemental navigation sensor equipment not augmented by ground- or space-based systems. Separate standards exist for GPS augmented by ground- or space-based methods. Additionally, a separate document will be created in the future to address standards for dual frequency equipment. The basis for this MOPS is RTCA/DO-229D class beta 1 receiver without SBAS requirements.

In this document, the term “shall” is used to indicate requirements. An approved design should comply with every requirement, which can be assured by inspection, test, analysis, or demonstration. The term “must” is used to identify items that are important but are either duplicated somewhere else in the document as a “shall”, or are considered to be outside the scope of this document. The term “should” is used to denote a recommendation that would improve the GPS equipment, but does not constitute a requirement.

The standards define minimum performance, functions and features for GPS sensors that provide position information to a multi-sensor system or separate navigation system. They also address Area Navigation (RNAV) equipment to be used for the en route, terminal, and Lateral Navigation (LNAV) phases of flight. These standards are based upon a nominal allocation of the aircraft-level requirements in RTCA/DO-236B, *Minimum Aviation System Performance Standards: Required Navigation Performance for Area Navigation*, accounting for the unique issues associated with GPS navigation service and minimizing the need for pilot training.

Compliance with these standards by manufacturers, installers and users is recommended as one means of assuring that the equipment will satisfactorily perform its intended functions under conditions encountered in routine aeronautical operations, and will ensure a basic compatibility with the requirements defined in RTCA/DO-236B.

The regulatory application of these standards is the responsibility of appropriate government agencies. In the United States, the Federal Aviation Administration (FAA) has published a Technical Standard Order (TSO) for GPS equipment to reference the requirements and bench test procedures in Section 2.

The word “equipment”, as used in this document, includes all components or units necessary (as determined by the equipment manufacturer or installer) to properly perform its intended function. For example, the airborne “equipment” may include: sensor(s), a computer unit, an input-output unit that interfaces with existing aircraft displays/systems, a control unit, a display, shock mount(s), etc. In the case of this example, all of the foregoing components or units constitute the “equipment”. It should not be inferred from this example, however, that all GPS navigation equipment will necessarily include all of the foregoing components or units. The particular components of GPS equipment will depend upon the design used by the equipment manufacturer, subject to the constraint that the equipment must meet the applicable requirements of this MOPS.