

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, D.C. 20036-5133 USA

Assessment of Radio Frequency Interference Relevant to the GNSS L5/E5A Frequency Band

RTCA DO-292
July 29, 2004

Prepared by: SC-159
© 2004 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This report was prepared by Special Committee 159 (SC-159) and approved by the RTCA Program Management Committee (PMC) on July 29, 2004.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity, and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organizations' recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1	INTRODUCTION	1
1.1	Background	1
1.2	Terms of Reference	2
1.3	Report Objectives	3
1.4	Report Organization	3
1.5	References	5
2	METHODOLOGIES OF AERONAUTICAL RFI SCENARIOS, RISK MODELING AND RFI ANALYSIS.....	7
2.1	Introduction and Basic Methodology	7
2.2	Spectrum Management for Safety Services: Regulations and Definitions.....	7
2.2.1	Relevant Definitions and Regulations in the ITU Radio Regulations.....	8
2.2.2	Relevant Definitions and Regulations in 47 CFR (FCC).....	10
2.2.3	Description and Regulatory Status of L5/E5 Allocation.....	10
2.3	Aeronautical System Risk Analysis with RFI Effects.....	11
2.3.1	Process Overview	11
2.3.1.1	Target Level of Safety	11
2.3.1.2	Hazard Analysis and Risk Allocation	12
2.3.1.3	Threat Risk and Occurrence Rate Considerations	12
2.3.2	System Considerations for Approach and Landing.....	13
2.3.2.1	Total System Error and Its Components	13
2.3.2.2	Obstacle Clearance Surface (OCS).....	13
2.3.2.3	NSE and FTE Impact on RFI Encounter Scenarios	14
2.3.2.4	Approach and Landing NSE and GPS Monitor Considerations	14
2.3.3	System Considerations for GNSS Signal Acquisition	14
2.4	Navigation System Performance and RFI	15
2.4.1	Description of Navigation System Performance	15
2.4.2	Effects of RFI on Navigation System Performance	16
2.4.3	Current Status of RFI Navigation Alerts and GPS Continuity and Integrity Risk Allocations	17
2.5	GPS Receiver Model for Performance and RFI Susceptibility Assessment	17
2.5.1	Antenna Gain	17
2.5.2	RF Front-end Frequency-Dependent Rejection	19
2.5.3	Maximum Receiver System Input Thermal Noise Density.....	19
2.5.4	Pulse Blanking	20
2.5.5	Receiver Effective Carrier -to-Noise Density Ratio (C/N0, EFF) Thresholds.....	21
2.6	Methodology for Aeronautical RFI Encounter Scenarios	22
2.6.1	Overview of Link Analysis Methodology.....	22
2.6.2	RFI Source Emissions and Effects Analysis	22
2.6.2.1	RFI Source Spectral Types	22
2.6.2.2	External RFI Emitter Classes.....	23
2.6.2.3	Effective Carrier-to-Noise Density Calculation Algorithm	24
2.6.3	Aeronautical Safety Margin	26
2.6.4	RFI Scenario Link Budget Templates.....	27
2.6.4.1	Link Budget Template Approach.....	27
2.6.4.2	Rationale for Two Allotments.....	28
2.6.4.3	Link Budget Templates Details and Rationale.....	29

2.7	Summary	31
2.8	References	31
3	AERONAUTICAL RFI ENCOUNTER SCENARIOS	33
3.1	Enroute Scenario	34
3.2	Transition to Final Approach Scenario.....	34
3.3	Non-Precision Approach with GNSS Guidance Scenario.....	34
3.4	Category I Precision Approach RFI Encounter Scenario.....	37
3.5	Category II/III Precision Approach RFI Scenario.....	38
3.5.1	Category II Vertical Flight Technical Error Considerations	38
3.5.2	Category II Vertical Encounter Minimum Separation Distance	39
3.5.3	Category III Vertical and Lateral RFI Encounter Considerations.....	40
3.6	Surface Movement Guidance RFI Encounter Scenarios	41
3.6.1	Taxiway Encounter Geometry	41
3.6.2	TSE Allowance for Continuity.....	42
3.7	Missed Approach.....	43
3.8	Take-Off.....	44
3.9	GPS Non-Precision Approach To 720ft HAT.....	46
3.10	Summary.....	46
3.10	Summary.....	47
3.11	References.....	47
4	GPS INTRASYSTEM AND GNSS INTERSYSTEM INTERFERENCE	49
4.1	Intrasystem and Intersystem Interference.....	49
4.2	Intrasystem Interference Characteristics	49
4.3	Effective Noise Density $N_{0,EFF}$	50
4.4	Spectral Separation Coefficient Calculation.....	50
4.5	Computation Methodology.....	51
4.6	Intrasystem and Intersystem L5/E5A Interference Numerology.....	53
5	INTERFERENCE FROM ONBOARD ELECTRONICS.....	55
5.1	Introduction	55
5.2	VHF Air-Ground Transceivers (Including ACARS).....	55
5.3	VHF Navigation Receivers.....	57
5.3.1	VHF Omni-directional Range (VOR) Receivers	57
5.3.2	VHF Instrument Landing System (ILS) Receivers	58
5.4	Emergency Locator Transmitters (ELTs).....	58
5.5	High Frequency (HF) Transceivers	59
5.6	Distance Measuring Equipment (DME).....	59
5.7	Pulsed Surveillance and Weather Radar Transmitters	61
5.7.1	ATCRBS	62
5.7.2	Mode S	62
5.7.3	TCAS	62

5.7.4	Automatic Dependent Surveillance – Broadcast (ADS-B)	63
5.7.5	Airborne Weather Radar	63
5.7.6	Overall Impact of Airborne Pulsed Systems	63
5.8	Mobile Satellite Services (Aircraft to Space)	65
5.8.1	Geosynchronous Aeronautical Mobile Satellite Service	65
5.8.2	Next-Generation Satellite Systems	66
5.9	Air – Ground Radiotelephone	67
5.9.1	General Aviation Air-Ground Radiotelephone	67
5.9.2	Commercial Aviation Air-Ground Radiotelephone	67
5.9.3	Cordless Handsets	68
5.10	Portable Electronic Devices	68
5.10.1	PED Emission Characteristics	68
5.10.2	PED-to-GPS Antenna Coupling Characteristics	69
5.10.3	Aggregate RFI Emissions Factor for PEDs	70
5.10.4	Aggregate On-board PED RFI Impact	70
5.11	References	71
6	FIXED AERONAUTICAL EMITTERS	73
6.1	VHF Ground Communications Transmitters	73
6.1.1	Overview	73
6.1.2	Aircraft Communications Addressing and Reporting System (ACARS)	74
6.1.3	VHF Air Traffic Control Communications	74
6.1.4	Harmonics from 118.0 – 137.0 MHz Ground-to Air Communications	75
6.1.5	VDL-3 (NEXCOM)	75
6.1.6	VDL-4	75
6.2	VHF Navigation Systems	76
6.2.1	VHF Omni-directional Range (VOR) Transmitters	76
6.2.2	Instrument Landing System (ILS) Localizer Transmitters	76
6.2.3	Local Area Augmentation System (LAAS) VHF Data Broadcast Transmitter	76
6.3	UHF Communications	77
6.4	Distance Measuring Equipment /TACAN (DME/T)	77
6.5	Secondary Surveillance Radar Interrogators	78
6.7	References	78
7	INTERFERENCE FROM AVIONICS ON NEARBY AIRCRAFT	79
7.1	VHF Communications	79
7.2	UHF Air-Ground Transceivers	80
7.3	Distance Measuring Equipment/TACAN (DME/TACAN)	80
7.4	Other Pulsed Sources	80
7.5	Joint Tactical Information Distribution System	80
7.5.1	JTIDS/MIDS Signal Structure	81
7.5.2	Restrictions on JTIDS/MIDS Operation in the NAS	82
7.5.2.1	JTIDS/MIDS Transmission Monitoring	82
7.5.2.2	JTIDS/MIDS Time Slot Duty Factor	82
7.5.2.3	JTIDS/MIDS Spectrum	84
7.6	Aeronautical Mobile Satellite Service	85
7.7	Next-Generation Satellite Systems	85

7.8	Airport Surface RFI Scenario and Link Calculations.....	85
8	COMMERCIAL BROADCAST SERVICES	87
8.1	AM Radio	87
8.2	FM Radio.....	87
8.3	Television	88
8.3.1	Analog Television	88
8.3.2	Digital Television.....	90
8.3.3	European Television.....	91
8.4	References	91
9	OTHER FIXED AND MOBILE INTERFERENCE SOURCES.....	93
9.1	Amateur Radio	93
9.2	Military Radar	94
9.3	JTIDS/MIDS Ground Equipment.....	95
9.3.1	US Army Ground Equipment.....	95
9.3.2	US Navy Ground Equipment	95
9.3.3	US Marine Corps Ground Equipment.....	96
9.3.4	US Air Force Platforms.....	96
9.4	VHF/UHF Fixed and Mobile Services	96
9.5	Wireless LAN Devices	97
9.6	Cellular Telephony	98
9.7	Cordless Telephony.....	98
9.7.1	Illicit Cordless Telephone Systems	99
9.8	Personal Radio Services	99
9.9	Ultra-Wideband (UWB) Systems.....	100
9.9.1	UWB Technology Overview.....	100
9.9.2	Review of Major UWB RFI Susceptibility Test and Analysis Activities.....	101
9.9.3	Current UWB Regulatory Status.....	102
9.9.3.1	UWB System Classifications.....	102
9.9.3.2	Operational Limitations	104
9.10	References.....	107
10	COMPOSITE PULSED RFI EFFECTS ON HIGH ALTITUDE OPERATIONS.....	109
10.1	Overall Composite RFI Scenario Analysis Methodology.....	109
10.1.1	Receiver Pulse Blanking, Filtering, and System Noise Assumptions	109
10.1.2	Theoretical Pulse Blanking Effects on Post-Correlation C/N0	110
10.2	Pulsed RFI Source Configurations, Assumptions, and Component Contributions	112
10.2.1	JTIDS/MIDS	112
10.2.1.1	JTIDS/MIDS Approach and Assumptions.....	113
10.2.1.2	JTIDS/MIDS RFI Parameter Results.....	114
10.2.2	1030/1090 MHz Surveillance Systems	114
10.2.2.1	Surveillance Systems Approach.....	115
10.2.2.2	Surveillance System RFI Parameter Results.....	115
10.2.3	DME/TACAN Interrogators On-board and on Nearby Aircraft	116
10.2.3.1	DME/TACAN Interrogator RFI Analysis Overview	116
10.2.3.2	DME/TACAN Interrogator RFI Effect Computation.....	117
10.2.4	DME/TACAN Ground Beacons	117

10.2.4.1	DME/TACAN Beacon Overview and General Approach	117
10.2.4.2	Rectangular Equivalent Pulse Width	120
10.2.4.3	Strong Pulse Collision Model - Net PDCb Approach for TACAN/DME RFI	122
10.2.4.4	Diffraction Loss Allowance for Beyond-Radio-LOS Beacons.....	124
10.2.4.5	DME/TACAN Beacon Component RFI Parameters for Worst-Case US Location.....	125
10.3	Composite Pulse RFI Effects on High Altitude Operations	126
10.3.1	High Altitude RFI Scenario Description	126
10.3.2	High Altitude Re-start Acquisition Analysis Strategy #1	127
10.3.3	High Altitude Re-start Acquisition Analysis Strategy #2	128
10.3.4	High Altitude Scenario RFI Link Analyses	129
10.3.4.1	High Altitude Re-start Acquisition RFI Link Analysis.....	129
10.3.4.2	High Altitude Enroute Tracking/Demod RFI Link Analysis	130
10.3.4.3	High Altitude Enroute Tracking Link Analysis with On-board PEDs RFI	132
10.4	Composite Pulse /Broadband RFI Effects on Transition Altitude Operations	133
10.4.1	Transition Altitude Scenario Detailed Description	133
10.4.2	Transition Altitude Scenario RFI Link Analysis Results.....	136
10.5	Conclusions and Recommendations	137
10.6	References.....	138
11	COMPOSITE PULSE/BROADBAND RFI EFFECTS ON APPROACH, TAKE-OFF, AND SURFACE MOVEMENT	141
11.1	MSS (Earth-to-Space) Mobile Earth Terminals	141
11.2	Ancillary Terrestrial Component (MSS) Repeaters.....	142
11.3	Composite L5 Broadband / Pulse RFI Environment for Approach, Take-off, and Surface Movement Scenarios	144
11.4	Approach, Take-off and Surface Movement Link Budget Calculations.....	145
11.4.1	Intentional Unlicensed In-band RFI EIRP	147
11.4.2	Surface Movement Separation Distance Derivation	150
11.5	LAAS and WAAS Scenario Issues.....	151
11.6	Recommendations.....	152
11.7	References.....	152
12	ADDITIONAL POTENTIAL INTERFERENCE SOURCES	155
12.1	Unintentional Emitters	155
12.2	Incidental RFI Emissions.....	155
12.3	Malfunctioning FCC-Licensed Equipment.....	156
12.4	Interference to GPS.....	157
12.5	Recommendations.....	158
12.6	References.....	159
13	MITIGATION TECHNIQUES FOR SIGNIFICANT SOURCES OF RFI	161
13.1	Interference Mitigation at the Source	161
13.1.1	Regulatory Control of Emissions	161
13.1.2	Identification and Localization of Interfering Sources.....	163
13.1.3	Mitigation of Interference Sources Aboard the Aircraft	164
13.1.4	Maintenance of an Incident Data Base.....	164

13.2	GPS Receiver Susceptibility Reduction.....	164
13.2.1	Adaptive Spatial (Antenna) Processing.....	164
13.2.2	Adaptive Temporal Filtering.....	165
13.2.3	Preselection	166
13.2.4	Improved Receiver Tracking Processes	166
13.2.5	Multibit Analog-to-Digital (A/D) Converters	166
13.2.6	Pulse Blanking	167
13.3	Mitigation at the Navigation System Architecture Level	167
13.3.1	Use of an Independent Conventional Navigation System.....	167
13.3.2	Use of Multiple Satellite Systems	167
13.3.3	Use of Multi-Frequency GNSS Receivers	168
13.4	Operational Constraints	168
13.5	References.....	168
14	CONCLUSIONS AND RECOMMENDATIONS	171
14.1	Summary Overview	171
14.2	Status of Recommendations from RTCA/DO-235A applicable to GNSS L5/E5A.....	172
14.3	Assessment Element Summaries	173
14.3.1	Aeronautical Navigation System Requirements and Analysis Methodology	173
14.3.2	Aeronautical RFI Encounter Scenario Development	174
14.3.3	Aeronautical RFI Source Assessments	175
14.3.3.1	GNSS L5/E5a Intra-system and Inter-system Interference.....	175
14.3.3.2	Interference from Onboard Electronic Equipment.....	175
14.3.3.3	Fixed Aeronautical Emitters	176
14.3.3.4	Interference from Avionics on Nearby Aircraft.....	176
14.3.3.5	Commercial Broadcast Service Emitters	176
14.3.3.6	Other Fixed and Mobile Interference Sources	176
14.3.3.7	Additional Interference Sources.....	177
14.3.3.8	Composite Pulsed RFI Effects on High Altitude L5 Operations	177
14.3.3.9	Composite Pulsed/Broadband RFI Effects on L5 Approach, Take-off, and Surface Operations 177	
14.3.4	Mitigation Techniques for Significant RFI Sources.....	178
14.4	Recommendations.....	178
	MEMBERSHIP.....	181

TABLE OF FIGURES

Figure 2-1	Measured L5 Receive Antenna Gain and Proposed Limits.....	18
Figure 2-2	Receiver Frequency-Dependent Rejection vs. Offset from L5	19
Figure 2-3	Block Diagram of a Typical Digital Pulse Blanking Receiver.....	20
Figure 2-4	Flow Chart for GNSS L5 RFI Source Composite.....	23
Figure 2-5	$N_{0,EFF}$ Algorithm Block Diagram.....	26
Figure 3-1	Non-Precision Approach Geometry (Side View).....	35
Figure 3-2	Category I Scenario.....	37
Figure 3-3	Category II/III Approach Geometry.....	39
Figure 3-4	Airport Runway Protection Zones - Top View	40
Figure 3-5	Taxiway RFI Encounter Geometry - Front View.....	42
Figure 3-6	Surface Movement Guidance Separation Distance Diagram	43
Figure 3-7	Missed Approach Scenario Geometry.....	44
Figure 3-8	Take-off Scenario Geometry	45
Figure 5-1	Standard DME/TACAN Channel Plan	60

Figure 6-1 ACARS Hardware Emission Spectrum.....	74
Figure 6-2 ATC VHF Harmonic Emission Spectrum.....	75
Figure 7-1 JTIDS/MIDS Time Slot and Pulse Transmission Structure.....	81
Figure 7-2 JTIDS/MIDS Hopping Frequencies.....	82
Figure 7-3 JTIDS/MIDS Geographic Area Pulse Densities.....	83
Figure 7-4 JTIDS/MIDS Pulse Spectral Mask.....	84
Figure 7-5 JTIDS/MIDS Pulse Measured Spectrum.....	85
Figure 8-1 FM Broadcast Harmonic Emission Spectrum.....	88
Figure 8-2 Broadcast TV Harmonic Emission Spectrum.....	89
Figure 10-1 Typical DME/TACAN Antenna Normalized Gain vs. Elevation Angle.....	119
Figure 10-2 DME/TACAN Beacons Around Harrisburg, PA.....	119
Figure 10-3 Rectangular Equivalent Pulse Width of a Weak Pulse.....	121
Figure 10-4 Strong Pulsewidth and Residual Equivalent Pulsewidth vs. Peak Received Power with -90 dBm Pulse Blanking Threshold.....	122
Figure 10-5 Effect of Diffraction in Extending Propagation Path.....	124
Figure 10-6 DME/TACAN Beacon $N_{0,eff}$ Degradation Factor Contours at FL400.....	126
Figure 10-7 Overall $N_{0,EFF}$ Degradation Factor Contours in CONUS at FL400.....	132
Figure 10-8 In-Band TACANs within the RLOS in the vicinity of DCA.....	134
Figure 10-9 DCA Runway 4 Approach Plate.....	135
Figure 11-1 Take-off Scenario L5 RFI Link Budget Flow Chart.....	145

TABLE OF TABLES

Table 2-1 LAAS/WAAS Navigation System Performance Specifications.....	16
Table 2-2 Key L5 User Antenna Gain Values Used in the RFI Analyses.....	18
Table 2-3 Typical L5 Receiver System Noise Budget.....	19
Table 2-4 GPS and WAAS Tracking and Demodulation Thresholds.....	21
Table 2-5 GPS L5 Acquisition Thresholds for 1 ms Correlations.....	21
Table 2-6 Template for Approach, Take-off, and Surface Movement Scenarios.....	29
Table 2-7 High Altitude $C/N_{0,eff}$ Acquisition Link Budget Template.....	30
Table 3-1 Taxiway Obstacle Free Zones.....	41
Table 3-2 Separation Distance Calculation For Take-off Scenario.....	46
Table 3-3 Aeronautical RFI Encounter Scenario Parameters.....	47
Table 4-1 Aviation Receiver RFI Parameters for L5 Intrasytem Interference.....	54
Table 4-2 Aviation Receiver RFI Parameters for E5A Intersystem Interference.....	54
Table 5-1 VHF Channels with Harmonics at $L5 \pm 10$ MHz.....	57
Table 5-2 ELT Characteristics.....	58
Table 5-3 Aircraft Effective Isotropic Radiated Power (EIRP).....	66
Table 5-4 Measured PED Emissions in the GPS L1 and L5 Bands and Applicable Standards.....	69
Table 6-1 Potential Interference from VHF Aeronautical Mobile Service.....	75
Table 8-1 Proximity of TV Carrier Harmonics to GPS L5 Band.....	89
Table 9-1 Amateur Radio Bands with Harmonics in GNSS L5 Band.....	93
Table 9-2 Other Amateur Bands Having Potential to Interfere with GNSS.....	93
Table 9-3 Land Mobile Frequency Bands.....	96
Table 9-4 Current Cellular Telephone Systems (824-894 MHz).....	98
Table 9-5 Standardized Cordless Telephone Systems.....	99
Table 9-6 Bands used by the various Personal Radio Services.....	100
Table 10-1 JTIDS/MIDS Factors.....	114
Table 10-2 ATC RFI Results.....	116
Table 10-3 DME/TACAN Pulse RFI Parameters Near the Harrisburg Hot-Spot.....	125
Table 10-4 High Altitude Scenario Pulsed RFI Composite Parameters.....	127
Table 10-5 High Altitude GPS Acquisition $C/N_{0,EFF}$ Link Budget (Strategy #1).....	130
Table 10-6 High Altitude $C/N_{0,EFF}$ Acquisition Link Budget (Strategy #2).....	130
Table 10-7 Tracking / Data Demodulation $C/N_{0,eff}$ Link Budget.....	131

Table 10-8 In-band TACAN Beacons Near DCA	133
Table 10-9 Composite Pulsed RFI Parameters at Teple FAF (1600' MSL).....	134
Table 10-10 Teple FAF GPS Acquisition $C/N_{0, \text{eff}}$ Link Budget.....	136
Table 10-11 Teple FAF Tracking / Data Demodulation $C/N_{0, \text{eff}}$ Link Budget.....	137
Table 11-1 $N_{0, \text{EFF}}$ Algorithm Input Parameters For All 7 Scenarios	144
Table 11-2 $I_{0\text{WBX}}$ and $I_{0\text{INBAND}}$ EIRP Link budget Template for LAAS Approach, Take-off, Missed Approach and NPA Scenarios.....	148
Table 11-3 $I_{0\text{WBX}}$ and $I_{0\text{INBAND}}$ EIRP Link budget Template for LAAS Approach, and Aircraft Surface Movement Scenarios.....	149
Table 11-4 $I_{0\text{WBX}}$ and $I_{0\text{INBAND}}$ EIRP Link budget Template for WAAS Approach, and Take-off Scenarios	150
Table 11-5 RFI Performance Summary of the 7 Scenarios (4 Emitters)	152
Table 14-1 Aeronautical RFI Encounter Scenario Parameters	174

APPENDICES

APPENDIX A.....	193
A Total System Error Statistics For Precision Approach and Landings	195
A.1 Category II Operations.....	195
A.1.1 Category II Flight Technical Error Background.....	195
A.1.2 Navigation System Error Background and Calculations	196
A.1.3 Total System Error Calculation	197
A.1.4 Recommendation	197
A.2 Category I Operations	199
A.2.1 Category I FTE Background and Calculations.....	199
A.2.2 NSE Background and Calculations	200
A.2.3 TSE Background and Calculations.....	200
A.2.4 Recommendation	200
A.3 References.....	204
APPENDIX B	205
B RFI Source Specifications.....	207
APPENDIX C	211
C GPS L5 SIGNAL STRUCTURE AND EFFECTS OF NARROWBAND INTERFERENCE	213
C.1 GPS L5 Signal Structure.....	213
C.1.1 L5 Signal Characteristics.....	213
C.1.1.1 PRN Code Structure	214
C.1.1.2 Code Generation.....	214
C.1.1.3 Q5 Synchronization Sequence.....	215
C.1.2 Navigation Data.....	216
C.1.2.1 Navigation Data Modulation	216
C.1.2.1.1 Forward Error Correction	216
C.1.2.1.2 I-Component Neuman-Hoffman Code	216
C.1.3 User-Received Signal Levels.....	216
C.1.3.1 Supporting Material.....	217
C.2 L5 GPS Code Power Spectrum.....	217
C.3 Effects of CW Interference	221
C.3.1 CW Interference Effects on Signal Acquisition	222
C.3.2 CW Interference Effects on Signal Tracking.....	222
C.3.2.1 Detailed Derivation of the Effects of CW Interference	224
C.3.2.1.1 Effects of CW Interference On L5 Q-Code Tracking.....	225
C.3.2.1.2 Effects of CW Interference on Carrier Tracking	227

C.3.3	GPS Receiver Susceptibility to Non-CW Narrowband Interference.....	228
C.4	References.....	233
APPENDIX D	235
D	MAXIMUM TOLERABLE INTERFERENCE ENVIRONMENT	237
D.1	$C/N_{0,EFF}$ Thresholds - Theoretical	237
D.1.1	Receiver Model	237
D.1.2	Acquisition	238
D.1.3	Acquisition of Rising Satellites	244
D.1.4	GPS Code and Carrier Tracking.....	245
D.1.5	GPS Data Demodulation	246
D.1.6	C/N_0 Thresholds - Simulations	246
D.2	Receiver Pulse Blanking and Saturation Effects on C/N_0	247
D.2.1	Effective C/N_0 for a Receiver Employing Pulse Blanking	247
D.2.2	Receiver Saturation Impact on Effective C/N_0	250
D.2.3	Influence of Selectivity and Gain Distribution on Receiver Saturation and Blanking	251
D.3	Sensitivity of $C/N_{0,EFF}$ to the Pulse Blanking Threshold.....	253
D.4	Estimation of Aggregate Intra-system/ Intersystem Interference Power	257
D.4.1	Aggregate RFI Power Estimation Approach	257
D.4.2	Simulation Description	257
D.4.3	Simulation Results.....	260
D.5	Elevation Angle and C/N_0 Probabilities for Satellite Acquisition	261
D.5.1	Probability of Satellite Acquisition	262
D.5.2	Satellite Geometry Scenarios.....	262
D.5.3	C/N_0 Probabilities	264
D.6	RFI Effects on High Altitude Operations over the European Hot-Spot.....	267
D.7	References.....	268
APPENDIX E	271
E	Receiver RFI Performance: Analysis/ Simulation/ Emulation	273
E.1	Detailed Derivation of ATC/ Surveillance System RFI Parameters.....	273
E.1.1	Background Emitter Distributions.....	274
E.1.2	Link Equations for Ground and Airborne Emitters	276
E.1.3	Pulsed Duty Factor Assumptions	278
E.1.3.1	ATCRBS and Mode S Sensors	278
E.1.3.2	ATCRBS and Mode S Transponders.....	278
E.1.3.3	1090 MHz Extended Squitter System.....	279
E.1.3.4	Traffic Alert and Collision Avoidance System.....	279
E.1.4	Surveillance System RFI Analysis	280
E.2	On-Board Pulsed RFI Transient and Steady-State Analysis.....	282
E.2.1	GNSS Active Antenna Unit Preselector Steady-State Frequency Domain Analysis	282
E.2.1.1	Antenna Unit Preselector and Low Noise Preamplifier Performance Aspects.....	282
E.2.1.2	Preselector Circuit Synthesis	283
E.2.1.3	Preselector Circuit Steady-State Frequency Response Computation	284
E.2.2	GNSS Active Antenna Unit Preselector Time Domain Analysis.....	285
E.2.2.1	DME and Surveillance Transmit Pulse Envelope Model	285
E.2.2.2	Airborne Antenna Coupling and Thevenin Equivalent Pulse Source Model	285
E.2.2.3	Preselector Time Domain Response Computation	286
E.2.3	Steady-State and Transient Response Results Summary and Conclusions	288
E.3	On-Board PEDs Aggregate Emission Analysis.....	289
E.3.1	PED Emission Considerations.....	289
E.3.2	PED Interference Propagation Loss Considerations.....	291
E.3.3	Aggregate PED RFI Emission Computation for Boeing 737-200.....	293
E.4	Propagation Modeling with the GPS RFI Environmental Evaluation Tool (GREET)	295

E.4.1	Fixed Emitter Database Interface	296
E.4.2	Fixed Emitter RFI Calculator	297
E.4.3	Emulation of DME/TACAN Ensemble Environment.....	298
E.5	Monte Carlo Analysis of the PDCb Blanking Model for TACAN/DME RFI.....	302
E.6	Hardware Prototype L5 Receiver Bench Tests	308
E.6.1	JTIDS/MIDS Environments	309
E.6.2	Test Configuration.....	309
E.6.3	Digital Pulse Blanker Soft Threshold.....	314
E.7	References.....	315
APPENDIX F	317
F	STANDARD TEST INTERFERENCE ENVIRONMENT.....	319
F.1	Introduction.....	319
F.2	Desired Signal Levels	319
F.3	Stress-Case Continuous Interference Environment	320
F.4	Stress-Case Pulsed Interference.....	322
APPENDIX G	325
G	INSTALLED AIRCRAFT GNSS ANTENNA PARAMETERS.....	327
G.1	Introduction.....	327
G.2	Frequency Response	327
G.3	Antenna Gain Pattern.....	327
G.3.1	Simulation.....	328
G.3.2	Full Scale Fuselage Section Tests	329
G.3.3	Scale Model Measurements.....	330
G.3.4	Antenna Gain Pattern Factor Discussion.....	330
G.4	Polarization Mismatch	331
G.5	Summary.....	331
G.6	References.....	332
APPENDIX H	341
H	Interference from an Aggregation of Emitters	343
H.1	Introduction.....	343
H.2	Circular Geometry of Emitters	343
H.3	Rectangular Geometry of Emitters	346
H.3.1	Merging Discrete Emitter Model with a Continuum of Emitter Model	348
H.4	Analysis of Emitters at Random Locations	351
H.5	Interference Power at Receiver Front End.....	352
H.6	Conclusions.....	353
H.7	References.....	353
APPENDIX I	355
I	Noise Equivalency Factor Measurement and Analysis Method	357
APPENDIX J	359
J	EUROCAE WG62 RFI Effects Analysis at US and European Hot-Spots.....	361
J.1	Effective Post-Correlation Carrier-to-Noise Density Ratio Degradation Computation	361
J.2	DME/TACAN Beacon Component RFI Parameters for Worst-Case European Location	362
J.3	European Worst-case High Altitude Acquisition Link budget	367
J.4	US High altitude RFI Acquisition Scenario Description.....	367
J.5	US Worst-case High Altitude Acquisition Link budget	368
J.6	Summary.....	369
J.7	References.....	369

APPENDIX K.....	377
K ACRONYMS, ABBREVIATIONS, and DEFINITIONS.....	379
K.1 Acronyms and Abbreviations	379
K.2 Definitions	388

TABLE OF FIGURES

Figure A- 1 GBAS NSE Distribution Averaged over All Geometries that Meet VAL<10 Meters.....	197
Figure A- 2 Category II TSE Probability Density Function	198
Figure A- 3 Category II Cumulative TSE Probability Function.....	198
Figure A- 4 Truncated TSE Probability Density Function for Auto-coupled Aircraft.....	202
Figure A- 5 Truncated “Two-Tier” FTE Probability Density Function for Manual Approach Aircraft ($\sigma_{FTE1} = 12.5$ ft and $\sigma_{FTE2} = 9$ ft).....	203
Figure A- 6 Truncated TSE Probability Density Function for Manual Approach Aircraft	203
Figure C- 1 Generation of L5 Codes.....	215
Figure C- 2 Modulation of L5 Signals.....	215
Figure C- 3 Convolutional Encoder.....	216
Figure C- 4 Total Received L5 RF Signal Strength Versus Elevation Angle.....	217
Figure C- 5 1-kHz Spaced Line Spectrum for a Typical L5 Code.....	218
Figure C- 6 1-kHz Spaced Line Spectrum for a Typical L5 Code – Close-In.....	219
Figure C- 7 50-Hz Spaced Line Spectrum for a Typical L5 Code.....	220
Figure C- 8 50-Hz Spaced Line Spectrum for a Typical L5 Code – Close-In.....	221
Figure C- 9 CW Effect Phase Diagram.....	223
Figure C- 10 Correlation Peak Distortion Versus CW Interference (121.756-kHz) Phase, 1-Chip Spacing	225
Figure C- 11 DLL Discriminators with CW Interference.....	226
Figure C- 12 RMS Code Tracking Error with CW Interference at 121.746-kHz – 1-Chip Spacing	226
Figure C- 13 Carrier Phase Errors for Different Phases of CW Interference	228
Figure C- 14 Pre-Correlation Interference Power Relative to Total Interference Power in 20 MHz Bandwidth – Acquisition Case.....	230
Figure C- 15 Pre-Correlation Interference Power Relative to Total Interference Power in 20 MHz Bandwidth – Tracking Case.....	231
Figure C- 16 Pre-Correlation Interference Power Correction Factor – Acquisition Case	232
Figure C- 17 Pre-Correlation Interference Power Correction Factor – Tracking Case.....	233
Figure D- 1 GPS L5 Receiver Digital Channel Model	237
Figure D- 2 Acquisition Decision Statistic Generation for I5/Q5 Technique.....	239
Figure D- 3 Acquisition Decision Statistic Generation for Q5-only Technique.....	239
Figure D- 4 Max. Dwell Time vs. Number of Correlators (1-ms Integration)	242
Figure D- 5 Max. Dwell Time vs. Number of Correlators (20-ms Integration)	242
Figure D- 6 Minimum $C/N_{0,EFF}$ to Achieve 1-min Acquisition of the First Satellite	243
Figure D- 7 Minimum $C/N_{0,EFF}$ - Subsequent (2 nd – 4 th) Satellite Acquisition.....	244
Figure D- 8 Probability of Cycle-slips vs. $C/N_{0,EFF}$	246
Figure D- 9 Monte-Carlo Simulation Results for L5 Carrier Phase Tracking and Data Demodulation ...	247
Figure D- 10 Correlator Model.....	248
Figure D- 11 Receiver Model Rejection Characteristics	252
Figure D- 12 Receiver Model Rejection Curve (12 dB/MHz Mask).....	252
Figure D- 13 CONUS Hotspot RFI Parameters vs. Blanking Threshold.....	254
Figure D- 14 CONUS Hotspot Overall RFI Parameters vs. Blanking Threshold.....	255
Figure D- 15 European Hotspot Overall RFI Parameters vs. Blanking Threshold Ground DME/TACAN beacons, JTIDS Case 8/ 51, ATC/ARNS.....	257
Figure D- 16 GPS Satellite Antenna Pattern on L5	258
Figure D- 17 GPS L5 user Received Power	258

Figure D- 18 Galileo Satellite Antenna Pattern on E5A	259
Figure D- 19 Galileo E5A User Received Power	259
Figure D- 20 GPS Patch Antenna Gain Pattern on L5.....	260
Figure D- 21 Probability of Maximum Elevation Angle Given 2 Satellite Failures.....	263
Figure D- 22 Post-Correlation Interference-Free C/N_0 vs. Elevation Angle	264
Figure D- 23 $P_{C/N_0 > X}$ for the Noise-Only Case.....	265
Figure D- 24 Expansion of $P_{C/N_0 > X}$ for the Noise-Only Case at Lower X Values	266
Figure D- 25 Overall L5/E5a $N_{0,EFF}$ Degradation Contours at FL400 for Europe	268
Figure E- 1 Cumulative Number of Nodes Within x Grid Units	274
Figure E- 2 Grid Effect as a Function of Normalized Range.....	275
Figure E- 3 4-Resonator L5 Bandpass Preselector Filter Equivalent Circuit	283
Figure E- 4 L5 Preselector Equivalent Circuit Insertion Loss vs. Frequency.....	284
Figure E- 5 1150 MHz DME Input and BPF Output Pulses.....	287
Figure E- 6 1090 MHz ATCRBS Input and BPF Output Pulses	288
Figure E- 7 NASA Interference Propagation Loss Measurement Set-up Diagram	291
Figure E- 8 Interference Path Loss Measurements on Boeing 737-200 Aircraft.....	293
Figure E- 9 GREET Flow Diagram	296
Figure E- 10 Normalized DME/TACAN Complex Envelope obtained from Otis AFB, MA TACAN ...	299
Figure E- 11 Emulated DME/TACAN Environment: 40 kft above Harrisburg, PA.	300
Figure E- 12 Envelop of Two Overlapping Gaussian Pulses.....	303
Figure E- 13 Aggregate Inter-Arrival Distributions.....	304
Figure E- 14 Simulation Results for Uniform Pulse Width Distribution.....	306
Figure E- 15 Prototype Receiver Test Configurations Diagram.....	310
Figure E- 16 DPB Threshold Test.....	315
Figure F- 1 Stress-case Continuous Interference Levels at the Antenna Port.....	320
Figure F- 2 Stress-Case Continuous Interference Environments	321
Figure G- 1 Measured L5 Patch Antenna Elevation Pattern and Proposed L5 Limits	333
Figure G- 2 GTD Roll Plane Pattern Simulations.....	333
Figure G- 3 Antenna on Flat Ground Plane Figure G- 4 Antenna on 1.76m Cylinder (Beechjet)	334
Figure G- 5 Antenna on 2.83m Cylinder (Canadair) Figure G- 6 Antenna on 6.76m Cylinder (737) ..	334
Figure G- 7 Fuselage Section Pattern Measurement Orientations	335
Figure G- 8 Antenna 1 Pitch Axis Pattern Scan.....	336
Figure G- 9 Antenna 1 Roll Axis Pattern Scan.....	336
Figure G- 10 Antenna 2 Pitch Axis Pattern Scan.....	337
Figure G- 11 BAC 1-11 1/9 Scale Model Radiation Distribution Pattern	339
Figure G- 12 L1 Patch Antenna on a Flat Ground Plane – Polarization Response.....	339
Figure H- 1 Receiver-Emitter Geometry-Side View	344
Figure H- 2 Limitation of Emitters by Earth’s Curvature.....	345
Figure H- 3 Total Power Plot for a Rectangular Continuum of Emitters, $D=1$	347
Figure H- 4 Square Enclosing Circle Enclosing a Square of Emitters.....	347
Figure H- 5 Geometry for Merging Discrete Emitters with Continuum Approximation	350
Figure H- 6 Example of Random Emitters in a City.....	351
Figure I- 1 Broadband Noise Normalization and Partial UWB Substitution Illustration	357
Figure I- 2 Broadband Noise Equivalency Factor Illustration	358
Figure J- 1 Considered DME/TACAN beacon antenna gains versus elevation	363
Figure J- 2 E5a/L5 effective post-correlation C/N_0 degradation due to DME/TACAN beacons over Europe at FL400 – blanking threshold of -117.1 dBW.....	363

Figure J- 3 E5b effective post-correlation C/N_0 degradation due to DME/TACAN beacons over Europe at FL400 – blanking threshold of -120.0 dBW	364
Figure J- 4 E5a/L5 effective post-correlation C/N_0 degradation due to DME/TACAN beacons over the US at FL400 – blanking threshold of -117.1 dBW	365
Figure J- 5 E5b effective post-correlation C/N_0 degradation due to DME/TACAN beacons over the US at FL400 – blanking threshold of -120.0 dBW European High altitude RFI Acquisition Scenario Description.....	365

TABLE OF TABLES

Table A- 1 Category I Average Geometry Probability Density Function.....	201
Table A- 2 Category I Average Geometry Probability Density Function.....	201
Table A- 3 Category I Average Geometry Probability Density Function.....	202
Table B- 1 Continuous Sources	207
Table B- 2 Pulsed Sources	208
Table C- 1 Received Minimum L5 RF Signal Strength.....	217
Table D- 1 LINE-OF-SIGHT VELOCITY UNCERTAINTY	240
Table D- 2 PDC_b and R_i Estimates of JTIDS/MIDS Case 8 per Blanking Threshold	256
Table D- 3 Aggregate power factors for L5 and E5A I or Q Components	261
Table D- 4 Satellite Failure Probabilities.....	263
Table D- 5 EU High Altitude Scenario Pulsed RFI Composite Parameters	267
Table D- 6 EU High Altitude GPS Acquisition $C/N_{0, \text{eff}}$ Link Budget.....	267
Table E- 1 SSR Interrogator Characteristics.....	277
Table E- 2 SSR Transponder Characteristics.....	277
Table E- 3 Summary Results – Generic Case.....	281
Table E- 4 Preselector Circuit Parameters at Selected Frequencies.....	285
Table E- 5 Representative Aircraft L-Band Antenna Coupling Factors	286
Table E- 6 Measured PED Emissions in the GPS L1 and L5 Bands	290
Table E- 7 Boeing 737-200 (#1883) PED Interference Path Losses to GPS Antenna.....	294
Table E- 8 GREET-Generated GPS L5-Interfering DME/TACANs at 40,000 ft Above Mean Sea Level (MSL) (* Type 1 = DME, Type 2= TACAN).....	301
Table E- 9 Detailed Results Associated with Figure E- 14.....	306
Table E- 10 Blanking test for N = 20 TACAN Emitters.....	307
Table E- 11 JTIDS/TACAN DME Noise Reference Calculation and L5 Transmit Level	311
Table E- 12 L5 Degradation vs. JTIDS Environments and L5 Carrier Levels.....	312
Table E- 13 L5 Degradation versus DME Frequency Location	313
Table F- 1 STRESS-CASE CONTINUOUS INTERFERENCE BANDWIDTH DEFINITIONS (GPS SIGNAL TRACKING).....	322
Table F- 2 STRESS-CASE PULSED INTERFERENCE.....	323
Table H- 1 Total Power for the Geometries Shown in Figure H-4	348
Table H- 2 Power Density Comparison, Height = 100 m, Emitter Spacing = 100 m.....	348
Table H- 3 Power Density Comparison, Height = 15 m, Emitter Spacing = 100 m.....	349
Table H- 4 Power Density Comparison, Height = 100 m, Emitter Spacing = 25 m.....	350
Table H- 5 Power Density Comparison, Height = 15 m, Emitter Spacing = 25 m.....	350
Table H- 6 Total Power Density from Discrete Emitters at Random Locations.....	351
Table H- 7 Noise to L5 Receiver Front End from Aggregate Unwanted RFI	352
Table H- 8 Noise to L5 Receiver Front End from Aggregate Intentional Unlicensed In-band RFI	352

Table J- 1 E5a/L5 high altitude (FL 400) European hot-spot degradation due to DME/TACAN and JTIDS/MIDS systems – blanking threshold of -117.1 dBW.....	366
Table J- 2 E5b high altitude (FL 400) European hot-spot degradation due to DME/TACAN and JTIDS/MIDS systems – blanking threshold of -120.0 dBW.....	367
Table J- 3 Galileo E5a/E5b and GPS L5 high altitude acquisition scenario power link budget over the EU hot-spot	367
Table J- 4 E5a/L5 high altitude (FL 400) US hot-spot degradation due to DME/TACAN and JTIDS/MIDS systems – blanking threshold of -117.1 dBW.....	368
Table J- 5 E5b high altitude (FL 400) US hot-spot degradation due to DME/TACAN and JTIDS/MIDS systems – blanking threshold of -120.0 dBW	368
Table J- 6 Galileo E5a/E5b and GPS L5 high altitude acquisition scenario power link budget over the US hot-spot	368

1 INTRODUCTION

1.1 Background

The original GNSS L1 RFI environment assessment by RTCA (RTCA/DO-235), completed in late 1996, identified potential sources of RFI and assessed the vulnerability of GNSS receivers (particularly GPS) to that interference. The navigation signals considered were the GPS and GLONASS Standard Positioning Service (SPS) signals on their respective L1 carriers, and the L1 signals transmitted by the FAA Wide Area Augmentation System (WAAS). The original assessment was motivated by a number of factors. These included sporadic GPS interference trouble reports from various RFI sources, the potential RFI from new sources in adjacent frequency bands, and the need to identify appropriate mitigation measures for flight-critical GNSS applications. Out of the original assessment work came susceptibility requirements for RTCA/DO-229 GPS/WAAS airborne receiver standard, two proposals for "Big-LEO" Mobile Satellite Service transmitter emission requirements, and several other key findings.

In a November 1999, letter, the Department of Transportation (DOT) requested that RTCA to "continue to further the necessary work for L5 and determine appropriate susceptibility criterion and subsequent unwanted emission protection levels for this new GPS signal." The letter went on to say "We ask that the RTCA take on this task and devote a Working Group towards defining the appropriate unwanted emission protection levels and susceptibility criteria for L5. We request that such work be published in an RTCA report similar in nature to Assessment of Radio Frequency Interference Relevant to the GNSS, RTCA Report DO-235 of January 1997. In response, the RTCA undertook to investigate the RFI environment near the GPS L5 frequency (1176.45 ± 12 MHz), and determine appropriate receiver susceptibility criteria and related RFI unwanted emission limits for the use with new civil signal. ." In a June 2000 DOT letter, the DOT requested that RTCA "examine the issues of potential interference from ultra-wideband (UWB) technology to critical aviation systems, including the Global Positioning System (GPS)." It went on to say "We ask RTCA's assistance in developing appropriate operational scenarios for these systems. It suggested, "RTCA may wish to expand the charter of the current SC-159 WG6 to include this work for analysis of impacts at both L5 and L1." In a July 2000 letter to Mr. Joseph Canny, DOT, RTCA replied, "SC-159 is currently addressing Ultra Wide Band (UWB) interference issues for the L5 band and will now include the L1 band in its work. Recent SC-159 documents [1-1, -2, -3] addressed these issues pertaining to GNSS L1. This report addresses potential radio frequency interference to the future GPS L5 signal when used for aeronautical radionavigation, and includes RFI to the Galileo E5A signal as well, where feasible.

The frequency band for L5 was selected from a large number of candidates, because it has the most favorable characteristics: It is close enough in frequency to L1 and L2 that the GPS satellite can support it; it is separated from L1 sufficiently to provide all the benefits from a second signal; and it is allocated worldwide to the aeronautical radionavigation service (ARNS). This allocation status will provide GPS L5 with regulatory protection from interference that is not available in bands allocated to other services.

The potential sources of RFI to the GPS L5 signal are vastly more complicated than those for the L1 signal. For instance, L1 operates in a frequency band where the only signal, which is in-band to GPS, is GPS itself, plus its own augmentations. Unlike L1, the L5