

RTCA, Inc.  
1140 Connecticut Avenue, NW, Suite 1020  
Washington, DC 20036-4008 USA

**MINIMUM OPERATIONAL PERFORMANCE  
STANDARDS FOR AERONAUTICAL MOBILE  
HIGH FREQUENCY DATA LINK (HF DL)**

Copies of this document may be obtained from

RTCA, Inc.  
1140 Connecticut Avenue, NW, Suite 1020  
Washington, DC 20036-4008 USA

Telephone: 202-833-9339  
Facsimile: 202-833-9434  
Internet: [www.rtca.org](http://www.rtca.org)

Please call RTCA for price and ordering information.

## FOREWORD

This report was prepared by Special Committee 188 (SC-188) and approved by the RTCA Program Management Committee (PMC) on December 14, 2000.

RTCA, Incorporated is not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunications Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This page intentionally left blank.

## TABLE OF CONTENTS

1	PURPOSE AND SCOPE.....	1
1.1	Introduction.....	1
1.2	System Overview.....	2
1.2.1	HF Data Link Architecture.....	3
1.2.2	Communications Characteristics.....	3
1.2.3	Ground Equipment Requirements.....	4
1.2.4	HF Data Link Requirements.....	4
1.2.5	Service Providers.....	4
1.2.6	Communications Protocols.....	4
1.3	Operational Applications.....	5
1.3.1	Air Traffic Services (ATS).....	5
1.3.1.1	Air Traffic Control (ATC).....	5
1.3.1.2	Flight Information Services (FIS).....	6
1.3.1.3	Alerting Services.....	7
1.3.1.4	Automatic Dependent Surveillance-Addressed (ADS-A).....	7
1.3.2	Aeronautical Operational Control (AOC).....	7
1.3.2.1	AOC Functions.....	7
1.3.2.2	Operations Services.....	8
1.4	Operational Goals.....	9
1.4.1	Global Coverage.....	9
1.4.2	Compatibility and Interoperability.....	9
1.4.3	End-to-End Service Criteria.....	9
1.5	Assumptions and Postulated Environment.....	10
1.5.1	Coverage.....	10
1.5.2	Data versus Voice Communications.....	10
1.5.3	Safety.....	11
1.5.4	Priority, Precedence and Preemption.....	11
1.6	Overview of Test and Performance Verification Procedures.....	11
1.6.1	Environmental Tests and Performance Verification.....	11
1.6.2	Bench Tests and Performance Verification.....	12
1.6.3	Installed Equipment Tests and Performance Verification.....	12
1.6.4	Operational Tests and Performance Verification.....	12
2	EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES.....	13
2.1	General Requirements.....	13
2.1.1	Airworthiness.....	13
2.1.2	Intended Function.....	13

2.1.3	Federal Communications Commissions Rules.....	13
2.1.4	Fire Protection.....	13
2.1.5	Operation of Controls.....	13
2.1.6	Accessibility of Controls.....	13
2.1.7	Effects of Tests.....	14
2.1.8	Performance in a Shared Environment.....	14
2.2	Equipment Performance Requirements, Standard Conditions.....	14
2.2.1	Avionics Subsystem Definitions and Overall Requirements.....	16
2.2.2	Priority, Precedence and Preemption (Voice/Data).....	16
2.2.2.1	Voice/Data Mode Selection.....	16
2.2.2.2	Dual HF Data Link Installations.....	17
2.2.3	HF Data Link Subnetwork Physical Layer Requirements.....	17
2.2.3.1	Signal-In-Space Modulation Definition.....	17
2.2.3.2	Signal-In-Space Transmission Requirements.....	17
2.2.3.2.1	Prekey Requirement.....	17
2.2.3.2.2	Preamble Requirement.....	17
2.2.3.2.3	Data Segment Requirement.....	17
2.2.3.2.3.1	Forward Error Correction.....	18
2.2.3.2.3.2	Interleaving Requirement.....	18
2.2.3.2.3.3	M-PSK Symbol Scrambling.....	18
2.2.3.2.4	Transmit Slot Time Synchronization.....	18
2.2.3.2.5	Transmit Pulse-Shaping Filter Response.....	18
2.2.3.2.6	Spectrum Control in Data Mode.....	18
2.2.3.2.7	Transmitter Peak Envelope Power.....	19
2.2.3.3	Reception Requirements.....	20
2.2.3.3.1	HF Data Link Receiver Sensitivity.....	20
2.2.3.3.2	Packet Error Rate Performance.....	20
2.2.3.3.3	Transmit to Receive Recovery Time.....	20
2.2.3.3.4	Receiver Signal Attenuation.....	20
2.2.3.3.5	Frequency Search.....	21
2.2.4	HF Data Link Subnetwork Data Link Layer Functions.....	21
2.2.4.1	Data Rate Communications.....	21
2.2.4.2	Selection of Downlink Slot by Aircraft.....	21
2.2.4.3	Maximum MPDU Size Adjustment.....	21
2.2.4.4	Data Rate and Interleaver Selection.....	22
2.2.4.5	Squitter PDU Format.....	22
2.2.4.5.1	SPDU ID.....	22
2.2.4.5.2	Ground Station Address.....	22
2.2.4.5.3	Frame ID.....	22
2.2.4.5.4	Slot Acknowledgment Codes.....	22
2.2.4.5.5	Slot Assignment Codes.....	22
2.2.4.5.6	Priority Field.....	22
2.2.4.5.7	Ground Station Active Frequency Field.....	23
2.2.4.5.8	Frame Check Sequence.....	23
2.2.4.5.9	Flush Field.....	23
2.2.4.6	MPDU Packet Encapsulation.....	23
2.2.4.7	MPDU Format Requirements.....	23

2.2.4.7.1 Mid (MPDU ID) Field .....	23
2.2.4.7.2 GS Field.....	23
2.2.4.7.3 Aircraft Address Field .....	24
2.2.4.7.4 FCS (Frame Check Sequence).....	24
2.2.4.7.5 Data Field .....	24
2.2.4.7.6 Flush Field.....	24
2.2.5 Packet-Mode Data Service Requirement .....	24
2.2.5.1 Packet-Mode Data-2 Service Requirements .....	25
2.2.5.2 Packet-Mode Data-3 Service Requirements .....	26
2.2.5.3 Priority, Precedence and Preemption (Data/Data).....	27
2.2.5.4 HF Data Link Subnetwork Requirements.....	28
2.2.5.4.1 Data-2 Requirements.....	29
2.2.5.4.2 Data-3 Requirements.....	29
2.2.5.4.3 Join and Leave Event Requirements .....	29
2.2.6 Aircraft Log-on Procedure.....	29
2.2.7 Recovery from Primary Power Interruption.....	30
2.2.8 Failure/Status Indication .....	30
2.3 Equipment Performance, Environmental Conditions .....	30
2.3.1 General Requirements.....	30
2.3.2 Equipment Configurations.....	31
2.3.3 Configuration Control.....	31
2.3.4 Specific Environmental Test Conditions .....	31
2.3.5 Performance vs. Test Requirements .....	31
2.4 Equipment Performance Verification Procedures.....	32
2.4.1 Definitions of Terms and Conditions of Test .....	32
2.4.2 Required Test Equipment .....	33
2.4.3 Detailed Test Procedures.....	34
2.4.4 Priority, Precedence and Preemption Test Requirements.....	34
2.4.5 Voice/Data Mode Selection Test Requirements.....	37
2.4.6 Dual HF Data Link Installation Test Requirements .....	37
2.4.7 Signal-In-Space Test Requirements .....	38
2.4.8 Transmit Pulse Shaping Filter and Spectrum Control Test Requirements.....	42
2.4.9 Prekey Time Test Procedure.....	42
2.4.10 Packet Error Rate Test Requirements.....	43
2.4.11 Transmit to Receive Recovery Time Test Procedure .....	47
2.4.12 Data Rate Communications Test Requirements .....	48
2.4.13 Selection of Downlink Slot by Aircraft Requirements .....	50
2.4.13.1 Transmit Slot Time Synchronization.....	51
2.4.14 Maximum MPDU Size Adjustment Test Requirements .....	51
2.4.15 Data Rate and Interleaver Selection Test Requirements .....	51
2.4.16 Squitter SPDU Format Test Requirements .....	53
2.4.17 MPDU Packet Encapsulation Test Requirements .....	53
2.4.18 MPDU Format Test Requirements .....	55
2.4.19 Packet Mode Data Services Test Requirements .....	56
2.4.19.1 Data 3/ATN/ISO-8208 Interfaces.....	56
2.4.19.1.1 Join and Leave Requirements .....	57

2.4.19.1.2	Data 3 Mapping for Priority, Precedence and Preemption.....	57
2.4.19.1.3	Data 2 Transfer.....	58
2.4.19.2	HF Data Link Subnetwork.....	58
2.4.19.2.1	HF Data Link Subnetwork Dependent Protocol.....	58
2.4.19.3	Avionics Subnetwork Interface.....	59
2.4.19.3.1	ISO-8208 Protocol.....	59
2.4.19.3.2	Channel State Test Procedures.....	60
2.4.19.3.3	Normal State Test Procedures.....	60
2.4.19.3.4	Call Setup and Clearing States.....	61
2.4.19.3.5	Restart Request States.....	65
2.4.19.3.6	Reset States.....	66
2.4.19.3.7	Interrupt Transfer States.....	67
2.4.19.3.8	Error Recovery Procedures.....	67
2.4.19.3.9	DCE Call Setup and Clearing States.....	69
2.4.19.3.10	DCE Restart States.....	72
2.4.19.3.11	DCE Reset States.....	73
2.4.19.3.12	DCE Flow Control Transfer States.....	74
2.4.19.3.13	DCE Interrupt Transfer States.....	76
2.4.19.3.14	Packet Assembly.....	77
2.4.19.3.15	Call Setup and Maintenance.....	80
2.4.19.3.16	Fast Select Facilities.....	80
2.4.19.3.17	Called and Calling Address Extension (NSAP) Test.....	82
2.4.19.3.18	Throughput Class Negotiation Facility.....	83
2.4.19.3.19	Transit Delay Selection and Indication Facility.....	83
2.4.19.3.20	Priority Facility.....	84
2.4.19.3.21	Multiple Channel Transactions.....	85
2.4.19.3.22	Call Request Procedures.....	85
2.4.19.3.23	Data Transmission Procedures.....	86
2.4.19.3.24	Clear Request Procedures.....	86
2.4.19.3.25	Reset Request Procedures.....	86
2.4.19.3.26	Receive Not Ready Status.....	86
2.4.19.3.27	Error Recovery Procedures.....	87
2.4.19.3.28	ISO-8208 DCE Timer Test Procedures.....	87
2.4.19.3.29	tN10 Timer Procedure.....	87
2.4.19.3.30	tN11 Timer Procedure.....	88
2.4.19.3.31	tN12 Timer Procedure.....	88
2.4.19.3.32	tN13 Timer Procedure.....	88
2.4.20	Aircraft Log-on Procedure Test Requirements.....	89
2.4.21	Recovery from Primary Power Interruption Test Requirements.....	90
2.4.22	Failure/Status Indication Test Requirements.....	91
2.4.23	Frequency Search.....	92
3	INSTALLED EQUIPMENT PERFORMANCE.....	94
3.1	Equipment Installation.....	94
3.1.1	Accessibility.....	94
3.1.2	Aircraft Environment.....	94

3.1.3	Display Visibility.....	94
3.1.4	Inadvertent Turn-Off.....	94
3.1.5	Failure Protection .....	94
3.1.6	Interface Interference Effects.....	94
3.1.7	Aircraft Power Source.....	94
3.2	Installed Equipment Performance Requirements .....	95
3.3	Conditions of Test.....	95
3.3.1	Power Input .....	95
3.3.2	Environment.....	95
3.3.3	Adjustment of Equipment.....	95
3.3.4	Warm-up Period.....	95
3.4	Test Procedures for Installed Equipment Performance .....	95
3.4.1	Conformity Inspection.....	96
3.4.2	Interference Tests .....	96
3.4.3	Power Fluctuation Tests.....	96
3.4.4	Ground Test Procedures .....	96
3.4.5	Flight Test Procedures .....	97
3.4.6	Installed System Performance Verification.....	97
4	EQUIPMENT OPERATIONAL PERFORMANCE CHARACTERISTICS .....	98
4.1	Operational Performance Requirements .....	98
4.1.1	Power Input .....	98
4.1.2	Communications Displays.....	98
4.1.3	Communications Controls .....	98
4.1.4	System Operational Indication .....	98
4.1.5	Equipment Operating Limitations .....	98
4.2	Test Procedures for Operational Requirements.....	98
4.2.1	Power Input .....	98
4.2.2	Communications Displays.....	99
4.2.3	Communications Controls .....	99
4.2.4	System Operational Indication .....	99
	MEMBERSHIP .....	100

## APPENDICES

Appendix A – GLOSSARY AND DEFINITION OF TERMS

Appendix B – REQUIREMENT/TEST COVERAGE MATRIX

**TABLE OF FIGURES**

<u>Figure 2.2-1</u>	Requirements Mapping.....	15
<u>Figure 2.2-2</u>	Transmit Spectrum Limits.....	19
<u>Figure 2.2-3</u>	HF Data Link Subnetwork Architecture (Airborne Side).....	25
<u>Figure 2.4-1</u>	Priority, Precedence and Preemption Test Setup.....	35
<u>Figure 2.4-2</u>	Voice/Data Mode Selection Test Setup.....	37
<u>Figure 2.4-3</u>	Dual HF Data Link Installation Test Setup.....	38
<u>Figure 2.4-4</u>	Signal-In-Space Test Setup.....	40
<u>Figure 2.4-5</u>	Transmit Pulse Shaping Filter and Spectrum Control Test Setup.....	42
<u>Figure 2.4-6</u>	Prekey Time Test Setup.....	43
<u>Figure 2.4-7</u>	PER Measurement Setup.....	46
<u>Figure 2.4-8</u>	Transmit to Receive Recovery Time Test Setup.....	48
<u>Figure 2.4-9</u>	Data Rate Communications Test Setup.....	48
<u>Figure 2.4-10</u>	Downlink Slot Selection Test Setup.....	50
<u>Figure 2.4-11</u>	MPDU Size Adjustment Test Setup.....	51
<u>Figure 2.4-12</u>	Data Rate and Interleaver Selection Test Setup.....	52
<u>Figure 2.4-13</u>	Squitter SPDU Format Test Setup.....	53
<u>Figure 2.4-14</u>	MPDU Encapsulation Test Setup.....	55
<u>Figure 2.4-15</u>	MPDU Format Test Setup.....	56
<u>Figure 2.4-16</u>	High-Level Test Set Up for DCE Interface Testing.....	57
<u>Figure 2.4-17</u>	Log-on Procedure Test Setup.....	90
<u>Figure 2.4-18</u>	Power Interruption Test Setup.....	91
<u>Figure 2.4-19</u>	Failure/Status Indication Test Setup.....	92
<u>Figure 2.4-20</u>	Frequency Search Test Setup.....	92

**TABLE OF TABLES**

<u>Table 2-1</u>	HF Data Link Priority Structure.....	27
<u>Table 2-2</u>	Environmental Conditions Structure.....	31

# 1 PURPOSE AND SCOPE

## 1.1 Introduction

These standards specify system characteristics that should be useful to designers, manufacturers, installers and users of the HF Data Link systems and equipment.

Compliance with these standards is recommended as one means of assuring that the HF Data Link avionics will perform its intended function(s) satisfactorily under all conditions normally encountered in routine aeronautical operations. Any regulatory application of this document is the sole responsibility of appropriate governmental agencies.

This document encompasses standards and descriptions of a system configuration including Ground Subnetworks; HF Data Link Subnetworks, of which the Aircraft is one part; and Aircraft Subnetworks. However, the specified Minimum Operational Performance Standards in this document address only the aircraft HF Data Link Subnetwork function.

The MOPS covers typical HF Data Link avionics requirements and tests for the aircraft avionics. It includes the purpose, scope and equipment performance requirements; recommended bench tests and other performance verification procedures; and installed-equipment tests and operational performance characteristics. The High Frequency Data Link (HF DL) functions operate in the aeronautical frequency bands 230 MHz. The transceiver must be capable of being tuned in integral multiples of 1 kHz to support the HF Data Link function and use the class of emission 2K80J2DEN.

Section 1.0 of this document provides general information needed to understand the rationale for HF Data Link equipment and system characteristics and requirements stated in the remaining sections. It describes typical applications and operational goals as envisioned by the members of Special Committee 188 and establishes the basis for the standards stated in Sections 2.0 through 3.0. Definitions and assumptions essential to proper understanding of this document are also provided in this section, while a more extensive glossary appears as Appendix A.

Section 2.0 contains the minimum performance standards for the aircraft HF Data Link function. These standards specify the required performance under standard and environmental conditions. Also included are recommended bench test procedures necessary to demonstrate equipment and network compliance with the stated minimum requirements.

Section 3.0 describes the performance required of the installed aircraft avionics equipment. Tests specifically for the installed equipment are included when performance cannot be adequately determined through bench testing.

Section 4.0 describes the operational performance characteristics for equipment installations and for network operation and defines conditions that will assure the equipment user that operations can be conducted safely and reliably in the expected