

RTCA
1828 L Street, NW, Suite 805
Washington, DC 20036

**Minimum Operational Performance Standards for Airborne ILS Glide Slope
Receiving Equipment Operating within the Radio Frequency
Range of 328.6-335.4 Megahertz**

RTCA DO-192
July 18, 1986

Prepared by:
SC-153

Copies of this document may be obtained from

RTCA, Incorporated
1828 L Street, NW, Suite 805
Washington, D.C. 20036-5133 U.S.A.

Telephone: 202-833-9339
Facsimile: 202-833-9434

Internet: www.rtca.org

Please contact RTCA for price and ordering information.

F O R E W O R D

This document was prepared by Special Committee 153 of the Radio Technical Commission for Aeronautics. It was approved by RTCA on July 18, 1986, and supersedes RTCA/DO-132A, "Performance Standards Airborne ILS Glide Slope Receiving Equipment," November 2, 1978.

RTCA is an association of aeronautical organizations of the United States from both government and industry. Dedicated to the advancement of aeronautics, RTCA seeks sound technical solutions to problems involving the application of electronics and telecommunications to aeronautical operations. Its objective is the resolution of such problems by mutual agreement of its member organizations.

The findings of RTCA are in the nature of recommendations to all organizations concerned. Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the Federal government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

In preparation of these standards RTCA SC-153 took into consideration comments received on behalf of the European Organisation for Civil Aviation Electronics (EUROCAE) WG-5.

THIS PAGE INTENTIONALLY LEFT BLANK

T A B L E O F C O N T E N T S

	<u>Page</u>
FOREWORD	i
TABLE OF CONTENTS	iii
1.0 PURPOSE AND SCOPE	1
1.1 Introduction	1
1.2 System Overview	2
1.3 Operational Applications	2
1.4 Operational Goals	2
1.4.1 Sensitivity	2
1.4.2 Receiver Selectivity	3
1.4.3 Spurious Response and Intermodulation	3
1.4.4 Warnings	3
1.4.5 Interface with Other Aircraft Systems	3
1.5 Assumptions	3
1.6 Test Procedures	3
1.7 Definitions of Terms	5
2.0 ILS GLIDE SLOPE EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES	7
2.1 General Requirements	7
2.1.1 Airworthiness	7
2.1.2 Intended Function	7
2.1.3 Federal Communications Commission Rules	7
2.1.4 Fire Protection	7
2.1.5 Operation of Controls	7
2.1.6 Accessibility of Controls	7
2.1.7 Frequency Display	8
2.1.8 Effects of Test	8
2.2 Minimum Performance Standards Under Standard Test Conditions	8
2.2.1 Centering Accuracy	8
2.2.2 On-Channel Signals	8
2.2.2.1 AGC	8
2.2.2.2 Bandwidth	8
2.2.3 Interfering Signals	8
2.2.3.1 Adjacent Channel and In Band Signals	8
2.2.3.2 Receiver Performance With Two Carriers	9

	<u>Page</u>
2.2.4 Course Deviation Indication	10
2.2.4.1 Electrical Course Deviation Output	11
2.2.4.2 Deflection Stability with Modulation Frequency	12
2.2.5 Warnings	12
2.2.6 Spurious Response	12
2.2.7 Emission of Radio Frequency Energy	12
2.2.8 Antenna Efficiency	13
2.2.9 Antenna Polarization	13
2.2.10 Antenna VSWR	13
2.3 Equipment Performance - Environmental Conditions	15
2.3.1 Temperature and Altitude Tests	15
2.3.1.1 Low Temperature Test	15
2.3.1.2 High Temperature Test	16
2.3.1.3 Altitude Tests	16
2.3.1.4 Decompression Test	16
2.3.1.5 Overpressure Test	16
2.3.2 Temperature Variation Test	17
2.3.3 Humidity Test	17
2.3.4 Shock Tests	17
2.3.4.1 Operational Shocks	17
2.3.4.2 Crash Safety Shocks	17
2.3.5 Vibration Tests	18
2.3.6 Explosion Test	18
2.3.7 Waterproofness Test	18
2.3.7.1 Drip Proof Test	18
2.3.7.2 Spray Proof Test	18
2.3.8 Fluids Susceptibility Tests	18
2.3.8.1 Spray Test	19
2.3.8.2 Immersion Test	19
2.3.9 Sand and Dust Test	19
2.3.10 Fungus Resistance Test	19
2.3.11 Salt Spray Test	20
2.3.12 Magnetic Effect Test	20
2.3.13 Power Input Tests	20
2.3.13.1 Normal Operating Conditions	20
2.3.13.2 Abnormal Operating Conditions	20

	<u>Page</u>
2.3.14 Voltage Spike Conducted Test	20
2.3.14.1 Category A Requirements	20
2.3.14.2 Category B Requirements	21
2.3.15 Audio Frequency Conducted Susceptibility Test	21
2.3.16 Induced Signal Susceptibility Test	21
2.3.17 Radio Frequency Susceptibility Test (Radiated and Conducted)	21
2.3.18 Emission of Radio Frequency Energy Test	22
2.4 Equipment Test Procedures	23
2.4.1 Definitions of Terms and Conditions of Tests	23
2.4.2 Description of Test Equipment	24
2.4.3 Detailed Test Procedures	25
2.4.3.1 Centering Accuracy	25
2.4.3.2 Receiver Performance with Two Carriers	27
2.4.3.3 AGC Characteristic	28
2.4.3.4 Interfering Signals	28
2.4.3.5 Course Deviation Indication	28
2.4.3.6 Warnings	30
2.4.3.7 Spurious Response	30
2.4.3.8 Emission of Radio Frequency Energy	30
2.4.3.9 Antenna Efficiency	31
2.4.3.10 Antenna Polarization	31
2.4.3.11 Antenna VSWR	32
3.0 INSTALLED EQUIPMENT PERFORMANCE	35
3.1 Equipment Installation	35
3.1.1 Equipment Accessibility	35
3.1.2 Aircraft Environment	35
3.1.3 Display Visibility	35
3.1.4 Antenna Location Considerations	35
3.1.5 Failure Protection	35
3.1.6 Inadvertent Turnoff	35
3.1.7 Aircraft Power Source	35
3.2 Installed Equipment Performance Requirements	36
3.2.1 Interference Effects	36
3.3 Conditions of Test	36
3.3.1 Power Input	36
3.3.2 Associated Equipment or Systems	36

	<u>Page</u>
3.3.3 Environment	36
3.3.4 Adjustment of Equipment	36
3.4 Test Procedures for Installed Equipment Performance	37
3.4.1 Ground Test Procedures	37
3.4.1.1 Conformity Inspection	37
3.4.1.2 Equipment Function	37
3.4.1.3 Interference Effects	37
3.4.1.4 Power Supply Fluctuations	37
3.4.1.5 Equipment Accessibility	38
3.4.2 Flight Test Procedures	38
3.4.2.1 Displayed Data Readability	38
3.4.2.2 Interference Effects	38
4.0 EQUIPMENT OPERATIONAL PERFORMANCE CHARACTERISTICS	39
4.1 Required Operational Performance Requirements	39
4.1.1 Power Input	39
4.1.2 Equipment Operating Modes	39
4.2 Test Procedures for Operational Performance Requirements	39
4.2.1 Power Input	39
4.2.2 Equipment Operating Modes	39
MEMBERSHIP	41
APPENDIX A Statistical Procedure for Determination of ILS Receiver Course Error	
APPENDIX B Receiver RF Input Voltage (Hard and Easy Microvolts)	

1.0 PURPOSE AND SCOPE

1.1 Introduction

This document contains minimum operational performance standards for airborne glide slope receiving equipment. These standards specify system characteristics that should be useful to designers, manufacturers, installers and users of the equipment.

Compliance with these standards is recommended as one means of assuring that the equipment will perform its intended function satisfactorily under all conditions normally encountered in routine operations.

Any regulatory application of this document is the sole responsibility of appropriate governmental agencies.

Section 1.0 provides information needed to understand the rationale for equipment characteristics and requirements stated in the remaining sections. It describes typical equipment applications and operational goals and establishes the basis for the standards stated in Sections 2.0 through 4.0. Definitions and assumptions essential to proper understanding of this document are also provided in Section 1.0.

Section 2.0 contains the minimum performance standards for the equipment. These standards specify the required performance under standard and environmental conditions. Also included are recommended bench test procedures necessary to demonstrate equipment compliance with the stated minimum requirements.

Section 3.0 describes the performance required of the installed equipment. Tests for the installed equipment are included when performance cannot be adequately determined through bench testing.

Section 4.0 describes the operational performance characteristics for equipment installations and defines conditions that will assure the equipment user that operations can be conducted safely and reliably in the expected operational environment.

This document considers an equipment configuration consisting of: Antenna system(s), transmission lines, radio receiver, converter and a course deviation indication display. Additional functions and components that refer to expanded equipment capabilities are identified as optional features.

The word "system" as used in this document refers to the ILS glide slope system. It includes all portions of both the ILS glide slope ground transmitter and the glide slope airborne equipment.

The word "equipment" as used in this document includes all components and units necessary for the system to properly perform its intended function. For example, the "equipment" may include an