

RTCA
One McPherson Square
1425 K Street, NW, Suite 500
Washington, DC 20005 USA

**Minimum Operational Performance Standards
(MOPS) for Airborne Area Navigation
Equipment Using Omega/VLF Inputs**

RTCA DO-190
Supersedes DO-140
May 16, 1986

Prepared by: SC-137
© RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

F O R E W O R D

This document was prepared by Special Committee 137 of the Radio Technical Commission for Aeronautics. It was approved by RTCA on May 16, 1986.

RTCA is an association of aeronautical organizations of the United States from both government and industry. Dedicated to the advancement of aeronautics, RTCA seeks sound technical solutions to problems involving the application of electronics and telecommunications to aeronautical operations. Its objective is the resolution of such problems by mutual agreement of its member organizations.

The findings of RTCA are in the nature of recommendations to all organizations concerned. RTCA is not an official agency of the United States Government and its recommendations may not be regarded as statements of official government policy unless so enunciated by the U. S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

Faint, illegible text at the top of the page, possibly a header or title.

Second block of faint, illegible text.

Third block of faint, illegible text.

THIS PAGE INTENTIONALLY LEFT BLANK

T A B L E O F C O N T E N T S

	<u>Page</u>
FOREWORD	i
TABLE OF CONTENTS	iii
1.0 PURPOSE AND SCOPE	1
1.1 Introduction	1
1.2 System Characteristics	2
1.2.1 Waypoint Definition	3
1.2.2 Course Selection	3
1.2.2.1 "TO-FROM" Equipment.....	3
1.2.2.2 "TO-TO" Equipment.....	3
1.2.3 Path Computation	4
1.2.4 Coordinate Systems	4
1.2.5 Position Sensing	5
1.2.6 Lateral and Vertical Steering Outputs	5
1.3 Intended Use and Operational Environment	6
1.3.1 Area Navigation in the Present ATC System	6
1.3.2 Historical Considerations	10
1.3.3 Route Width Consideration	11
1.3.3.1 En route RNAV Route.....	11
1.3.3.2 En route VOR Airway Route.....	11
1.3.4 Postulated Air Traffic Control Environment	12
1.3.5 Operational Environment Assumptions	13
1.4 Error Budgets	13
1.4.1 Error Budget - 2D	13
1.4.1.1 VOR/DME Sensors.....	14
1.4.1.2 Omega/VLF Error Budget.....	14
1.4.1.3 North Reference Effects	14
1.4.2 Error Budget - VNAV	15
1.5 Test Procedures	15
1.5.1 Bench Tests	15
1.5.2 Environmental Tests	15
1.5.3 Installed Tests	16
1.5.4 Operational Tests	16
1.6 Definitions of Terms	16
1.7 General Characteristics of Omega/VLF RNAV Systems	16

1.7.1	Basic Elements of the System	16
1.7.2	Mode of Navigation	17
1.7.3	Area of Coverage	17
1.7.4	Station Selection	17
1.7.5	Input Data	17
1.7.6	Data Initialization	17
1.7.7	Accuracy	18
2.0	EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES	19
2.1	General Requirements	19
2.1.1	Airworthiness	19
2.1.2	General Performance	19
2.1.3	Fire Resistance	19
2.1.4	Operation of Controls	19
2.1.5	Accessibility of Controls	19
2.1.6	Aircraft Interfaces	19
2.1.7	Control/Display Capability	19
2.1.8	Control/Display Readability	20
2.1.9	Effects of Test	20
2.1.10	Maneuver Anticipation and Direct-To Function	20
2.1.11	Aircraft Attitude	20
2.2	2D RNAV Functional and Accuracy Requirements - Standard Conditions	20
2.2.1	Equipment Functional Requirements	20
2.2.1.1	Cross-Track Deviation.....	20
2.2.1.2	Waypoint Distance Display (Output Display)..	21
2.2.1.3	"TO-FROM" Indication.....	21
2.2.1.4	Course Selection.....	22
2.2.1.5	Waypoint Entry.....	22
2.2.1.6	Waypoint Storage.....	22
2.2.1.7	Waypoint or Leg Sequencing.....	22
2.2.1.8	Position Display.....	23
2.2.1.9	Input Data Observation.....	23
2.2.1.10	Failure/Status Indications.....	23
2.2.1.11	Station Deselection/Reselection and Indication.....	24
2.2.1.12	Equipment Computational Response Time.....	24
2.2.1.13	Secondary Navigation Mode.....	24
2.2.1.14	Resynchronization, Reacquisition, and Reinitialization.....	24
2.2.2	2D Performance Requirements	24
2.2.2.1	Synchronization.....	24
2.2.2.2	Static Signal Tracking.....	25
2.2.2.3	2D Accuracy Requirements (95% probability)..	26

	<u>Page</u>
2.2.2.4 Position Accuracy Following Direction Change.....	26
2.2.2.5 Position Accuracy Following Velocity Change.....	27
2.3 VNAV Functional and Accuracy Requirements - Standard Conditions	27
2.3.1 Equipment Functional Requirements	27
2.3.1.1 Waypoint Altitude.....	27
2.3.1.2 Vertical Path Deviation.....	27
2.3.1.3 Vertical Profile.....	27
2.3.2 VNAV Accuracy Requirements	28
2.4 Equipment Performance - Environmental Conditions	29
2.4.1 Temperature and Altitude Tests	29
2.4.1.1 Low Operating Temperature Test.....	29
2.4.1.2 High Short-Time Operating Temperature Test..	30
2.4.1.3 High Operating Temperature Test.....	30
2.4.1.4 In-Flight Loss of Cooling Test.....	30
2.4.1.5 Altitude Test.....	30
2.4.1.6 Decompression Test.....	31
2.4.1.7 Overpressure Test.....	31
2.4.2 Temperature Variation Test	31
2.4.3 Humidity Test	31
2.4.4 Shock Tests	32
2.4.4.1 Operational Shocks.....	32
2.4.4.2 Crash Safety Shocks.....	32
2.4.5 Vibration Test	32
2.4.6 Explosion Proofness Test.....	33
2.4.7 Waterproofness Tests	33
2.4.7.1 Drip Proof Test.....	33
2.4.7.2 Spray Proof Test.....	33
2.4.7.3 Continuous Stream Proof Test	33
2.4.8 Fluids Susceptibility Tests	34
2.4.8.1 Spray Test.....	34
2.4.8.2 Immersion Test.....	34
2.4.9 Sand and Dust Test	35
2.4.10 Fungus Resistance Test	35
2.4.11 Salt Spray Test	35
2.4.12 Magnetic Effect Test	35

	<u>Page</u>
2.4.13 Power Input Tests	36
2.4.13.1 Normal Operating Conditions.....	36
2.4.13.2 Abnormal Operating Conditions.....	36
2.4.14 Voltage Spike Conducted Test	36
2.4.14.1 Category A Requirements.....	36
2.4.14.2 Category B Requirements.....	37
2.4.15 Audio Frequency Conducted Susceptibility Test	37
2.4.16 Induced Signal Susceptibility Test	37
2.4.17 Radio Frequency Susceptibility Test (Radiated and Conducted)	37
2.4.18 Emission of Radio Frequency Energy Test	38
2.5 Equipment Test Procedures	39
2.5.1 Definitions of Terms and Conditions of Tests	39
2.5.2 Test Procedures	40
2.5.3 Detailed Performance Tests	42
2.5.3.1 Waypoint Entry and Storage.....	42
2.5.3.2 Failure/Status Indications.....	43
2.5.3.3 Synchronization.....	43
2.5.3.4 Static Signal Tracking.....	43
2.5.3.5 Secondary Navigation Mode.....	45
2.5.3.6 Cross-Track Deviation.....	45
2.5.3.7 Direction Change.....	45
2.5.3.8 Velocity Change.....	46
2.5.3.9 2D Position Accuracy.....	46
2.5.4 VNAV Functional and Accuracy Requirements - Standard Conditions	50
2.5.4.1 Static Tests.....	50
2.5.4.2 Dynamic Tests.....	54
2.5.4.3 VNAV Accuracy Requirements.....	57
3.0 INSTALLED EQUIPMENT PERFORMANCE	61
3.1 Equipment Installation	61
3.1.1 Accessibility	61
3.1.2 Display Visibility	61
3.1.3 Interference Effects	61
3.1.4 Inadvertent Turnoff	61
3.2 Installed Equipment Performance Requirements	61
3.2.1 General Performance Requirements	61

	<u>Page</u>
3.2.1.1 Cross-Track Deviation Display.....	61
3.2.1.2 Vertical Path Deviation Display.....	62
3.2.1.3 Lateral Maneuver Anticipation.....	62
3.2.1.4 Automatic Lateral Course Change.....	62
3.2.1.5 Direct-to Function.....	62
3.2.1.6 Vertical Maneuver Anticipation.....	64
3.2.1.7 Automatic Altitude Change.....	64
3.2.1.8 Display of Selected Waypoint.....	64
3.2.2 Installed Accuracy	64
3.2.2.1 Background.....	64
3.2.2.2 Standard Error Budget.....	64
3.2.2.3 System Error Tradeoffs.....	66
3.3 Conditions of Test.....	66
3.3.1 Power Input	66
3.3.2 Associated Equipment or Systems	67
3.3.3 Environment	67
3.3.4 Adjustment of Equipment	67
3.3.5 Warm-Up Period	67
3.4 Test Procedures for Installed Equipment Performance	69
3.4.1 Ground Test Procedures	69
3.4.1.1 Conformity Inspection.....	69
3.4.1.2 Equipment Function.....	69
3.4.1.3 Interference Effects.....	69
3.4.1.4 Power Supply Fluctuations.....	70
3.4.1.5 Equipment Accessibility.....	70
3.4.2 Flight Test Procedures	70
3.4.2.1 Displayed Data Readability.....	70
3.4.2.2 Interference Effects.....	70
3.4.2.3 Flight Demonstration.....	70
3.4.2.4 Simulator Demonstration.....	72
4.0 OPERATIONAL CHARACTERISTICS	73
4.1 Required Operational Characteristics	73
4.1.1 Power Input	73
4.1.2 Navigation Displays	73
4.1.3 Navigation Controls	73
4.2 Test Procedures for Operational Characteristics	73
4.2.1 Power Input	73
4.2.2 Navigation Displays	73

	<u>Page</u>
4.2.3 Navigation Controls	73
4.2.4 System Operational Integrity	74
MEMBERSHIP	75
APPENDIX A Postulated Area Navigation Operational Environment Definition	
APPENDIX B Omega/VLF Error Mechanisms	
APPENDIX C Glossary of Terms for Navigation Functions	
APPENDIX D Great Circle Course Computations	
APPENDIX E Implementing Epoch Year Magnetic Variation Values	
APPENDIX F Acceptable Procedural Techniques for Lateral Maneuver Anticipation	
APPENDIX G Omega/VLF Atmospheric Noise Model	
APPENDIX H Acceptable Trade-Off Techniques for Determining System Performance	

TABLES

Table 1-1 Summary of Representative Vertical Guidance Error Budget in Feet	7
Table 2-1 Omega/VLF Equipment Error	26
Table 2-2 Minimum Accuracy Requirements for Vertical Guidance Equipment Employed in Airborne Vertical Navigation Systems in Feet ..	28
Table 2-3 RNAV/VNAV Test/Requirements Cross Reference	42
Table 2-4 Test Flight Plan for Continental U.S.A.	48
Table 2-5 Test Conditions for Continental U.S.A. Flight Plan	48
Table 2-6 VNAV Static Tests - Single Waypoint Plus Ascent/Descent Angle	52
Table 2-7 VNAV Static Tests - Dual Waypoints With Associated Altitudes	53
Table 2-8 VNAV Dynamic Tests - Single Waypoint Plus Ascent/Descent Angle	58
Table 2-9 VNAV Dynamic Tests - Dual Waypoints Plus Associated Altitudes	59

FIGURES

Figure 1-1 Vertical Clearance Boundaries (Typical)	9
Figure 2-1 Equipment Test Set-Up	41
Figure 2-2 Test Set-Up	51
Figure 2-3 Vertical Path for Single Waypoint/Descent Angle	55
Figure 2-4 Vertical Path for Dual Waypoints With Associated Altitudes	56
Figure 3-1 "Corner Cut" Turn Expansion for Maneuver Anticipation Test	63
Figure 3-2 Direct-to Function	65

1.0 PURPOSE AND SCOPE

1.1 Introduction

This document contains minimum operational performance standards for airborne area navigation equipment (2D and 3D) operated in the National Airspace System (NAS) using Omega/VLF signals. Performance standards for equipment operated in other airspace, such as the North Atlantic Minimum Navigation Performance Standard (MNPS), are contained in the respective guidance material for that airspace. Incorporated within these standards are equipment characteristics that should be useful to users, designers, manufacturers and installers of the equipment. This document defines the performance functions and features for a 2D system which performs both lateral and vertical guidance. Equipment may be manufactured and tested to meet 2D or 3D requirements (or both) in the en route mode.

Section 1.0 of this document provides information needed to understand the rationale for equipment characteristics and requirements stated in the remaining sections. Typical equipment applications and operational goals are described, and these form the basis for the standards stated in Sections 2.0 through 4.0. Comments pertaining to other RNAV systems have been included for explanatory and tutorial purposes. Definitions and assumptions essential to proper understanding of this document are also provided in this section.

Section 2.0 contains the minimum performance standards for the equipment. These standards define the required performance under standard operating conditions and stressed physical environmental conditions. It also details the recommended bench test procedures necessary to demonstrate compliance.

NOTE: For those systems that have already demonstrated compliance with RTCA Document DO-164A, "Minimum Performance Standards - Airborne Omega Receiving Equipment", it is only necessary to demonstrate compliance with requirements in this document that exceed DO-164A standards.

Section 3.0 describes the performance required of the installed equipment. Tests for the installed equipment are included when performance cannot be adequately determined through bench testing.

Section 4.0 describes the operational characteristics for equipment installations and defines conditions that will assure the operator that operations can be conducted safely and reliably in the expected operational environment.

Compliance with these standards by manufacturers, installers and users is recommended as a means of assuring that the equipment will satisfactorily perform its intended function(s) under all conditions normally encountered in routine aeronautical operations.