

Manual of Petroleum Measurement Standards Chapter 8.1

Standard Practice for Manual Sampling of Petroleum and Petroleum Products

FOURTH EDITION, OCTOBER 2013



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the instructions. At all times users should employ sound business, scientific, engineering, and judgment safety when using this standard.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety datasheet.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2013 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

	Page
1	Scope 1
2	Referenced Documents 2
3	Terminology 3
4	Significance and Use 7
5	Health and Safety Precautions. 8
6	Apparatus 9
7	Sampling Devices/Equipment and Accessories 14
8	Manual Sampling Concepts and Objective 19
9	Sampling Requirements, Considerations, and Procedures 21
10	Special Instructions for Specific Products 39
11	Keywords 43
Appendix X1 (Nonmandatory Information) Crude Oil Sample Handling—Test Matrix 44	
Figures	
1	Example of a Fixed Volume Cylinder with an Outage Tube 4
2	Example of a Fixed Volume Cylinder and Transfer Line. 5
3	Examples of a Small Volume (5 cm (2 in.)) and a Large Volume PSU (10 cm (4 in.)). 5
4	Examples of Closed/Restricted Sampling Equipment 6
5	Illustration of Common Spot Sample Positions. 6
6	Typical Sample Carrier 8
7	Amber and Clear Boston Round Bottles 9
8	Example of Single Floating Piston (Variable Volume) Cylinder (FPC) 11
9	Example of Single Floating Piston (Variable Volume) Cylinder (FPC) 12
10	Example of Single Floating Piston (Variable Volume) Cylinder (FPC) 12
11	Example of Typical High-Pressure Sampling System. 13
12	Cage Samplers. 15
13	Weighted Bottle 15
14	Weighted Beakers 16
15	Example of Bottom Water and ROB/OBQ Sampler/Scraper. 16
16	Tank Sample Taps 17
17	Probe Designs 18
18	Example of Core/Interface Samplers—Thief 19
19	Example of Core/Zone Samplers. 20
20	Example of Dead Bottom Samplers 20
21	Tube Sampler 21
22	Auger Sampler 21
23	Example of Nozzle Extender 21
24	Slotted Standpipe 23
25	Examples of Sample Labels/Tags 26
26	Examples of Typical Vapor Control Valves. 29
27	Example of a Lock Valve and Closed System Sampler 30
28	Example of Closed System Restricted Flow Sampler. 30
29	Location of Sample Points at Different Levels for Rail Cars 33

30	Location of Sample Points from Exposed Surface for Rail Cars	34
31	Example of Probe in High-Pressure Sampling System Pipeline	35
32	Example of Double Piston (Variable Volume) Cylinder (DPC)	38

Tables

1	Sampling from Horizontal Cylindrical Tanks	7
2	Commonly Used Manual Sampling Devices for Liquid Products	14
3	Typical Sampling Procedures and Applicability	22
4	Recommended Weighted Sampling Bottle or Beaker Openings	27
5	Spot Sample Minimum Requirements	27
6	Tap Sampling Requirements	28
7	Minimum Number of Packages to be Selected for Sampling	32
8	Size of Grease Samples	43
X1.1	Crude Oil Sample Handling—Test Matrix	45

Standard Practice for Manual Sampling of Petroleum and Petroleum Products¹

This standard is issued under the fixed designation D4057; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

INTRODUCTION

The previous version of the manual sampling practice described the various sampling methods and apparatus, with much focus on crude oils and semi-solids and solids. Also, previous versions did not significantly address closed or restricted sampling, which continue to become more prevalent.

This version will provide guidance on manual sampling terminology, concepts, equipment, containers, procedures, and will provide some specific guidance related to particular products and tests. The type and size of the sample obtained, and the handling method, will depend on the purpose for which it was taken. Refer to the test method for any specific sampling and handling requirements up to the point of testing. It remains the responsibility of the subcommittee for the relevant test method to provide guidance, or warnings, regarding sample container selection; preparation; cleanliness; heat, pressure, or light; sample size requirements for testing and retention; and any other special handling requirements necessary to ensure a representative sample is tested.

In addition to the individual test method, for guidance on container, size, mixing and special handling, further guidance may be provided in Practice [D5854](#) (API *MPMS* Chapter 8.3), Practice [D5842](#) (API *MPMS* Chapter 8.4), and Practice [D4306](#). While this practice will provide some general guidance regarding sample chain of custody, Guide [D4840](#) should also be consulted.

This document has been developed jointly between the American Petroleum Institute (API) and ASTM International.

1. Scope

1.1 This practice covers procedures and equipment for manually obtaining samples of liquid petroleum and petroleum products, crude oils, and intermediate products from the sample point into the primary container are described. Procedures are also included for the sampling of free water and other heavy components associated with petroleum and petroleum products.

1.2 This practice also addresses the sampling of semi-liquid or solid-state petroleum products.

1.3 This practice provides additional specific information about sample container selection, preparation, and sample handling.

1.4 This practice does not cover sampling of electrical insulating oils and hydraulic fluids. If sampling is for the precise determination of volatility, use Practice [D5842](#) (API *MPMS* Chapter 8.4) in conjunction with this practice. For sample mixing and handling, refer to Practice [D5854](#) (API *MPMS* Chapter 8.3).

1.5 The procedures described in this practice may also be applicable in sampling most non-corrosive liquid industrial chemicals provided that all safety precautions specific to these chemicals are followed. Also, refer to Practice [E300](#). The procedures described in this practice are also applicable to sampling liquefied petroleum gases and chemicals. Also refer to Practices [D1265](#) and [D3700](#). The procedure for sampling bituminous materials is described in Practice [D140](#). Practice [D4306](#) provides guidance on sample containers and preparation for sampling aviation fuel.

¹ This practice is under the jurisdiction of ASTM Committee [D02](#) on Petroleum Products and Lubricants and the API Committee on Petroleum Measurement and is the direct responsibility of Subcommittee [D02.02](#) /COMQ on Hydrocarbon Measurement for Custody Transfer (Joint ASTM-API). This practice has been approved by the sponsoring committees and accepted by the Cooperating Societies in accordance with established procedures. This practice was issued as a joint ASTM-API standard in 1981.

Current edition approved Dec. 1, 2012. Published August 2013. Originally approved in 1981. Last previous edition approved in 2011 as D4057 – 06 (2011). DOI: 10.1520/D4057-12.