

# Butterfly Valves: Double-flanged, Lug- and Wafer-type

**Downstream Segment**

API STANDARD 609  
SEVENTH EDITION, OCTOBER 2009

EFFECTIVE DATE: APRIL 1, 2010



## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

*Copyright © 2009 American Petroleum Institute*

## Foreword

This standard is a purchase specification for butterfly valves designed for installation between flanges specified in ASME B16.1, ASME B16.5, ASME B16.24, and ASME B16.42, Classes 125-600; MSS SP-44, Class 150; and ASME B16.47, Series A, Class 150 (was MSS SP-44 except for certain materials) or Series B (was API 605), Class 150 for the NPS sizes defined herein.

This standard requires the purchaser to specify certain details and features. Although it is recognized that the purchaser may desire to modify, delete, or amplify sections of this standard, it is strongly recommended that such modifications, deletions, and amplifications be made by supplementing this standard, rather than by rewriting or incorporating sections thereof into another complete standard.

API standards are published as an aid to procurement of standardized equipment and materials. These standards are not intended to inhibit purchasers or producers from purchasing or producing products made to specifications other than those of API.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, [standards@api.org](mailto:standards@api.org).

## **Important Information Concerning Use of Asbestos or Alternative Materials**

Asbestos is specified or referenced for certain components of the equipment described in some API standards. It has been of extreme usefulness in minimizing fire hazards associated with petroleum processing. It has also been a universal sealing material, compatible with most refining fluid services.

Certain serious adverse health effects are associated with asbestos, among them the serious and often fatal diseases of lung cancer, asbestosis, and mesothelioma (a cancer of the chest and abdominal linings). The degree of exposure to asbestos varies with the product and the work practices involved.

Consult the most recent edition of the Occupational Safety and Health Administration (OSHA), U.S. Department of Labor, Occupational Safety and Health Standard for Asbestos, Tremolite, Anthophyllite, and Actinolite, 29 *Code of Federal Regulations* Section 1910.1001; the U.S. Environmental Protection Agency, National Emission Standard for Asbestos, 40 *Code of Federal Regulations* Sections 61.140 through 61.156; and the U.S. Environmental Protection Agency (EPA) rule on labeling requirements and phased banning of asbestos products (Sections 763.160-179).

There are currently in use and under development a number of substitute materials to replace asbestos in certain applications. Manufacturers and users are encouraged to develop and use effective substitute materials that can meet the specifications for, and operating requirements of, the equipment to which they would apply.

SAFETY AND HEALTH INFORMATION WITH RESPECT TO PARTICULAR PRODUCTS OR MATERIALS CAN BE OBTAINED FROM THE EMPLOYER, THE MANUFACTURER OR SUPPLIER OF THAT PRODUCT OR MATERIAL, OR THE MATERIAL SAFETY DATASHEET.

## Contents

	Page
<b>1</b>	<b>Scope</b> . . . . . <b>1</b>
<b>2</b>	<b>Normative References</b> . . . . . <b>1</b>
<b>3</b>	<b>Pressure-temperature Ratings</b> . . . . . <b>2</b>
<b>3.1</b>	<b>Valve Rating</b> . . . . . <b>2</b>
<b>3.2</b>	<b>Shell Rating</b> . . . . . <b>2</b>
<b>3.3</b>	<b>Seat Rating</b> . . . . . <b>2</b>
<b>4</b>	<b>Design</b> . . . . . <b>3</b>
<b>4.1</b>	<b>General</b> . . . . . <b>3</b>
<b>4.2</b>	<b>Body</b> . . . . . <b>4</b>
<b>4.3</b>	<b>Face-to-face Dimensions</b> . . . . . <b>4</b>
<b>4.4</b>	<b>Disc Clearance</b> . . . . . <b>5</b>
<b>4.5</b>	<b>Shaft and Shaft Seals</b> . . . . . <b>5</b>
<b>4.6</b>	<b>Piping Connection External Bolt Holes</b> . . . . . <b>8</b>
<b>4.7</b>	<b>Seat Retainer—Category B Valves Only</b> . . . . . <b>8</b>
<b>4.8</b>	<b>Operating Mechanisms</b> . . . . . <b>11</b>
<b>4.9</b>	<b>Electrical Continuity</b> . . . . . <b>11</b>
<b>4.10</b>	<b>Packing Gland Bolting—Category B Valves Only</b> . . . . . <b>11</b>
<b>5</b>	<b>Materials</b> . . . . . <b>11</b>
<b>5.1</b>	<b>Body</b> . . . . . <b>11</b>
<b>5.2</b>	<b>Trim</b> . . . . . <b>11</b>
<b>5.3</b>	<b>Seat Retainer—Category B Valves Only</b> . . . . . <b>12</b>
<b>5.4</b>	<b>Packing or Shaft Seal Materials</b> . . . . . <b>12</b>
<b>5.5</b>	<b>Gland Bolting</b> . . . . . <b>12</b>
<b>5.6</b>	<b>Operating Mechanisms—Category B Valves Only</b> . . . . . <b>12</b>
<b>6</b>	<b>Examination, Inspection, and Testing</b> . . . . . <b>12</b>
<b>6.1</b>	<b>Examination Requirements</b> . . . . . <b>12</b>
<b>6.2</b>	<b>Inspection by the Purchaser</b> . . . . . <b>12</b>
<b>6.3</b>	<b>Pressure Tests</b> . . . . . <b>12</b>
<b>6.4</b>	<b>Repair of Defects</b> . . . . . <b>12</b>
<b>7</b>	<b>Markings</b> . . . . . <b>13</b>
<b>8</b>	<b>Packaging and Shipping</b> . . . . . <b>13</b>
<b>8.1</b>	<b>Coatings</b> . . . . . <b>13</b>
<b>8.2</b>	<b>Shaft Packing</b> . . . . . <b>13</b>
<b>8.3</b>	<b>Packaging</b> . . . . . <b>14</b>
<b>8.4</b>	<b>Recommended Spare Parts</b> . . . . . <b>14</b>
	<b>Annex A (normative) Disc-to-pipe Clearances</b> . . . . . <b>15</b>
	<b>Annex B (normative) Information to be Specified by Purchaser</b> . . . . . <b>19</b>
<b>Figures</b>	
<b>1</b>	<b>External Bolting Options for Lug- and Wafer-type Valves</b> . . . . . <b>9</b>
<b>2</b>	<b>Limitations for Flange Face Interruptions that Fall Within the Gasket Seating Area (NPS 6 through NPS 48)</b> . . . . . <b>10</b>
<b>A.1</b>	<b>Dimensional Locations for Concentric-type Construction (Category A)</b> . . . . . <b>16</b>
<b>A.2</b>	<b>Nomenclature and Explanation of Offset-seat-type Construction (Category B)</b> . . . . . <b>17</b>

**A.3 Relationship of Unlined Steel Pipe Schedules to Valve Category, Size, and ASME Class..... 18**

**Tables**

**1 Minimum Seat Pressure-temperature Ratings for Category B Valves with PTFE or RPTFE Seats..... 3**  
**2 Face-to-face Dimensions for Category A Valves (Lug- and Wafer-type) ..... 5**  
**3 Face-to-face Dimensions for Category B Valves ..... 6**  
**A.1 Nominal Radial Clearances ..... 15**

# Butterfly Valves: Double-flanged, Lug- and Wafer-type

## 1 Scope

1.1 This standard covers design, materials, face-to-face dimensions, pressure-temperature ratings, and examination, inspection and test requirements for gray iron, ductile iron, bronze, steel, nickel-based alloy, or special alloy butterfly valves that provide tight shutoff in the closed position. The following two categories of butterfly valves are included.

- a) Category A—Manufacturer's rated cold working pressure (CWP) butterfly valves, usually with a concentric disc and seat configuration. Sizes covered are NPS 2 to NPS 48 for valves having ASME Class 125 or Class 150 flange bolting patterns.
- b) Category B—ASME Class and pressure-temperature rated butterfly valves that have an offset seat and either an eccentric or a concentric disc configuration. These valves may have a seat rating less than the body rating. For lug and wafer, Class 150, 300, and 600, sizes covered are NPS 3 to NPS 24. For double-flanged long pattern, Class 150, 300, and 600, sizes covered are NPS 3 to NPS 36. For double-flanged short pattern, Class 150 and 300, sizes covered are NPS 3 to NPS 48. For double-flanged short pattern, Class 600, sizes covered are NPS 3 to NPS 24.

1.2 Valve configurations include double-flanged, lug- and wafer-types with facings that permit installation between ASME and MSS flanges that conform to the standards and specifications listed in Section 2.

## 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. Text in brackets after a publication title indicates a restriction on the classes to which the publication applies.

API Standard 598, *Valve Inspection and Testing*

API Standard 607, *Fire Test for Soft-seated Quarter-turn Valves*

ASME B1.1<sup>1</sup>, *Unified Inch Screw Threads* [UN and UNR Thread Form]

ASME B16.1, *Gray Iron Pipe Flanges and Flanged Fittings* [Classes 25, 125, and 250]

ASME B16.5, *Pipe Flanges and Flanged Fittings* [NPS 1/2 through NPS 24 Metric/Inch Standard]

ASME B16.20, *Metallic Gaskets for Pipe Flanges—Ring-Joint, Spiral-Wound, and Jacketed*

ASME B16.24, *Cast Copper Alloy Pipe Flanges and Flanged Fittings* [Classes 150, 300, 600, 900, 1500 and 2500]

ASME B16.34, *Valves—Flanged, Threaded, and Welding End* [Standard Class 150, 300, and 600 only]

ASME B16.42, *Ductile Iron Pipe Flanges and Flanged Fittings* [Class 150 and 300]

ASME B16.47, *Large Diameter Steel Flanges: NPS 26 Through NPS 60* [Class 150 only]

ASME B31.3, *Process Piping*

---

<sup>1</sup> ASME International, 3 Park Avenue, New York, New York 10016-5990, [www.asme.org](http://www.asme.org).