

Recommended Practice on Procedures for Testing Casing and Tubing Connections

ANSI/API RECOMMENDED PRACTICE 5C5
THIRD EDITION, JULY 2003

REAFFIRMED, AUGUST 2010

**ISO 13679:2002 (Identical), Petroleum and natural
gas industries—Procedures for testing casing and
tubing connections**



AMERICAN PETROLEUM INSTITUTE



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication date as an operative API standard or, where an extension has been granted, upon republication. Status of the publication can be ascertained from the API Upstream Segment, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the general manager of the Upstream Segment, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

Copyright © 2003 American Petroleum Institute

API Foreword

This standard is under the jurisdiction of the API Standards Subcommittee on Tubular Goods (API C1/SC5). This API standard is identical with the English version of ISO 13679:2002. ISO 13679 was prepared by Technical Committee ISO/TC 67, Materials, equipment and offshore structures for petroleum and natural gas industries, SC 5, Casing, Tubing, and Drilling Pipe.

This standard shall become effective on the date printed on the cover but may be used voluntarily from the date of publication.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to the Upstream Segment, API, 1220 L Street, NW, Washington, DC 20005.

Contents

Page

API Foreword	ii
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	2
3.1 Terms and definitions	2
3.2 Symbols and abbreviated terms	4
4 General requirements	8
4.1 Connection geometry, test load envelope and performance data sheet	8
4.2 Quality control	9
5 General test requirements	9
5.1 Test classes	9
5.2 Test matrix	10
5.3 Test programme	14
5.4 Calibration and accreditation requirements	15
5.5 Rehearsal tests	16
5.6 Material property tests	16
5.7 Make-up and break-out procedures	17
5.8 Internal pressure leak detection	18
5.9 Internal pressure leak trap device	18
5.10 External pressure leak detection	25
5.11 Data acquisition and test methods	28
5.12 Thermal cycling tests	30
6 Connection test specimen preparation	32
6.1 General connection test objectives	32
6.2 Connection test specimen identification and marking	33
6.3 Connection test specimen preparation	33
6.4 Connection test specimen machining	35
6.5 Machining tolerances	36
6.6 Tolerance limits on machining objectives	37
6.7 Grooved torque shoulder	37
7 Test procedures	38
7.1 Principle	38
7.2 Make-up/break-out tests	38
7.3 Test load envelope tests	40
7.4 Limit load tests	52
7.5 Limit load test path (see Figures 18 and 19)	55
8 Acceptance criteria	57
8.1 Make-up and break-out tests	57
8.2 Test load envelope tests	58
8.3 Limit load tests	58
9 Test reports	59
Annex A (normative) Connection geometry and performance data sheet	60
Annex B (informative) Connection test load envelope and limit loads	67
Annex C (normative) Data forms	85

Annex D (normative) Connection full test report	115
Annex E (normative) Connection testing summary report.....	118
Annex F (informative) Frame load range determination	121
Annex G (informative) Interpolation and extrapolation considerations	122
Annex H (informative) Special application testing	124
Annex I (informative) Rationale for design basis	130
Annex J (normative) Independent seal testing of connections with metal-to-metal and resilient seals.....	133
Bibliography.....	139
Table 1 — Test matrix — Test series and specimen identification numbers.....	11
Table 2 — Connection test specimen objectives for all CAL.....	32
Table 3 — Guidelines for selecting connection test specimens for testing a metal-to-metal sealing, tapered thread connection with a torque shoulder.....	33
Table 4 — Tolerance limits on machining objectives.....	36
Table 5 — Specimen description and summary of test series for a metal-to-metal sealing, tapered thread connection with a torque shoulder	38
Table 6 — Test Series A load steps (see Figures 13 or 14, as applicable) — Testing in quadrants I, II, III, IV (no bending) at ambient temperature	42
Table 7 — Test Series B load steps without bending for connection rated equal to pipe body (see Figure 15) — Testing in quadrants I and II without bending at ambient temperature	46
Table 8 — Test Series B load steps with bending for connection rated equal to pipe body (see Figure 16) — Testing in quadrants I and II with bending at ambient temperature	47
Table A.1 — Connection geometry and performance property data sheet.....	61
Table A.2 — Example Series A test load envelope for a connection rated equal to pipe body — 178 mm <i>D</i> × 10,16 mm wall thickness × grade P-110 (7 in 29 lb/ft P-110) strength (see Figure A.1).....	62
Table A.3 — Detailed load steps	63
Table B.1 — Areas and dimensions	70
Table B.2 — Required dimensions for critical cross-section computation	84
Table F.1 — Typical results from frame load range determination (200 kN to 2 000 kN).....	121
Figure 1 — Connection application level test programme.....	12
Figure 2 — Collared leak trap device for internal pressure leak detection	19
Figure 3 — Flexible boot leak trap device for internal pressure leak detection	20
Figure 4 — Ported box leak trap device for internal pressure leak detection.....	20
Figure 5 — Internal pressure leak detection by bubble method	22
Figure 6 — Example of a plot for determining leak detection sensitivity.....	23
Figure 7 — Leak detection by helium mass spectrometer method	24
Figure 8 — Example set-up for Test Series A	25

Figure 9 — Example of leak detection system for Test Series A..... 26

Figure 10 — Test Series C thermal/mechanical cycles for CAL II, III, and IV..... 30

Figure 11 — Connection test specimen nomenclature and unsupported length 34

Figure 12 — Torque shoulder pressure bypassing grooves..... 37

**Figure 13 — Test Series A load path for connection rated greater than or equal to pipe body
in compression..... 44**

Figure 14 — Test Series A load path for connection rated less than pipe body in compression 45

Figure 15 — Test Series B load paths without bending for connection rated equal to pipe body..... 49

Figure 16 — Test Series B load paths with bending for connection rated equal to pipe body 50

**Figure 17 — Test Series B load paths for connection rated less than pipe body in compression
and with bending..... 51**

Figure 18 — Limit load test paths for connections rated equal to or stronger than pipe body 53

Figure 19 — Limit load test paths for connections weaker than pipe body 54

Figure B.1 — Pipe body and connection test load envelopes at specified dimensions 68

Figure C.1 — Recommended layout of mother joints for test and material specimens..... 86

Figure G.1 — Example premium connection design space 123

**Figure J.1 — Ported box leak trap device for internal pressure leak detection showing
modifications for resilient seal 135**

Figure J.2 — Connection acceptance levels with resilient seal ring..... 136

**Figure J.3 — Alternative testing sequence for a connection with metal-to-metal (MTM) and
resilient seal (RS) features 138**

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13679 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 5, *Casing, tubing and drill pipe*.

Introduction

This International Standard is part of a process to provide reliable tubing and casing connections for the oil and natural gas industry which are fit for purpose. It has been developed based on improvements to API Recommended Practice 5C5 and proprietary test procedures, with input from leading users, manufacturers and testing consultants from around the world. This International Standard represents the knowledge of many years of testing and qualification experiences.

The validation of connection test load envelope and failure limit loads is relevant to design of tubing and casing for the oil and natural gas industries. Tubing and casing are subject to loads which include internal pressure, external pressure, axial tension, axial compression, bending, torsion, transverse forces and temperature changes. The magnitude and combination of these loads result in various pipe body and connection failure modes. Although pipe body test and limit loads are well understood in general, the same cannot be stated for the connection. These failure modes and loads are generally different and often less than that of the pipe. Consequently experimental validation is required. Well design matches the test and limit loads of both the connection and pipe to the well conditions to provide load capacities with suitable reliability.

The validation of test and limit loads requires testing at the extremes of performance parameters to these defined loads. Testing at the extremes of the performance parameters assures that the production population, which falls within these limits, will meet or exceed the performance of the test population. Thread connection performance parameters include dimensional tolerances, mechanical properties, surface treatment, make-up torque and the type and amount of thread compound. For typical proprietary connections, worst-case tolerances are known and defined in this International Standard. For other connections design analysis is required to define worst-case tolerance combinations.

Users of this International Standard should be aware that further or differing requirements might be needed for individual applications. This International Standard is not intended to inhibit a vendor from offering, or a purchaser from accepting, alternate equipment or engineering solutions for the individual application. This may be particularly applicable when there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this International Standard and provide details.

This International Standard consists of the following major parts. Based on manufacturer's-supplied data specified in Annex A and/or calculations in Annex B, tests are conducted in accordance with Clauses 4 to 8 and reported on the data forms given in Annex C. Annex D lists all the information that is to be provided in the full report whereas Annex E lists the information that is to be provided in a summary test report. This summary test report lists the minimum information necessary to fully specify the connection tested and its preparation is intended for broader distribution. Annex F gives an example of a load frame calibration. Annex G gives considerations for possible connection product line qualification. Annex H provides guidelines for supplemental tests, which may be required for special applications. Annex I gives the design rationale for this International Standard. Annex J gives requirements for connections that contain both a metal-to-metal seal and a resilient seal which are tested separately.

Supplementary tests may be appropriate for specific applications that are not evaluated by the tests herein. The user and manufacturer should discuss well applications and limitations of the connection being considered.

Representatives of users and/or other third party personnel are encouraged to monitor the tests. ISO 13679 covers the testing of connections for the most commonly encountered well conditions. Not all possible service scenarios are included. For example, the presence of a corrosive fluid, which may influence the service performance of a connection, is not considered.

This International Standard includes provisions of various nature. These are identified by the use of certain verbal forms:

— SHALL is used to indicate that a provision is a REQUIREMENT, i.e. MANDATORY;

- SHOULD is used to indicate that a provision is a RECOMMENDATION to be used as good practice, but is not mandatory;
- MAY is used to indicate that a provision is OPTIONAL, i.e. indicates a course of action permissible within the limits of the document;
- CAN is used to indicate statements of POSSIBILITY and CAPABILITY.

Petroleum and natural gas industries — Procedures for testing casing and tubing connections

1 Scope

This International Standard establishes minimum design verification testing procedures and acceptance criteria for casing and tubing connections for the oil and natural gas industries. These physical tests are part of a design verification process and provide objective evidence that the connection conforms to the manufacturer's claimed test load envelope and limit loads.

It categorizes test severity into four test classes.

It describes a system of identification codes for connections.

This International Standard does not provide the statistical basis for risk analysis.

This International Standard addresses only three of the five distinct types of primary loads to which casing and tubing strings are subjected in wells: fluid pressure (internal and/or external), axial force (tension or compression), bending (buckling and/or wellbore deviation), as well as make-up torsion. It does not address rotation torsion and non-axisymmetric (area, line or point contact) loads.

This International Standard specifies tests to be performed to determine the galling tendency, sealing performance and structural integrity of casing and tubing connections. The words casing and tubing apply to the service application and not to the diameter of the pipe.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3183-1, *Petroleum and natural gas industries — Steel pipe for pipelines — Technical delivery conditions — Part 1: Pipes of requirement class A*

ISO 3183-2, *Petroleum and natural gas industries — Steel pipe for pipelines — Technical delivery conditions — Part 2: Pipes of requirements class B*

ISO 3183-3, *Petroleum and natural gas industries — Steel pipe for pipelines — Technical delivery conditions — Part 3: Pipes of requirement class C*

ISO 10400:1993, *Petroleum and natural gas industries — Formulae and calculation for casing, tubing, drill pipe, and line pipe properties*

ISO 10422, *Petroleum and natural gas industries — Threading, gauging and thread inspection of casing, tubing and line pipe threads*

ISO 11960, *Petroleum and natural gas industries — Steel pipes for use as casing or tubing for wells*

ISO 13680, *Petroleum and natural gas industries — Corrosion-resistant alloy seamless tubes for use as casing, tubing and coupling stock — Technical delivery conditions*