

Fabrication Considerations for Vanadium-Modified Cr-Mo Steel Heavy Wall Pressure Vessels

API TECHNICAL REPORT 934-B
FIRST EDITION, APRIL 2011



AMERICAN PETROLEUM INSTITUTE

Fabrication Considerations for Vanadium-Modified Cr-Mo Steel Heavy Wall Pressure Vessels

Downstream Segment

API TECHNICAL REPORT 934-B
FIRST EDITION, APRIL 2011



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2011 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Status of publications can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

| | Page |
|---|-----------|
| 1 Scope | 1 |
| 2 Normative References | 1 |
| 3 Definitions and Acronyms | 2 |
| 3.1 Definitions | 2 |
| 3.2 Acronyms | 3 |
| 4 Design and Fabrication | 4 |
| 4.1 Background | 4 |
| 4.2 Identified Fabrication Problems | 4 |
| 4.3 Code References and Design Allowables | 8 |
| 4.4 Incorporation Into API 941 | 10 |
| 4.5 Additional Characteristics | 11 |
| 4.6 Metallurgical Concerns During Fabrication | 11 |
| 4.7 Best Practices for Fabricating V-Modified 2¹/₄Cr-1Mo Vessels | 15 |
| 5 Assessment of Fabricators | 18 |
| 5.1 Current Worldwide Fabrication Capability | 18 |
| 5.2 Approving New Fabricators | 18 |
| Annex A (informative) SAMPLE Fabrication Plan | 22 |
| Annex B (informative) Example of a Detailed Fabrication Plan | 23 |
| Annex C (informative) Sample Fabrication Schedule | 27 |
| Bibliography | 28 |
| Figures | |
| 1 Charpy V-Notch Toughness of Conventional and Vanadium-modified 2¹/₄Cr-1Mo Deposited Weld Metal after DHT and ISR Heat Treatment | 6 |
| 2 Vanadium Content versus Creep Rupture of Cr-1Mo-V Steels | 11 |
| 3 Typical Conventional and Vanadium-modified 2¹/₄Cr-1Mo Weld Metal Hardness After Various Heat Treatments | 13 |
| 4 Diffusible Hydrogen Test Results for 2¹/₄Cr-1Mo Weld Metal | 13 |
| 5 Charpy V-Notch Toughness of Vanadium-modified 2¹/₄Cr-1Mo Deposited Weld Metal after ISR Using a Second Alternative Wire Flux Combination | 15 |
| A.1 Sample Fabrication Plan | 22 |
| Tables | |
| 1 Typical Properties of Materials of Construction | 9 |
| 2 Toughness Properties of Vanadium-modified Sub-Arc Weld Metal as Function of Heat Treatment Condition | 15 |
| 3 Point System for Evaluating New Fabricators | 19 |
| B.1 Example Construction Schedule | 23 |

Introduction

This document is intended as a best practice guideline to be used by fabricators, in conjunction with API 934-A, when constructing new heavy wall pressure vessels with vanadium-modified Cr-Mo steels intended for service in petroleum refining, petrochemical, or chemical facilities. These materials are primarily used in high temperature, high pressure services which contain hydrogen.

The document provides typical practices to be followed during fabrication based upon experience and the knowledge gained from actual problems that have occurred during the fabrication of vanadium-modified Cr-Mo steels.

Background

The use of chrome-molybdenum steel vessels in hydrogen service can be traced back to the mid 1920s in Germany where they were used for reactors in high pressure hydrogenation plants. These vessels were fabricated from 2.25 % to 3.8 % chrome-molybdenum alloys operating in the pressure range of 28 to 70 MPa (4000 to 10,000 psi). [1] These steels are now referred to as the "First Generation" technology and were in use until the mid 1960s. The steels have evolved with significant improvements in each generation that can be summarized as follows.

Second Generation (Mid 1960s to 1970s) The birth of modern hydroprocessing reactors manufactured from heavy wall 2¹/₄Cr-1Mo alloys with improved toughness (54 Joules at 10 °C [40 ft-lbs at 50 °F]), but with no particular temper embrittlement controls.

Third Generation (1970s to 1980s) Added J-factor limit of 180 to control temper embrittlement and developed improved toughness to 54 Joules at -18 °C (40 ft-lbs at 0 °F). Also, began step cooling tests with varying criteria, and precautions against weld overlay disbondment.

Fourth Generation (1980s to 1990s) Improved temper embrittlement control by lowering J-factor limit to 100 and achieving better results after step cooling. This generation also had toughness improvements to 54 Joules at -32 °C (40 ft-lbs at -25 °F)

Today "Fifth Generation" grades [2] of conventional 2¹/₄Cr-1Mo steels have a 54-Joule (40 ft-lb) transition temperature typically lower than -40 °C (-40 °F), and even lower for conventional 3Cr-1Mo steels. Vanadium-modified Cr-Mo steels with 2¹/₄ % and 3 % Cr were introduced for service with higher strength levels and increased hydrogen attack resistance. These grades achieved a 54 Joule (40 ft-lb) transition temperature typically around -29 °C (-20 °F). The vanadium-modified steels also offered enhanced creep rupture properties, lower temper embrittlement susceptibility, and a much lower susceptibility to hydrogen disbonding of weld overlay compared with conventional Cr-Mo steels.

As of 2009, over four hundred vanadium-modified reactors have been fabricated around the world with many more under construction.

Fabrication Considerations for Vanadium-Modified Cr-Mo Steel Heavy Wall Pressure Vessels

1 Scope

This best practice report complements API 934-A and specifies additional fabrication considerations that should be observed when constructing a new heavy wall pressure vessel using vanadium-modified Cr-Mo materials intended for hydrogen service at elevated temperature and pressure. It applies to vessels that are designed, fabricated, certified and documented in accordance with ASME Code Section VIII, Division 2, including Paragraph 3.4 of the ASME Code, Supplemental Requirements for Cr-Mo Steels and ASME Code Case 2151, as applicable (or equivalent international codes).

Nominal material chemistries covered by this report are the vanadium-modified steels including 2¹/₄Cr-1Mo-¹/₄V, 3Cr-1Mo-¹/₄V-Ti-B, and 3Cr-1Mo-¹/₄V-Cb-Ca steels. The interior surfaces of these vessels may have an austenitic stainless steel cladding or weld overlay to provide additional corrosion resistance.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Recommended Practice 582, *Welding Guidelines for the Chemical, Oil, and Gas Industries*

API Recommended Practice 934-A, *Materials and Fabrication Requirements for 2¹/₄Cr-1Mo & 3Cr-1Mo Steel Heavy Wall Pressure Vessels for High Temperature, High Pressure Hydrogen Service*

API Recommended Practice 941, *Steels for Hydrogen Service at Elevated Temperatures and Pressures in Petroleum Refineries and Petrochemical Plants*

ASME Boiler and Pressure Vessel Code ¹, *Section II, Materials, Part A, Ferrous Material Specifications*

ASME Boiler and Pressure Vessel Code, *Section II, Materials, Part C, Specifications for Welding Rods, Electrodes and Filler Metals*

ASME Boiler and Pressure Vessel Code *Section II, Materials, Part D, Properties*

ASME Boiler and Pressure Vessel Code *Section VIII, Div. 2 Rules for Construction of Pressure Vessels – Alternate Rules*

ASME SA 20, *Specification for General Requirements for Steel Plates for Pressure Vessels*

ASME SA 182, *Specification for Forged or Rolled Alloy Steel Pipe Flanges, Forged Fittings, and Valves and Parts for High-Temperature Service*

ASME SA 335, *Specification for Seamless Ferritic Alloy-Steel Pipe for High-Temperature Service*

ASME SA 336, *Specification for Alloy Steel Forgings for Pressure and High-Temperature Parts*

ASME SA 369, *Specification for Carbon and Ferritic Alloy Steel Forged and Bored Pipe for High Temperature Service*

¹ ASME International, 3 Park Avenue, New York, New York 10016-5990, www.asme.org.