

Recommended Practice for Testing Well Cements

API RECOMMENDED PRACTICE 10B-2
SECOND EDITION, APRIL 2013

REAFFIRMED, APRIL 2019



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this Recommended Practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2013 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

Page

1	Scope	1
2	Normative References	1
3	Terms, Definitions, and Symbols	1
3.1	Terms and Definitions	1
3.2	Symbols	7
4	Sampling	9
4.1	General	9
4.2	Sampling Cement at a Field Location	9
4.3	Sampling Cement Blends at a Blending Facility	9
4.4	Sampling Dry Cement Additives	9
4.5	Sampling Liquid Cement Additives	9
4.6	Sampling Mixing Water	9
4.7	Shipping and Storage	9
4.8	Sample Preparation Prior to Testing	11
4.9	Sample Disposal	11
5	Preparation of Slurry	11
5.1	General	11
5.2	Apparatus	11
5.3	Procedure	13
5.4	Test Fluid Conditioning	21
6	Determination of Slurry Density	22
6.1	Apparatus	22
6.2	Procedure	22
7	Well-simulation Compressive-strength Tests	24
7.1	General	24
7.2	Sampling	24
7.3	Apparatus	24
7.4	Procedure	25
7.5	Determination of Cement Compressive Strength at the Top of a Long Cement Column	28
8	Non-destructive Sonic Determination of Compressive Strength of Cement	34
8.1	General	34
8.2	Apparatus	34
8.3	Sampling	34
8.4	Preparation of Slurry	34
8.5	Procedure	34
8.6	Curing Time	34
8.7	Curing Schedules	34
8.8	Data Reporting	35
9	Well-simulation Thickening Time Tests	35
9.1	General	35
9.2	Apparatus and Material	35
9.3	Test Procedure	37
9.4	Determination of Test Schedule	39

Contents

	Page
10 Static Fluid-loss Tests	48
10.1 General	48
10.2 Apparatus	49
10.3 Safety	50
10.4 Performing Static Fluid-loss Test Using Non-stirred Fluid-loss Cell.	50
10.5 Performing a Static Fluid-loss Test Using Stirred Fluid-loss Apparatus	54
10.6 Fluid-loss Results and Reporting	57
11 Determination of Rheological Properties and Gel Strength Using a Rotational Viscometer	59
11.1 General	59
11.2 Apparatus	59
11.3 Calibration	63
11.4 Determination of Rheological Properties	63
11.5 Determination of Gel Strength	65
11.6 Characterization of Rheological Behavior	65
12 Well-simulation Slurry Stability Tests	66
12.1 Introduction	66
12.2 Slurry Mixing and Conditioning	66
12.3 Free-fluid Test with Heated Static Period	66
12.4 Free-fluid Test with Static Period at Ambient Temperature	70
12.5 Sedimentation Test	70
13 Compatibility of Wellbore Fluids	75
13.1 General	75
13.2 Preparation of Test Fluids	75
13.3 Rheological Properties	77
13.4 Thickening Time	78
13.5 Compressive Strength	78
13.6 Solids Suspension and Static Gel Strength	78
13.7 Spacer Surfactant Screening Test (SSST)	80
13.8 Interpretation	82
14 Pozzolans	84
14.1 General	84
14.2 Types of Pozzolan	85
14.3 Physical and Chemical Properties	85
14.4 Slurry Calculations	86
14.5 Bulk Volume of a Blend.	88
15 Test Procedure for Arctic Cementing Slurries	88
15.1 General	88
15.2 Preparation of Cement Slurry	88
15.3 Fluid Fraction	88
15.4 Thickening Time	89
15.5 Compressive Strength	89
15.6 Strength After Freeze-thaw Cycling at Atmospheric Pressure	89

Contents

Page

Annex A (normative) Procedure for Preparation of Large Slurry Volumes	91
Annex B (normative) Calibration and Verification of Well Cement Testing Equipment	93
Annex C (normative) Alternative Apparatus for Well-simulation Thickening-time Tests	106
Annex D (informative) Cementing Temperatures and Schedules	109
Bibliography	111

Figures

1 Commonly Used Sampling Devices	10
2 Example of Common Mixing Device	12
3 Common Blade Assembly	12
4 Common Pressurized Fluid Density Balance	23
5 Common Pressurized Fluid Density Balance	24
6 Diagram of Mold Preparation	27
7 Typical Pressurized Consistometer	37
8 Typical Hesitation Squeeze Pressure and Temperature Schedule	46
9 Common High-temperature, High-pressure, Nonstirred Fluid-loss Cell Bodies	51
10 Common Screwed-cap Type, High-temperature, High-pressure, Double-ended Fluid-loss Cell	51
11 Common Stirred Fluid-loss Apparatus	54
12 Cell and Components of Common Stirred Fluid-loss Apparatus	55
13 Typical Rotational Viscometer Schematic	60
14 Rotor and Bob Dimensions (R1-B1)	61
15 Typical Sedimentation Tube	71
16 Compatibility Testing Flowchart	76
17 Typical Conductivity Titration vs Fresh Water Spacer Volume Percent in SSST Apparatus	84
A.1 Example of a Common Cement-mixing Device for Large Volumes	91
B.1 Worn Blade (right) Compared to a New One (left)	97
B.2 Common Calibrating Device for Pressurized Consistometer Potentiometer	102
B.3 Fixture for Calibration of Upper Density Range	104
C.1 Alternative Consistometer Design for Well-Simulation Thickening Time, Example 1	107
C.2 Alternative Consistometer Design for Well-simulation Thickening Time, Example 2	108

Tables

1 Symbols	7
2 Well-simulation Test Schedules for Curing Compressive Strength Specimens (SI)	30
3 Well-simulation Test Schedules for Curing Compressive Strength Specimens (USC)	32
4 Vapor Pressure and Volume Expansion of Water at Temperatures Between 100 °C (212 °F) and 316 °C (600 °F)	52
5 Fluid-loss Results Reporting Form	58
6 Dimensions of Rotors and Bobs	60
7 Shear Rate for Rotor-Bob Combinations	62
8 Shear Stress per Degree of Dial Deflection	62

Contents

	Page
9	Maximum Shear Stress for Various Configurations (300° Maximum Deflection) 62
10	Example Rheological Data Report. 64
11	Optional Free Fluid and Sedimentation Results-report Form 73
12	Mixtures for Testing. 77
13	Rheological Compatibility of Mud, Cement Slurry, and Spacer. 79
B.1	Equipment Calibration Requirements. 93
B.2	Calibration and Verification of Well Cement Testing Equipment. 94
B.3	Rheometer Calibration 100
B.4	Slurry Consistency vs Equivalent Torque (for Potentiometer with Radius of 52 mm ±1 mm) 102
D.1	T_{PBHC} for Casing and Liner Well-simulation Tests 109
D.2	T_{PSP} for Squeeze-cementing Well-simulation Tests 110

Introduction

Users of this standard should be aware that further or differing requirements may be needed for individual applications. This standard is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this standard and provide details.

In this standard, where practical, U.S. customary units (USC) are included in brackets for information. The units do not necessarily represent a direct conversion of metric units (SI) to USC units, or USC to SI. Consideration has been given to the precision of the instrument making the measurement. For example, thermometers are typically marked in one degree increments, thus temperature values have been rounded to the nearest degree.

In this standard, calibrating an instrument refers to assuring the accuracy of the measurement. Accuracy is the degree of conformity of a measurement of a quantity to its actual or true value. Accuracy is related to precision, or reproducibility of a measurement. Precision is the degree to which further measurements or calculations will show the same or similar results. Precision is characterized in terms of the standard deviation of the measurement. The results of calculations or a measurement can be accurate, but not precise, precise but not accurate, neither and both. A result is valid if it is both accurate and precise.

Well cement classes and grades are defined in API Specification 10A.

Warning—The tests specified in this standard require the handling of hot, pressurized equipment and materials that may be hazardous and can cause injury. Do not exceed manufacturer's safety limits. Only trained personnel should perform these tests.

Recommended Practice for Testing Well Cements

1 Scope

This standard specifies methods and gives recommendations for the testing of cement slurries and related materials under simulated well conditions.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Specification 10A, *Specification for Cements and Materials for Well Cementing*

API Recommended Practice 13B-1, *Recommended Practice for Field Testing Water-based Drilling Fluids*

API Recommended Practice 13B-2, *Recommended Practice for Field Testing Oil-based Drilling Fluids*

API Recommended Practice 13J, *Testing of Heavy Brines*

ASTM C109/C109M-07¹, *Standard Test Method for Compressive Strength of Hydraulic Cement Mortars (Using 2 in. or [50 mm] Cube Specimens)*

ASTM C188-95, *Standard Test Method for Density of Hydraulic Cement*

ASTM C618-08, *Standard Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use in Concrete*

3 Terms, Definitions, and Symbols

3.1 Terms and Definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

absolute density

Density of a material without the fluid around the particles, similar to the relative density and can be obtained by multiplying the relative density of a material by the density of water at 4 °C, 1000 kg/m³ (8.345 lbm/gal).

3.1.2

absolute volume

The volume occupied by a material, not including the intergranular space in the case of a solid.

3.1.3

additive

Material incorporated in a cement slurry to modify or enhance some desired property.

¹ ASTM International, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428, www.astm.org.