

General-Purpose Gear Units for Petroleum, Chemical and Gas Industry Services

API STANDARD 677
THIRD EDITION, APRIL 2006

REAFFIRMED, NOVEMBER 2016



AMERICAN PETROLEUM INSTITUTE

General-Purpose Gear Units for Petroleum, Chemical and Gas Industry Services

Downstream Segment

API STANDARD 677
THIRD EDITION, APRIL 2006

REAFFIRMED, NOVEMBER 2016



AMERICAN PETROLEUM INSTITUTE

SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

FOREWORD

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

Suggested revisions are invited and should be submitted to the Standards and Publications Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

CONTENTS

| | Page |
|---|------|
| 1 GENERAL..... | 1 |
| 1.1 Scope | 1 |
| 1.2 Alternative Designs | 1 |
| 1.3 Conflicting Requirements | 1 |
| 1.4 Definition of Terms | 1 |
| 1.5 Referenced Publications | 2 |
| 1.6 Dimensions..... | 3 |
| 2 BASIC DESIGN | 3 |
| 2.1 General..... | 3 |
| 2.2 Shaft Assembly Designation | 5 |
| 2.3 Shaft Rotation | 6 |
| 2.4 Rating..... | 6 |
| 2.5 Casings..... | 14 |
| 2.6 Casing Connections..... | 16 |
| 2.7 Gear Elements | 17 |
| 2.8 Dynamics | 19 |
| 2.9 Bearings and Bearing Housings | 22 |
| 2.10 Lubrication..... | 24 |
| 2.11 Materials..... | 24 |
| 2.12 Nameplates and Rotation Arrows | 25 |
| 3 ACCESSORIES..... | 26 |
| 3.1 General..... | 26 |
| 3.2 Couplings and Guards | 26 |
| 3.3 Mounting Plates | 26 |
| 3.4 Controls and Instrumentation | 28 |
| 3.5 Piping and Appurtenances..... | 28 |
| 3.6 Special Tools | 28 |
| 4 INSPECTION, TESTING, AND PREPARATION FOR SHIPMENT | 28 |
| 4.1 General..... | 28 |
| 4.2 Inspection..... | 29 |
| 4.3 Testing | 31 |
| 4.4 Preparation for Shipment..... | 33 |
| 5 VENDOR'S DATA..... | 34 |
| 5.1 General..... | 34 |
| 5.2 Proposals | 34 |
| 5.3 Contract Data..... | 35 |
| APPENDIX A GENERAL-PURPOSE GEAR DATA SHEETS | 37 |
| APPENDIX B LATERAL CRITICAL SPEED MAP AND MODE SHAPES FOR A TYPICAL ROTOR..... | 53 |
| APPENDIX C TYPICAL LUBE-OIL SYSTEMS..... | 57 |
| APPENDIX D MATERIAL SPECIFICATIONS FOR GENERAL-PURPOSE GEAR UNITS | 61 |
| APPENDIX E VENDOR DRAWING AND DATA REQUIREMENTS | 65 |
| APPENDIX F REFERENCED SPECIFICATIONS | 73 |

| | | |
|------------|--|----|
| APPENDIX G | SPIRAL BEVEL GEAR-TOOTH CONTACT ARRANGEMENT REQUIREMENTS FOR INSPECTION | 75 |
| APPENDIX H | RESIDUAL UNBALANCE WORKSHEETS | 85 |

Figures

| | | |
|-----|--|----|
| 1 | Shaft Assembly Designations | 7 |
| 2 | Shaft Rotation Designations | 8 |
| 3 | Material Index Number, Through Hardened | 11 |
| 4 | Allowable Bending Stress Number, S_a | 12 |
| B-1 | Lateral Critical Speed Map for a Typical Rotor | 54 |
| B-2 | Mode Shapes versus Support Stiffness for a Typical Rotor | 55 |
| C-1 | Typical Circulating Lube-oil System for Gear Units | 59 |
| C-2 | Typical Pressurized Lube-oil System for Hydrodynamic Bearings in Gear Units | 60 |
| G-1 | Gear-tooth Nomenclature | 75 |
| G-2 | Determining Mounting Distances | 76 |
| G-3 | Reference Points in Bevel Gear Drives | 78 |
| G-4 | Backlash in the Plane of Rotation | 79 |
| G-5 | Measurement of Normal Backlash | 81 |
| G-6 | Axial Movement Necessary to Obtain a Change in Backlash | 82 |
| G-7 | Typical No Load Tooth Contact Pattern | 83 |
| G-8 | Preferred Contact Resulting from Correct Mounting Position | 83 |
| G-9 | Common Types of Contact Error | 84 |
| H-1 | Residual Unbalance Worksheet | 87 |
| H-2 | Residual Unbalance Polar Plot Worksheet | 88 |
| H-3 | Sample Residual Unbalance Worksheet for Left Plane | 89 |
| H-4 | Sample Residual Unbalance Polar Plot Worksheet for Left Plane | 90 |
| H-5 | Sample Residual Unbalance Worksheet for Right Plane | 91 |
| H-6 | Sample Residual Unbalance Polar Plot Worksheet for Right Plane | 92 |

Tables

| | | |
|-----|---|----|
| 1 | Driver Trip Speeds | 4 |
| 2 | Shaft Assembly Combinations | 5 |
| 3 | Minimum Gear Service Factors | 8 |
| 4 | Material Index Number, I_m and Maximum L/d Ratios | 11 |
| 5 | Allowable Bending Stress Number, S_a | 12 |
| 6 | Overhung Load Factors Applied to Parallel Shaft and Right Angle Gears | 12 |
| 7 | Drain Pipe Sizes | 16 |
| 8 | Casing Vibration Levels | 21 |
| 9 | Maximum $d_m N$ Numbers for Rolling Element Bearings | 22 |
| D-1 | Gear Unit Housings | 63 |
| D-2 | Shafts, Pinions ^c , & Gear Wheels ^c | 63 |
| D-3 | Fabricated Gears | 64 |
| G-1 | Recommended Values of Normal Backlash at Tight Points of Mesh (All Values in Inches) | 78 |

General-purpose Gear Units for Petroleum, Chemical and Gas Industry Services

1 General

1.1 SCOPE

1.1.1 This standard covers the minimum requirements for general-purpose, enclosed single and multistage gear units incorporating parallel shaft helical and right angle spiral bevel gears for the petroleum, chemical, and gas industries. Gears manufactured according to this standard shall be limited to the following pitchline velocities. Helical gears shall not exceed 60 m/s (12,000 ft/min), and spiral bevels shall not exceed 40 m/s (8,000 ft/min). Spiral bevel gearsets shall be considered matched sets.

Note 1: This standard is not intended to apply to gears in special-purpose service, which are covered in API Std 613; to gears integral with other equipment; to epicyclic gear assemblies; or gears with non-involute tooth forms.

Note 2: This standard requires the purchaser to specify certain details and features. A bullet (•) at the beginning of a paragraph indicates that either a decision by, or further information from, the purchaser is required. Further information should be shown on the data sheets or stated in the quotation request and purchase order.

1.1.2 General-purpose gears are applied in equipment trains that are usually spared, or are in noncritical service.

Typical applications for which this standard is intended are cooling tower water pump systems, forced and induced draft fan systems, and other general-purpose equipment trains.

1.2 ALTERNATIVE DESIGNS

The vendor may offer alternative designs. Equivalent metric dimensions, fasteners, and flanges may be substituted as mutually agreed upon by the purchaser and the vendor.

1.3 CONFLICTING REQUIREMENTS

In case of conflict between this standard and the inquiry or order, the information included in the order shall govern.

1.4 DEFINITION OF TERMS

Terms used in this standard are defined in 1.4.1 through 1.4.26.

1.4.1 axially (horizontally) split: A joint that is parallel to the shaft centerline.

1.4.2 bending stress number (S): Defined in 2.4.4.2.

1.4.3 critical speed: A shaft rotational speed at which the rotor-bearing-support system is in a state of resonance.

1.4.4 design: Requirements normally defined by the equipment designer and the manufacturer.

Note: The use of the word design in any term (such as design power, design pressure, design temperature, or design speed) should be avoided in the purchaser's specifications.

1.4.5 DN: An alphanumeric designation of size for components of a pipework system, which is used for reference purposes. It comprises the letters DN followed by a dimensionless whole number which is indirectly related to the physical size, in millimeters (mm), of the bore or outside diameter of the end connection.

Note 1: The number following the letters DN does not represent a measurable value (ISO 6708: 1995).

1.4.6 gear: Refers to either the pinion or gear wheel.

1.4.7 gear-rated power: The maximum power specified by the purchaser on the data sheets and stamped on the nameplate (see 2.4.1).

1.4.8 gear service factor (SF): The factor that is applied to the tooth pitting index and bending stress number, depending on the characteristics of the driver and the driven equipment, to account for differences in potential overload, shock load, and/or continuous oscillatory torque characteristics.

1.4.9 hunting tooth combination: Exists for mating gears when a tooth on the pinion does not repeat contact with a tooth on the gear until it has contacted all the other gear teeth.