

Rheology and Hydraulics of Oil-well Fluids

API RECOMMENDED PRACTICE 13D
SIXTH EDITION, MAY 2010



AMERICAN PETROLEUM INSTITUTE

Rheology and Hydraulics of Oil-well Fluids

Upstream Segment

API RECOMMENDED PRACTICE 13D
SIXTH EDITION, MAY 2010



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this Recommended Practice should consult with the appropriate authorities having jurisdiction.

Users of this Recommended Practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2010 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

Page

Foreword.....	iii
1 Scope	1
2 Normative references	2
3 Terms, definitions, symbols and abbreviations	2
4 Fundamentals and fluid models.....	6
4.1 Flow regime principle.....	6
4.2 Viscosity	7
4.3 Shear stress	8
4.4 Shear rate	9
4.5 Relationship of shear stress and shear rate.....	11
4.6 Fluid characterization.....	11
4.7 Newtonian fluids	11
4.8 Non-Newtonian fluids.....	11
4.9 Rheological models.....	12
5 Determination of drilling fluid rheological parameters.....	13
5.1 Measurement of rheological parameters	13
5.2 Rheological models.....	15
6 Prediction of downhole behaviour of drilling fluids	18
6.1 Principle.....	18
6.2 Circulating temperature predictions in oil-well drilling	18
6.3 Prediction of downhole rheology of oil-well drilling fluids	20
6.4 Prediction of downhole density of oil-well drilling fluids.....	22
7 Pressure-loss modeling.....	25
7.1 Principle.....	25
7.2 Basic relationships.....	25
7.3 Surface-connection pressure loss.....	26
7.4 Drillstring and annular frictional pressure loss	27
7.4.1 Principle.....	27
7.4.2 Section lengths for pressure-loss calculations	27
7.4.3 Fluid velocity.....	27
7.4.4 Hydraulic diameter	27
7.4.5 Rheological parameters	28
7.4.6 Shear-rate geometry correction factors	28
7.4.7 Shear rate at the wall.....	29
7.4.8 Shear stress at the wall (flow equation).....	29
7.4.9 Flow regime.....	29
7.4.10 Critical flow rate.....	31
7.4.11 Friction factor.....	31
7.4.12 Frictional pressure loss	32
7.4.13 Special considerations.....	33
7.5 Bit pressure loss.....	34
7.6 Downhole-tools pressure loss	34
7.7 Choke-line pressure loss	35
7.8 Casing pressure.....	35
7.9 Equivalent circulating density (ECD).....	35
8 Swab/surge pressures	36
8.1 Principle.....	36
8.2 Controlling parameters	36

8.2.1	String speed	36
8.2.2	Displaced fluid	36
8.2.3	Compressibility	36
8.2.4	Clinging factor.....	37
8.2.5	Effective velocity.....	37
8.2.6	Pumps on.....	37
8.2.7	Drilling fluid properties as a function of pressure and temperature.....	37
8.2.8	Frictional pressure loss	37
8.2.9	Acceleration pressure drop	37
8.2.10	Breaking the gel	38
8.3	Closed-string procedure	38
8.4	Open-string procedure	39
8.5	Transient swab/surge analysis.....	39
9	Hole cleaning.....	40
9.1	Description of the challenge.....	40
9.2	How cuttings are transported.....	40
9.2.1	Vertical versus high angle	40
9.2.2	Forces acting on cuttings	40
9.3	Review of modeling approaches.....	41
9.3.1	Vertical and low-inclination wells	41
9.3.2	High-angle wells.....	42
9.4	Recommended calculation methods	43
9.4.1	Vertical and low-angle wells	43
9.4.2	High-angle wells.....	44
9.4.3	Impact of drillpipe rotation.....	45
9.5	Recommended hole cleaning practices	46
9.5.1	Guidelines on viscous / dense pills	46
9.5.2	Circulation prior to tripping	46
9.5.3	Recommended drilling practices	47
9.6	Impact of cuttings loading on ECD	47
9.6.1	Vertical and low-angle Wells	47
9.6.2	High-angle wells.....	47
9.6.3	Calculation methods.....	47
9.7	Barite sag.....	47
10	Hydraulics optimization	49
10.1	Optimization objectives.....	49
10.1.1	Principle of hydraulic optimization	49
10.1.2	Maximizing HSI and impact force.....	49
10.1.3	Maximizing jet velocity	50
10.1.4	Annular velocity	50
10.2	Calculation.....	50
10.3	Reaming while drilling with a pilot-bit configuration	52
10.4	Bit-nozzle selection	52
10.5	Pump-off pressure/force	52
11	Rig-site monitoring	53
11.1	Introduction	53
11.2	Measurement of annular pressure loss.....	53
11.2.1	Equivalent circulating density	53
11.2.2	Pumps-off measurements.....	54
11.2.3	Data formats	54
11.2.4	Drillers logs	55
11.2.5	Time-based log format.	55
11.3	Validation of hydraulics models.....	56
11.3.1	Principle.....	56
11.3.2	Rigsite calibration.....	56
11.3.3	Drillpipe rotation	56
11.4	Interpretation table for downhole pressure measurements.....	57

Annex A	59
A.1 Well information	59
A.2 Drilling fluid information	59
A.3 Wellbore temperature and profile	59
A.4 Wellbore schematic	60
Annex B	61
B.1 Downhole density modeling	61
B.2 Downhole rheology modeling	62
B.2.1 Rheological profiles	62
B.2.2 Results for rheological models	62
Annex C	63
C.1 Input parameters	63
C.2 Pressure loss in drillstring	63
C.3 Pressure loss in annulus	63
Annex D	65
D.1 Input parameters	65
D.2 Closed-ended case	65
D.3 Open-ended case	65
Annex E	67
E.1 Input parameters	67
E.2 Hole cleaning in marine riser	67
E.3 Hole cleaning in vertical casing	67
E.4 Hole cleaning in open hole section	68
Annex F	70
F.1 Input parameters	70
F.2 Maximum hydraulic impact	71
F.2.1 Maximum hydraulic impact method	71
F.2.2 Maximum hydraulic power method	72
F.3 Comparison of optimization methods	73
Bibliography	74

Rheology and hydraulics of oil-well drilling fluids

1 Scope

1.1 The objective of this Recommended Practice (RP) is to provide a basic understanding of and guidance about drilling fluid rheology and hydraulics, and their application to drilling operations.

1.2 The target audience for this RP covers both the office and wellsite engineer. The complexity of the equations used is such that a competent engineer can use a simple spreadsheet program to conduct the analyses. Given that the equations used herein are constrained by the spreadsheet limitation, more advanced numerical solutions containing multiple subroutines and macros are not offered. This limitation does not mean that only the results given by the spreadsheet methods are valid engineering solutions.

1.3 Rheology is the study of the deformation and flow of matter. Drilling fluid hydraulics pertains to both laminar and turbulent flow regimes. The methods for the calculations used herein take into account the effects of temperature and pressure on the rheology and density of the drilling fluid.

1.4 For this RP, rheology is the study of flow characteristics of a drilling fluid and how these characteristics affect movement of the fluid. Specific measurements are made on a fluid to determine rheological parameters under a variety of conditions. From this information the circulating system can be designed or evaluated regarding how it will accomplish certain desired objectives.

1.5 The purpose for updating the existing RP, last published in May 2003, is to make the work more applicable to the complex wells that are now commonly drilled. These include: High-Temperature/High-Pressure (HTHP), Extended-Reach Drilling (ERD), and High-Angle Wells (HAW). Drilling fluid rheology is important in the following determinations:

- a) calculating frictional pressure losses in pipes and annuli,
- b) determining equivalent circulating density of the drilling fluid under downhole conditions,
- c) determining flow regimes in the annulus,
- d) estimating hole-cleaning efficiency,
- e) estimating swab/surge pressures,
- f) optimizing the drilling fluid circulating system for improved drilling efficiency.

1.6 The discussion of rheology in this RP is limited to single-phase liquid flow. Some commonly used concepts pertinent to rheology and flow are presented. Mathematical models relating shear stress to shear rate and formulas for estimating pressure losses, equivalent circulating densities and hole cleaning are included.

1.7 The conventional U.S. Customary (USC) unit system is used in this RP.

1.8 Conversion factors and examples are included for all calculations so that USC units can be readily converted to SI units.

Where units are not specified, as in the development of equations, any consistent system of units may be used.

1.9 The concepts of viscosity, shear stress, and shear rate are very important in understanding the flow characteristics of a fluid. The measurement of these properties allows a mathematical description of circulating fluid flow. The rheological properties of a drilling fluid directly affect its flow characteristics and all hydraulic calculations. They must be controlled for the fluid to perform its various functions.

1.10 This revised document includes some example calculations to illustrate how the equations contained within the document can be used to model a hypothetical well. Due to space constraints, it has not been possible to include a step-by-step procedure for every case. However, the final results should serve as a benchmark if the user wishes to replicate the given cases.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Recommended Practice 13B-1/ISO 10414-1, *Recommended Practice Standard Procedure for Field Testing Water-based Drilling Fluids*

API Recommended Practice 13B-2/ISO 10414-2, *Recommended Practice Standard Procedure for Field Testing Oil-based Drilling Fluids*

API Recommended Practice 13D:2003, *Recommended Practice on the Rheology and Hydraulics of Oil-well Drilling Fluids*

API Recommended Practice 13M/ISO 13503-1, *Recommended Practice for the Measurement of Viscous Properties of Completion Fluids*

3 Terms, definitions, symbols and abbreviations

Symbol	Definition	Standard Units	Conversion Multiplier	SI Units
A	Numerator in Blasius form of friction-factor equation	dimensionless	-	dimensionless
A	Surface area	in ²	6.4516E+02	mm ²
a ₁	Density correction coefficient for pressure	lb _m /gal	1.1983E+02	kg/m ³
a ₂	Density correction coefficient for temperature	lb _m /gal/°F	2.1569E+02	kg/m ³ /°C
A _b	Bit cross-sectional area	in ²	6.4516E+02	mm ²
a _p	Pipe acceleration	ft/s ²	3.048E-01	m/s ²
B	Exponent in Blasius form of friction-factor equation	dimensionless	-	dimensionless
b ₁	Density correction coefficient for pressure	lb _m /gal/psi	1.7379E-02	kg/m ³ /(Pa)
b ₂	Density correction coefficient for temperature	lb _m /gal/psi/°F	3.1283E-02	kg/m ³ /(Pa)/°C
B	Expansibility of the conduit			
B _a	Well geometry correction factor	dimensionless	-	dimensionless
B _x	Viscometer geometry correction factor	dimensionless	-	dimensionless
c ₁	Density correction coefficient for pressure	lb _m /gal/psi ²	2.5206E-06	kg/m ³ /(Pa) ²
c ₂	Density correction coefficient for temperature	lb _m /gal/psi ² /°F	4.5370E-06	kg/m ³ /(Pa) ² /°C
c _a	In-situ cuttings volume concentration	decimal fraction	-	decimal fraction
CaCl ₂	CaCl ₂ concentration	wt%	-	wt%
CCI	Carrying Capacity Index	-	-	-
C _{dt}	Proportionality constant for downhole tool pressure loss	-	-	-