

# **Recommended Practice on Application Care, and use of Wire Rope for Oil Field Service**

API RECOMMENDED PRACTICE 9B  
TWELFTH EDITION, JUNE 2005





# **Recommended Practice on Application Care, and use of Wire Rope for Oil Field Service**

**Upstream Segment**

API RECOMMENDED PRACTICE 9B  
TWELFTH EDITION, JUNE 2005



## SPECIAL NOTES

Page

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

*Copyright © 2005 American Petroleum Institute*

## **API FOREWORD**

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

Suggested revisions are invited and should be submitted to the Standards and Publications Department, API, 1220 L Street, NW, Washington, DC 20005, [standards@api.org](mailto:standards@api.org).

# CONTENTS

|   | Page |
|---|------|
| 1 SCOPE.....  | 1    |
| 2 REFERENCES .....  | 1    |
| 3 FIELD CARE AND USE OF WIRE ROPE.....  | 1    |
| 3.1 Handling on Reel .....  | 1    |
| 3.2 Handling During Installation .....  | 1    |
| 3.3 Care of Wire Rope .....   | 3    |
| 3.4 Seizing .....   | 7    |
| 3.5 Zinc-poured spelter socketing.....  | 8    |
| 3.6 Socketing (Resin Poured) .....  | 9    |
| 3.7 Attachment of Clips .....   | 10   |
| 3.8 Casing-Line and Drilling-Line Reeving Practice.....                           | 13   |
| 4 RECOMMENDED DESIGN FEATURES .....   | 14   |
| 4.1 Importance of Design.....   | 14   |
| 4.2 Socket Baskets .....  | 14   |
| 4.3 Material for Sheave Grooves .....   | 15   |
| 4.4 Bearings .....  | 15   |
| 4.5 Diameter of Drums .....   | 15   |
| 4.6 Drum Grooves.....   | 15   |
| 4.7 Diameter of Sheaves .....   | 15   |
| 4.8 Sheave Grooves .....  | 17   |
| 5 EVALUATION OF ROTARY DRILLING LINE.....   | 19   |
| 5.1 Total Service Performed .....   | 19   |
| 5.2 Round-Trip Operations .....   | 20   |
| 5.3 Drilling Operations .....   | 21   |
| 5.4 Coring Operations.....  | 21   |
| 5.5 Setting Casing Operations.....  | 22   |
| 5.6 Short Trip Operations .....   | 22   |
| 5.7 Other Operations.....   | 22   |
| 5.8 Evaluation of Service.....  | 23   |
| 5.9 Rotary Drilling Line Ton-Mile Calculators .....                               | 23   |
| 5.10 Rotary Drilling Line Service-Record Form .....                               | 23   |
| 6 CUTOFF PRACTICE FOR ROTARY DRILLING LINES .....                                 | 25   |
| 6.1 Service Life.....   | 25   |
| 6.2 Initial Length of Line .....  | 25   |
| 6.3 Service Goal.....   | 25   |
| 6.4 Variations in Line Services .....   | 26   |
| 6.5 Cutoff Length.....  | 26   |
| 7 FIELD TROUBLES AND THEIR CAUSES.....  | 26   |
| Tables  |      |
| 1 Typical Sizes and Construction of Wire Rope for Oilfield Service .....          | 2    |
| 2 Attachment of Clips.....  | 11   |
| 3 Attachment of Double Saddle Clips .....   | 12   |
| 4 Recommended Reeving Arrangements for 14, 12, 10, 9, and 6-Line String-Ups ..... | 14   |
| 5 Sheave-diameter Factors.....  | 15   |
| 6 Relative Bending Life Factors for Various Construction .....                    | 16   |
| 7 Groove Radii for Sheaves.....   | 18   |
| 8 Ton-Mile Goal per Foot of Rope.....   | 26   |

Figures

|    |   |    |
|----|---|----|
| 1  | Efficiencies of Wire Ropes Bent Around Stationary Sheaves.....                    | 4  |
| 2  | Efficiency of Wire Rope Reeving for Multiple Sheave Blocks Cases A, B and C ..... | 5  |
| 3  | Efficiency of Wire Rope Reeving for Multiple Sheave Blocks Cases D and E .....    | 6  |
| 4  | Fatigue Fractures in Outer Wires Caused by the Formation of Martensite .....      | 7  |
| 5  | Putting a Seizing on a Wire Rope.....   | 8  |
| 6  | Correct Method of Attaching Clips to Wire Rope.....                               | 12 |
| 7  | Incorrect Methods of Attaching Clips to Wire Rope.....                            | 12 |
| 8  | Typical Reeving Diagram.....  | 13 |
| 9  | Relative Service for Various DT/d Ratios for Sheaves .....                        | 17 |
| 10 | Sheave Groves .....   | 19 |
| 11 | Use of Sheave Groves .....  | 19 |
| 12 | Facsimile of Rotary Drilling Line Service Record Form.....                        | 24 |
| 13 | Relationship Between Rotary-line Initial Length and Service Life.....             | 25 |

# Recommended Practice on Application Care, and use of Wire Rope for Oil Field Service

## 1 Scope

**1.1** This recommended practice covers typical wire rope applications for the oil and gas industry.

**1.2** Typical practices in the application of wire rope to oil field service are indicated in Table 1, which shows the sizes and constructions commonly used. Because of the variety of equipment designs, the selection of other constructions than those shown is justifiable.

**1.3** In oilfield service, wire rope is often referred to as wire line or cable. For the purpose of clarity, these various expressions are incorporated in this recommended practice.

## 2 References

API

- Spec 4F *Specification for Drilling and Well Servicing Structure*
- Spec 8A *Specification for Drilling and Production Hoisting Equipment*
- Spec 8C *Specification for Drilling and Production Hoisting Equipment*
- Spec 9A *Specification for Wire Rope*

ASTM<sup>1</sup>

- B-6 *Standard Specification for Zinc*

## 3 Field Care and Use of Wire Rope

### 3.1 HANDLING ON REEL

**3.1.1** *Use of Binding or Lifting Chain.* When handling wire rope on a reel with a binding or lifting chain, wooden blocks should always be used between the rope and the chain to prevent damage to the wire or distortion of the strands in the rope.

**3.1.2** *Use of Bars.* Bars for moving the reel should be used against the reel flange, and not against the rope.

**3.1.3** *Sharp Objects.* The reel should not be rolled over or dropped on any hard, sharp object in such a manner that the rope will be bruised or nicked.

**3.1.4** *Dropping.* The reel should not be dropped from a truck or platform. This may cause damage to the rope as well as break the reel.

**3.1.5** *Mud, Dirt, or Cinders.* Rolling the reel in or allowing it to stand in any medium harmful to steel such as mud, dirt, or cinders should be avoided. Planking or cribbing will be of assistance in handling the reel as well as in protecting the rope against damage.

**3.1.6** *Lifting the Reel.* The preferred method for lifting a reel with slings is to use a spreader bar that is of sufficient length to keep the sling legs from contacting the reel. This will prevent the flanges of the reel from being bent, distorted, broken or damaged in any way by the slings.

**3.1.7** *Shaft through Arbor Holes.* When lifting reels of wire rope, care must be taken that the shaft through the reel is of adequate length for the task, plus its wall thickness and diameter are of sufficient strength and size respectively to safely support the weight without damaging the center holes of the two flanges of the reel.

### 3.2 HANDLING DURING INSTALLATION

**3.2.1** *Stringing of Blocks.* Blocks should be strung to give a minimum of wear against the sides of sheave grooves.

**3.2.2** *Changing Lines and Cutoff.* It is good practice in changing lines to suspend the traveling block from the crown on a single line. This tends to limit the amount of rubbing on guards or spacers, as well as chances for kinks. This practice is also very effective in pull-through and cut-off procedure.

---

<sup>1</sup> ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, Pennsylvania 19428-2959, [www.astm.org](http://www.astm.org).