

Hairpin-type Heat Exchangers

API STANDARD 663
FIRST EDITION, MAY 2014



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2014 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

	Page
1 Scope	1
2 Normative References.....	1
3 Terms and Definitions.....	1
4 General	3
5 Proposal Information Required	4
6 Drawings and Other Required Data.....	4
6.1 Outline Drawings and Other Supporting Data	4
6.2 Information Required After Outline Drawings Are Reviewed.....	5
6.3 Reports and Records	7
7 Design.....	7
7.1 Design Temperature	7
7.2 Design Pressure	7
7.3 Cyclic Design.....	8
7.4 Shell	8
7.5 Front Closure	8
7.6 Rear Closure	10
7.7 Tube Bundle.....	10
7.8 Nozzles and Other Connections	13
7.9 Shell Supports	18
7.10 Gaskets.....	18
7.11 Flanged External Girth Joints	18
7.12 Cladding for Corrosion Allowance	19
8 Materials.....	19
8.1 General	19
8.2 Requirements for Carbon Steel in Sour or Wet Hydrogen Sulfide Service	19
8.3 Gaskets.....	20
8.4 Tubes.....	20
9 Fabrication	20
9.1 Shells	20
9.2 Tubes.....	20
9.3 Welding.....	21
9.4 Heat Treatment.....	21
9.5 Dimensional Tolerances	22
9.6 Gasket Contact Surfaces Other Than Nozzle Flange Facings	22
9.7 Tube-to-Tubesheet Joints	22
9.8 Assembly	23
10 Inspection and Testing	23
10.1 Quality Assurance.....	23
10.2 Quality Control.....	24
10.3 Pressure Testing	25
10.4 Nameplates and Stampings	26
11 Preparation for Shipment	26
11.1 Protection.....	26
11.2 Identification	27

Contents

	Page
12 Supplemental Requirements	27
12.1 General	27
12.2 Design	27
12.3 Examination	27
Annex A (informative) Recommended Practices	29
Annex B (informative) Hairpin Heat Exchanger Checklist	31
Annex C (informative) Hairpin Heat Exchanger Datasheets	33
Bibliography	44
Figures	
1 Typical Components of a Hairpin Heat Exchanger	2
2 Typical Front Closure	9
3 Typical Separated Head Front Closure	9
4 Typical Rear Closures	10
5 Typical Impingement Sleeve	12
6 Directions of Forces and Moments on Connections	15
Tables	
1 Minimum Wall Thickness of Tubes	11
2 Shell Side Nozzle Allowable Forces and Moments at Nozzle-to-Header Intersection on the Shell Surface	15
3 Tube Side Nozzle Allowable Forces and Moments at the Face of the Terminal Connection	15
4 G Values for Tube Side Allowable Nozzle Load Calculation	17
5 Gasket Contact Surface Finishes	22
6 Maximum Allowable Tube Wall Thickness Reduction for Roller-Expanded Tube-to-Tubesheet Joints	23
7 Hardness Limits	24
B.1 Checklist for Hairpin Heat Exchangers	31

Introduction

It is necessary that users of this standard be aware that further or differing requirements can be needed for individual applications. This standard is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This can be particularly applicable where there is an innovative or developing technology. Where an alternative is offered, it is the responsibility of the vendor to identify any variations from this standard and provide details.

This standard requires the purchaser to specify certain details and features.

A bullet (●) at the beginning of a section or subsection indicates a requirement for the purchaser to make a decision or provide information (for information, a checklist is provided in Annex B).

In this standard, where practical, U.S. Customary (USC) or other units are included in parentheses for information.

Hairpin-type Heat Exchangers

1 Scope

This standard specifies requirements and gives recommendations for the mechanical design, materials selection, fabrication, inspection, testing and preparation for shipment of hairpin heat exchangers for use in the petroleum, petrochemical and natural gas industries. Hairpin heat exchangers include double-pipe and multi-tube type heat exchangers.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Standard 521, *Pressure-relieving and Depressuring Systems*

ASME B16.5¹, *Pipe Flanges and Flanged Fittings: NPS 1/2 through NPS 24 Metric/Inch Standard*

NACE MR0103², *Materials Resistant to Sulfide Stress Cracking in Corrosive Petroleum Refining Environments*

NACE MR0175, *Petroleum and natural gas industries—Materials for use in H₂S containing environments in oil and gas production—Parts 1, 2 and 3*

NACE SP0472, *Methods and Controls to Prevent In-Service Environmental Cracking of Carbon Steel Weldments in Corrosive Petroleum Refining Environments*

TEMA³, Ninth Edition, *Standards of the Tubular Exchanger Manufacturers Association*

3 Terms and Definitions

For the purposes of this document, the following definitions apply.

3.1

cyclic service

Process operation with periodic variation in temperature, pressure and/or flowrate.

3.2

double-pipe

Single pipe within a shell.

3.3

effective heat transfer area

Outside surface area of the tubes that contributes to heat transfer including finned surface area (if any).

¹ ASME International, 3 Park Avenue, New York, New York 10016-5990, www.asme.org.

² NACE International (formerly the National Association of Corrosion Engineers), 1440 South Creek Drive, Houston, Texas 77218-8340, www.nace.org.

³ Tubular Exchanger Manufacturers Association, 25 North Broadway, Tarrytown, New York 10591, www.tema.org.