

Manual of Petroleum Measurement Standards Chapter 8.2

Standard Practice for Automatic Sampling of Petroleum and Petroleum Products

FIFTH EDITION, NOVEMBER 2020

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this publication should consult with the appropriate authorities having jurisdiction.

Users of this publication should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Users of instructions should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the instructions. At all times users should employ sound business, scientific, engineering, and judgment safety when using this publication.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

Page

Introduction	1
1 Scope	1
2 Referenced Documents	2
3 Terminology	2
4 Significance and Use	4
5 Representative Sampling Components	4
6 Design Criteria	4
7 Automatic Sampling Systems	5
8 Sampling Location	6
9 Mixing of the Flowing Stream	8
10 Proportionality	10
11 Sample Extractor Grab Volume	10
12 Containers	10
13 Sample Handling and Mixing	11
14 Control Systems	11
15 Sample System Security.	13
16 System Proving (Performance Acceptance Tests)	13
17 Performance Monitoring.	14
18 Crude Oil.	15
19 Refined Products.	27
20 Keywords	27
Annex A1—Calculation of the Margin of Error Based on Number of Sample Grabs	27
Annex A2—Theoretical Calculations for Selecting the Sampler Probe Location	29
Annex A3—Portable Sampling Units	34
Annex A4—Profile Performance Test	38
Annex A5—Sampler Acceptance Test Data	40
Appendix X1—Design Data Sheet for Automatic Sampling System.	43
Appendix X2—Comparison of Percent Sediment and Water versus Unloading Time Period.	45
Appendix X3—Sampling Frequency and Sampling System Monitoring Spreadsheet.	46
Appendix X4—Sampling System Monitoring—Additional Diagnostics	46
Bibliography	47

Contents

Page

Summary of Changes	47
--------------------------	----

Figures

1 In-Line Sampling System	6
2 Slip Stream Sample Loop Sampling System	7
3 Sample Volume Regulator	7
4 Typical Portable Installation	8
5 Linefill	8
6 Probe Design	9
7 Probes for Line Sampling	9
8 Sample Probe with Multiple Containers	11
9 Sampling Components and Related Tests	14
10 Flowchart	15
11 Probe Chamfer Design	17
12 Beveled Probe	18
13 Sequence of Acceptance Test Activities	21
14 Performance Criteria	24
A1.1 Number of Samples versus Margin of Error	29
A2.1 Comparison of Mixing Devices	30
A3.1 Portable Sampler Operational Data Confirmation of Mixing and Flow Sensor Velocity	35
A3.2 Portable Sampler Operational Data Confirmation of Free Water Sampled	36
A3.3 Typical Piping Schematic to be Recorded for Discharges	37
A3.4 Typical Piping Schematic to be Recorded for Loading	38
A4.1 Multi Probe for Profile Testing	39
A5.1 Sampler Acceptance Test Data Sheet	41
X1.1 Design Data Sheet for Automatic Sampling System	44
X2.1 Comparison of Percent Sediment and Water versus Unloading Time Period	45

Tables

1 Sample Frequency Variables	12
2 Container Size when Used in Different Applications	19
3 Allowable Deviations for the Single and Dual Sampler Water Injection Acceptance Tests (Volume by Percent)	20
4 Sample System Monitoring Variables	23
5 Linearity Performance Factor Variable	25
6 Sample System Monitoring Variable Resolutions	25
A1.1 Symbols	27
A1.2 Samples versus Margin of Error	28
A2.1 Symbols Used in Annex A2	31
A2.2 Dispersion Factors	31
A2.3 Suggested Resistance Coefficients, K	31
A2.4 Dissipation Energy Factors	32
A2.5 Dissipation Energy Relationships	32
A4.1 Typical Profile Test Data, in Percent by Volume of Water	39
A4.2 Calculation of Point Averages and Deviation	40
X4.1 Sample System Monitoring—Diagnostics Variables	46



Designation: D4177 – 20



Manual of Petroleum Measurement Standards (MPMS), Chapter 8.2

Standard Practice for Automatic Sampling of Petroleum and Petroleum Products¹

This standard is issued under the fixed designation D4177; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

INTRODUCTION

The previous version of the automatic sampling practice described the design, installation, testing, and operation of automated equipment for the extraction of representative samples from the flowing stream and storing mainly for crude oil.

This practice is a performance-based standard. It still includes the design, installation, testing, and operation of automated equipment for extraction of representative samples. It also includes the testing and proving of a sampling system in the field under actual operating conditions to ensure that the equipment, installation, and operating procedures produce representative samples. The acceptance criteria for custody transfer are covered in this practice. This practice does not address how to sample crude at temperatures below the freezing point of water. Extensive revisions have been made to the prior version of D4177 (API *MPMS* Chapter 8.2).

This practice also provides guidance for periodic verification of the sampling system.

This practice is separated into three parts:

General—Sections 5 – 17 (Part I) are currently applicable to crude oil and refined products. Review this section before designing or installing any automatic sampling system.

Crude Oil Sampling—Section 18 (Part II) contains additional information required to complete the design, testing, and monitoring of a crude oil sampling system.

Refined Product Sampling—Section 19 (Part III) contains additional information required to complete the design of a refined product sampling system.

A representative sample is “A portion extracted from the total volume that contains the constituents in the same proportions that are present in that total volume.” Representative samples are required for the determination of chemical and physical properties that are used to establish standard volumes, prices, and compliance with commercial and regulatory specifications.

The process of obtaining a representative sample consists of the following: the physical equipment, the correct matching of that equipment to the application, the adherence to procedures by the operator(s) of that equipment, and the proper handling and analysis.

1. Scope*

1.1 This practice describes general procedures and equipment for automatically obtaining samples of liquid petroleum

¹ This practice is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and the API Committee on Petroleum Measurement, and is the direct responsibility of Subcommittee D02.02 /COMQ the joint ASTM-API Committee on Hydrocarbon Measurement for Custody Transfer (Joint ASTM-API). This practice has been approved by the sponsoring committees and accepted by the Cooperating Societies in accordance with established procedures. This practice was issued as a joint ASTM-API standard in 1982.

Current edition approved Oct. 1, 2020. Published October 2020. Originally approved in 1982. Last previous edition approved in 2016 as D4177 – 16^{ε1}. DOI: 10.1520/D4177-20.

and petroleum products, crude oils, and intermediate products from the sample point into the primary container. This practice also provides additional specific information about sample container selection, preparation, and sample handling. If sampling is for the precise determination of volatility, use Practice D5842 (API *MPMS* Chapter 8.4) in conjunction with this practice. For sample mixing and handling, refer to Practice D5854 (API *MPMS* Chapter 8.3). This practice does not cover sampling of electrical insulating oils and hydraulic fluids.

*A Summary of Changes section appears at the end of this standard