

Shop-welded Tanks for Storage of Production Liquids

API SPECIFICATION 12F
FOURTEENTH EDITION, OCTOBER 2024

API MONOGRAM PROGRAM EFFECTIVE DATE: APRIL 30, 2025



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

	Page
1 Scope.....	1
1.1 General.....	1
1.2 Compliance	1
2 Normative References	1
3 Terms and Definitions.....	3
4 Materials	5
4.1 General.....	5
4.2 Plates	5
4.3 Sheets	6
4.4 Welding Electrodes	6
4.5 Structural Shapes	6
4.6 Piping.....	6
4.7 Flanges	6
4.8 Couplings	6
4.9 Bolting.....	6
5 Design.....	7
5.1 General.....	7
5.2 Loads	7
5.3 Load Combinations	7
5.4 Tank Uplift	7
5.5 Other Design Conditions	7
5.6 Joint Design	8
5.7 Tank Dimensions	8
5.8 Bottom Design	8
5.9 Shell Design	9
5.10 Roof Design.....	9
5.11 Floating Roof.....	12
5.12 Appurtenance Designs.....	13
6 Venting Requirements	16
6.1 Normal Venting	16
6.2 Venting Due to Upset Conditions	16
6.3 Emergency Venting	16
6.4 Combination Gauge Hatch-pressure/Vacuum Relief Valve (Gauging Port)	16
7 Fabrication, Testing, and Painting.....	16
7.1 Fabrication	16
7.2 Welding.....	17
7.3 Testing	17
7.4 External Painting	17
7.5 Internal Coating	17
8 Markings.....	17
9 Inspection and Rejection.....	18
9.1 Inspection Notice.....	18
9.2 Inspection.....	18
9.3 Rejection.....	18
Annex A (normative) Tanks with High Pressure/Vacuum Ratings	19
Annex B (informative) Suggestions for Ordering.....	28

Figures

1	Tank Dimensions	11
2	Type A (Unskirted) Cone Bottom	12
3	Type B (Skirted) Cone Bottom	12
4	Top Angle Detail	13
5	24 in. Wide x 36 in. High Cleanout	14
6	Detail of Shell Plate Opening	15
7	Suggested Nameplate Format.....	18
A.1	ASME Flanged and Dished Head	21
A.2	Skirt Vent Hole Details	21
A.3	Skirt Inspection Opening Detail	22
A.4	Skirt Attachment Detail	22
A.5	Skirt Base Ring	23
A.6	Roof-to-Stiffener Shell Detail	24
A.7	Cleanout Repad Details	24
A.8	Manway and Davit Arm Details	25
A.9	Lifting Lug/Tailing Lug Details.....	26
A.10	Overview of Tank Design and Appurtenances.....	27

Tables

1	Tank Dimensions.....	10
---	----------------------	----

Shop-welded Tanks for Storage of Production Liquids

1 Scope

1.1 General

1.1.1 This specification covers new shop-fabricated vertical, cylindrical, aboveground, welded steel storage tanks in the standard sizes and capacities. It defines the material, design, fabrication, and testing requirements, as well as identifying the acceptable internal pressures given in Table 1.

1.1.2 This specification is designed to provide the oil production industry with tanks of adequate safety and reasonable economy for use in the storage of crude petroleum and other liquids commonly handled and stored by the production segment of the industry. This specification is for the convenience of purchasers and manufacturers in ordering and fabricating tanks.

1.1.3 Only tanks built to the requirements stated in this specification may be identified as 12F tanks. Tanks built to dimensions other than listed in Table 1 or Annex A are outside the scope of this specification.

1.1.4 This specification has requirements given in two alternate systems of units. The manufacturer shall comply with the US customary (USC) units. The metric (SI) unit equivalent is provided for convenience.

NOTE Per API document style, SI unit values appear first, followed by their USC equivalents in parentheses.

1.2 Compliance

1.2.1 The manufacturer is responsible for complying with all the provisions of this specification. The purchaser may make any investigation necessary to satisfy himself or herself of manufacturer compliance and may reject any material that does not comply with this specification. The purchaser may wish to avail himself or herself of this right and furnish their own inspection independently of any supervisory inspection furnished by the manufacturer.

1.2.2 This specification is not intended to cover storage tanks to be erected in areas subject to regulations that are more stringent than the requirements contained in this specification. When this document is specified for such tanks, it should be followed insofar as it does not conflict with regulatory requirements.

1.2.3 Once the tank has been placed into service, it should be maintained according to API 12R1, API 653, or an owner program specifically designed for tank maintenance.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.