

# Refractory Installation Quality Control— Inspection and Testing of AES/RCF Linings and Materials

API STANDARD 976  
SECOND EDITION, OCTOBER 2024



## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

## **Important Information Concerning Use of Asbestos or Alternative Materials**

Asbestos is specified or referenced for certain components of the equipment described in some API standards. It has been extremely useful in minimizing fire hazards associated with petroleum processing. It has also been a universal sealing material, compatible with most refining fluid services.

Certain serious adverse health effects are associated with asbestos, among them the serious and often fatal diseases of lung cancer, asbestosis, and mesothelioma (a cancer of the chest and abdominal linings). The degree of exposure to asbestos varies with the product and the work practices involved.

Consult the most recent edition of the Occupational Safety and Health Administration (OSHA), U.S. Department of Labor, Occupational Safety and Health Standard for Asbestos, Tremolite, Anthophyllite, and Actinolite, 29 *Code of Federal Regulations* Section 1910.1001; the U.S. Environmental Protection Agency, National Emission Standard for Asbestos, 40 *Code of Federal Regulations* Sections 61.140 through 61.156; and the U.S. Environmental Protection Agency (EPA) rule on labeling requirements and phased banning of asbestos products (Sections 763.160–179).

There are currently several substitute materials in use and under development to replace asbestos in certain applications. Manufacturers and users are encouraged to develop and use effective substitute materials that can meet the specifications for, and operating requirements of, the equipment to which they would apply.

**Safety and health information with respect to particular products or materials can be obtained from the employer, the manufacturer, or supplier of that product or material, or the material safety datasheet.**

## Contents

	Page
1	Scope..... 1
2	Normative References ..... 1
3	Terms and Definitions ..... 1
4	Responsibilities ..... 6
4.1	Owner ..... 6
4.2	Installer ..... 7
4.3	Inspector ..... 8
4.4	Fiber Refractory Manufacturer ..... 8
4.5	Fiber Component Fabricator ..... 8
5	Inspector Qualifications ..... 8
6	Materials ..... 9
6.1	Physical Property Requirements for Refractory ..... 9
6.2	Anchors ..... 9
6.4	Marking ..... 10
6.5	Weather Protection ..... 10
6.6	Shelf Life ..... 10
6.7	Discarding Criteria ..... 10
7	Lining Design ..... 10
8	Rigidized and Surface-treated Fiber ..... 20
9	QA/QC, Examination, and Testing ..... 20
9.1	Anchor Inspection and Testing ..... 20
9.2	Anchor Stud Welding ..... 20
9.3	Fiber Lining Inspection and Testing ..... 20
9.4	Installation Workmanship for Fiber Linings ..... 21
10	Preparation for Shipment ..... 22
	Annex A (normative) Refractory Compliance Datasheet ..... 23
	Bibliography ..... 25

## Figures

1	Typical Stud Layout for Overlap Blanket Systems ..... 12
2	Typical Layered Fiber Lining Anchoring Systems ..... 13
3	Examples of Modular Fiber Systems ..... 14
4	Hardware Span Required for Overhead Section Modules and Typical Staples to Secure Batten Strip to Module in Overhead Installations ..... 15
5	Typical Module Orientations ..... 16
6	Typical Joint Details for Single Batten Strips ..... 17

## Contents

	Page
<b>7</b> Typical Blanket Lining Repair of Hot-face Layer .....	17
<b>8</b> Typical Blanket Lining Repair of Multiple Layers .....	18
<b>9</b> Typical Repair of Modular Fiber Linings .....	19
<b>A.1</b> Compliance Datasheet—Fiber Materials .....	24

## Tables

<b>1</b> Documentation Required for Fiber.....	9
<b>2</b> Maximum Temperature of Anchor Tips .....	9
<b>3</b> Minimum Hammer and/or Bend Test Frequency .....	20
<b>A.1</b> Test Methods to Determine RCF/AES Properties.....	23

# Refractory Installation Quality Control— Inspection and Testing of AES/RCF Linings and Materials

## 1 Scope

This standard provides installation quality control procedures and lining system design requirements for alkaline earth silicate fiber (AES)/refractory ceramic fiber (RCF) linings and may be used to supplement owner specifications. Materials, equipment, and personnel are qualified by the methods described, and applied refractory quality is closely monitored, based on defined procedures and acceptance criteria. The responsibilities of inspection personnel who monitor and direct the quality control process are also defined.

The lining described in this standard is for internal refractory linings on the process side of the equipment. External insulation and jacketing are not covered in this standard.

## 2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API Standard 936, *Refractory Installation Quality Control – Inspection and Testing of Monolithics*

ASTM C177,<sup>1</sup> *Standard Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Guarded-Hot-Plate Apparatus*

ASTM E1172, *Standard Practice for Describing and Specifying a Wavelength-Dispersive X-Ray Spectrometer*

ASTM C201, *Standard Test Method for Thermal Conductivity of Refractories*

ASTM C892, *Standard Specification for High-Temperature Fiber Blanket Thermal Insulation*

SSPC-SP 3,<sup>2</sup> *Power Tool Cleaning*

SSPC-SP 7/NACE No. 4, *Brush-Off Blast Cleaning*

## 3 Terms and Definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **alkaline earth silicate fiber**

#### **AES**

Manmade vitreous fiber (MMVF) composed of at least 18 % alkali earth oxides developed to meet the fiber exemption requirements spelled out in 97/69/EC of the Dangerous Substances Initiative in the European Union (EU). These fibers are exonerated from the EU carcinogen classification on the basis of their low bio-persistence. They also may be known as bio-fiber, bio-soluble, or low bio-persistence fiber.

### 3.2

#### **anchor**<sup>3</sup>

Metallic or refractory device that holds the refractory or insulation in place.

<sup>1</sup> ASTM International, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428, [www.astm.org](http://www.astm.org).

<sup>2</sup> The Society for Protective Coatings, 40 24th Street, 6th Floor, Pittsburgh, Pennsylvania 15222, [www.sspc.org](http://www.sspc.org).

<sup>3</sup> Definition from API Standard 560, Fired Heaters for General Refinery Service.