

IN-LB

Inch-Pound Units

SI

International System of Units

Pervious Concrete—Report

Reported by ACI Committee 522

ACI PRC-522-23



American Concrete Institute
Always advancing



Pervious Concrete—Report

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Pervious Concrete—Report

Reported by ACI Committee 522

Norbert J. Delatte, Chair

John T. Kevern, Secretary

Othman Alshareedah
 Daniel Biddle
 William Brant
 Heather Brown
 John Cook
 Bernard Eckholdt III
 Aly Eldarwish
 Scott Erickson
 Dale Fisher
 Walter Flood IV
 Bruce Glaspey
 Liv Haselbach

Amanda Hult
 Frank Kozeliski
 David Liguori
 Jesse Long
 Allyn Luke
 Brian Lutey
 Kamyar Mahboub
 Steven Mallicoat
 Luis Mata
 Somayeh Nassiri
 Narayanan Neithalath
 Matthew Offenber

Oon-Soo Ooi
 Thomas Rozsits
 George Seegebrecht
 David Smith
 Alan Sparkman
 Christopher Tull
 Robert Varner
 Charles Weiss
 Jason Wimberly
 Peter Yen

Consulting Members

Manoj Chopra
 Bruce Ferguson
 Daniel Huffman
 Scott Palotta

Stephen Rohrbach
 Joseph Rottman
 Andy Youngs

This report provides technical information on pervious concrete's application, design methods, materials, properties, mixture proportioning, construction methods, testing, and inspection.

The term "pervious concrete" typically describes a near-zero-slump, open-graded material consisting of portland cement, coarse aggregate, little or no fine aggregate, admixtures, and water. The combination of these ingredients will produce a hardened material with connected pores, ranging in size from 0.08 to 0.32 in. (2 to 8 mm), that allow water to pass through easily. The void content can range from 15 to 35%, with typical compressive strengths of 400 to 4000 psi (2.8 to 28 MPa). The drainage rate of pervious concrete pavement will vary with aggregate size and density of the mixture but will generally fall into the range of 2 to 18 gal./min/ft² (81 to 730 L/min/m²). Pervious concrete is widely recognized as a sustainable building material, as it reduces stormwater runoff,

improves stormwater quality, may recharge groundwater supplies, and can reduce the impact of the urban heat island effect.

Keywords: construction; design; drainage; green building; LEED® credit; permeability; pervious concrete pavement; stormwater; sustainability; testing.

CONTENTS

CHAPTER 1—INTRODUCTION AND SCOPE, p. 2

1.1—Introduction, p. 2

1.2—Scope, p. 3

CHAPTER 2—NOTATION AND DEFINITIONS, p. 3

2.1—Notation, p. 3

2.2—Definitions, p. 3

CHAPTER 3—APPLICATIONS, p. 4

3.1—General, p. 4

3.2—Building applications: history, p. 4

3.3—Pavement applications, p. 5

3.4—Other applications, p. 7

ACI Committee Reports and Guides are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI PRC-522-23 supersedes ACI 522R-10(11) and was published in June 2023.

Copyright © 2023, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

CHAPTER 4—MATERIALS, p. 7

- 4.1—General, p. 7
- 4.2—Aggregates for use in pervious concrete, p. 7
- 4.3—Cementitious materials, p. 8
- 4.4—Water, p. 8
- 4.5—Admixtures, p. 8

CHAPTER 5—PROPERTIES, p. 8

- 5.1—General, p. 8
- 5.2—Permeability, p. 8
- 5.3—Compressive strength, p. 10
- 5.4—Flexural strength, p. 11
- 5.5—Durability under freezing-and-thawing conditions, p. 12
- 5.6—Surface abrasion and raveling resistance, p. 13
- 5.7—Fracture toughness, p. 14
- 5.8—Acoustic absorption, p. 14
- 5.9—Slip and fall prevention, p. 14
- 5.10—Urban heat island mitigation, p. 15
- 5.11—Pollutant removal capacity, p. 15

CHAPTER 6—PERVIOUS CONCRETE MIXTURE PROPORTIONING, p. 15

- 6.1—General discussion of proportioning, p. 15
- 6.2—Proportioning criteria, p. 15
- 6.3—Proportioning process, p. 16
- 6.4—Mixture proportioning process examples, p. 17

CHAPTER 7—PERVIOUS PAVEMENT DESIGN, p. 19

- 7.1—Introduction, p. 19
- 7.2—Site design, p. 19
- 7.3—Structural design, p. 19
- 7.4—Stormwater management design, p. 21
- 7.5—Other considerations, p. 29

CHAPTER 8—PERVIOUS PAVEMENT CONSTRUCTION, p. 30

- 8.1—General construction principles, p. 30
- 8.2—Subgrade/subbase preparation, p. 30
- 8.3—Placing, p. 31
- 8.4—Compaction and finishing, p. 33
- 8.5—Jointing, p. 33
- 8.6—Curing and protection, p. 33
- 8.7—Cold weather protection, p. 35
- 8.8—Hot weather protection, p. 35

CHAPTER 9—QUALITY CONTROL AND ASSURANCE INSPECTION AND TESTING, p. 35

- 9.1—General, p. 35
- 9.2—Preconstruction inspection and testing, p. 35
- 9.3—Inspection and testing during construction, p. 36
- 9.4—Postconstruction inspection and testing, p. 36

CHAPTER 10—PERFORMANCE, p. 37

- 10.1—General, p. 37
- 10.2—Changes in infiltration rates, p. 37
- 10.3—Structural distress, p. 38

10.4—Surface distress, p. 38

10.5—Resistance to freezing and thawing, p. 38

10.6—Resistance to deicers, p. 39

10.7—Repairing pervious concrete pavements, p. 39

10.8—Maintenance, p. 40

10.9—Pervious concrete overlay field durability and performance, p. 40

CHAPTER 11—LIMITATIONS, POTENTIAL APPLICATIONS, AND RESEARCH NEEDS, p. 41

11.1—Pervious concrete in cold climates, p. 41

11.2—Characterization of the material structure, p. 42

11.3—Strength and other testing needs and limitations, p. 42

11.4—Nondestructive determination of performance and properties, p. 43

11.5—Stormwater management, p. 43

11.6—Urban heat island effect, carbonation, and other thermal properties, p. 44

11.7—Construction, operation, and maintenance needs, p. 45

11.8—Other novel applications and uses, p. 45

CHAPTER 12—THE ENVIRONMENT AND PERVIOUS CONCRETE, p. 46**CHAPTER 13—REFERENCES, p. 46**

Authored documents, p. 47

CHAPTER 1—INTRODUCTION AND SCOPE**1.1—Introduction**

The term “pervious concrete” typically refers to a hydraulic-cement concrete proportioned with sufficient, distributed, interconnected macroscopic voids that allow water to flow through the material under the action of gravity alone. The mixture often is composed of open-graded coarse aggregate, cementitious binder, little or no fine aggregate, admixtures, and water (Fig. 1.1a). The combination of these



Fig 1.1a—Pervious concrete pavement (photo courtesy of M. Offenberger).



Fig 1.1b—Uniform porosity observed from a core sample (photo courtesy of J. Montgomery).

ingredients will produce a hardened material with voids (Fig. 1.1b), ranging in size from 0.08 to 0.32 in. (2 to 8 mm), that allow water to flow through easily. The void content can range from 15 to 35%. The infiltration rate of pervious concrete pavement will vary with aggregate size and density of the mixture but will generally fall into the range of 250 to 1700 in./h (0.17 to 1.20 cm/s).

1.2—Scope

The Environmental Protection Agency (EPA) recognizes that stormwater runoff is the single largest contributor to surface water impairment in the United States. Stormwater runoff also has the potential to pollute surface and groundwater supplies. Furthermore, as land is developed, stormwater runoff leaves the site in higher rates and volumes than predevelopment, leading to downstream flooding and bank erosion. Pervious concrete pavement reduces the impact of development by reducing the rate of or eliminating stormwater runoff and protecting water supplies. This report provides technical information on pervious concrete applications, design methods, materials, properties, mixture proportioning, construction methods, testing, and inspection.

CHAPTER 2—NOTATION AND DEFINITIONS

2.1—Notation

A_b	=	area of the nonpervious area to be drained, ft ² (m ²)
A_p	=	area of the pervious pavement, ft ² (m ²)
C	=	runoff coefficient
c	=	cement content, lb (kg)

D_a	=	diameter between coarse aggregate particles
D_c	=	diameter between coarse aggregate particles coated with cement paste or mortar
d_1	=	thickness of the pavement, ft (m)
d_2	=	thickness of the subgrade, ft (m)
f'_c	=	specified compressive strength of concrete, psi (MPa)
f_r	=	modulus of rupture of concrete, psi (MPa)
t	=	time, s
h_1	=	initial head, in. (mm)
h_2	=	final head, in. (mm)
h_c	=	thickness of the pervious concrete layer, ft (m)
h_{curb}	=	height of curb to hold ponded water, ft (m)
h_s	=	thickness of the subbase or reservoir layer, ft (m)
I	=	rainfall intensity, ft (m)
k	=	permeability, in./s (mm/s)
p_1	=	percentage of void space in the pavement
p_2	=	percentage of void space in the subgrade
R	=	pressure reflection coefficient
r_c	=	porosity of the pervious concrete layer, %
r_s	=	porosity for the subbase or reservoir layer, %
V	=	total volume of water to be drained, ft ³ (m ³)
V_p	=	available storage in pavement, ft ³ (m ³)
V_r	=	required storage volume, ft ³ (m ³)
V_s	=	available storage in subgrade, ft ³ (m ³)
w	=	water content, lb (kg)

2.2—Definitions

ACI provides a comprehensive list of acceptable definitions through an online resource, ACI Concrete Terminology. Definitions provided herein complement that resource.

exfiltration rate—the design or measure rate at which water exits the pervious concrete system.

hydraulic conductivity—the ease of which fluids pass through concrete as a function of fluid density and viscosity and degree of saturation, also known as the coefficient of permeability when referring to water under saturated conditions.

impervious area—an area covered by a material that prevents precipitation from infiltrating soils and recharging groundwater supplies.

infiltration rate—the design or measured rate at which water enters the pervious concrete surface.

percolation rate—the rate, usually expressed as inches (millimeters) per hour or inches (millimeters) per day, at which water moves through pervious concrete.

permeability—the ability of pervious concrete to allow fluids (typically water) to pass through as a function of sample volume, fluid head, and fluid viscosity.

pervious concrete—hydraulic cement concrete proportioned with sufficient, distributed, interconnected macroscopic voids that allow water to flow through the material under the action of gravity alone.

pervious pavement—a pavement comprising material with sufficient continuous voids to allow water to pass from the surface to the underlying layers.