

**Please be aware that this PDF has been created from the original hardcopy document, which might not be in good condition and so the PDF might reflect this.**

This British Standard, having been prepared under the direction of the Pressure Vessel Standards Committee, was published under the authority of the Board of BSI and comes into effect on 1 January 1985.

© British Standards Institution, 1985

First published March 1976  
First revision January 1982  
Second revision January 1985

ISBN 0 580 14036 9

#### British Standards Institution

Incorporated by Royal Charter, BSI is the independent national body for the preparation of British Standards. It is the UK member of the International Organization for Standardization and UK sponsor of the British National Committee of the International Electrotechnical Commission.

#### Copyright

Users of British Standards are reminded that copyright subsists in all BSI publications. No part of this publication may be reproduced in any form without the prior permission in writing of BSI. This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols and size, type or

grade designations. Enquiries should be addressed to the Publications Manager, British Standards Institution, Linford Wood, Milton Keynes MK14 6LE. The number for telephone enquiries is 0908 320033 and for telex 825777.

#### Contract requirements

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

#### Revision of British Standards

British Standards are revised, when necessary, by the issue either of amendments or of revised editions. It is important that users of British Standards should ascertain that they are in possession of the latest amendments or editions. Information on all BSI publications is in the *BSI Catalogue*, supplemented each month by *BSI News* which is available to subscribing members of the institution and gives details of new publications, revisions, amendments and withdrawn standards. Any person who, when making use of a British Standard, encounters an inaccuracy or ambiguity, is requested to notify BSI without delay in order that the matter may be investigated and appropriate action taken.

The following BSI reference relates to the work on this standard: Committee reference PVE/1

### Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Pressure Vessel Standards Committee (PVE/-) to Technical Committee PVE/1, upon which the following bodies were represented:

Associated Offices Technical Committee  
Association of Consulting Engineers  
British Chemical Engineering Contractors' Association  
British Compressed Gases Association  
British Gas Corporation  
British Steel Industry

Electricity Supply Industry in England and Wales  
Energy Industries Council  
Engineering Equipment and Materials Users' Association  
Health and Safety Executive  
Independent Engineering Insurers' Committee  
Institution of Chemical Engineers  
Institution of Gas Engineers  
Liquefied Petroleum Gas Industry Technical Association (UK)  
Process Plant Association  
Water-tube Boilermakers' Association  
Welding Institute

### Amendments issued since publication

Amd. No.	Date of issue	Text affected

British Standards Institution · 2 Park Street London W1A 2BS · Telephone 01-629 9000 · Telex 266933

## BS 5500:1985 Unfired fusion welded pressure vessels

### Enquiry Cases – Introduction

In accordance with the provisions of clause 1.2, the publication of Enquiry Cases will be notified in *BSI News* and will be made available for inclusion in the ring-binder in a separate section following the text of the specification and the appendices.

The table below is for recording cases as they are published and included in the binder, and for noting their subsequent routing.

In general, cases will be extant, as adjuncts to the standard and open to public comment, until the text of the standard is amended to incorporate the substance of particular cases. This will be done in the course of the normal updating procedure and each case so dealt with will be recorded on the final page of the relevant amendment.

When an enquiry case is superseded by amended text to the standard, it will be removed from the list in the subsequent amendment or when a new edition of the standard is published and only those remaining extant, as described above, will be referred to. Consequently, the numerical sequence of enquiry case numbers in the first column will not be continuous because of these omissions.

Enquiry Case No.	Date of publication	Subject of the Enquiry Case	Subsequent Enquiry Case routing (e.g. incorporated into BS 5500)	Date of subsequent action
5500/15	November 1979	Vessels under external pressure: permissible design stresses		
5500/17	November 1979	Split ring flanges		
5500/18	December 1979	Design stresses for ASTM A106B tubes (equivalent to BS 3602-410)		
5500/19	December 1979	Maximum stress at a cylinder/nozzle junction due to application of internal pressure		
5500/20	December 1979	Pressure vessels designed for low pressure but having excess in-built thickness		
5500/24	May 1980	Compensation for openings in vessels subject to external pressure		
5500/25	May 1980	Specification of hot properties for steel		
5500/29	December 1980	Derivation of design strength values from actual, rather than specified, material properties		
5500/31	May 1981	Interpretation of the term 'significant general yielding'		
5500/33	August 1981	Verification of shape of vessels subject to external pressure		Page 4 reissued April 1983
5500/34	September 1981	Longitudinal compressive stress limit for pressure vessels		

Enquiry Case No.	Date of publication	Subject of the Enquiry Case	Subsequent Enquiry Case routing (e.g. incorporated into BS 5500)	Date of subsequent action
5500/36	September 1981	Loose flanges split across a diameter and keyed into the back of a component		
5500/38	June 1982	The use of austenitic stainless steel tube to ASTM A312		
5500/39	June 1982	Jacketed construction: blocking ring/jacket attachment using fillet welds		
5500/40	June 1982	Reduction of area in all weld tensile test		
5500/41	June 1982	Vessels fabricated in Ni-Fe-Cr-Mo-Cu alloy NA16		
5500/42	December 1982	Recommended values for design stresses for BS 3692 grade 8.8 bolting material		
5500/44	December 1982	Limits of applicability of 3.5.4.2 to openings in vessel ends		
5500/45	May 1983	Design of reverse flange/flat cover combinations under internal pressure		Page 3 reissued April 1984
5500/46	May 1983	Set-in branches with added compensation rings		
5500/47	May 1983	Construction categories		
5500/49	September 1983	Integrity of construction categories		
5500/52	April 1984	Vessels under external pressure: simplified calculations		
5500/53	April 1984	Supports and mounting for horizontal vessels		
5500/54	May 1984	Bolted flat end plates		
5500/55	May 1984	Design stresses for ASTM A182, A240 and A312 materials		
5500/56	May 1984	Table 5.7 (1) Minimum through-thickness dimension		
5500/57	May 1984	ASTM A333 Gr 6 steels with restricted maximum carbon content		
5500/58	May 1984	Bolted flanges complying with ANSI B16.5		
5500/59	October 1984	Non-destructive testing requirements in the cases of assembled components and following the repair of a defect		
5500/60	October 1984	Value of stress $f_t$ to be used to calculate test pressure where time-dependent design strengths are applicable		

**Acknowledgements**

The following figures are reproduced by courtesy of the American Welding Research Council.

Figure G.2(29) was originally published as Fig. 2 on page 21 of WRC Bulletin 90 September 1963

Figure G.2(30) was originally published as Fig. 3 on page 21 of WRC Bulletin 90 September 1963

Figure G.2(31) was originally published as Fig. 7 on page 24 of WRC Bulletin 90 September 1963

Figure G.2(32) was originally published as Fig. 8 on page 24 of WRC Bulletin 90 September 1963

Figure G.2(33) was originally published as Fig. 9 on page 25 of WRC Bulletin 90 September 1963

Figure G.2(34) was originally published as Fig. 10 on page 25 of WRC Bulletin 90 September 1963

Figure G.2(35) was originally published as Fig. 11 on page 26 of WRC Bulletin 90 September 1963

Figure G.2(36) was originally published as Fig. 12 on page 26 of WRC Bulletin 90 September 1963

Figures G.2(37), G.2(38), G.2(39), G.2(40), G.2(41), G.2(42), G.2(43) and G.2(44) are reproduced by courtesy of the *Institute Journal of Solids and Structures*, 1967.

# BS 5500: 1985

Issue 1, January 1985

## Summary of pages

	No. of sheets	
Preliminary pages:	8	(title page, Enquiry Cases — Introduction, acknowledgements, summary of pages, pages i to ix)
Section one:	3	(pages 1/1 to 1/5)
Section two:	17	(pages 2/1 to 2/33)
Section three:	51	(pages 3/1 to 3/102)
Section four:	7	(pages 4/1 to 4/13)
Section five:	11	(pages 5/1 to 5/22)
Appendix A:	4	(pages A/1 to A/7)
Appendix B:	3	(pages B/1 to B/5)
Appendix C:	4	(pages C/1 to C/7)
Appendix D:	7	(pages D/1 to D/14)
Appendix E:	28	(pages E/1 to E/55)
Appendix F:	1	(pages F/1 to F/2)
Appendix G:	35	(pages G/1 to G/69)
Appendix H:	1	(page H/1)
Appendix J:	2	(pages J/1 to J/4)
Appendix K:	1	(pages K/1 to K/2)
Appendix L:	i	(pages L/1 to L/2)
Appendix M:	1	(page M/1)
Appendix N:	2	(pages N/1 to N/3)
Appendix P:	1	(page P/1)
Appendix Q:	1	(pages Q/1 to Q/2)
Appendix R:	1	(page R/1)
Appendix S:	1	(page S/1)
Concluding pages:	1	(reference standards)

**Contents**

	Page		Page	
Cooperating organizations	Inside front cover	3.7	Supports, attachments and internal structures	3/56
Foreword	ix	3.7.1	General	3/56
<b>Specification</b>		3.7.2	Supports	3/56
<b>Section one. General</b>		3.8	Bolted flanged connections	3/57
1.1 Scope	1/1	3.8.1	General	3/57
1.2 Interpretation	1/1	3.8.2	Notation	3/60
1.3 References	1/1	3.8.3	Narrow faced flanges	3/61
1.4 Definitions	1/1	3.8.4	Full faced flanges with soft ring type gaskets	3/81
1.4.1 Purchaser	1/1	3.9	Flat heat exchanger tubesheets	3/82
1.4.2 Manufacturer	1/2	3.9.1	Notation	3/82
1.4.3 Inspecting Authority	1/2	3.9.2	Characteristics of perforated plates	3/83
1.4.4 Regulating Authority	1/2	3.9.3	Tubesheets of exchangers with confined floating heads or U-tubes	3/83
1.5 Responsibilities	1/2	3.9.4	Tubesheets of exchangers with unconfined heads	3/83
1.5.1 Responsibilities of the purchaser	1/2	3.9.5	Allowable shell and tube longitudinal stresses	3/86
1.5.2 Responsibilities of the manufacturer	1/2	3.9.6	Allowable tube joint end load	3/86
1.5.3 Responsibilities of the Inspecting Authority	1/3	3.10	Design of welds	3/98
1.5.4 Certification	1/3	3.10.1	General	3/98
<b>Section two. Materials</b>		3.10.2	Weld joints for principal seams	3/98
2.1 General	2/1	3.10.3	Welded joints for other than principal seams	3/98
2.2 Selection of materials	2/1	3.10.4	Welded joints in time dependent applications	3/98
2.3 Nominal design strength	2/1	3.11	Jacket construction	3/101
2.4 Carbon, carbon manganese and alloy steels	2/1	3.11.1	General	3/101
2.5 Aluminium	2/2	3.11.2	Jacketed cylindrical shells	3/101
<b>Section three. Design</b>		3.11.3	Welded jacket connections	3/101
3.1 Purpose	3/1	3.11.4	Outlet branches	3/101
3.2 Application	3/1	3.11.5	Compensation	3/101
3.3 Corrosion, erosion and protection	3/2	3.12	Manholes and inspection openings	3/101
3.3.1 General	3/2	<b>Section four. Manufacture and workmanship: steel</b>		
3.3.2 Additional thickness to allow for corrosion	3/2	4.1	General aspects of construction	4/1
3.3.3 Linings and coatings	3/2	4.1.1	Fully dimensioned drawing	4/1
3.3.4 Wear plates	3/2	4.1.2	Material identification	4/1
3.4 Construction categories and design stresses	3/2	4.1.3	Order of completion of weld seams	4/1
3.4.1 Construction categories	3/2	4.1.4	Junction of more than two weld seams	4/1
3.4.2 Design stresses	3/2	4.2	Cutting, forming and tolerances	4/1
3.5 Vessels under internal pressure	3/4	4.2.1	Cutting of material	4/1
3.5.1 Cylindrical and spherical shells	3/4	4.2.2	Forming of shell sections and plates	4/1
3.5.2 Domed ends	3/4	4.2.3	Assembly tolerances	4/2
3.5.3 Conical ends and truncated cones	3/5	4.2.4	Tolerances for vessels subject to internal pressure	4/3
3.5.4 Openings and branch connections	3/16	4.2.5	Tolerances for vessels subject to external pressure	4/3
3.5.5 Flat ends and flat plates	3/31	4.3	Welded joints	4/3
3.5.6 Spherically domed and bolted ends conforming to figure 3.5.6	3/37	4.3.1	General	4/3
3.6 Vessels under external pressure	3/38	4.3.2	Welding consumables	4/4
3.6.1 General	3/38	4.3.3	Preparation of plate edges and openings	4/4
3.6.2 Cylindrical shells	3/38	4.3.4	Assembly for welding	4/4
3.6.3 Conical shells	3/40	4.3.5	Attachments and the removal of temporary attachments	4/4
3.6.4 Spherical shells	3/41	4.3.6	Butt joints	4/4
3.6.5 Hemispherical ends	3/42	4.3.7	Welding: general requirements	4/4
3.6.6 Torispherical ends	3/42	4.4	Heat treatment	4/5
3.6.7 Ellipsoidal ends	3/42	4.4.1	Preheat requirements	4/5
3.6.8 Procedure by which the departure from the mean circle may be obtained	3/42			

	Page		Page
4.4.2	4/6	5.8	5/7
4.4.3	4/6	5.8.1	5/7
4.4.4	4/6	5.8.2	5/7
4.4.5	4/6	5.8.3	5/8
4.5	4/8	5.8.4	5/8
		5.8.5	5/9
		5.8.6	5/10
		5.8.7	5/11
		5.8.8	5/11
		5.8.9	5/11
		5.8.10	5/11
<b>Section four A. Manufacture and workmanship: aluminium</b>		<b>Section five A. Inspection and testing: aluminium</b>	
4A.1	4/9	5A.1	5/13
4A.1.1	4/9	5A.2	5/13
4A.1.2	4/9	5A.3	5/13
4A.1.3	4/9	5A.4	5/13
4A.1.4	4/9	5A.5	5/14
4A.1.5	4/9	5A.5.1	5/14
4A.2	4/9	5A.5.2	5/14
4A.2.1	4/9	5A.5.3	5/14
4A.2.2	4/9	5A.5.4	5/14
4A.2.3	4/10	5A.5.5	5/14
4A.2.4	4/10	5A.5.6	5/14
4A.2.5	4/11	5A.5.7	5/14
4A.3	4/11	5A.5.8	5/14
4A.3.1	4/11	5A.6	5/14
4A.3.2	4/11	5A.6.1	5/15
4A.3.3	4/11	5A.6.2	5/15
4A.3.4	4/12	5A.6.3	5/15
4A.3.5	4/12	5A.6.4	5/15
4A.3.6	4/12	5A.6.5	5/15
4A.3.7	4/12	5A.6.6	5/16
4A.4	4/12	5A.7	5/17
4A.4.1	4/12	5A.7.1	5/17
4A.4.2	4/13	5A.7.2	5/17
4A.4.3	4/13	5A.7.3	5/17
4A.4.4	4/13	5A.7.4	5/17
4A.4.5	4/13	5A.8	5/17
4A.5	4/13	5A.8.1	5/17
		5A.8.2	5/17
		5A.8.3	5/19
		5A.8.4	5/19
		5A.8.5	5/19
		5A.8.6	5/20
		5A.8.7	5/20
		5A.8.8	5/20
		5A.8.9	5/20
		5A.8.10	5/20
<b>Section five. Inspection and testing: steel</b>		<b>Appendices</b>	
5.1	5/1	A.	A/1
5.2	5/1	B.	B/1
5.3	5/1		
5.4	5/1		
5.6	5/1		
5.6.1	5/1		
5.6.2	5/2		
5.6.3	5/2		
5.6.4	5/2		
5.6.5	5/3		
5.6.6	5/3		
5.7	5/4		
5.7.1	5/4		
5.7.2	5/4		
5.7.3	5/7		

	Page		Page
C.	Recommended practice for assessment of vessels subject to fatigue	C/1	3.8.1.4 Recommended design stress values for flange bolting materials 3/58
D.	Recommended practice for carbon and carbon manganese steel vessels required to operate at low temperature	D/1	3.8.3(1) Moment arms for flange loads under operating conditions 3/62
E.	Recommended welded connections for pressure vessels	E/1	3.8.3(2) Gasket materials and contact facings: gasket factors ( $m$ ) for operating conditions and minimum design seating stress ( $y$ ) 3/66
F.	Recommended alternative design method of compensation using area replacement	F/1	3.8.3(3) Effective gasket width 3/68
G.	Stresses from local loads, thermal gradients, etc: recommended methods of calculation	G/1	3.8.3(4) Values of $T$ , $Z$ , $Y$ and $U$ (factors involving $K$ ) 3/70
H.	General recommendations for post-weld heat treatment of dissimilar ferritic steel joints	H/1	3.9 Values of $\Delta C$ as a function of $F_s$ and $R$ for all tubesheets, and $C_0$ for U-tube-sheets only 3/85
J.	Pressure relief protective devices	J/1	3.9.6 Values of $F_r$ for typical tube joints 3/86
K.	Derivation of material nominal design strengths for construction category 1 and 2 vessels	K/1	4.2.4.1.1 Circumference 4/3
L.	Basis of the design charts for openings and branches	L/1	4.2.4.1.4 Tolerance on depth of domed ends 4/3
M.	Safe external working pressure for cylindrical sections outside the circularity limits specified in 3.6	M/1	4.4.1.1 Preheating recommendations for welding 4/5
N.	Check list of matters on which, if relevant, agreement is required	N/1	4.4.3.1 Requirements for post-weld heat treatment of ferritic steel vessels 4/7
P.	Stainless steel components with higher design stresses	P/1	4A.2.4.1.1 Circumference 4/10
Q.	Recommendations for preparation and testing of production control test plates	Q/1	4A.2.4.1.4 Tolerance on depth of domed ends 4/11
R.	Supporting information for 3.5.5: flat ends and flat plates	R/1	5.6.4.1.1 Thickness limits for examination of internal flaws 5/2
S.	Optional documentation for supply with vessel	S/1	5.7(1) Acceptance levels 5/5
			5.7(2) Acceptance levels (re-assessment of category 2 construction) 5/6
			5.8.10 Principal stages of inspection 5/11
			5A.4 Number of test specimens for weld procedure approval and production control tests 5/14
			5A.5 Mechanical test requirements for butt weld procedure and welder approval 5/14
			5A.7 Acceptance levels 5/18
			5A.8.10 Principal stages of inspection 5/21
			A.3 Classification of stresses for some typical cases A/4
			D.3.2.1 Impact requirements at the reference temperature of carbon and carbon manganese steel plates, tubes and forgings D/3
			G.2.2.2 Values of $K_1$ and $K_2$ G/9
			G.3.3.2.3 Design factors $K_1$ and $K_2$ G/53
			G.3.3.2.4 Design factors, $K_3$ and $K_4$ and allowable tangential shearing stresses G/54
			G.3.3.2.5.1 Design factor $K_6$ G/55
			G.3.3.2.5.2 Values of constants $C_4$ , $C_5$ , $K_5$ , $K_7$ and $K_8$ G/56
			G.3.3.3 Values of $K_{10}$ and $K_{11}$ G/57
			G.4(1) Hoop stress factor $C_1$ G/66
			G.4(2) Bending stress factor $C_2$ G/66
			G.4(3) Meridional stress factor $C_3$ G/67
			G.4(4) Branch bending stress factor $C_4$ G/67
			H.1 Classification of materials H/1
			J.7.1 Coefficients of discharge J/2
			P.1 Design strength values P/1
<b>Tables</b>			
2.3	Design strength values: index of steels	2/2	
2A.3	Design strength values: aluminium and aluminium alloys	2/33	
2.4	Additional materials that may be used for category 3 construction	2/33	
3.4	Construction categories	3/3	
3.5.2.3	Values of $e/D \times 10^3$ for unpierced domed ends in terms of $h_e/D$ and $p/f$	3/9	
3.5.3	Junction at the large base of the cone with knuckle: values of $C_1$ as a function of $\psi$ and $r/D_e$	3/14	
3.5.4(1)	Thickness of branches	3/19	
3.5.4(2)	Design values of $t_r/T_r$	3/24	
3.6(1)	Derivation of $L_e$	3/42	
3.6(2)	Values for $G$ and $N$ which may be assumed	3/43	
3.6(3)	$E$ values for ferritic and austenitic steels and aluminium alloys (Young's Modulus)	3/51	
3.6(4)	Values of $(\sigma_e/E)(d/e_w)^2$ for internal flat bar stiffeners	3/54	
3.6(5)	Values of $(\sigma_e/E)(d/e_w)^2$ for external flat bar stiffeners	3/55	

# BS 5500: 1985

Issue 1, January 1985

Figures		Page		Page	
3.5.2.1	Domed ends	3/5	3.6(1)	Design curves: calculation of minimum cylindrical shell thickness (values of $n$ for which $K$ is a minimum)	3/44
3.5.2.3	Design curves for unpierced domed ends	3/7	3.6(2)	Values of $e$ for use with equation 2	3/45
3.5.3(1)	Cone/cone and cone/cylinder junctions	3/11	3.6(3)	Curves for evaluation of allowable pressure $p$	3/46
3.5.3(2)	Maximum angle $\psi$ for large base of cone	3/12	3.6(4)	Schematic representation of stiffeners	3/48
3.5.3(3)	Value of coefficient $M$ for a junction at the large base of the cone without knuckle	3/13	3.6(5)	Design of stiffeners	3/51
3.5.3(4)	Design curves: determination of $C_1$	3/13	3.6(6)	Values of $\beta$ for use with equation 3	3/52
3.5.3(5)	Maximum angle $\psi$ for small base of cone	3/14	3.6(7)	Conical sections: typical stiffeners	3/53
3.5.3(6)	Value of coefficient $M$ for a junction at the small base of the cone without knuckle	3/14	3.8.3(1)	Classification of flanges for calculation purposes	3/62
3.5.4(0)	Positions of openings or nozzles in dished ends	3/15	3.8.3(2)	Location of gasket load reaction	3/69
3.5.4(1)	Design curves for protruding nozzles	3/15	3.8.3(3)	Values of $T$ , $U$ , $Y$ and $Z$	3/74
3.5.4(2)	Design curves for flush nozzles in spherical shells ( $d/D < 0.5$ ) and for flush nozzles in conical shells ( $d/D < 0.3$ )	3/15	3.8.3(4)	Values of $F$ (integral-type flange factors)	3/75
3.5.4(3)	Design curves for flush nozzles in cylindrical shells ( $0 < d/D < 0.3$ )	3/18	3.8.3(5)	Values of $V$ (integral-type flange factors)	3/75
3.5.4(4)	Design curves for flush nozzles in cylindrical shells ( $0.2 < d/D \leq 1.0$ )	3/20	3.8.3(6)	Values of $F_L$ (loose hub flange factors)	3/76
3.5.4(5)	Nozzle in a conical shell	3/21	3.8.3(7)	Values of $V_L$ (loose hub flange factors)	3/76
3.5.4(6)	Notation applicable to spheres	3/22	3.8.3(8)	Values of $f$ (hub stress correction factors)	3/76
3.5.4(7)		3/23	3.8.4	Full faced flange with soft ring type gasket	3/81
3.5.4(8)		3/26	3.9(1)	$F$ versus wall thickness/i.d. ratio for integral vessel	3/84
3.5.4(9)		3/26	3.9(2)	Design curves: determination of $C$	3/87
3.5.4(10)		3/26	3.9(3)	Design curves: determination of $F_o$	3/88 3/89
3.5.4(11)	Notation applicable to cylinders	3/26	3.9(4)	Design curves: determination of $F_i$	3/90 3/91
3.5.4(12)		3/27	3.9(5)	Typical clamped and simply supported configurations	3/92
3.5.4(13)		3/27	3.9(6)	Characteristics for perforated thin plates, $e < 2P$	3/93
3.5.4(14)		3/27	3.9(7)	Characteristics for perforated thick plates, $e \geq 2P$	3/94
3.5.4(15)		3/27	3.9(8)	Determination of the buckling length $L_k$	3/95
3.5.4(16)	Arrangement factor $g$	3/28	3.10(1)	Butt welds in plates of unequal thickness	3/99
3.5.4(17)	Branch compensation	3/28	3.10(2)	Butt welds with offset of median lines	3/100
3.5.4(18)	Notation applicable to spheres and cylinders	3/29	3.11(1)	Some acceptable types of jacketed vessels	3/102
3.5.4(19)		3/29	3.11(2)	Typical blocking ring and sealer ring construction	3/102
3.5.4(20)	Modified flush branch compensation	3/30	5.7	Partial non-destructive testing (NDT) category 2 constructions	5/7
3.5.4(21)	Modified protruding branch compensation	3/30	A.3	Stress categories and limits of stress intensity	A/6
3.5.5(1)	Typical welded flat ends and covers	3/32	B.3(1)	Stresses in a cylindrical shell under combined loading	B/3
3.5.5(2)	Typical non-welded flat ends and covers	3/33	B.3(2)	Stresses in a spherical shell under combined loading	B/4
3.5.5(3)	Flat unstayed heads: design curves	3/34	B.3(3)	Stresses in a conical shell under combined loading	B/5
3.5.5(4)	Value of coefficient $Z$ for non-circular flat heads	3/35			
3.5.5(5)	Typical stays: areas supported by stays	3/36			
3.5.6	Spherically domed and bolted end	3/37			
3.6(0)	Stiffening rings for cylindrical vessels subject to external pressure	3/44			

	Page		Page
C.2.1		E.1(6)	Typical full penetration joint preparations for one-sided welding only: aluminium and its alloys
		E.1(7)	Typical full penetration joint preparations for two-sided welding only: aluminium and its alloys
C.3.1		E.1(8)	Typical full penetration joint preparations for one-sided welding with temporary backing or permanent backing: aluminium and its alloys
		E.2(1)	Standard weld details
C.4.3		E.2(2)	Transverse and longitudinal sections of branch connections
D.2(1)		E.2(3)	Weld details for set-in branches
		E.2(4)	
		E.2(5)	
D.2(2)		E.2(6)	Set-on branches
		E.2(7)	
		E.2(8)	
		E.2(9)	
		E.2(10)	
		E.2(11)	Set-in branches: fillet welded connections
D.2(3)		E.2(12)	Set-in branches: partial penetration butt welded connections
		E.2(13)	Set-in branches: full penetration connections
D.2(4)		E.2(14)	
		E.2(15)	Set in branches: full penetration connections with asymmetrical butt joints
D.3(1)		E.2(16)	Set-in branches: full penetration connections welded from one side only
D.3(2)		E.2(17)	Forged branch connections
		E.2(18)	
D.3(3)		E.2(19)	Set-on branches with added compensation rings
D.3.2.1		E.2(20)	Set-in branches with added compensation rings
		E.2(21)	
		E.2(22)	
D.4(1)		E.2(23)	Studded connections
D.4(2)		E.2(24)	Socket welded and screwed connections
		E.2(25)	Flanges
D.5		E.2(26)	
		E.2(27)	
E.1(1)		E.2(28)	Jacketed vessels: typical vessel/blocking ring attachments
		E.2(29)	Jacketed vessels: typical blocking ring/jacket attachments
E.1(2)		E.2(30)	Jacketed vessels: typical sealer rings
		E.2(31)	Jacketed vessels: typical through connections
E.1(3)		E.2(32)	Flat ends and covers
		E.2(33)	Tube to tubeplate connections
E.1(4)		E.2(34)	
		E.2(35)	
		E.2(36)	
		E.2(37)	Tubeplate to shell connections: accessible for welding on both sides of the shell
E.1(5)		E.2(38)	
		E.2(39)	


# BS 5500: 1985

Issue 1, January 1985

	Page		Page
E.2(40)	Tubeplate to shell connections: accessible for welding from <i>outside</i> of shell only	E/51	G.2(20) Circumferential moment G.2(21) Longitudinal moment G.2(22) Chart for findings and $u$ G.2(23) Spherical shell subjected to a radial load
E.2(41)	Tubeplate to shell connections: accessible for welding on <i>both</i> sides of shell	E/52	G.2(24) Deflections of a spherical shell subjected to a radial load $W$
E.2(42)	Tubeplate to shell connections	E/53—E/55	G.2(25) Moments and membrane forces in a spherical shell subjected to a radial load $W$
E.2(43)			G.2(26) Spherical shell subjected to an external moment
E.2(44)			G.2(27) Deflections of a spherical shell subjected to an external moment $M$
F.2	Compensation of welded branch or standpipe or opening	F/2	G.2(28) Moments and membrane forces in a spherical shell subjected to an external moment $M$
G.2(0)	Restriction on vessel/attachment geometry	G/2	G.2(29) Maximum stress in sphere for internal pressure (flush nozzles)
G.2(1)	Vessel with central radial load	G/3	G.2(30) Maximum stress in sphere for internal pressure (protruding nozzles)
G.2(2)	Vessel with radial load out of centre	G/3	G.2(31) Maximum stress for thrust loading (flush nozzles)
G.2(3)	Graph for finding equivalent length $L_c$	G/4	G.2(32) Maximum stress in sphere for thrust loading (protruding nozzles)
G.2(4)	Chart for finding $64 \frac{r}{t} \left( \frac{C_x}{r} \right)^2$	G/4	G.2(33) Maximum stress in sphere for moment loading (flush nozzles)
G.2(5)	Cylindrical shells with radial load: circumferential moment per millimetre width	G/5	G.2(34) Maximum stress in sphere for moment loading (protruding nozzles)
G.2(6)	Cylindrical shells with radial load: longitudinal moment per millimetre width	G/6	G.2(35) Maximum stress in sphere for shear loading (flush nozzles)
G.2(7)	Cylindrical shells with radial load: circumferential membrane force per millimetre width	G/7	G.2(36) Maximum stress in sphere for shear loading (protruding nozzles)
G.2(8)	Cylindrical shells with radial load: longitudinal membrane force per millimetre width	G/8	G.2(37) Shakedown values for pressure loading (flush nozzle)
G.2(9)	Hoop bending moment due to a radial line load variation round circumference	G/10	G.2(38) Shakedown values for pressure loading (protruding nozzle)
G.2(10)	Longitudinal moment from radial line load variation round circumference	G/11	G.2(39) Shakedown values for thrust and moment loadings (flush nozzle)
G.2(11)	Circumferential membrane stress from radial line load variation round circumference	G/12	G.2(40) Shakedown values for thrust and moment loadings (protruding nozzle)
G.2(12)	Longitudinal membrane forces from radial line load variation round circumference	G/13	G.2(41) Shakedown values for thrust and moment loadings (flush nozzle)
G.2(13)	Hoop bending moment due to a radial line load variation along cylinder	G/15	G.2(42) Shakedown values for thrust and moment loadings (protruding nozzle)
G.2(14)	Longitudinal moment due to a radial line load variation along cylinder	G/16	G.2(43) Shakedown values for thrust and moment loadings (flush nozzle)
G.2(15)	Hoop membrane forces due to a radial line load variation along cylinder	G/17	G.2(44) Shakedown values for thrust and moment loadings (protruding nozzle)
G.2(16)	Longitudinal membrane forces due to a radial line load variation along cylinder	G/18	G.3(1) Typical brackets G.3(2) Reinforcing plate on cylindrical shell
G.2(17)	Maximum radial deflection of a cylindrical shell subjected to a radial load $W$ uniformly distributed over a square $2C \times 2C$	G/20	G.3(4) Typical ring support
G.2(18)		G/21	G.3(5) Typical steelwork under ring support
G.2(19)	Graphs for finding the square $2C_1 \times 2C_1$ equivalent to a rectangular loading area $2C_2 \times 2C_2$	G/22	G.3(6) Leg supports for vertical vessels G.3(7) Typical ring girder G.3(8) Typical supports for horizontal vessels

	Page		Page
G.3(9) Cylindrical shell acting as beam over supports	G/50	G.3(16) Typical ring stiffeners	G/57
G.3(10) Factor for bending moment at mid-span	G/51	G.4(1) Nozzle geometry	G/62
G.3(11) Factors for bending moment at supports	G/52	G.4(2) Transient fluid and metal temperatures	G/62
G.3(12) Portion of shell ineffective against longitudinal bending	G/53	G.4(3) Inner surface thermal stress factors $K_1$ and $k_1$	G/63
G.3(13) Circumferential bending moment diagrams	G/54	G.4(4) Outer surface thermal stress factors $K_2$ and $k_2$	G/64
G.3(15) Saddle supports	G/56	G.4(5) Mean temperature factors $K_b$ and $K_s$	G/65

Licensed copy. Recirculation - Michigan, Version correct as of 20/04/2020.



**Foreword**

This British Standard has been prepared under the direction of the Pressure Vessel Standards Committee. It is a new edition of the 1982 version and incorporates all technical changes up to and including Amendment No. 3 (April 1984) associated with that version. The proposals in ISO/DIS 2694 'Pressure vessels', drafted by Technical Committee 11 of the International Organization for Standardization (ISO), have been taken into account where considered appropriate.

NOTE. Some of the figures in this standard have been taken from ISO/DIS 2694 and employ the comma as the decimal marker; normal BSI practice is to use the full point.

BS 5500, which covers pressure vessels manufactured from carbon, ferritic alloy and austenitic steels, and from aluminium, replaced the following standards:

BS 1500 Fusion welded pressure vessels for general purposes  
Part 1 Carbon and low alloy steels  
Part 3 Aluminium

BS 1515 Fusion welded pressure vessels for use in the chemical, petroleum and allied industries  
Part 1 Carbon and ferritic alloy steels  
Part 2 Austenitic stainless steel

The previous editions stated the intention of integrating into one British Standard the requirements for design, manufacture, testing and inspection of fusion welded pressure vessels. It is still intended to keep under review the question of publishing appropriate supplements covering other types of pressure vessels, for some of which separate British Standards currently exist. In the meantime, by agreement between the parties concerned, this standard may be used where applicable in place of other British Standards. If there is sufficient demand from industry, the standard will also be extended to cover other non-ferrous materials.

The format adopted to facilitate amendments to the text and the incorporation of supplements covering other types of vessels and materials in the previous editions, has been retained.

The requirements of this standard vary considerably depending upon the thickness and type of material to be used. When this combination is such as will permit satisfactory fabrication by relatively straightforward processes, spot non-destructive testing is permitted without any penalty in design thickness; in certain cases visual inspection only is permitted with an appropriate penalty on design thickness.

The strengths that may be assumed for design purposes of materials covered by current British Standards are individually specified in table 2.3. The concept of design strength tables, as used in BS 1500, has been reintroduced because of the difficulty of specifying in any other way

appropriate design strengths for materials and product forms covered by a variety of standard specifications which have been revised to line up with relevant ISO material standards. Appropriate modifications to the tables and to appendix K are incorporated, these being concerned with the coverage of the types and ranges of material in the revised standards rather than with significant changes to the presently permitted strength levels which, except in the creep range, are generally consistent with those permitted by BS 1515.

A significant departure from pressure vessel standards prior to BS 5500 is that design strengths in the creep range are given for a range of design lifetimes that may be extended, on expiry, on the basis of periodic 'fitness-for-continued-service reviews' based on inspection and consideration of actual load-temperature history. This approach recognizes the limitations inherent in any simple design method for vessels operating in the creep range and also provides a flexible basis that may be used in cases where the design strength values which have been derived from ISO data, are significantly different from those used with success in the past.

Specific requirements for these reviews are not given in this standard because they require development and will be covered by other standards publications for the periodic inspection of pressure vessels.

Recommendations covering aspects requiring further consideration in particular cases are given in the appendices. The British Standards Institution will be pleased to receive constructive proposals based on experience or research that may lead to improvements in these appendices.

As with the previous editions, it is intended to keep this standard up to date by the issue from time to time of replacement pages, or additional pages where necessary. Each replacement or added page will carry an issue number (with date) indicating its relationship to the original standard, the pages of which are marked 'Issue 1'. For example,

Issue 1 will indicate an original page or one that has been added to the original standard and has not been amended since insertion;

Issue 2 will indicate a first revision of either an original page or an added page;

Issue 3 will indicate either an original page revised for the second time since publication or an added page revised for the second time since insertion.

Side-lining on replacement pages will indicate that changes of technical or reference significance have been made at that point.

# British Standard Specification for Unfired fusion welded pressure vessels

## Section one. General

### 1.1 Scope

This British Standard specifies requirements for the design, construction, inspection, testing and certification of unfired fusion welded pressure vessels. The materials of construction are defined in section two. The term 'pressure vessel' as used in this standard includes branches up to the point of connection to the connecting piping by bolting, screwing or welding, and supports, brackets or other attachments directly welded to the pressure containing shell.

This standard applies only to pressure vessels manufactured under the survey of a competent engineering inspection Authority or Organization. The intent of this requirement may be regarded as satisfied where inspection is carried out by competent personnel of a separate engineering inspection department maintained by the purchaser of the vessel. An inspection department maintained by the manufacturer does not satisfy this requirement except:

- (a) that specific responsibilities may be delegated at the discretion of the Inspecting Authority or Organization; or
- (b) in the case of vessels for the manufacturer's own use and not for re-sale.

The vessels covered by this standard shall be made only by the manufacturers who can satisfy the Inspecting Authority or Organization that they are competent and suitably equipped to fulfil the appropriate requirements of this standard. (See also asterisked footnote.)

This standard does not cover the following.

- (a) Storage tanks designed for the storage of liquids at near atmospheric pressures, i.e. where the pressure additional to that due to the hydrostatic head does not exceed 140 mbar† above or 6 mbar below atmospheric pressure in accordance with such standards as BS 799, BS 2594, BS 2654, BS 4741, BS 5387.

Low pressure, above ground storage tanks which have a single vertical axis of revolution designed for the storage of liquids at a pressure not exceeding 1 bar†.

- (b) Vessels in which the stresses calculated in accordance with the equations given in section three of this standard are less than 10 % of the design stress permitted by section three.

(c) Strip wound compound or other special designs of vessels which may be appropriate for very high pressures.

(d) Transport vessels, i.e. vessels used for transport of contents under pressure.

- (e) Vessels for specific applications which are covered by standards listed in the *BSI Catalogue*.

Manufacturing techniques of glassed steel vessels may require special design considerations subject to the limits imposed by the method of construction and which should have the agreement of the Inspecting Authority.

### 1.2 Interpretation

If any ambiguity be found or doubt arise as to the meaning or effect of any part of this standard or as to whether anything ought to be done or omitted to be done in order that this standard should be complied with in full, the question shall be referred to the Pressure Vessels Technical Committee (PVE/I) of the British Standards Institution, whose interpretation of the requirements of this standard upon the matter at issue shall be given free of charge and shall be final and conclusive. Parties adopting this standard for the purposes of any contract shall be deemed to adopt this provision unless they expressly exclude it or else import an arbitration provision in terms extending to interpretation of this standard. However, this provision is limited to questions of interpretation and does not confer upon the committee any power, duty or authority to adjudicate upon the contractual rights or duties of any person under a contract except in so far as they may necessarily be affected by the interpretation arrived at by the committee.

Findings or rulings of the committee upon all enquiries, including matters of interpretation, which are of sufficient importance that both enquiries and replies be made public as soon as possible will be published in an enquiry-reply form for inclusion in the BS 5500 ring binder as Enquiry Cases. Their availability will be notified in *BSI News*.

After taking into account any public comment thereon, Enquiry Cases may be incorporated, as appropriate, into the standard as amendments which will form part of the next convenient annual updating.

### 1.3 References

The titles of the publications referred to in this standard are listed on the last page.

### 1.4 Definitions

For the purposes of this British Standard the following definitions apply.

**1.4.1 purchaser.** The organization or individual who buys the finished pressure vessel for its own use or as an agent for the owner.

\* A national scheme to provide assurance that vessels are manufactured in conformity with this British Standard without the necessity for a purchaser specifically to commission the competent Inspection Authority is operated by the Pressure Vessels Quality Assurance Board under the aegis of the Institution of Mechanical Engineers. Manufacturers holding a valid PVQAB Certificate of Authorization relating to the manufacture of pressure vessels to the relevant construction categories defined in this standard may also be deemed to be competent and suitably equipped for this purpose.

† 1 mbar =  $10^2 \text{ N/m}^2 = 100 \text{ Pa}$ .

1 bar =  $10^5 \text{ N/m}^2 = 0.1 \text{ N/mm}^2 = 100 \text{ kPa}$ .