

# **Manual of Petroleum Measurement Standards Chapter 12.4.1**

## **Calculation of Petroleum Quantities— Base Prover Volume Determination— Waterdraw Volumetric Method**

FIRST EDITION, SEPTEMBER 2023



## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

**Shall:** As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

**Should:** As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

**May:** As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

**Can:** As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).



# Contents

	Page
1 Scope .....	1
1.1 Application .....	1
2 Normative References .....	2
3 Terms, Definitions, Acronyms, Abbreviations, and Symbols .....	2
3.1 Terms and Definitions .....	2
3.2 Acronyms, Abbreviations, and Symbols .....	5
4 Calibration Requirements .....	11
4.1 General .....	11
4.2 Displacement Provers .....	11
4.3 Open Tank Provers .....	12
4.4 Range ('Out' R%, 'Back' R%, 'Trip' R%, and 'Q <sub>av</sub> ' R%) .....	12
4.5 Displacement Prover Wear ( $\Delta BPV$ , $\Delta BPV\%$ ) .....	12
4.6 Verification Tolerance for Open Tank Prover ( $\Delta V$ , $\Delta V\%$ ) .....	13
5 Correction Factors .....	13
5.1 General .....	13
5.2 Water Density ( $RHOW_i$ ) .....	14
5.3 Water Density in Test Measure at $P_b$ ( $RHOW_{tm}$ ) .....	15
5.4 Water Density in Prover at $P_b$ ( $RHOW_p$ ) .....	15
5.5 Compressibility Factor of Water ( $F$ ) .....	16
5.6 Correction for Pressure on Water ( $CPL$ ) .....	17
5.7 Correction for Pressure on Water in Test Measure ( $CPL_{tm}$ ) .....	17
5.8 Correction for Pressure on Water in Open Tank Prover ( $CPL_p$ ) .....	17
5.9 Correction for Pressure on Water in Displacement Prover ( $CPL_p$ ) .....	17
5.10 Uncertainty of Patterson-Morris and Tanaka Water Density Correlations .....	18
5.11 Correction for Temperature on Steel Container ( $CTS$ ) .....	19
5.12 Correction for Pressure on Steel Container ( $CPS$ ) .....	20
6 Volume, Mass, and Range Equations .....	21
6.1 General .....	21
6.2 Test Measure Fill .....	22
6.3 Mass for a Pass ( $M_{pass}$ ) .....	23
6.4 Calibrated Prover Volume for a Pass ( $CPV_{usc\_pass}$ , $CPV_{si\_pass}$ ) .....	23
6.5 Calibrated Prover Volume for a Single Roundtrip ( $CPV_{usc\_trip}$ , $CPV_{si\_trip}$ ) .....	24
6.6 Average Calibrated Prover Volumes ( $Avg\ CPV_{out}$ , $Avg\ CPV_{back}$ , $Avg\ CPV_{trip}$ ) .....	24
6.7 Range Equations ('Out' R%, 'Back' R%, 'Trip' R%, and 'Q <sub>av</sub> ') .....	25
6.8 New Base Prover Volume ( $BPV_{new}$ ) .....	26
6.9 Converting $CPV$ and $BPV$ to Other Base Conditions .....	26
6.10 Converting $CPV_{usc}$ and $BPV_{usc}$ to $CPV_{si}$ and $BPV_{si}$ .....	27
6.11 Converting $CPV_{si}$ and $BPV_{si}$ to $CPV_{usc}$ and $BPV_{usc}$ .....	29
7 Precision, Rounding, Discrimination, and Reporting Levels .....	30
7.1 Precision .....	30
7.2 Rounding .....	31
7.3 Discrimination and Reporting Levels .....	31
8 Typical Steel Properties .....	38
9 Process Maps—BPV Calculations .....	38

<b>Annex A (informative) BPV SI Unit Examples .....</b>	<b>56</b>
<b>Annex B (informative) BPV USC Unit Examples.....</b>	<b>72</b>
<b>Bibliography .....</b>	<b>88</b>

## Figures

<b>1 Uncertainty of Patterson-Morris-Tanaka Correlation (ppm) .....</b>	<b>18</b>
<b>2 SI Process Map—Waterdraw Volumetric Method for Displacement Prover .....</b>	<b>40</b>
<b>3 USC Process Map—Waterdraw Volumetric Method for Displacement Prover .....</b>	<b>44</b>
<b>4 SI Process Map—Waterdraw Volumetric Method for Open Tank Prover .....</b>	<b>48</b>
<b>5 USC Process Map—Waterdraw Volumetric Method for Open Tank Prover .....</b>	<b>52</b>
<b>A.1 Unidirectional Displacement Prover—Integral Detector Design.....</b>	<b>57</b>
<b>A.2 Bidirectional Displacement Prover—Integral Detector Design.....</b>	<b>61</b>
<b>A.3 Unidirectional Displacement Prover—External Detector Design .....</b>	<b>65</b>
<b>A.4 Open Tank Prover .....</b>	<b>69</b>
<b>B.1 Unidirectional Displacement Prover—Integral Detector Design.....</b>	<b>73</b>
<b>B.2 Bidirectional Displacement Prover—Integral Detector Design.....</b>	<b>77</b>
<b>B.3 Unidirectional Displacement Prover—External Detector Design .....</b>	<b>81</b>
<b>B.4 Open Tank Prover .....</b>	<b>85</b>

## Tables

<b>1 Pipe Dimensions .....</b>	<b>33</b>
<b>2 Flow Rate .....</b>	<b>33</b>
<b>3 Temperature.....</b>	<b>34</b>
<b>4 Pressure.....</b>	<b>34</b>
<b>5 Test Measures .....</b>	<b>34</b>
<b>6 Water Compressibility Factor .....</b>	<b>35</b>
<b>7 Water Density .....</b>	<b>35</b>
<b>8 Coefficient of Thermal Expansion.....</b>	<b>35</b>
<b>9 Modulus of Elasticity .....</b>	<b>35</b>
<b>10 Correction Factors .....</b>	<b>36</b>
<b>11 Mass and Volume .....</b>	<b>36</b>
<b>12 BPV Volumes .....</b>	<b>37</b>
<b>13 Unit Conversion .....</b>	<b>37</b>
<b>14 Typical Steels' Modulus of Elasticity .....</b>	<b>38</b>
<b>15 Typical Steels' Coefficient of Thermal Expansion .....</b>	<b>38</b>



# Waterdraw Volumetric Method

## 1 Scope

This document provides standardized calculation methods for the quantification of liquids and the determination of base prover volumes (BPVs) under defined conditions by waterdraw method, regardless of the point of origin or destination or units of measure required by governmental organizations. The criteria contained in this document allows different individuals, using various computer languages on different computer hardware (or manual calculations), to arrive at identical results using the same standardized input data.

This publication rigorously specifies the equations for computing correction factors, rules for rounding, the sequence of the calculations, and the discrimination levels of all numbers to be used in these calculations. No deviations from these specifications are permitted since the intent of this document is to serve as a rigorous standard.

### 1.1 Application

#### 1.1.1 General

The BPV of a prover (displacement or open tank) may be determined by one of three methods: waterdraw, master meter, or gravimetric.

This document specifies the equations, rules for rounding, the sequence of the calculations, and the discrimination levels for the waterdraw volumetric method.

The operational procedures and acceptance criteria employed to calibrate a prover by the waterdraw method are specified in API *MPMS* Ch. 4.9.2. See API *MPMS* Ch. 4.9.1 for additional information.

#### 1.1.2 Applicable Liquids

The application of this standard shall be limited to potable water, which is assumed to be clean, air/gas free, and to properly implement the procedures to correct measured volumes at flowing temperatures and pressures to corresponding volumes at base (reference or standard) conditions. To accomplish this, the density correlations for water specified in API *MPMS* Ch. 11.4.1 are contained in this document.

#### 1.1.3 Base Conditions

Historically, the measurement of some liquids for custody transfer and process control have been stated in volume units at base (reference or standard) conditions.

The base conditions for the measurement of liquids, such as crude petroleum and its liquid products, having a vapor pressure equal to or less than atmospheric pressure at the base temperature are as follows.

- International System (SI) of Units.
  - Pressure: 101.325 kPa (14.696 psia).
  - Temperature: 15.00 °C (59.0 °F).
- U.S. customary (USC) units.
  - Pressure: 14.696 psia (101.325 kPa).
  - Temperature: 60.0 °F (15.556 °C).