

**ASME B18.6.3-2024**

(Revision of ASME B18.6.3-2013)

# **Machine Screws, Tapping Screws, and Metallic Drive Screws (Inch Series)**

---

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

**ASME B18.6.3-2024**  
(Revision of ASME B18.6.3-2013)

# **Machine Screws, Tapping Screws, and Metallic Drive Screws (Inch Series)**

---

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: June 21, 2024

This Standard will be revised when the Society approves the issuance of a new edition.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The standards committee that approved the code or standard was balanced to ensure that individuals from competent and concerned interests had an opportunity to participate. The proposed code or standard was made available for public review and comment, which provided an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity. ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor does ASME assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representatives or persons affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

The endnotes and preamble in this document (if any) are part of this American National Standard.



ASME Collective Membership Mark

All rights reserved. “ASME” and the above ASME symbol are registered trademarks of The American Society of Mechanical Engineers. No part of this document may be copied, modified, distributed, published, displayed, or otherwise reproduced in any form or by any means, electronic, digital, or mechanical, now known or hereafter invented, without the express written permission of ASME. No works derived from this document or any content therein may be created without the express written permission of ASME. Using this document or any content therein to train, create, or improve any artificial intelligence and/or machine learning platform, system, application, model, or algorithm is strictly prohibited.

The American Society of Mechanical Engineers  
Two Park Avenue, New York, NY 10016-5990

Copyright © 2024 by  
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS

# CONTENTS

|   |           |
|---|-----------|
| Foreword . . . . .  | vii       |
| Committee Roster . . . . .  | ix        |
| Correspondence With the B18 Committee . . . . .                                       | x         |
| Summary of Changes . . . . .  | xii       |
| <b>1</b> <b>Introductory Notes</b> . . . . .  | <b>1</b>  |
| <b>2</b> <b>General Data for Machine Screw and Tapping Screw Heads</b> . . . . .      | <b>2</b>  |
| <b>3</b> <b>General Data for Machine Screws</b> . . . . .                             | <b>4</b>  |
| <b>4</b> <b>General Data for Tapping Screws</b> . . . . .                             | <b>6</b>  |
| <b>5</b> <b>General Data for Metallic Drive Screws</b> . . . . .                      | <b>10</b> |
| <b>Mandatory Appendices</b>   |           |
| I            Protrusion Gaging of Flat Countersunk Heads . . . . .                    | 87        |
| II           Across-Corners Gaging of Hex Heads . . . . .                             | 88        |
| III          Gaging of Recessed Heads, Types I, IA, and III . . . . .                 | 89        |
| IV          Wobble Gaging of Recessed Heads . . . . .                                 | 95        |
| V           Dimensions for No. 0000, No. 000, and No. 00 Thread Sizes . . . . .       | 98        |
| VI          Dimensions of Type C Tapping Screws . . . . .                             | 99        |
| VII         Type VI Recess Gage Requirements . . . . .                                | 101       |
| <b>Nonmandatory Appendices</b>  |           |
| A           Dimensions of Header Points for Machine Screws Before Threading . . . . . | 104       |
| B           Determination of Maximum Effective Design Grip Lengths . . . . .          | 106       |
| C           Formulas for Dimensions . . . . .   | 108       |
| D           Approximate Hole Sizes for Tapping Screws . . . . .                       | 119       |
| E           Wrench Openings for Hex Head Screws, and Square and Hex Nuts . . . . .    | 142       |
| <b>Figures</b>  |           |
| 4.3.1-1     Types A, AB, B, BF, BP, and BT . . . . .                                  | 81        |
| 4.3.2-1     Types C, D, F, G, T, and TRS . . . . .                                    | 82        |
| 4.11.3-1    Typical Torsional Strength Test Fixture . . . . .                         | 85        |
| I-1         Protrusion Gage . . . . .   | 87        |
| II-1        Typical Gaging Fixture . . . . .  | 88        |
| III-1-1     Penetration Gage for Types I, IA, and III Recesses . . . . .              | 90        |
| IV-1        Wobble Gaging Fixture . . . . .   | 96        |
| D-1         Drilled Hole . . . . .  | 119       |
| D-2         Cored Hole . . . . .  | 119       |
| D-3         Punched Hole . . . . .  | 119       |
| D-4         Hand-Pierced Hole . . . . .   | 119       |

|     |                                 |     |
|-----|---------------------------------|-----|
| D-5 | Type I Extruded Hole . . . . .  | 120 |
| D-6 | Type II Extruded Hole . . . . . | 120 |

**Tables**

|           |  |    |
|-----------|--|----|
| 2.2.1-1   | Dimensions of Slotted Flat Countersunk Head Screws . . . . .   | 12 |
| 2.2.1-2   | Recess Dimensions for Flat Countersunk Head Screws . . . . .   | 15 |
| 2.2.1-3   | Dimensions of Slotted 100-deg Flat Countersunk Head Screws (Machine Screws Only)                           | 17 |
| 2.2.1-4   | Recess Dimensions for 100-deg Flat Countersunk Head Screws (Machine Screws Only)                           | 18 |
| 2.2.1-5   | Dimensions of Slotted Close Tolerance 100-deg Flat Countersunk Head Screws (Machine Screws Only) . . . . . | 19 |
| 2.2.1-6   | Recess Dimensions for Close Tolerance 100-deg Flat Countersunk Head Screws (Machine Screws Only) . . . . . | 20 |
| 2.2.2-1   | Dimensions of Slotted Oval Countersunk Head Screws . . . . .   | 21 |
| 2.2.2-2   | Recess Dimensions of Oval Countersunk Head Screws . . . . .  | 23 |
| 2.2.3-1   | Dimensions of Slotted Undercut 82-deg Flat Countersunk Head Screws . . . . .                               | 25 |
| 2.2.3-2   | Recess Dimensions for Undercut 82-deg Flat Countersunk Head Screws . . . . .                               | 27 |
| 2.2.3-3   | Dimensions of Slotted Undercut Oval Countersunk Head Screws . . . . .                                      | 29 |
| 2.2.3-4   | Recess Dimensions for Undercut Oval 82-deg Countersunk Head Screws . . . . .                               | 31 |
| 2.2.4-1   | Dimensions of Flat Countersunk Trim Head Screws . . . . .  | 32 |
| 2.2.4-2   | Recess Dimensions for Flat Countersunk Trim Head Screws . . . . .  | 34 |
| 2.2.4-3   | Dimensions of Oval 82-deg Countersunk Trim Head Screws . . . . .   | 35 |
| 2.2.4-4   | Recess Dimensions for Oval 82-deg Countersunk Trim Head Screws . . . . .                                   | 38 |
| 2.2.5-1   | Head Dimensions for Slotted Pan Head Screws . . . . .  | 40 |
| 2.2.5-2   | Dimensions of Type I Cross Recessed Pan Head Screws . . . . .  | 42 |
| 2.2.5-3   | Recess Dimensions for Pan Head Screws (Types IA, III, and VI) . . . . .                                    | 43 |
| 2.2.5-4   | Recess Dimensions for Combination Slotted-Pan Head Screws . . . . .  | 45 |
| 2.2.6-1   | Dimensions of Slotted Fillister Head Screws . . . . .  | 47 |
| 2.2.6-2   | Recess Dimensions for Fillister Head Screws . . . . .  | 48 |
| 2.2.6-3   | Dimensions of Slotted Drilled Fillister Head Screws (Machine Screws Only) . . . . .                        | 50 |
| 2.2.7-1   | Dimensions of Slotted Truss Head Screws . . . . .  | 51 |
| 2.2.7-2   | Recess Dimensions for Truss Head Screws . . . . .  | 53 |
| 2.2.7-3   | Dimensions of Combination Slotted Truss Head Screws . . . . .  | 55 |
| 2.2.8-1   | Dimensions of Slotted Binding Head Screws (Machine Screws Only) . . . . .                                  | 57 |
| 2.2.8-2   | Recess Dimensions for Binding Head Screws (Machine Screws Only) . . . . .                                  | 58 |
| 2.2.9-1   | Dimensions of Plain (Unslotted) and Slotted Regular and Large Hex Head Screws . . . .                      | 59 |
| 2.2.9-2   | Recess Dimensions for Indented Regular and Large Hex Head Screws . . . . .                                 | 61 |
| 2.2.9-3   | Recess Dimensions for Type I Nonindented Regular and Large Hex Head Screws . . . .                         | 62 |
| 2.2.10-1  | Dimensions of Plain and Slotted Hex Washer Head Screws . . . . .   | 63 |
| 2.2.10-2  | Recess Dimensions for Indented Hex Washer Head Screws . . . . .  | 65 |
| 2.2.10-3  | Recess Dimensions for Combination Slotted Type I Indented Hex Washer Head Screws                           | 66 |
| 2.2.11-1  | Dimensions of Slotted Round Head Screws . . . . .  | 67 |
| 2.2.11-2  | Recess Dimensions for Round Head Screws . . . . .  | 69 |
| 2.2.11-3  | Recess Dimensions for Combination Slotted Round Head Screws . . . . .                                      | 70 |
| 2.2.12-1  | Dimensions of Slotted Round Washer Head Screws . . . . .   | 72 |
| 2.2.12-2  | Recess Dimensions for Round Washer Head Screws . . . . .   | 73 |
| 4.1.1.1-1 | Dimensions of Threads and Points for Types AB and ABR Thread-Forming Tapping Screws                        | 74 |

|           |   |     |
|-----------|---|-----|
| 4.1.1.2-1 | Dimensions of Threads and Points for Types B and BP Thread-Forming Tapping Screws                                 | 75  |
| 4.1.1.4-1 | Dimensions of Threads and Points for Type A Thread-Forming Tapping Screws . . . . .                               | 76  |
| 4.1.2.1-1 | Dimensions of Threads and Points for Types BF and BT Thread-Cutting Tapping Screws                                | 77  |
| 4.1.2.2-1 | Dimensions of Threads and Points for Types D, F, G, and T Thread-Cutting Tapping Screws                           | 78  |
| 4.1.3-1   | Dimensions of Type TRS Tapping Screws . . . . .   | 80  |
| 4.3.1-1   | Thread Lengths for Types A, AB, B, BF, BP, and BT Tapping Screws . . . . .  | 81  |
| 4.3.2-1   | Thread Lengths for Types C, D, F, G, T, and TRS Tapping Screws . . . . .  | 82  |
| 4.11.1-1  | Standard Test-Plate Thickness and Hole Sizes for Drive-Test Inspection of Tapping Screws                          | 83  |
| 4.11.2-1  | Maximum Drive Torque for Type TRS Tapping Screws . . . . .  | 84  |
| 4.11.3-1  | Torsional Strength Requirements for Tapping Screws . . . . .  | 85  |
| 5-1       | Dimensions of Round Head Type U Metallic Drive Screws . . . . .   | 86  |
| III-1-1   | Dimensions of Gage Heads for Types I, IA, and III Recesses . . . . .  | 91  |
| III-1-2   | Dimensions of Gage Heads for Type I Recess . . . . .  | 92  |
| III-1-3   | Dimensions of Gage Points for Type IA Recess . . . . .  | 93  |
| III-1-4   | Dimensions of Type III Square Penetration Gage Points . . . . .   | 94  |
| III-1-5   | Dimensions of Type III Square Fit Gage Points . . . . .   | 94  |
| IV-1      | Gage Body Diameters . . . . .   | 96  |
| IV-2      | Gaging Limits for Types I, IA, and III Recesses . . . . .   | 97  |
| V-1       | Dimensions for No. 0000, No. 000, and No. 00 Thread Sizes . . . . .   | 98  |
| VI-1      | Dimensions of Threads and Points for Type C Thread-Forming Tapping Screws . . . . .                               | 100 |
| VII-2-1   | Dimensions for Type VI Recess Gage Elements . . . . .   | 102 |
| A-1       | Dimensions of Header Points for Machine Screws Before Threading . . . . .   | 104 |
| B-1       | Constants for Determining Maximum Effective Design Grip Length on Types AB, A, and BP<br>Tapping Screws . . . . . | 107 |
| C-1       | Flat Countersunk Head Screws . . . . .  | 109 |
| C-2       | Undercut Flat Countersunk Head Screws . . . . .   | 110 |
| C-3       | 100-deg Flat Countersunk Head Screws . . . . .  | 111 |
| C-4       | Close Tolerance 100-deg Flat Countersunk Head Screws . . . . .  | 111 |
| C-5       | Oval Countersunk Head Screws . . . . .  | 112 |
| C-6       | Undercut Oval Countersunk Head Screws . . . . .   | 112 |
| C-7       | Pan Head Screws . . . . .   | 113 |
| C-8       | Truss Head Screws . . . . .   | 113 |
| C-9       | Fillister Head Screws . . . . .   | 114 |
| C-10      | Drilled Fillister Head Screws . . . . .   | 114 |
| C-11      | Binding Head Screws . . . . .   | 114 |
| C-12      | Round Head Screws . . . . .   | 115 |
| C-13      | Flat and Oval Countersunk Trim Head Screws . . . . .  | 116 |
| C-14      | Slot Width in Slotted Head Screws . . . . .   | 118 |
| C-15      | Machine Screw Nuts . . . . .  | 118 |
| D-1       | Approximate Hole Sizes for Steel Type AB Thread-Forming Tapping Screws . . . . .                                  | 121 |
| D-2       | Approximate Hole Sizes for Steel Types B and BP Thread-Forming Tapping Screws . .                                 | 123 |
| D-3       | Approximate Hole Sizes for Steel Types BF and BT Thread-Cutting Tapping Screws . .                                | 126 |
| D-4       | Approximate Hole Sizes for Steel Types D, F, G, and T Thread-Cutting Tapping Screws                               | 128 |
| D-5       | Approximate Hole Sizes for Steel Type A Thread-Forming Tapping Screws . . . . .                                   | 132 |
| D-6       | Approximate Hole Sizes in Steel Sheet Metals for Steel Type C Thread-Forming Tapping<br>Screws . . . . .          | 134 |

|     |  |     |
|-----|--|-----|
| D-7 | Approximate Hole Sizes for Thread Rolling Screws . . . . .             | 136 |
| E-1 | Wrench Openings for Hex Head Screws, and Square and Hex Nuts . . . . . | 142 |

# FOREWORD

American National Standards Committee B18 for the standardization of bolts, screws, nuts, rivets, and similar fasteners was organized in March 1922 as Sectional Committee B18 under the aegis of the American Engineering Standards Committee (later the American Standards Association, then the United States of America Standards Institute and, as of October 6, 1969, the American National Standards Institute, Inc.), with the Society of Automotive Engineers and the American Society of Mechanical Engineers as joint sponsors. Subcommittee 3\* was subsequently established and charged with the responsibility for technical content of standards covering slotted and recessed head screws.

An American Standard setting forth slotted head proportions was approved and published in April 1930. Over the years following the issuance of this document, the need for standards more comprehensive than head configurations became apparent. At a meeting held on April 14, 1942, Subcommittee 3\* was reorganized and enlarged, and the following operating scope was established:

The scope of Subcommittee 3\* shall consist of the development and promulgation of American Standards embracing screw products variously known as machine screws, wood screws, tapping screws, slotted head cap screws, slotted headless set screws, and machine screw nuts. The standards shall comprise complete product standards covering all dimensions and tolerances required for the specification and production of the products. Details shall include boundary dimensions, such as nut width and thickness; screw head dimensions; slot and recess dimensions; body dimensions; thread classification or thread detail, as required; thread length; point design; chamfers; underhead fillets; and supporting general specifications covering the quality, finish, and the acceptable tolerances and limits as well as any information that may be necessary to ensure satisfactory application of the products.

Several meetings of the Subcommittee over the ensuing 3 years resulted in the development and acceptance of a proposed revision containing complete product standards coverage for slotted and recessed head machine, tapping and wood screws; slotted and hexagon head cap screws; and slotted headless set screws. Following approval by the B18 Committee and sponsor organizations, this proposal was forwarded to the American Standards Association and declared an American Standard, ASA B18.6, on April 12, 1947.

Recognizing the need for further refinements, Subcommittee 3\* at a meeting held on February 1, 1951, established three standing working subgroups: one to develop details pertinent to tapping screw threads; a second to review, revise, and develop head dimensions and tolerances; and a third to correlate and edit the technical information emanating from the other two groups. Also at this meeting, numerous suggested changes were reviewed and assigned to the respective subgroups for further development. Additional meetings of the Subcommittee were held on October 9, 1952; October 29, 1953; and April 1 and 2, 1954. Between each of these meetings the subgroups held numerous working sessions and carried on technical development in cooperation with the technical committees of the U.S. Machine Screw and Tapping Screw Service Bureaus.

At the April 1954 meeting, Subcommittee 3\* contemplating a partial revision of the ASA B18.6 document, recommended the publication of standards for wood screws, cap and set screws, machine screws, and tapping and drive screws in four separate documents, each of which would consist of a complete product specification. This approach was confirmed by the B18 Committee with the further stipulation that the coverage for hexagon head cap screws, square head set screws, and machine screw nuts from the ASA B18.2 standard be transferred to the documents covering cap and set screws and machine screws, respectively. It was understood that jurisdiction over the square head set screws and hexagon head cap screws would remain with Subcommittee 2 and that Subcommittee 3\* would retain responsibility for machine screw nuts. Following this confirmation and additional direction, the preparation of proposals for the new documents was undertaken.

The proposed standard covering slotted and recessed head machine screws and machine screw nuts was approved by Subcommittee 3\* at a meeting held on December 6, 1955. After being circulated to industry for comment, it was revised and subsequently approved by letter ballot of the B18 Committee in March of 1958. The proposal was, however, redrafted to incorporate additional revisions and refinements adopted by Subcommittee 3\* at meetings held on October 30, 1958 and September 17, 1959. The revised proposal was recirculated to the B18 Committee and was approved by the sponsor organizations and the American Standards Association and formally designated an American Standard, ASA B18.6.3, on February 12, 1962.

---

\* As of April 1, 1966, Subcommittee 3 was redesignated Subcommittee 6.

Following issuance of the 1962 document, Subcommittee 3\* and the working subgroups continued to develop revisions and refinements reflecting changes in industry practices and technical improvements. Work over the intervening years culminated in the Subcommittee 6 acceptance of a draft dated November 1969, incorporating revisions in the following areas: inclusion of Type IA cross recess data; addition of the No. 0000, No. 000, and No. 00 sizes to most slotted head styles; extensions of size coverage for 100-deg flat countersunk heads and binding heads in smaller sizes, and for pan heads in larger sizes; redimensioning of flat and oval countersunk heads; revision of thread lengths; inclusion of appendices for wobble gaging of recessed heads and wrench sizes for square and hex products; and a complete revamping of the format.

This revision was approved as an American National Standard on May 22, 2003.

In late 2008 the ASME B18.6 Subcommittee undertook a revision of B18.6.3. The first major decision was to combine B18.6.3 and B18.6.4 into one standard for all types of screws, machine and tapping. This was decided since over 50% of both standards were identical, and they both contained essentially the same head and recess data.

The Type VI recess design, having six internal lobes, was introduced into this Standard because of its wide use. The Type II recess was removed from the Standard because there is no documented use of this design today. A grade of hardened steel machine screw was added to the standard along with references to stainless steel and nonferrous materials. The thread Type TRS, for thread rolling screws, was added in the tapping screw section. The Type A thread type was moved back into the body of the standard from the Appendix because it is still in high use in several industries. The Type ABR thread, a Type AB with a radius point, was also introduced. Machine screw nuts were moved to ASME B18.2.2. ASME B18.6.3-2010 was approved as an American National Standard on September 8, 2010.

The 2010 revision was extensive, and users reported numerous minor errors. ASME B18.6.3-2013 corrected the reported errors and updated the quality requirements to reflect the publication of ASME B18.18. ASME B18.6.3-2013 was approved as an American National Standard on February 5, 2013.

Since publication of ASME B18.6.3-2013, users have requested guidance or clarification on a number of issues. In 2016, a joint task group was formed with the SAE Fastener Committee to review these items. The primary items addressed were updating guidance on hydrogen embrittlement testing, lowering core hardness and updating case hardening practices to conform to current industry best practices, revising the tapping screw thread length to accommodate more definitive and practical identification of thread termination, and updating items missed in the 2013 revision.

ASME B18.6.3-2024 was approved by the American National Standards Institute as an American National Standard on January 22, 2024.

# ASME B18 COMMITTEE

## Standardization of Bolts, Nuts, Rivets, Screws, Washers, and Similar Fasteners

(The following is the roster of the committee at the time of approval of this Standard.)

### STANDARDS COMMITTEE OFFICERS

**S. Brahimi**, *Chair*  
**J. Medcalf**, *Vice Chair*  
**S. Khan**, *Secretary*

### STANDARDS COMMITTEE PERSONNEL

|   |   |
|---|---|
| <b>T. Anderson</b> , Bay Bolt, Inc.                           | <b>R. Lund</b> , Fastenal Co.   |
| <b>L. Borowski</b> , Greenslade and Company, Inc.             | <b>J. Medcalf</b> , Agrati, Inc.  |
| <b>S. Brahimi</b> , Industrial Fasteners Institute            | <b>F. Perry</b> , Deere and Co.   |
| <b>B. Cao</b> , Infasco                                       | <b>A. Scheer</b> , Stanley Engineered Fastening                                     |
| <b>L. Claus</b> , NNI Training and Consulting, Inc.           | <b>D. Bankston</b> , <i>Contributing Member</i> , Bothell Co.                       |
| <b>D. Collis</b> , Lindfast Solutions Group                   | <b>J. J. Grey</b> , <i>Contributing Member</i> , Fastener Consulting Services, Inc. |
| <b>W. Guth</b> , Electric Boat Corp.                          | <b>M. Keller</b> , <i>Contributing Member</i>                                       |
| <b>J. C. Jennings</b> , United States Department of the Navy  | <b>D. Korneffel</b> , <i>Contributing Member</i> , Partsolutions, LLC               |
| <b>S. Khan</b> , The American Society of Mechanical Engineers | <b>R. D. Strong</b> , <i>Contributing Member</i> , Consultant                       |
| <b>W. H. King</b> , Brighton Best International               | <b>C. B. Williamson</b> , <i>Contributing Member</i> , Fastenal Co.                 |

### SUBCOMMITTEE 6 — SLOTTED AND RECESSED HEAD SCREWS

|  |  |
|--|--|
| <b>L. Claus</b> , <i>Chair</i> , NNI Training and Consulting, Inc.               | <b>F. Lajewardi</b> , H. Paulin and Co.                          |
| <b>L. Borowski</b> , <i>Vice Chair</i> , Greenslade and Co., Inc.                | <b>R. Lund</b> , Fastenal Co.                                    |
| <b>S. Khan</b> , <i>Secretary</i> , The American Society of Mechanical Engineers | <b>J. Medcalf</b> , Agrati, Inc.                                 |
| <b>M. Abbott</b> , University of North Carolina at Charlotte                     | <b>D. M. Pawlekti</b> , Shamrock International                   |
| <b>T. Anderson</b> , Bay Bolt, Inc.  | <b>H. D. Stetson</b> , Valley Fastener Group, LLC                |
| <b>S. Brahimi</b> , Industrial Fasteners Institute                               | <b>J. J. Stoczanskyj</b> , Beacon Fasteners and Components, Inc. |
| <b>M. Byrne</b> , General Fasteners Co.  | <b>C. Vertullo</b> , Carver Engineering and Manufacturing, Inc.  |
| <b>J. P. Fragnoli</b> , General Fasteners Co.                                    | <b>J. York</b> , Fastenal Co.                                    |
| <b>W. H. King</b> , Brighton Best International                                  | <b>G. Simpson</b> , <i>Contributing Member</i> , Semblex Corp.   |

# CORRESPONDENCE WITH THE B18 COMMITTEE

**General.** ASME codes and standards are developed and maintained by committees with the intent to represent the consensus of concerned interests. Users of ASME codes and standards may correspond with the committees to propose revisions or cases, report errata, or request interpretations. Correspondence for this Standard should be sent to the staff secretary noted on the committee's web page, accessible at <https://go.asme.org/B18committee>.

**Revisions and Errata.** The committee processes revisions to this Standard on a periodic basis to incorporate changes that appear necessary or desirable as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published in the next edition of the Standard.

In addition, the committee may post errata on the committee web page. Errata become effective on the date posted. Users can register on the committee web page to receive e-mail notifications of posted errata.

This Standard is always open for comment, and the committee welcomes proposals for revisions. Such proposals should be as specific as possible, citing the paragraph number, the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent background information and supporting documentation.

## Cases

(a) The most common applications for cases are

(1) to permit early implementation of a revision based on an urgent need

(2) to provide alternative requirements

(3) to allow users to gain experience with alternative or potential additional requirements prior to incorporation directly into the Standard

(4) to permit the use of a new material or process

(b) Users are cautioned that not all jurisdictions or owners automatically accept cases. Cases are not to be considered as approving, recommending, certifying, or endorsing any proprietary or specific design, or as limiting in any way the freedom of manufacturers, constructors, or owners to choose any method of design or any form of construction that conforms to the Standard.

(c) A proposed case shall be written as a question and reply in the same format as existing cases. The proposal shall also include the following information:

(1) a statement of need and background information

(2) the urgency of the case (e.g., the case concerns a project that is underway or imminent)

(3) the Standard and the paragraph, figure, or table number

(4) the editions of the Standard to which the proposed case applies

(d) A case is effective for use when the public review process has been completed and it is approved by the cognizant supervisory board. Approved cases are posted on the committee web page.

**Interpretations.** Upon request, the committee will issue an interpretation of any requirement of this Standard. An interpretation can be issued only in response to a request submitted through the online Inquiry Submittal Form at <https://go.asme.org/InterpretationRequest>. Upon submitting the form, the inquirer will receive an automatic e-mail confirming receipt.

ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the information submitted, it is the opinion of the committee that the inquirer should seek assistance, the request will be returned with the recommendation that such assistance be obtained. Inquirers can track the status of their requests at <https://go.asme.org/Interpretations>.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME committee or subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Interpretations are published in the ASME Interpretations Database at <https://go.asme.org/Interpretations> as they are issued.

**Committee Meetings.** The B18 Standards Committee regularly holds meetings that are open to the public. Persons wishing to attend any meeting should contact the secretary of the committee. Information on future committee meetings can be found on the committee web page at <https://go.asme.org/B18committee>.

# ASME B18.6.3-2024

## SUMMARY OF CHANGES

Following approval by the ASME B18 Standards Committee and ASME, and after public review, ASME B18.6.3-2024 was approved by the American National Standards Institute on January 22, 2024.

In ASME B18.6.3-2024, figures and tables have been redesignated. ASME B18.6.3-2024 includes the following additional changes identified by a margin note, **(24)**.

| <i>Page</i> | <i>Location</i> | <i>Change</i>  |
|-------------|-----------------|--|
| 1           | 1.7             | Updated  |
| 2           | 2.1.1           | Revised  |
| 3           | 2.1.5           | Subparagraphs (a) through (c) revised  |
| 4           | 3.2             | Revised  |
| 5           | 3.8.3           | Revised in its entirety, and para. 3.8.4 deleted   |
| 5           | 3.9             | Second sentence revised  |
| 5           | 3.11            | (1) Subparagraph (a)(7) revised<br>(2) Example (2) deleted, and subsequent Examples redesignated |
| 6           | 4.1.1.4         | Revised  |
| 6           | 4.1.2.1         | Penultimate sentence revised   |
| 7           | 4.1.3           | Revised  |
| 7           | 4.2             | Second sentence revised  |
| 7           | 4.3             | (1) Revised in its entirety<br>(2) Former Figure 3 deleted                                       |
| 8           | 4.8.1.1         | Second sentence deleted  |
| 8           | 4.8.1.2         | Revised  |
| 9           | 4.8.1.3         | Reference to SAE J423 revised to SAE J42 and in-text table revised                               |
| 9           | 4.9             | Reference to ASTM F1941 revised to ASTM F1941/F1941M   |
| 9           | 4.11.1          | Revised  |
| 10          | 4.11.5          | (1) First sentence added<br>(2) Second paragraph revised in its entirety                         |
| 11          | 5.6             | First sentence revised   |
| 11          | 5.7             | Reference to ASTM F1941 revised to ASTM F1941/F1941M   |
| 81          | Figure 4.3.1-1  | Former Figure 1 revised  |
| 82          | Figure 4.3.2-1  | Former Figure 2 revised  |
| 15          | Table 2.2.1-2   | Note (6) added   |
| 23          | Table 2.2.2-2   | Note (6) added   |
| 27          | Table 2.2.3-2   | Values in “Type III, Driver Size” column revised   |
| 43          | Table 2.2.5-3   | Note (6) added   |
| 48          | Table 2.2.6-2   | Note (6) added   |
| 53          | Table 2.2.7-2   | Note (6) added   |
| 61          | Table 2.2.9-2   | Note (4) added   |

| <i>Page</i> | <i>Location</i> | <i>Change</i>   |
|-------------|-----------------|---|
| 65          | Table 2.2.10-2  | Note (6) added  |
| 73          | Table 2.2.12-2  | Note (3) added  |
| 74          | Table 4.1.1.1-1 | Former General Note (d) redesignated as Note (1)(c)   |
| 75          | Table 4.1.1.2-1 | Former General Note (c) added to Note (1)   |
| 76          | Table 4.1.1.4-1 | (1) Nominal Sizes 2, 4, 6, 8, 10, and 12 made bold and Note (1) revised<br>(2) Former General Note (d) added to Note (1)  |
| 96          | Figure IV-1     | Revised   |
| 102         | Table VII-2-1   | (1) For drive and gage size number 7, minimum diameter $M$ and maximum diameter $P_1$ revised<br>(2) For drive and gage size numbers 9 and 50, maximum diameter $C$ revised |
| 121         | Table D-1       | "In Asbestos Compositions" section deleted  |
| 123         | Table D-2       | "In Asbestos Compositions" section deleted  |
| 132         | Table D-5       | "In Asbestos Compositions" section deleted  |

INTENTIONALLY LEFT BLANK

# MACHINE SCREWS, TAPPING SCREWS, AND METALLIC DRIVE SCREWS (INCH SERIES)

## 1 INTRODUCTORY NOTES

### 1.1 Scope

This Standard is intended to cover the complete general and dimensional data for the various types of slotted and recessed head machine screws, tapping screws, and metallic drive screws recognized as American National Standard. Also included are appendices that provide specifications and instructions for the protrusion gaging of flat countersunk head screws; across-corners gaging of hex head screws; penetration gaging and wobble gaging of recessed head screws; approximate hole size for tapping screws; wrench openings for hex and square products; thread dimensions for the No. 0000, No. 000, and No. 00 sizes; means for determining effective grip lengths on screws; documentation for screw types and head types relegated to not-recommended or limited-usage status; and formulas on which dimensional data are based. It shall be understood, however, that where questions arise concerning acceptance of product, the dimensions in the tables shall govern over recalculation by formula.

The inclusion of dimensional data in this Standard is not intended to imply that all of the products described are stock production sizes. Consumers should consult with suppliers concerning the availability of products.

### 1.2 Dimensions

All dimensions in this Standard are given in inches, unless stated otherwise.

### 1.3 Options

Options, where specified, shall be at the discretion of the manufacturer unless otherwise agreed upon by the manufacturer and the purchaser.

### 1.4 Responsibility for Modification

The manufacturer shall not be held responsible for malfunctions of product determined to be due to plating or other modifications when such plating or modification is not accomplished under the manufacturer's control or direction.

### 1.5 Terminology

For definitions of terms relating to fasteners or features thereof used in this Standard, see ASME B18.12.

### 1.6 Comparison With ISO

This Standard has no ISO counterpart.

### 1.7 Referenced Standards

Unless otherwise specified, the standards referenced shall be the latest at the time of order placement.

ASME B1.1. Unified Inch Screw Threads (UN and UNR Thread Form). The American Society of Mechanical Engineers.

ASME B1.3. Screw Thread Gaging Systems for Acceptability: Inch and Metric Screw Threads (UN, UNR, UNJ, M, and MJ). The American Society of Mechanical Engineers.

The American Society of Mechanical Engineers.

ASME B18.2.9. Straightness Gage and Gaging for Bolts and Screws. The American Society of Mechanical Engineers.

ASME B18.12. Glossary of Terms for Mechanical Fasteners. The American Society of Mechanical Engineers.

ASME B18.18. Quality Assurance for Fasteners. The American Society of Mechanical Engineers.

(24)