

# Refractory Installation Quality Control— Inspection and Testing of AES/RCF Fiber Linings and Materials

API STANDARD 976  
FIRST EDITION, MARCH 2018



AMERICAN PETROLEUM INSTITUTE

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this standard should consult with the appropriate authorities having jurisdiction.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the standard. At all times users should employ sound business, scientific, engineering, and judgment safety when using this standard.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, [standards@api.org](mailto:standards@api.org).



## Contents

	Page
<b>1</b>	<b>Scope</b> . . . . . <b>1</b>
<b>2</b>	<b>Normative References</b> . . . . . <b>1</b>
<b>3</b>	<b>Terms and Definitions</b> . . . . . <b>2</b>
<b>4</b>	<b>Responsibilities</b> . . . . . <b>7</b>
<b>4.1</b>	<b>Owner/EM</b> . . . . . <b>7</b>
<b>4.2</b>	<b>Installer</b> . . . . . <b>7</b>
<b>4.3</b>	<b>Inspector</b> . . . . . <b>8</b>
<b>4.4</b>	<b>Refractory Manufacturer</b> . . . . . <b>9</b>
<b>4.5</b>	<b>Fiber Component Fabricator</b> . . . . . <b>9</b>
<b>5</b>	<b>Inspector Qualifications</b> . . . . . <b>9</b>
<b>6</b>	<b>Materials</b> . . . . . <b>9</b>
<b>6.1</b>	<b>Physical Property Requirements for Refractory</b> . . . . . <b>9</b>
<b>6.2</b>	<b>Anchors</b> . . . . . <b>10</b>
<b>6.3</b>	<b>Packaging</b> . . . . . <b>10</b>
<b>6.4</b>	<b>Marking</b> . . . . . <b>10</b>
<b>6.5</b>	<b>Weather Protection</b> . . . . . <b>11</b>
<b>6.6</b>	<b>Shelf Life</b> . . . . . <b>11</b>
<b>6.7</b>	<b>Discarding Criteria</b> . . . . . <b>11</b>
<b>7</b>	<b>Lining Design</b> . . . . . <b>11</b>
<b>8</b>	<b>Rigidized and Surface-treated Fiber</b> . . . . . <b>19</b>
<b>9</b>	<b>QA/QC, Examination, and Testing</b> . . . . . <b>19</b>
<b>9.1</b>	<b>Anchor Inspection and Testing</b> . . . . . <b>19</b>
<b>9.2</b>	<b>Anchor Stud Welding</b> . . . . . <b>19</b>
<b>9.3</b>	<b>Fiber Lining Inspection and Testing</b> . . . . . <b>19</b>
<b>9.4</b>	<b>Installation Workmanship for Fiber Linings</b> . . . . . <b>20</b>
<b>10</b>	<b>Preparation for Shipment</b> . . . . . <b>21</b>
	<b>Annex A (normative) Refractory Compliance Datasheet</b> . . . . . <b>22</b>
	<b>Annex B (informative) Refractory Inspector Minimum Competencies</b> . . . . . <b>25</b>
<b>Figures</b>	
<b>1</b>	<b>Typical Stud Layout for Overlap Blanket Systems</b> . . . . . <b>12</b>
<b>2</b>	<b>Typical Layered Fiber Lining Anchoring Systems</b> . . . . . <b>13</b>
<b>3</b>	<b>Examples of Modular Fiber Systems</b> . . . . . <b>14</b>
<b>4</b>	<b>Hardware Span Required for Overhead Section Modules and Typical Staples to Secure Batten Strip to Module in Overhead Installations</b> . . . . . <b>15</b>
<b>5</b>	<b>Typical Module Orientations</b> . . . . . <b>16</b>
<b>6</b>	<b>Typical Joint Details for Single Batten Strips</b> . . . . . <b>17</b>
<b>7</b>	<b>Typical Blanket Lining Repair of Hot-face Layer</b> . . . . . <b>17</b>
<b>8</b>	<b>Typical Blanket Lining Repair of Multiple Layers</b> . . . . . <b>17</b>
<b>9</b>	<b>Typical Repair of Modular Fiber Linings</b> . . . . . <b>18</b>
<b>Tables</b>	
<b>1</b>	<b>Documentation Required for Fiber per ASTM C892</b> . . . . . <b>9</b>
<b>2</b>	<b>Maximum Temperature of Anchor Tips</b> . . . . . <b>10</b>



## **Important Information Concerning Use of Asbestos or Alternative Materials**

Asbestos is specified or referenced for certain components of the equipment described in some API standards. It has been extremely useful in minimizing fire hazards associated with petroleum processing. It has also been a universal sealing material, compatible with most refining fluid services.

Certain serious adverse health effects are associated with asbestos, among them the serious and often fatal diseases of lung cancer, asbestosis, and mesothelioma (a cancer of the chest and abdominal linings). The degree of exposure to asbestos varies with the product and the work practices involved.

Consult the most recent edition of the Occupational Safety and Health Administration (OSHA), U.S. Department of Labor, Occupational Safety and Health Standard for Asbestos, Tremolite, Anthophyllite, and Actinolite, 29 *Code of Federal Regulations* Section 1910.1001; the U.S. Environmental Protection Agency, National Emission Standard for Asbestos, 40 *Code of Federal Regulations* Sections 61.140 through 61.156; and the U.S. Environmental Protection Agency (EPA) rule on labeling requirements and phased banning of asbestos products (Sections 763.160-179).

There are currently a number of substitute materials in use and under development to replace asbestos in certain applications. Manufacturers and users are encouraged to develop and use effective substitute materials that can meet the specifications for, and operating requirements of, the equipment to which they would apply.

**Safety and health information with respect to particular products or materials can be obtained from the employer, the manufacturer, or supplier of that product or material, or the material safety datasheet.**

# Refractory Installation Quality Control—Inspection and Testing of AES/RCF Fiber Linings

## 1 Scope

This standard provides installation quality control procedures and lining system design requirements for AES/RCF fiber linings, and may be used to supplement owner specifications. Materials, equipment, and personnel are qualified by the methods described, and applied refractory quality is closely monitored, based on defined procedures and acceptance criteria. The responsibilities of inspection personnel who monitor and direct the quality control process are also defined.

The lining described in this standard is for internal refractory linings on the process side of the equipment. External insulation and jacketing are not covered in this standard.

## 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Standard 560, *Fired Heaters for General Refinery Service*

API Standard 936, *Refractory Installation Quality Control – Inspection and Testing of Monolithics*

ASTM C1771<sup>1</sup>, *Standard Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Guarded-Hot-Plate Apparatus*

ASTM E1172, *Standard Practice for Describing and Specifying a Wavelength-Dispersive X-Ray Spectrometer*

ASTM E1361, *Standard Guide for Correction of Inter-element Effects in X-Ray Spectrometric Analysis*

ASTM C201, *Standard Test Method for Thermal Conductivity of Refractories*

ASTM C612, *Standard Specification for Mineral Fiber Block and Board Thermal Insulation*

ASTM C680, *Standard Practice for Estimate of the Heat Gain or Loss and the Surface Temperatures of Insulated Flat, Cylindrical, and Spherical Systems by Use of Computer Programs*

ASTM C892, *Standard Specification for High-Temperature Fiber Blanket Thermal Insulation*

ASTM C1113, *Standard Test Method for Thermal Conductivity of Refractories by Hot Wire (Platinum Resistance Thermometer Technique)*

BS EN 1094-1<sup>2</sup>, *Insulating refractory products. Terminology, classification and methods of test for high temperature insulation wool products*

SSPC-SP 3<sup>3</sup>, *Power Tool Cleaning*

SSPC-SP 7/NACE No. 4, *Brush-Off Blast Cleaning*

---

<sup>1</sup> ASTM International, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428, [www.astm.org](http://www.astm.org).

<sup>2</sup> BSI, 389 Chiswick High Road, London, W4 4AL, United Kingdom, [www.bsigroup.com](http://www.bsigroup.com).

<sup>3</sup> The Society for Protective Coatings, 40 24th Street, 6th Floor, Pittsburgh, Pennsylvania 15222, [www.sspc.org](http://www.sspc.org).